

**INTEGRATING FACIAL EXPRESSIONS AND SKIN
TEXTURE IN FACE RECOGNITION**

by

ZHI ZHANG

September 2008

A Dissertation Submitted to the
Faculty of the Graduate School of
the State University of New York at Buffalo
in partial fulfillment of the requirements for the
degree of

DOCTOR OF PHILOSOPHY

Department of Computer Science and Engineering

© Copyright by
Zhi Zhang
2008

INTEGRATING FACIAL EXPRESSIONS AND SKIN TEXTURE IN FACE RECOGNITION

A Dissertation Presented

by

ZHI ZHANG

Approved as to style and content by:

Venugopal Govindaraju, Chair

Peter D. Scott, Member

Vipin Chaudhary, Member

Jan Chomicki, Director of Graduate Study
Department of Computer Science and Engi-
neering

To Wenjiao and Jingyi.

ACKNOWLEDGMENTS

My research work is deeply indebted to Dr. Venugopal Govindaraju, my advisor, who provide me with an excellent research environment in the Center for Unified Biometrics and Sensors (CUBS). The more valuable is his intellectual guidance on my dissertation research and always having an open door for discussion.

My deep appreciation goes to the members of my dissertation committee, Dr. Venugopal Govindaraju, Dr. Peter D. Scott and Dr. Vipin Chaudhary, for their support and valuable input to improve this work.

My research work could not be completed without collaborations from my wonderful colleagues in CUBS. I am indebted to Philip Kilinskas, Vartika Singh, Thomas E. Slowe, Jiang Li, Huaigu Cao, Dr. Zhixin Shi, Faisal Farooq, Ifeoma Nwogu, Xujun Peng, Praveer Mansukhani, Achint Oommen Thomas, Anurag Bharadwaj and Daekeun You, for their great help in various manners. Most importantly, I owe my sincere thanks to Dr. Sergey Tulyakov for his tremendous help and support in my dissertation research.

My sincere thanks also go to the staff of CUBS, Ms. Eugenia Smith, Ms. Mary Jane Gallo and Mr. Ed Sobczak, for their most generous and patient help on administrative work.

I am deeply thankful to my parents for bringing me into this world and supporting me throughout my pursuit of higher education.

Finally and most importantly, I would like to express my heartfelt thanks to Wenjiao, my beloved wife, for her selfless love, sacrifice and encouragement.

ABSTRACT

Face recognition is the most common biometric modality in use today. In this thesis, we have investigated two new aspects of face recognition, namely the use of skin marks as an additional biometric trait and the use of facial expressions both as a biometric as well as a behavior indicator. Most of the current face recognition systems, such as Eigenfaces, Fisherfaces, and Active Appearance Models are designed to process faces holistically. These methods cannot adequately model the local features such as moles, and scars. We have developed an algorithm for facial skin mark detection based on modeling the local skin patches using Principal Component Analysis (PCA). We have also explored different ways of calculating distances between the original patches and PCA models for this purpose.

Most of the behavioral science research on facial expression analysis operates within the framework of the Facial Action Coding System (FACS). FACS is a quantitative system for measuring all visible facial muscle movement and is thus ideal for identifying unique individual patterns in movement. We have developed a system that extracts the AUs automatically and have tested the hypothesis - facial expressions can be used as features for person identification and thereby augment face biometrics.

We use the displacement of face landmark points extracted from the neutral face and the face expression at its ‘emotional apex’ (instead of using a video sequence as in previous work) to construct a single feature vector having that particular expression. Genuine and impostor distributions are constructed accordingly for pairs of same people and different people with same and different expressions. We have conducted experiments on the publicly available Cohn-Kanade Facial Expression Database and

verified if the distributions of genuine and impostor match scores are different by using the Wilcoxon rank sum test.

We have also developed methods that automatically classify facial expressions (sad, happy, anger, etc.) based on the extracted AUs and distinguishing between those expressions which arise involuntarily through natural emotions and those that are “posed”. This latter classification is based on behavioral science guidelines that “posed” expressions are distinguishable by examination of characteristics such as expression symmetry and presence of the right combination of AUs.

TABLE OF CONTENTS

	Page
ACKNOWLEDGMENTS	v
ABSTRACT	vi
LIST OF TABLES	xi
LIST OF FIGURES	xiii
 CHAPTER	
1. INTRODUCTION	1
1.1 Motivation	2
1.2 Problem Statement	4
1.3 Related Work	5
1.3.1 Face as a Biometric Trait	5
1.3.2 Facial Expression	6
1.3.3 Deceit Detection	8
1.4 Outline of the Dissertation	9
2. FACIAL SKIN MARKS AS BIOMETRICS	11
2.1 Introduction	12
2.1.1 Face Processing	12
2.1.2 Soft Biometrics	14
2.1.3 Scars, Marks, and Tattoos	15
2.1.4 Related Work	16
2.2 Study of Facial Skin Marks	18
2.2.1 Facial Skin Mark Dataset	18
2.2.2 Statistical Analysis	19

2.3	Detection of Facial Skin Marks	23
2.3.1	PCA Models of Skin Patches	23
2.3.2	Distances between Skin Patches and PCA Models	27
2.3.3	Experiment and Discussion	29
2.3.3.1	Skin Patch Dataset	29
2.3.3.2	Experiment of Detecting Facial Skin Marks	29
2.3.3.3	Discussion	32
2.4	Facial Skin Marks as Biometric Trait	32
2.4.1	Feature Presentation of Facial Skin Marks	32
2.4.2	Matching Algorithm	34
2.4.3	Combined Biometrics of Facial Skin Mark and Face	35
2.4.4	Experiment and Result	39
2.4.4.1	Facial Skin Marks as Sole Biometric Trait	39
2.4.4.2	Combined Biometrics of Facial Skin Mark and Eigenfaces	42
2.5	Conclusion	44
3.	DECEIT DETECTION FROM INVOLUNTARY FACIAL EXPRESSIONS	48
3.1	Introduction	49
3.1.1	Introduction to Lying	49
3.1.1.1	The Nature of Deceit	49
3.1.1.2	The Evidence of Deceit	52
3.1.1.3	The Detection of Deceit	54
3.1.2	Related Work	56
3.1.3	Facial Action Coding System	58
3.2	Dataset Acquisition and Preprocessing	60
3.2.1	CUBRC-CUBS Dataset	60
3.2.2	Manual Preprocessing	62
3.3	Deceit Detection in the Face	63
3.3.1	Deceit Indicators	65
3.3.1.1	DI for Anger	68

3.3.1.2	DI for Enjoyment	68
3.3.1.3	DI for Fear	69
3.3.1.4	DI for Sadness	69
3.4	Feature Definitions	70
3.4.1	Distance Based Features	70
3.4.2	Texture Based Features	70
3.5	Experiment and Result	71
3.5.1	Experiment Results of DBFs	71
3.5.2	Experiment Results of TBFs	73
3.5.3	Experiment Results of Deceit Indicators	73
3.6	Conclusion	74
4.	FACIAL EXPRESSION AS BIOMETRICS	75
4.1	Introduction	75
4.1.1	Facial Expression Analysis	75
4.1.2	Related Work	78
4.2	Facial Expression as Biometrics	79
4.3	Feature Definitions	80
4.4	Experiment and Result	82
4.4.1	Experiment on Cohn-Kanade Database	83
4.4.2	Experiment on CUBRC-CUBS Database	86
4.5	Conclusion	88
5.	CONCLUSION	91
	BIBLIOGRAPHY	94

LIST OF TABLES

Table	Page
2.1	The facial skin marks dataset built on The AR Face Database. 18
2.2	Statistics of the number of facial skin marks in all the facial images and the intra-class differences in number of facial skin marks for all the subjects. 21
2.3	Four different experiment modes under various system and parameter settings. 30
3.1	Deceit indicators for macro-expressions and micro-expressions. 53
3.2	Four reliable expressions with their associated facial Action Units. 54
3.3	Manual test results of correlation between specific DI and instances of deceit or verity. 58
3.4	AUs related to contractions of specific facial muscles. 59
3.5	FACS descriptions of AUs of interest. 65
3.6	FACS definitions of AUs of interest and their representations in major components and optional components. 67
3.7	Test results of detecting major components represented by distance based features. 72
3.8	Test results of detecting major components represented by texture based features. 73
3.9	Test results of detecting instances of deceit from involuntary facial expressions. 74
4.1	Means and standard deviations for different matching score sets of the Cohn-Kanade Facial Expression Database. 84

4.2	p-values of the Wilcoxon Rank-Sum test on corresponding score sets on on the Cohn-Kanade Facial Expression Database.	84
4.3	Score statistics and p-values of the Wilcoxon Rank-Sum test on emotion identification score sets after PCA transform on the Cohn-Kanade Facial Expression Database.	85
4.4	Score statistics and p-values of the Wilcoxon Rank-Sum test on biometric score sets after PCA transform on the Cohn-Kanade Facial Expression Database.	86
4.5	Score statistics of the CUBRC-CUBS Database matching score sets.	87

LIST OF FIGURES

Figure	Page
2.1 Examples of one image in The AR Face Database with its facial skin marks and inner eye corners labeled.	19
2.2 Histogram of numbers of skin marks labeled for all the images in the facial skin mark dataset.	20
2.3 Extreme cases of images in the facial skin mark dataset.	22
2.4 Sample image showing two levels of facial skin patches constructed around one facial skin mark.	24
2.5 PCA modeling of facial skin patches containing facial skin marks.	25
2.6 PCA modelings of facial skin patches containing no facial skin marks.	26
2.7 ROC curves for different facial skin mark detection scenarios.	31
2.8 The framework of personal identification system utilizing facial skin marks as sole biometrics.	33
2.9 The framework of personal identification system utilizing combination of biometrics of facial skin marks and face.	37
2.10 ROC curves for personal identification based on biometric trait of facial skin marks alone.	40
2.11 ROC curves for three person identification systems: Eigenfaces, facial skin mark, and combined system.	43
2.12 ROC curves with log-scaled FAR axis for three personal identification systems: Eigenfaces, facial skin mark, and combined system.	45
3.1 The human muscles of the head and neck.	60

3.2	The sample images of genuine and deceitful expressions in the CUBRC-CUBS Dataset.	61
3.3	The genuine and deceitful smiles of one subject in the CUBRC-CUBS Dataset.	62
3.4	The framework of deceit detection system based on reliable facial expressions through DI detections.	64
3.5	The sample images of AUs of interest.	66
4.1	Sample images showing the prototypic expressions.	77
4.2	Two sample images showing subtle changes in facial features.	78
4.3	Sample facial image shown with tracker points and extracted reference frame.	81
4.4	ROC performance curves for face expression biometrics on two databases.	89

CHAPTER 1

INTRODUCTION

The face is an important feature for the person identification and conveys significant social information. Due to the important role of face in social interaction, psychological processes involved in face perception are known to be present from birth, to be complex, and to involve large and widely distributed areas in the brain. The face is not only one of the first visual patterns infants learn to recognize, but it is also one of the natural means for human beings to recognize each other. For these reasons face processing, including but not limited to detection, tracking, modeling, analysis, and synthesis, has been a problem of prime interest in the fields of computer vision, biometrics, pattern recognition and machine learning for decades. Due to its nature of unobtrusiveness and ease of use, face has been one of the most successful biometric traits. This work provides new expansions in several directions in the field of face processing. We investigated the feasibility and performance of the two new face related biometric traits, facial skin mark and facial expression. We also proposed an unobtrusive approach in deceit detection utilizing face related information. These described approaches can be applied to enhance the existing biometric systems, and improve the practice of deceit detection for law enforcement, private investigators, etc.

The first part of this work is on the study of facial skin marks and the feasibility of their utilization as a biometric trait. This effort is further divided into two parts, one part is focused on developing a system that performs facial skin mark detection,

and the other part is focused on conducting tests of utilizing facial skin marks as biometric trait for personal identification.

In the second part of this work, we conduct an investigation of a system that detects deceptive instances of facial expressions, in an *unobtrusive* manner, by measuring several previously identified deceit indicators, based upon reliable facial expressions, through computer vision analysis of facial images.

The third part of this work is focused on the study of employing emotion expression face dynamics for the purposes of biometric person identification, and the statistical testing showed that such features can be utilized as a biometric trait for the task of person identification.

1.1 Motivation

Biometrics, the study of methods for uniquely recognizing humans based upon one or more intrinsic physical or behavioral traits, is gaining acceptance as the technology that can meet up with the ever increasing demands for security in critical applications such as forensic, government, and commerce. A biometric system automatically recognizes individuals based on certain biometric traits, either physiological or behavioral, or both. Therefore, the fundamental requirement for any biometric system is a single or a combination of human traits, such as fingerprint, face, hand-geometry, iris, retina, palm-print, ear, voice, gait, signature, keystroke dynamics, etc., that have several desirable properties [53]:

- Universality: each person should have the characteristic.
- Uniqueness: this is how well the biometric separates individually from another.
- Permanence: this measures how well a biometric resists aging.
- Collectability: ease of acquisition for measurement.

- Performance: accuracy, speed, and robustness of technology used.
- Acceptability: degree of approval of a technology.
- Non-circumvention: difficulty of producing fake substitutes.

However, a human trait that possesses all these seven properties has not been identified yet. As a result, none of the existing biometric recognition systems can provide perfect performance in recognition, which leaves a scope for further improving these biometric systems through different approaches, such as introducing new human biometric traits or information that could be applied to improve certain properties of some existing biometric trait.

The estimation of credibility of others is a task that all people engage in a daily basis, during normal social circumstance. Despite the daily practice, psychology research has shown that humans are generally bad at judging deceit or verity in others. The same credibility estimation process conducted by law enforcement, private investigators, and agents from border patrol, airlines, and other government and corporate officials requires more accuracy and effectiveness. Therefore, an automatic system that could aid humans in this judgment would be highly valuable and practical.

As one of the most widely utilized deceit detection systems, polygraph testing, or psychophysiological detection of deception examination, is proved to be reliable for this cause by measuring and recording several physiological responses, such as blood pressure, pulse, respiration and skin conductivity, while the subject is asked and answers a series of questions, on the basis that false answers will produce distinctive measurements. Several other technologies are also used in the field of lie detection, such as voice stress analysis, functional magnetic resonance imaging (fMRI), electroencephalography, and cognitive chronometry. However, the effectiveness and accuracy of these systems are waned by their overt and obtrusive approaches, which invites premeditated counter-measurements of the target subject. A covert system

could leverage the fact that the subject would be unaware that they are being scrutinized by a reliable deceit detector.

1.2 Problem Statement

The objective of this work is to explore and investigate different approaches to advance and improve the study of face biometrics, and expand the scope of face processing by incorporating face related information into the application of deceit detection. Three major directions were pursued in this thesis through integrating local facial skin texture and facial dynamics into these investigations.

Firstly, the study of employing facial skin mark information as a biometric trait for the purpose of biometric person verification was conducted. The results of the study on utilizing PCA models for the detection of facial skin marks as well as a novel combination algorithm of conventional biometric trait, face, and facial skin marks for the task of personal identification were presented.

Secondly, a system that could detect deceit unobtrusively by measuring several previously identified deceit indicators (DIs) based upon the involuntary, or reliable, facial expressions through computer vision analysis of facial images was proposed and developed. This approach recognizes and detects four reliable expressions, namely anger, enjoyment, fear, and sadness, by recognizing action units (AUs) associated with each of these expressions.

Finally, the last objective is to investigate the possibility of employing emotion expression face dynamics for the purposes of biometric person identification. In our experiments, we utilized the displacements of tracker points based on facial dynamics as our features, and the statistical testing demonstrated that facial expression was suitable for the task of personal identification.

1.3 Related Work

1.3.1 Face as a Biometric Trait

Facial images contain a significant amount of information including information about the identity, emotional state, ethnic origin, gender, age, and head orientation of a person shown in a facial image. This sort of information plays a significant role during face-to-face communication between humans. The use of facial information during interaction is made possible by the remarkable ability of humans to accurately recognize and interpret faces and facial gestures in real time. The ultimate question is that whether or not computers can also acquire the information from facial images with the similar accuracy. Therefore the ultimate goal is to make the computers to achieve the processing accuracy as close as possible to the human level.

Images containing faces are essential to intelligent vision-based human computer interaction, and research efforts in face processing, including face recognition, face tracking, pose estimation and expression recognition. However, for an automated face processing system, the very first step is always to detect and locate the faces in the given images. Many factors can make the seemingly easy task from the point of view of human being challenging, such as pose, lighting conditions, presence or absence of certain facial features (for example beards, mustaches, spectacles), facial expression, occlusion, image orientation, image condition, et al. [103]. Yang et al. [101] presented a hierarchical knowledge-based approach for the task of face detection. Similar rule-based approaches were seen in [59, 54]. Feature-based approaches were presented in [62, 47]. Algorithms based on template matching were presented in [28, 61]. Different appearance-based methods were presented: Eigenfaces [97], Active Appearance Models (AAM) in 2D [25], distribution-based [89], neural network [78], supporting vector machine (SVM) [84, 70], naive Bayes classifier [83], hidden Markov model (HMM) [74], information-theoretical based [23].

As one of the most successful applications of image analysis and understanding and the major part of face processing, face recognition has recently received significant attention being the research focus of a lot of research groups [109], especially during the past several years. Reasons for this trend include the wide range of commercial and law enforcement applications, and the availability of feasible technologies after over 30 years of research. Although, current face recognition systems have improved considerably, the performance of these systems is still far away from the capability of the human perception system. Most of the face recognition systems has been formulated as recognizing three-dimensional (*3D*) objects from two-dimensional (*2D*) images. Most of the face recognition algorithms can be divided into three categories following the guideline of the psychological study of how humans perceive faces: holistic matching methods [97, 8, 108], feature-based (or structural) matching methods [54, 80, 79], and hybrid methods [12].

1.3.2 Facial Expression

Facial expressions are the changes of facial appearance in response to a person's internal emotional states, intentions, or social communications. And facial expression is one of the most powerful, natural, non-verbal, and immediate means for human beings to communicate their emotions and express their intentions. It is faster for human beings to communicate their emotions through facial expressions than through verbalization, and people even communicate their expressions before they realize their own feelings.

The study of facial expressions was primarily a research subject for psychologists. However, with the advent of automatic face recognition and detection research pioneered by researchers like Pentland [97, 96] and Takeo Kanade [77, 78], the study of facial expressions to create automatic facial expression systems gained prominence. In the past couple of decades, a lot of research work [10, 11, 20, 32, 43, 46, 63, 76,

92, 106, 100, 99] has been conducted to investigate and implement computer systems that could understand and use this natural form of human communications with the accomplishments in the related areas such as psychological studies, human movement analysis, face detection, face tracking, and recognition make the automatic facial expression analysis possible. In 1978, Suwa et al. [90] presented an early attempt to analyze facial expressions automatically by tracking the motion of 20 identified spots on an image sequence. Mase and Pentland [68] pioneered the work in automatic facial expression recognition. They used the concept of optical flow estimation to observe and detect facial expressions. Essa and Pentland [43] used optical flow to create a mesh model of the face and used this face model to recognize different facial expressions.

The facial action units proposed by Ekman were used for automatic facial expression analysis by Tian et al. [94]. In their model for facial expression analysis first a facial feature tracking is performed to extract key points on the face, and, by using found key points, action units are recognized. Further, after applying a neural network, facial expressions are recognized. In [19], an HMM based classifier is used to recognize facial expressions based on geometric features extracted from a 3D model of the face. The use of appearance based model for feature extraction followed by classification using SVM-HMM is followed in [5]. Tian et al. [95] proposed a combination of appearance based and geometric features of face for automatic facial expression recognition system which uses Gabor filters for feature extraction and neural networks for classification. Abboud et al. [4, 3] propose a statistical model for facial expression analysis and synthesis based on Active Appearance Models (AAM) to model the face.

1.3.3 Deceit Detection

A lie, or called prevarication, is a type of deception in the form of an untruthful statement with the intention to deceive, often with the further intention to maintain a secret or reputation, to protect someone's feelings from getting hurt, or to avoid punishment. To lie is to state something one believes is false with the intention that it will be taken for the truth by someone else. The detection of deceit is the practice of determining whether someone is lying. Activities of the body not easily controlled by the conscious mind are compared under different circumstances. Usually this involves asking the subject control questions where the answers are known to the examiner and comparing them to questions where the answers are not known.

Being the most broadly used tool for deceit measurement, the polygraph is a limited method as it suffers from human operator subjectivity and the fact that subjects are aware of their measurement. This reduces performance because subject behavior changes, making their deceit or verity more difficult to measure, in addition to the fact that counter-measures can be planned in advance. Law enforcement and private investigators rely heavily upon the testimony of witnesses and suspects to solve criminal cases. Courts are centered upon the assumption that witnesses are credible. Agents from border patrol, airlines, and other government and corporate officials require accurate and truthful information from subjects in order to maintain proper safety for the benefit of society. Based upon analysis of face, voice and body behavior, training aids for humans to detect deceit have been developed in the psychology community. While these forms of training do increase humans' ability to detect deceit, humans are subjective and qualitative in nature.

Several research efforts are underway to replace humans with an automatic system for deceit detection. Buddharaju et al. [14] proposed a methodology to compute the average periorbital temperature signal utilizing thermal video images to generate an estimate of stressful (deceptive) or non-stressful (non-deceptive) subjects on a

large and realistic mock-crime interrogation experiment. While a promising area of research, it requires thermal video equipment, which is expensive and could potentially limit broad deployment. Lu et al. [66] presented a method of blob analysis for analyzing the movement of the head and hands based on the identification of skin color, and a proof-of-concept study of accessing behavioral indicators of deception and behavioral state based on the blob analysis of the head and hands was conducted. For their system to be able to screen and detect the behavioral state of people, an automated, near real-time system is necessary, which incurred challenges related from both software and hardware issues. The work seen in [87] and other efforts leveraging similar modalities, require active sensing, which could possibly be detected and counter-measured by the subject.

During the research in psychology of facial behavior, Ekman et al. [42] found that while culture and society affect voluntary use of facial expression, there exist expressions that arise as a result of inner felt emotion, and are thus involuntary. Naturally, these facial behaviors transcend culture, sex, and age. It was postulated that if voluntarily arising expressions are visibly different from those expressions arising from involuntary triggers, a contradiction can be detected, and deceit can be inferred.

1.4 Outline of the Dissertation

The rest of the dissertation is organized as follows.

In Chapter 2 we present the results of the study of facial skin marks, mainly nevi or other small scale structures of freckles, scars, etc. We describe our work on building a facial image dataset with ground truth of facial skin marks and performing statistical analysis of facial skin marks. A facial skin mark detection algorithm based on PCA modeling was proposed and developed, where two PCA models were constructed for local facial skin patches - the PCA model trained on facial skin patches with facial skin marks in the center and the PCA model trained on facial skin patches

with no skin marks in the center. A framework of utilizing facial skin marks as a biometric trait was proposed with two different approaches - one employing facial skin marks as sole biometric trait for the task of personal identification and the other one combining facial skin marks with one conventional biometric trait, developed and through experiments, facial skin mark showed a less perfect property of universality, which was improved by the combined approach.

In Chapter 3, an unobtrusive approach for deceit detection based on measuring several prior identified deceit indicators that involved involuntary, or reliable, facial expressions through computer vision analysis of image sequences was proposed and developed, which can recognize and detect four reliable facial expressions by recognizing action units (AUs) associated with each of these expressions. The system was evaluated on a dataset of verified video data.

In Chapter 4, an investigation of the possibility of utilizing the information of face expression for the purpose of personal identification was proposed and developed with the assumption that the emotional face expressions of a person are repeatable, therefore this information can be applied for personal identification. Features of displacements of tracker points, instead of person specific geometric or textural features traditionally employed in face biometrics, were utilized. The statistical testing on two datasets showed promising performance.

Finally, Chapter 5 contains the summary of our work and contributions made in this dissertation.

CHAPTER 2

FACIAL SKIN MARKS AS BIOMETRICS

In this chapter, we investigate the application of facial skin mark information for the task of biometric person verification and also present an algorithm for the detection of facial skin marks based on principal components analysis (PCA) modeling of local facial skin patches.

For the task of utilizing facial skin mark information for biometric verification, the position, size and color intensity of the facial skin marks are considered and represented as features for facial skin mark based face matching algorithm. The proposed and implemented matching algorithm based on biometric trait of facial skin marks has good performance on facial images with some facial skin marks detected, but cannot be applied to faces with no detected facial skin marks. Due to the property of non-universality of facial skin mark information as a biometric trait, a novel combination algorithm that combines traditional biometrics, Eigenfaces algorithm, and facial skin mark matching algorithm has been proposed and implemented. The resulting combined face matching algorithm has universality property and delivers better performance than either of these two matching algorithms alone.

For the task of detecting facial skin marks, we proposed and implemented an algorithm to detect facial skin marks by utilizing principal component analysis of local facial skin patches. We construct two types of PCA models, one for the facial skin patches with no facial skin marks and one for the facial skin patches with facial skin marks. Additionally, we consider different ways of calculating distances between original facial skin patches and the corresponding PCA models. The experiments

showed good performance of proposed skin mark detection method and the possibility of its incorporation into traditional face recognition models and algorithms.

For the purpose of training and testing of the aforementioned systems, we built a dataset that contains ground-truthed information of facial skin marks of all the facial images from publicly available dataset - the AR Face Database [67]. Statistical analysis of the facial skin mark information was also conducted on the facial skin mark dataset as the basis of this part of work.

2.1 Introduction

2.1.1 Face Processing

As one of the first visual patterns infants learn to recognize, face is also one of the natural means for human being to recognize each other. For this reason and several others, face processing, including but not limited to detection, tracking, modeling, analysis, and synthesis faces, has been a problem of prime interest in the fields of computer vision, biometrics, pattern recognition and machine learning for decades. Due to its nature of unobtrusiveness and ease of use, face has been one of the successful biometric traits.

Images containing faces are essential to intelligent vision-based human computer interaction, and research efforts in face processing, including face recognition, face tracking, pose estimation and expression recognition. However, for an automated face processing system, the very first step is always to detect and locate the faces in the given images. Many factors can make the seemingly relatively easy task from the point of view of human being challenging, such as pose, presence or absence of certain facial features (for example beards, mustaches, spectacles), facial expression, occlusion, image orientation, image condition, et al. [103]. Yang et al. [101] presented a hierarchical knowledge-based approach for the task of face detection. Similar rule-based approaches were seen in [59, 54]. Feature-based approaches were presented in [62,

29, 58, 102, 104, 69, 47]. Algorithms based on template matching were presented in [28, 61]. Different appearance-based methods were presented: Eigenfaces [97], Active Appearance Models (AAM) in 2D [24, 27, 33, 25, 26, 31], distribution-based [89], neural network [78], supporting vector machine (SVM) [84, 70], naive Bayes classifier [83], hidden Markov model (HMM) [74], information-theoretical based [23].

As the major part of face processing, face recognition has been the research focus of a lot of research groups [109], especially during the past several years. Reasons for this trend include the wide range of commercial and law enforcement applications, and the availability of feasible technologies after over 30 years of research. Although, current face recognition systems have improved considerably, the performance of these systems is still far away from the capability of the human perception system. Most of the face recognition systems has been formulated as recognizing three-dimensional (3D) objects from two-dimensional (2D) images. Most of the face recognition algorithms can be divided into three categories following the guideline of the psychological study of how humans perceive faces:

- *Holistic matching methods.* The whole face region is used as input to the system.
- *Feature-based (or structural) matching methods.* Local features, such as the eyes, nose and mouth are extracted and their locations and local statistics are used as input to the system.
- *Hybrid methods.* Combine the first two systems to mimic the human perception system.

Well known holistic matching methods include the successful low-dimensional reconstruction of faces using Karhunen-Loeve (KL) or principal components analysis (PCA) [57, 85, 97], and Fisherfaces or LDA/FLD [8, 44, 91, 108, 107], et al. Feature-based methods include methods based on geometry of local features [54, 56], and

1D [80] and pseudo-2D [79] HMM methods, et al. Examples of hybrid methods include modular Eigenfaces approach [72], and the Morphable Model in 3D [12], et al.

2.1.2 Soft Biometrics

Primary biometric traits based on physiological or behavioral characteristics of human being, such as fingerprint, face, hand-geometry, retina, palmprint, voice, gait, signature, and keystroke dynamics, are widely utilized for the task of person recognition [50]. Jain et al. [52] proposed the utilization of “soft” biometric traits to complement the identity information provided by the primary biometric identifiers, and the definition of soft biometric traits was given as “characteristics that provide some information about the individual, but lack the distinctiveness and permanence to sufficiently differentiate any two individuals”. Gender, height, weight, age, and ethnicity are some examples of the common characteristics of human that can be regarded as soft biometrics.

Wayman [98] proposed the utilization of such soft biometric traits for filtering large biometric database. In [50], a framework based on the Bayesian decision theory for integrating the soft biometric information with the output of the primary biometric system. We have demonstrated that the utilization of ancillary user information like gender, height, and ethnicity can improve the performance of the traditional biometric systems like fingerprint.

According to the definition of soft biometric traits, scars, marks, and tattoos can also provide *some* information about the individual, and the information may not be sufficient to identify human beings just like the features utilized in the personal identification system developed by Alphonse Bertillon [9] for identification of criminals. Although in nature, these soft biometric characteristics are not as permanent or reliable as the traditional biometric identifiers, such like fingerprint, they can certainly

provide some information about the identity of the user that leads to higher accuracy in establishing the user identity. However, an optimum weighting scheme based on the discriminative abilities of the primary and the soft biometric traits is needed to achieve an improvement in recognition performance.

2.1.3 Scars, Marks, and Tattoos

Scars are areas of fibrous tissue that replace normal skin or other tissue after injury. A scar results from the biologic process of wound repair in the skin and other tissues of the body. Skin scars occur when the deep, thick layer of skin, or the dermis, is damaged. The worse the damage is, the worse the scar will be. Therefore, scarring is a natural part of the healing process. With the exception of very minor lesions, every wound, for example after accident, disease, or surgery, results in some degree of scarring.

Tattoos are permanent markings made by inserting ink into the layers of skin to change the pigment for decorative or other reasons. Except tattoos on animals, which are mainly used for identification or branding, tattoos on humans are a type of decorative or spiritual body modification that could serve as purposes of rites of passage, marks of status and rank, symbols of religious and spiritual devotion, decorations for bravery, sexual lures and marks of fertility, pledges of love, punishment, amulets and talismans, protection, and as the marks of outcasts, slaves and convicts.

There are other skin marks, such as moles, freckles, birthmarks, which are related with melanin. In humans, melanin is the primary determinant of human skin color and also found in hair, the pigmented tissue underlying the iris, the medulla and zona reticularis of the adrenal gland, the stria vascularis of the inner ear, and other parts. Human skin has pigmentation or melanin to absorb some of the potentially dangerous ultraviolet radiation in sunlight. A localized concentration of melanin in the skin can form into a mole or a freckle, technically known as a *melanocytic naevus*.

The idea of using tattoos for criminal identification can be traced back to Cesare Lombroso [65], who placed heavy emphasis on the widespread prevalence of tattoos [7]. Bertillonage, a criminal identification system based on anthropometry [75], included individual body markings of moles, tattoos, and scars. In the study of Burma in 1959 [16], tattoos were considered a source of information for determine gang membership. It is now a common practice for law enforcement agencies to photograph and catalog scars, tattoos and marks (SMT) as part of the Computerized Criminal History (CCH) record. To ensure the uniformity in the capture and exchange of data on SMT, in 1993, the document of the ANSI/NIST-ITL 1-2000 [2] was released by American National Standards Institute (ANSI) with classification standards for data of Scar, Mark & Tattoo (SMT).

For facial regions, tattoos are rare relative to other body parts, and skin marks other than tattoos are more common. Nevi or other small scale structures, such as freckles or scars, have different appearance from normal facial skin regions. Information of these facial skin irregularities have been shown useful by law enforcement agencies for purpose of person identification. With their relatively stable appearance, these irregularities, especially prominent moles, freckles or scars, in the face region present potential valuable information, and therefore can greatly facilitate the task of face recognition. This information can also be utilized for indexing large face image databases. Queries like “*show all the faces with one prominent mole near the right corner of the left eye*” can greatly narrow down the search space in a large database.

2.1.4 Related Work

Most of the current face recognition systems are designed to process faces holistically. One of the most prominent examples of holistic matching algorithms, the Eigenfaces approach [97], which introduces PCA on the raw image data to reduce feature dimension, therefore implicitly treats local variations as noise. Similar approaches in-

clude Fisherfaces [8]. Other model based systems, such as Active Appearance Model in $2D$ [25], or the Morphable Model in $3D$ [12] use PCA to model intra-class variations. Small unexpected details cannot be captured by these methods. Many existing algorithms utilize textons, DCT coefficients or Gabor wavelet features to represent local facial skin information, but there are no explicit representations of facial skin marks.

A couple of groups of researchers have focused their work on exploiting facial skin marks. The work by Lin et al. [64] utilizes a multilayer representation of a face with global appearance, facial features, skin texture and irregularities. A SIFT framework is utilized to detect and describe details of irregular skin regions, which are combined into an elastic graph for recognition. Based on the $3D$ Morphable Model developed in [12], the work of Pierrard et al. [73] presented a framework to localize prominent skin irregularity, mainly moles, in facial skin regions. Their system detects potential moles with a sensitive multi-scale template matching algorithm. Using skin segmentation and local saliency measurement, the candidates are filtered based on their discriminative potential.

Jain et al. [51] designed and built a prototype content-based tattoo image retrieval system that computes the similarity scores between the query and stored templates based on image content, such as shape, color and texture, and retrieves the most similar tattoo images from the database. Ivanov et al. [48] introduced a technique of classifier combination used in a human identification system, which allows representing a class of popular classifier combination rules and methods within a single formalism.

	Number of subjects	Number of images
Female	55	110
Male	65	130

Table 2.1. The facial skin marks dataset built on The AR Face Database.

2.2 Study of Facial Skin Marks

2.2.1 Facial Skin Mark Dataset

No public dataset of skin marks, especially facial skin marks, was found. Instead, generic face databases have to be considered. In this part of work, *The AR Face Database* [67] was utilized to build a facial skin mark dataset. The advantage of this public available dataset is that most of the subjects of the 60 females and 76 males had two sessions of images taken, with two weeks in between these sessions, which provides possible changes of appearance in the facial skin regions of the same subject, such as changes of make-up, facial hair, facial skin irritations (for example acne, razor burns), and spectacles et al. Based on these changes, the characteristics of facial skin marks, especially intra-class stability, can be analyzed in certain extend.

In this part of work, we build a facial skin mark dataset on the frontal images with neutral expression of each subject in the AR face database, as shown in Table 2.1. 240 images of 120 subjects in total were included in this dataset with exactly 2 images per subject.

The purpose of building this dataset of facial skin marks is to set up a dataset with *ground truth* instead of just utilizing a template matching scheme, therefore we introduced human intervention by following a semi-automatic approach for this purpose. First, all the images were studied by human observer closely in the full size and then one seed pixel for each facial skin mark was labeled manually. The inner eye corners of each face in the images were also marked for reference purpose. Figure 2.1 shows an example of the result of this process with each blue dot centered at the




Figure 2.1. Examples of one image in The AR Face Database with its facial skin marks, including moles and scars, and inner eye corners labeled, shown in blue dots.

corresponding seed pixel. These information were then stored in a meta file for later usage. All of the 240 facial images aforementioned images were processed accordingly.

2.2.2 Statistical Analysis

With the ground-truthed dataset, statistical analysis was done on the characteristics of facial skin marks, especially their universality and intra-class stability.

A total number of 1963 facial skin marks, including moles, scars, and other prominent skin irregularities were found. Figure 2.2 shows the histogram of the number of facial skin marks in each of the available facial images in the facial skin mark dataset we built. As shown in Table 2.2, the minimum number of facial skin marks in one facial image is 0, while the maximum number is 37 with a standard deviation of 5.5. Figure 2.3 shows examples of these two extreme cases with one case showing a face with 35 skin marks and the other one with no skin mark showing at all. From Figure 2.2, we can conclude that these extreme cases happen far less frequently compared




Figure 2.2. Histogram of numbers of skin marks labeled for all the images in the facial skin mark dataset.

	Number of facial skinmarks for all the facial images	Intra-class differences in number of facial skin marks
Min	0	0
Max	37	10
Average	8.2	1.7
Stdev	5.5	1.7

Table 2.2. Statistics of the number of facial skin marks in all the facial images and the intra-class differences in number of facial skin marks for all the subjects.

with the cases where number of facial skin marks lies between these two numbers. The total number of facial images that contain 3 to 12 facial skin marks comprises 74.5% of all the available images. And 98.8% of all the available facial images have at least one facial skin mark.

Intra-class differences are measured by calculating the differences between the number of facial skin marks of the two images from the same subject. The right column in Table 2.2 summaries the analysis on this matter. Within the 120 subjects, the minimum intra-class difference is 0, while the maximum difference is 10, with the average of 1.7 and the standard deviation of 1.7. Causes of this discrepancies could be one or more of the following conditions:

- Occlusion caused by change of
 - Hair
 - Facial hair
 - Cosmetics
 - Spectacles, et al.
- Short term changes of skin appearance caused by
 - Acne
 - Freckles



Figure 2.3. Extreme cases of images in the facial skin mark dataset. The image on the left hand side shows 35 skin marks in the face region, while the image on the right hand side shows 0 facial skin marks.

- Razor burns, et al.
- Environment changes such as changes of lighting.

Proper compensation can be done to eliminate environment changes to certain level. However, it is rather difficult a task to counteract the other changes since the appearance of facial skin region changes over time. Among types of facial skin marks, moles and scars are more stable than small dark regions caused by acne, freckles, razor burns or other skin irritations, however, it is difficult to recognize them completely separately since they all tend to have the similar appearance in contrast to their surrounding normal skin regions.

Although, this analysis of facial skin marks was only conducted on a dataset with limited size, it can, to some extend, be used to justify the characteristics of facial skin marks as a potential biometric trait. First, the universality of facial skin marks is satisfying with over 90% availability. In order to test the intra-class stability, experiments were conducted and results were shown in Section 2.4.

2.3 Detection of Facial Skin Marks

In this part of work, an algorithm based on principal components analysis (PCA) for detection of facial skin mark was introduced and implemented. The main difficulty in constructing this facial skin mark detection algorithm is that there usually exists only a subtle difference between facial skin marks and the surrounding normal skin. Additionally, variations in the background normal skin regions can be significant due to the gradients in illumination and skin reflectance. In order to account for changes in illumination of surrounding skin, Pierrard and Vetter [73] model the logarithm of local neighborhood image brightness as a quadratic function. The differences between original images and fitted image models are accumulated and utilized for facial skin mark detection.

2.3.1 PCA Models of Skin Patches

In our work we model the local skin patches using principal components analysis (PCA). The idea is similar to utilizing PCA for face detection [97, 96]:

- 1. Train a PCA model on a given set of facial images.
- 2. For an unknown image, calculate the distance between it and its PCA projection.
- 3. Determine whether this unknown image is a facial image by judging this distance.

Similarly, we can utilize PCA to model a facial skin patch surrounding a facial skin mark as shown in Figure 2.4. In our approach, only the center region in each of the facial skin patches was considered for the purpose of facial skin mark detection, i.e. either there is a facial skin mark in the center region of the testing facial skin patch or there is no facial skin mark. Therefore, in order to emphasize the distance between facial skin patches with facial skin marks in the center and facial skin patches




Figure 2.4. Two levels of facial skin patches constructed for one facial skin mark. The big facial skin patch enclosed by white square is the facial skin patch utilized for PCA modeling, and smaller facial skin patch enclosed by gray square is the facial skin patch utilized for skin mark detection.

with no facial skin marks in the center, two levels of patching were introduced in this part of work, namely facial skin patches for PCA modeling and facial skin patches for detection of facial skin marks, as shown as two squares of different sizes in Figure 2.4. The PCA models were constructed on facial skin patches for PCA modeling, while, when calculating the distances between the original facial skin patch and its PCA projection, only the central regions in these patches, i.e. the facial skin patches for detection of facial skin marks, were considered and utilized. The closeness of original patch to its PCA projection calculated in the aforementioned manner would indicate whether the testing facial skin patch contains facial skin mark in its center region.

Since there are basically two types of facial skin patches extracted, namely facial skin mark patches (facial skin patches with facial skin marks in the center regions)




Figure 2.5. PCA modeling of facial skin patches containing facial skin marks in the center regions. The first row shows the original facial skin patches, the second row shows the corresponding reconstructed facial skin patches from PCA_{SM} , and the third row shows the corresponding reconstructed facial skin patches from PCA_{NS} .

and normal facial skin patches (facial skin patches with no skin marks in the center regions), two different PCA models were constructed accordingly - the PCA model for facial skin patches with skin marks (PCA_{SM}), and the PCA model for facial skin patches with no skin marks (PCA_{NS}). Figure 2.5 and Figure 2.6 demonstrate some examples of original facial skin patches of these two types and their projections to both of these PCA models just mentioned.

The first row in Figure 2.5 shows some examples of facial skin patches with facial skin marks in the center regions. And the second row shows the reconstructed facial skin patches from the PCA model trained with facial skin mark patches, where small dark areas can be observed in the center of these patches. The third row shows the reconstructed facial skin patches from PCA trained with normal facial skin patches, where the existing skin marks are almost smoothed out entirely. The first row in Figure 2.6 shows some examples of normal facial skin patches with no facial skin




Figure 2.6. PCA modelings of facial skin patches containing no facial skin marks in the center regions. The first row shows the original facial skin patches, the second row shows the corresponding reconstructed facial skin patches from PCA_{SM} , and the third row shows the corresponding reconstructed facial skin patches from PCA_{NS} .

marks in the center regions. The second row shows the reconstructed facial skin patches from PCA trained with facial skin mark patches, where small dark area can be observed in the center of these patches. The third row shows the reconstructed facial skin patches from PCA trained with normal facial skin patches, and this row is almost identical to the original facial skin patches in the first row.

It can be noted from these example images that the two trained PCA models PCA_{NS} and PCA_{SM} indeed differ from each other. PCA_{NS} seems to be able to smooth out the center regions of the patches, and if there was a facial skin mark presented at the center of the facial skin patch, it would be eliminated by this projection. On the other hand, PCA_{SM} seems to be able to reconstruct a facial skin mark (a darker region) at the center regions of the patches, even if there was no facial skin mark in the original facial skin patches. Both of these two PCA models seem to be efficient at representing the brightness of the image outside the center regions.

2.3.2 Distances between Skin Patches and PCA Models

For this part of work, in order to detect facial skin marks, a proper distance measure has to be utilized to provide good discrimination between facial skin patches with facial skin marks in the center regions and facial skin patches without facial skin marks in the center regions.

Let us denote the original facial skin patch as $I(x, y)$, its projection to PCA_{NS} subspace as $I_{NS}(x, y)$, and its projection to PCA_{SM} subspace as $I_{SM}(x, y)$. One method to calculate the distance between the original image and its projections is to use the Euclidean distances [97]:

$$\begin{aligned} Dist_{Euc}^2(I, I_{NS}) &= \|I(x, y) - I_{NS}\|^2 = \sum_{(x, y)} (I(x, y) - I_{NS}(x, y))^2 \\ Dist_{Euc}^2(I, I_{SM}) &= \|I(x, y) - I_{SM}\|^2 = \sum_{(x, y)} (I(x, y) - I_{SM}(x, y))^2 \end{aligned} \quad (2.1)$$

After initial experiments, we concluded that distances calculated based on Equation 2.1 do not provide good discrimination between facial skin patches with facial skin marks in the center regions and facial skin patches without facial skin marks in the center regions. In order to improve this desired discrimination, two different directions were explored in this part of work:

- Restricting the distance calculation to a smaller window in the center of the facial skin patches.
- Testing alternative distance calculations.

Figure 2.4 shows one example of a larger facial skin patch utilized for performing PCA projections and a smaller facial skin patch utilized for calculating the distances to the PCA projections for one facial skin mark. Note these two facial skin patches are all in square shape, and the sizes of these two facial skin patches can be set to any reasonable values according to the resolution of the given facial images. Most

importantly, the ratio of the sizes of these two facial skin patches can also be altered, and the facial skin patch utilized for calculating the distances can be the same size of the facial skin patch utilized for conducting PCA projections, which degraded to the approach in Equation 2.1.

Among additional distance formulas, two distance measurements were considered: absolute distance (same as Manhattan distance) as shown in Equation 2.2, and signed distance as shown in Equation 2.3.

$$\begin{aligned} Dist_{Abs}(I, I_{NS}) &= \sum_{(x, y)} |I(x, y) - I_{NS}(x, y)| \\ Dist_{Abs}(I, I_{SM}) &= \sum_{(x, y)} |I(x, y) - I_{SM}(x, y)| \end{aligned} \quad (2.2)$$

Signed distance is not technically a distance, but it is rather a measurement that was utilized in this part of work for making a decision on whether one facial skin mark can be detected in the testing facial skin patch. Note, that the measurement of signed distance is equivalent to the difference between the average pixel values in the original facial skin patch and the average pixel values in the PCA reconstructed facial skin patch.

$$\begin{aligned} Dist_{Sgn}(I, I_{NS}) &= \sum_{x, y} (I(x, y) - I_{NS}(x, y)) \\ Dist_{Sgn}(I, I_{SM}) &= \sum_{x, y} (I(x, y) - I_{SM}(x, y)) \end{aligned} \quad (2.3)$$

$$\begin{aligned} S_{Abs} &= \omega_1 \times Dist_{Abs}(I, I_{NS}) + \omega_2 \times Dist_{Abs}(I, I_{SM}) \\ S_{Sgn} &= \omega_1 \times Dist_{Sgn}(I, I_{NS}) + \omega_2 \times Dist_{Sgn}(I, I_{SM}) \end{aligned} \quad (2.4)$$

Although, it is feasible to utilize just a single PCA model, for example PCA_{NS} , and one corresponding distance measurement, for example $Dist_{Abs}(I, I_{NS})$ for the task of detecting the presence of facial skin marks, we found that it is advantageous to utilize both of the two PCA models, PCA_{NS} and PCA_{SM} , and to combine their distance measurements into one classification score S for making the final decision. In this part of work, a simple weighted sum combination method was adopted, and score calculation formulas based on these two distance measurements are shown in

Equation 2.4. The weights, ω_1 and ω_2 , were chosen so that the equal error rate (EER) is minimized for the system.

2.3.3 Experiment and Discussion

2.3.3.1 Skin Patch Dataset

In order to train and test our facial skin mark detection system, a dataset that has images of both facial skin patches with facial skin marks and facial skin patches without facial skin marks was required. As discussed in Section 2.2.2, 1963 facial skin marks, including moles, scars, and other prominent skin irregularities, in total, were labeled from all the facial images in the facial skin mark dataset. In this part of work, for each located facial skin mark, the facial skin patches surrounding these facial skin marks were cropped and saved as facial skin mark images for subsequent training and testing of aforementioned facial skin mark detection algorithm. In addition to saving facial skin patches with labeled facial skin marks, patches of smooth skin that does not contain any facial skin marks were also randomly selected, cropped and saved as smooth skin images. In total, 1020 smooth skin images were available for the purpose of training and testing of the aforementioned system.

2.3.3.2 Experiment of Detecting Facial Skin Marks

Extensive experiments were conducted with various combinations of different distance measurements between original facial skin patch images and their PCA projections, different sizes of PCA modeling and distance calculation facial skin patches, and different numbers of principal components in the PCA models.

After automated brute force searching for the combination of different solutions, the best system performance with regards to best equal error rate has been achieved utilizing the following system and parameter settings, or the column denoted as “SA” in Table 2.3:

- Size of facial skin patches for PCA modeling: 29×29 pixels.

Settings	SA	SS	FA	FS
Size of patches for PCA modeling	29 × 29 pixels			
# of eigenvectors in the PCA models	11			
Size of patches for distance calculation	9 × 9 pixels		29 × 29 pixels	
Distance measurement	Absolute	Signed	Absolute	Signed

Table 2.3. Four different experiment modes under various system and parameter settings.

- Number of eigenvectors in the PCA models: 11.
- Size of facial skin patches for distance calculation: 9 × 9 pixels.
- Distance measurement: Absolute distance formula.

The ROC curve of this system setting is shown as a curve in dashed line in Figure 2.7, or “Small patch, absolute distances”. For the purpose of comparison, other three ROC curves were shown in Figure 2.7 as well, and the system and parameter setting choices of these experiments are shown in Table 2.3, with “SS” corresponding to the ROC curve in solid line, “FA” corresponding to the ROC curve in dash dot dash line, “FS” corresponding to the ROC curve in dotted line. Note, that all these ROC curves are constructed utilizing the final combined scores S_{Abs} and S_{Sgn} as shown in Equation 2.4.

It is interesting to note that the ROC curves corresponding to signed distance calculation have strange behavior in the low FRR and high FAR regions. This behavior can be explained by the presence of facial skin marks, where pixels are of lower intensity in color than the surrounding normal skin pixels. The absolute distance calculation seems to have an adequate handling of such cases. On the other hand, signed distances might have better performance in the low FAR and high FRR regions.




Figure 2.7. ROC curves for different facial skin mark detection scenarios. System and parameter settings details are shown in Table 2.3.

2.3.3.3 Discussion

The presented algorithm is based on PCA modeling of local skin patches and thus follows the traditional strategy applied in models like AAM [25] or 3D Morphable Model [12] of faces. Therefore, it might be possible to directly incorporate facial skin mark approach in these existing models by expanding the number of landmark points to include facial skin marks. It could be a good direction to alter and expand such models by creating person specific models that incorporate facial skin marks for the task of person authentication.

2.4 Facial Skin Marks as Biometric Trait

To verify the feasibility of using facial skin marks alone to perform personal identification, one framework was proposed as shown in Figure 2.8. Facial images are enrolled by processes of face segmentation, facial skin marks detection, and feature extraction for all the detected marks, then the features are stored into the database. For a probe image, the similar process would be conducted to extract its features, then the probe features would be matched against all the records in the database. Finally, the match with the highest score would be returned as identification result.

2.4.1 Feature Presentation of Facial Skin Marks

Based on the seed pixel manually labeled for each facial image in the facial skin mark dataset, a region growing algorithm was utilized on each of region of interest that contains one of the facial skin marks, so that each of the facial skin marks would grow from one pixel into a patch containing a group of pixels that have similar intensity. After the region growing algorithm, the centers of the facial skin marks were re-calculated accordingly. This step is necessary because the manual process of seed pixel labeling may not be very accurate due to human operation and intervention, and the seed pixels may not be at the centers of each facial skin mark.




Figure 2.8. The framework of personal identification system utilizing facial skin marks as sole biometrics.

Two types of features were defined for facial skin marks in this part of work, namely *distance feature* and *local features*. For the distance feature, one polar coordinate system was built on each facial image. The middle point of the two inner eye corners, O , was designated as the pole and the ray from O to the left corner of the right eye was designated as polar axis. Then, the distance feature of each facial skin mark, M_i , can be represented by the polar coordinates of its newly calculated center point, (r_i, θ_i) . Two local features were introduced in this part of work, namely the area of the facial skin mark, A_i , and the average intensity of all the pixels included in this skin mark, I_i , for facial skin mark M_i .

2.4.2 Matching Algorithm

Since it is possible even for the images of the same subject to have different number of facial skin marks extracted, the matching of any two facial images based on facial skin marks could easily result in matching N facial skin marks in one image against M facial skin marks in the other image, where $N \neq M$. In order to match two facial images, G_1 and G_2 , based on their facial skin marks, we introduced the following matching algorithm.

For the i^{th} facial skin mark in G_1 , and for the j^{th} facial skin mark in G_2 , the weighted distance between these two facial skin marks is calculated as:

$$D_{i, j} = \sqrt{\sum_{f=1}^{fn} (\omega_f \times Dist(F_{i, f}, F_{j, f}))^2}, \quad \begin{array}{l} 0 \leq i < M \\ 0 \leq j < N \end{array} \quad (2.5)$$

In Equation 2.5, fn is the number of features for each facial skin mark, and as aforementioned, there are 3 features defined for each skin mark in this work. ω_f is the weight for the f^{th} feature, with

$$\sum_{f=1}^{fn} \omega_f = 1 \quad (2.6)$$

$Dist(F_i, F_j)$ calculates the distance between two features F_i and F_j . Depending on the type of these features, $Dist(F_i, F_j)$ could stand for Euclidean distance or simple subtraction of these two features. If this $D_{i, j}$ is smaller than a preset threshold, then these two facial skin marks are considered matched. After processing all the possible matching pairs of facial skin marks in G_1 and G_2 , the number of matches, $N_{matches}$, are counted. Then the final matching score of matching these two images is calculated as shown in Equation 2.7.

$$S = \frac{N_{matches}}{N_{matching_pairs}} \quad (2.7)$$

If this score S is higher than a threshold, then these two images are considered matched, otherwise not matched. Another scenario need to be considered is when at least one of the matching faces has no or too few facial skin marks detected. A flag was introduced for these cases, where the flag would be set to “*FAIL*”. For normal cases, where the two matching faces both have enough number of facial skin marks detected, this flag is set to “*OK*”.

2.4.3 Combined Biometrics of Facial Skin Mark and Face

None of the biometric traits currently deployed for practical systems or studied for research purposes has perfect characteristics on all the 7 properties of biometric traits as mentioned in Section 1.3.1. Based on the statistical study on facial skin marks discussed in Section 2.2, one of the prominent weak points for facial skin mark as a potential biometric trait is that it does not has a perfect universality property. Therefore, for a certain percentage of population, facial skin mark may not work as a biometric trait due to various reasons, such as natural smooth skin, lighting conditions, or heavy cosmetic makeups. In order to solve this problem, we proposed to combine facial skin mark with another biometric trait with a better property

of universality. In this part of work, we chose face biometrics, more specifically Eigenfaces [97, 96] approach was adopted as face recognition method.

The major problem, which needed to be solved, is how to combine two different recognition systems for these two biometric traits. In this part of work, we employed the weighted sum combination method to combine the scores produced by the Eigenfaces matching algorithm and facial skin mark matching algorithms. Usually this combination method has reasonably good performance [48], but the weights should be trained with the help of training data. Since not all faces possess skin marks and skin mark matching score cannot be calculated for these facial images, we need to provide a separate processing for such cases. The general structure of the combination algorithm is shown in Figure 2.9.

The system has two execution branches depending on whether both matching facial images have skin marks detected. If there are no skin marks in either of these images, we can only employ Eigenfaces matching algorithm. The Eigenfaces matching score, $S_{Eigenfaces}$, will be calculated and the system would accept verification of these two matching facial images if the Eigenfaces matching score is greater than a predefined threshold, θ_E , as shown in Equation 2.8.

$$S_{Eigenfaces} > \theta_E \tag{2.8}$$

If both of these matching facial images have facial skin marks detected, two matching processes will be conducted on these images, and two sets of matching scores, the Eigenfaces matching score, $S_{Eigenfaces}$, and the matching score from the facial skin mark matching algorithm, $S_{SkinMark}$ will be calculated. Then, the system would accept verification of these two matching facial images if the weighted sum of these two scores is greater than a predefined threshold, θ_C , as shown in Equation 2.9.

$$\omega \times S_{Eigenfaces} + (1 - \omega) \times S_{SkinMark} > \theta_C \tag{2.9}$$




Figure 2.9. The framework of personal identification system utilizing combination of biometrics of facial skin marks and face. Eigenfaces approach was adopted as recognition algorithm for biometrics of face.

The particular choice of operating parameters ω , θ_E , and θ_C will result in specific values of FAR and FRR for this combined system of facial skin mark and Eigenfaces. $\{\omega, \theta_E, \theta_C\}$ was introduced as a choice of combinations of all these three operating parameters, and different choice of combinations of these parameters may result in different system performance in term of false rejection rate (FRR) and false acceptance rate (FAR). We regard the choice of a set of parameters $\{\omega, \theta_E, \theta_C\}_O$ locally optimal, if the performance of the corresponding system is optimal or its FAR (FAR_O) and FRR (FRR_O) are optimal, i.e. no other set of parameters $\{\omega, \theta_E, \theta_C\}_i$ delivers better system performance in terms of FAR (FAR_i) and FRR (FRR_i), as shown in Equation 2.10.

$$\{\omega, \theta_E, \theta_C\}_O \text{ is optimal, when } \begin{cases} FAR_O \leq FAR_i \\ FRR_O \leq FRR_i \end{cases}, \quad \forall \{\omega, \theta_E, \theta_C\}_i \quad (2.10)$$

With the set of locally optimal values FAR_O and FRR_O , one ROC curve can be produced for the combined system of facial skin mark and Eigenfaces with optimal combinations of these types, as shown in Figure 2.9. Note that different points on the produced ROC curve will generally represent a combined system with different value combinations of these parameters: ω , θ_E and θ_C .

The presented combination algorithm in this part of work is different from both serial and parallel combination architectures investigated previously in the field of classifier combination. It is also different from combination methods that are based on classifier selection methods. The difference stems from the fixed branch selection which is determined by the presence of skin marks in matching pair of input facial images. We can name this type of combination as “*branch combinations*”.

From the implementation point of view, the training of the presented combination method might rely on exhaustive search for locally optimal pairs of (FAR , FRR)

with respect to these system parameters of ω , θ_E and θ_C . In this part of work, we applied some additional optimizations for this search: efficient calculation of FAR and FRR based on sorted arrays of genuine and impostor matching scores and utilizing discrete nature of calculated FAR and FRR determined by the limited number of total training samples.

2.4.4 Experiment and Result

Two set of experiments were conducted in this part of work. One set of experiment is utilizing facial skin marks as sole biometric trait to perform personal identification. The other is utilizing the combination of facial skin marks and a conventional face recognition algorithm, Eigenfaces algorithm, to perform person identification. For these two sets of experiment modes, the facial skin mark dataset, as mentioned in Section 2.2, was utilized, and of the two images of each subject, one is taken as a gallery image and the other as a probe image.

2.4.4.1 Facial Skin Marks as Sole Biometric Trait

In this set of experiments, facial skin mark alone was utilized as a biometric trait to perform the task of person identification. A system was built as described in Figure 2.8. Due to the nature of this trait, it is possible that the images of some of the subjects may show only a few skin marks or even not show any facial skin marks at all, which is the reason we need to introduce a flag as mentioned above. With that flag introduced, if the number of detected facial skin marks is below a predefined threshold for either of the facial images to be matched against each other, the flag is set to “*FAIL*”, and the system can reject matching this pair of facial images. The system only matches pair of facial images with the number of detected facial skin marks exceeding that predefined threshold.

In order to evaluate the system under various conditions, two modes of experiments were conducted.




Figure 2.10. ROC curves for person identification system based on biometric trait of facial skin marks alone. The solid curve shows the ROC curve for system testing on facial images with enough facial skin marks shown, while the dotted curve shows the ROC curve for system testing on all the available facial images in the facial skin mark dataset.

- Mode 1: System test on facial images with certain number of facial skin marks.
- Mode 2: System test on all the available facial images.

For Mode 1, the system only process the facial images showing number of facial skin marks greater or equal to a predefined threshold, F_n . In this part of work, this threshold, F_n , was set to 1, which is a very low number, and basically, all the facial images showing facial skin marks would be chosen, processed, and matched. This number can be set to higher values to ensure the quality of matching of facial images which have enough facial skin marks detected for the purpose of matching. For Mode 2, the system processes all the available facial images with no regards in the facial skin mark dataset, which contains both facial images with some number of facial skin marks detected and facial images with no facial skin marks.

With these two modes of experiments conducted on the available facial skin mark dataset, the results are shown in Figure 2.10. The solid curve represents the ROC curve of the experiment conducted on facial images in the facial skin mark dataset with at least one facial skin mark. The dotted curve represents the ROC curve of the experiment conducted on all the available facial images in the facial skin mark dataset. These two curves are almost identical except in the region of low FRR region, where the system performance under Mode 1 is slightly better than the system performance under Mode 2, which can be explained by the noise introduced by matching two facial images where not enough facial skin marks can be detected from either or both of these matching facial images in experiment Mode 2. This figure also demonstrates the issue of the not so perfect property of universality of facial skin mark as a sole biometric trait for the task of personal identification, which is the reason we conducted the second part of experiment for this part of work.

2.4.4.2 Combined Biometrics of Facial Skin Mark and Eigenfaces

In this set of experiments, two biometric traits, facial skin mark and face, were employed for the task of personal identification. Our system was built as described in Figure 2.9. Due to the branching nature of the combination algorithm as described in Section 2.4.3, we can analyze the system performance improvements introduced by either of these two branches.

If either of the two matching facial images has no skin marks detected, the system has to rely only on Eigenfaces matching algorithm. Consequently, this algorithm with branch combination can be regarded as improvement over the algorithm utilized by system employing facial skin mark as sole biometric trait, especially in the cases where facial skin mark matcher can only make decisions of rejection due to absence of facial skin marks detected in either of these two matching facial images.

In order to compare and evaluate the performances of systems employing different combinations of these two biometric traits for the task of person identification, three modes of experiments were conducted.

- Mode 1: System employing biometric trait of face.
- Mode 2: System employing biometric trait of facial skin mark.
- Mode 3: System employing biometric traits of facial skin mark and face.

For Mode 1, the system only utilizes face, in this work Eigenfaces, as biometric trait for the task of person identification. For Mode 2, the system only utilizes facial skin mark as biometric trait for the task of person identification. For Mode 3, the system utilizes combined biometric traits of facial skin mark and face for the task of person identification. For these 3 testing modes, experiments were conducted on all the available facial images in the facial skin mark dataset, which contains both facial images with some number of facial skin marks detected and facial images with no facial skin marks.




Figure 2.11. ROC curves for three person identification systems: the system utilizes Eigenfaces alone as biometric trait shown in dashed curve, the system utilizes facial skin mark alone as biometric trait shown in dotted curve, and the system utilizes combined biometrics of Eigenfaces and facial skin mark shown in solid curve.

The experiment results of these three modes of testing conducted on the available facial skin mark dataset are shown in Figure 2.11 and Figure 2.12. These two figures are identical in essence except that the FAR axis is shown in log-scale in Figure 2.12 in order to better demonstrate the performance differences of these different testing modes in the region of small FAR values. In these two figures, the solid curve represents the ROC curve of the experiment conducted on the system that combines biometric traits of facial skin mark and face for the task of person identification. The dashed curve represents the ROC curve of the experiment conducted on the system that utilizes Eigenfaces for the task of person identification. The dotted curve represents the ROC curve of the experiment conducted on the system that utilizes facial skin mark for the task of person identification.

The behavior of ROC curves in the region of low FRR as shown in the Figure 2.11 indicates that the performance of combined matcher in experiment Mode 3 is dominated by the performance of a Eigenfaces matching algorithm in experiment Mode 1. On the other hand, in the area of small FAR as shown in Figure 2.12, uniform improvement of the system performance in experiment Mode 3 with combined biometrics can be observed over both system performance in experiment Mode 1 and that in experiment Mode 2. In other words, the ROC curve of the experiment Mode 3 outperforms the other two experiment modes in both low FAR region and low FRR region, especially in the latter region. This improvement can be explained by the agreeable ability of facial skin mark matching algorithm to reject false matches based on the information of facial skin mark. Such information seems to be ignored or not utilized in Eigenfaces matching algorithm.

2.5 Conclusion

This part of work investigated the utilization of facial skin mark information as a biometric trait for the purpose of biometric person verification, presented the results




Figure 2.12. ROC curves for three person identification systems: the system utilizes Eigenfaces alone as biometric trait shown in dashed curve, the system utilizes facial skin mark alone as biometric trait shown in dotted curve, and the system utilizes combined biometrics of Eigenfaces and facial skin mark shown in solid curve. The FAR axis was log-scaled in order to better show the performance of these algorithms for small FAR values.

of the study on employing PCA models for the detection of facial skin marks, and also presented a novel combination algorithm of conventional biometric algorithm, Eigenfaces, and facial skin mark matcher for the task of person identification.

For the task of facial skin mark detection, two PCA models were constructed for local skin patches - the PCA model trained on facial skin patches with facial skin marks in the center and the PCA model trained on facial skin patches with no skin marks in the center. It seems to be beneficial to utilize both of these PCA models on the testing facial skin patch in order to determine whether there is a facial skin mark at the center of the patch. The experiments confirm that our proposed solution can be sufficient for the task of facial skin mark detection and subsequent incorporation into traditional face recognition algorithms.

Our experiments show that successful facial skin mark detection requires two facial skin patch sizes or resolutions - one for modeling local skin neighborhood and the other for calculating facial skin mark detection confidence. Note that the work of Pierrard et al. [73] essentially uses similar tactics by quadratic modeling of local neighborhood with omitted center pixel, and using the difference between model's approximation and original center pixel for skin mark detection. But our PCA model approach allows better neighborhood modeling and includes explicit training.

As for the task of utilizing facial skin mark as a biometric trait, two different approaches were developed - one employing facial skin marks as sole biometric trait for the task of person identification and the other one combining facial skin marks with a conventional biometric trait, in this part of work face. Two sets of experiments were conducted accordingly, and Eigenfaces were adopted as the face recognition algorithm for the combined approach. The resulting combined face matching system has universality property and delivers better performance than either of the two matching algorithms, Eigenfaces and facial skin mark, alone. Future work comprises expanding current study of facial skin marks by incorporating more face image data,

especially images with high resolution, and introducing more detailed classification and analysis of different types of facial skin marks. Study of the pattern of long term changes of facial skin marks can be useful in further evaluation of the stability of facial skin mark as a biometric trait. Combining facial skin marks with other conventional models could also be an interesting problem to investigate.

CHAPTER 3

DECEIT DETECTION FROM INVOLUNTARY FACIAL EXPRESSIONS

Being the most broadly used tool for deceit measurement, the polygraph is a limited method as it suffers from human operator subjectivity and the fact that target subjects are aware of the measurement, which invites the opportunity to alter their behavior or plan counter-measures in advance.

The approach presented in this chapter attempts to circumvent these problems by unobtrusively and automatically measuring several previously identified Deceit Indicators (DIs) based upon involuntary, so-called reliable facial expressions through computer vision analysis of image sequences in real time. Reliable expressions, as noted by the psychology community, are expressions which are impossible for a significant percentage of the population to convincingly simulate, without feeling a true inner felt emotion. The strategy is to detect the difference between the expressions which arise from internal emotion, implying verity, and those expressions which are simulated, implying deceit.

First, a group of facial action units (AUs) related to these reliable expressions are detected based on distance-based and texture-based features. Then, these DIs can be measured and finally a decision of either deceit or verity will be made accordingly. The performance of this proposed approach is evaluated by its real time implementation for deceit detection.

3.1 Introduction

People have long sought to separate truths and deceptions from the world around them. Humans have to rely on others for actions and decisions. In reality, for divergent needs and motivations, people root their deceptions and betrayals. As a response, we take the natural step of attempting to find out whether somebody is being truthful or not. The estimation of credibility of others is a task that all people engage in a daily basis, during normal social interaction. Despite the daily practice, psychology research has shown that humans are generally bad at judging deceit or verity in others. An automatic system that could aid humans in this judgment would be highly valuable. As one of the most widely utilized systems, polygraph testing has proved to be reliable for this cause, however, it follows an overt approach, which invites premeditated counter-measurements of the target subject. A covert system could leverage the fact that the subject would be unaware that they are being scrutinized by a reliable deceit detector.

3.1.1 Introduction to Lying

3.1.1.1 The Nature of Deceit

A lie is a type of deception in the form of an untruthful statement with the intention to deceive, often with the further intention to maintain a secret or reputation, to protect someone's feelings from getting hurt, or to avoid punishment. To lie is to state something one believes is false with the intention that it be taken for the truth by someone else. A liar is a person who is lying, who has previously lied, or who tends by nature to lie repeatedly. Lying is typically used to refer to deceptions in oral or written communication. It is possible that a true statement can be considered a lie if the person making that statement is doing so to deceive, and in this situation, it is the intent of being untruthful rather than the truthfulness of the statement itself that is considered. As defined by Ekman [35], lying is both actively misleading

others through the verbal fabrication of thoughts or events *AND* passively concealing information relevant or pertinent to others. The motivation for this definition is psychological, in that, the physical signs that people show are the same for both forms of deception. For the purposes of this part of work, Ekman's definition will be adopted.

A fundamental assumption of this part of research is that the stronger an emotion is felt, the more difficult it is to conceal in the face, body and voice [45]. Leakage, in this context, is defined as the indications of deception that the liar fails to conceal. The assumption that leakage becomes greater with greater emotion is generally regarded as fact by the academic psychological community [35] for the vast majority of people. Nevertheless, there do exist, so called, natural liars, who are capable of completely containing their emotions, giving away no indication of their lies. For these rare people, it has not been determined, what ability they have to inhibit their heat (far infrared) responses and their autonomic nervous system (breathing, heart rate, etc) responses. Three factors could affect people when they lie.

The fear of being caught: For the general population, increases in the fear of being caught, make their lies more detectable, through the emotions shown on face and body. The fear of being caught will be greatest in the following situations:

- The target is reputed to be difficult to fool.
- The target begins by being suspicious.
- The liar has had very little practice and little or no record of success.
- The liar's personality makes them inclined to have a fear of being caught.
- The stakes are high.
- Punishments are at stake, instead of a reward.
- Both rewards and punishments are at stake.

- The target does not benefit from the lie.
- The punishment for being caught lying is very substantial.

As the number of times a liar is successful increases, the fear of being caught will decrease. In general, this works to the liar's benefit, by helping them to keep from showing visible evidence of the strong fear emotion. Though, sometimes they may make careless mistakes if their fear of being caught is reduced too much. Importantly, fear of being disbelieved looks the same as fear of being caught. The result of this is that if the liar believes that their truth will be disbelieved, detection of the lies will be much more difficult. Fear of being disbelieved stems from:

- Having been disbelieved in high stakes truth telling before.
- The target being reputed to be unfair, or untrustworthy.
- Little experience in high stakes interviews or interrogations.

Deception guilty: Deception guilt is the feeling of guilt the liar experiences as a result of lying and usually shares an inverse relationship with the fear of being caught. Deception guilty is greatest in the following situations:

- The target is unwilling.
- The deceit benefits the liar.
- The target loses by being deceived.
- The target loses more or equal to the amount gained by the liar.
- The deceit is unauthorized and the situation is one where honesty is authorized.
- The liar has not been deceiving for a long period of time.
- The liar and target share social values.

- The liar is personally acquainted with the target.
- The target can't easily be faulted (as mean or gullible).
- The liar has acted to win confidence in his trustworthiness.

Duping delight: Duping delight [35], is characterized by the liar's emotions of relief of having pulled the lie off, pride in the achievement, or smug contempt for the target. Signs or leakage of these emotions can betray the liar if not concealed. Duping delight is greatest in the following situations:

- The target poses a challenge by being reputed to be difficult to fool.
- The lie is challenging, because of what must be concealed or fabricated.
- There are spectators that are watching the lie, and appreciate the liar's performance.

3.1.1.2 The Evidence of Deceit

As documented in psychological studies, reports and journals, evidence of deceit, or indications of deceit, can be found in the following channels:

- Words, such as careless errors, slips of tongue, tirades, and indirect or confusing speech.
- Voice, such as vocal artifacts of pauses, rising in pitch and lowering of pitch.
- Body, mainly gestural and autonomic nervous system (ANS) responses.
- Face, which is the part of our interest.

The visual evidence of the intent to deceive shown in the face has more information than the evidence shown in the human's body, but this necessitates a much more complex interpretation as a result. For this reason, Ekman [41], sought to create

Expression Type	Deceit Indication
Macro-Expression	<ul style="list-style-type: none"> • Appears simulated instead of naturally occurring. • Natural macro-expressions showing the effects of being voluntarily attenuated or squelched. • Lasts less than 2/3 second or longer than 4 seconds. • Abrupt onset. • The peak is held too long. • Abrupt or otherwise unsmooth offset. • Where there are multiple independent AUs, the apexes of these AUs don't overlap. • Asymmetric facial expressions.
Micro-Expression	<ul style="list-style-type: none"> • Appearance of micro-expression. • A person's macro-expressions are not matching his/her micro-expressions.

Table 3.1. Deceit indicators for macro-expressions and micro-expressions.

a system to classify facial expressions as sums of fundamental facial Action Units (AUs), which are based upon the underlying musculature of the face.

The person may display both macro-expression and micro-expressions. Micro-expressions have duration of less than 1/3 second and possibly last only for 1/25 of a second. They generally indicate some form of suppression or concealment. Macro-expressions last longer than 1/3 second and can be either truly emotionally expressive, or faked by the liar to give false impression [38]. The following is a qualitative outline of how the face indicates deceit.

Both *Macro-Expressions* and *Micro-Expressions* can be used as evidence of deceit in certain situations, as shown in Table 3.1.

While accurate, reliable detection of these indicators will require fundamental research, it appears feasible. Several research groups [93, 105] have undertaken research to detect a subset of the facial action units (AUs) defined by Ekman [45]. These systems do not run in real time and were not specifically designed for deception detection. In addition to the global indicators described above, Ekman has identified a few specific expressions which are very useful when searching for evidence of suppressed

Expressions	AU Combinations
Anger	AU 23
Enjoyment	AU 6+12
Fear	AU 1+2+4 or AU 20
Sadness	AU 1+4+15

Table 3.2. Four reliable expressions with their associated facial Action Units.

emotion [35]. These expressions rely upon so-called “reliable muscles”, which cannot be voluntarily controlled by the vast majority of people.

Ekman has proved that there is a measurable difference between a true smile, coined Duchenne Smile, and a deceitful or “polite” smile, Non-Duchenne Smile. Duchenne Smiles stimulate both the zygomatic major muscle and the orbicularis oculi muscle. Non-Duchenne Smiles stimulate only the zygomatic major muscle. The zygomatic major muscle is the muscle that moves the mouth edges upward and broader. The orbicularis oculi lateralis muscles encircle each eye, and aid in restricting and controlling the skin around the eyes. Orbicularis oculi lateralis muscles cannot be moved into the correct smile position voluntarily by most of the population. Only a natural feeling of happiness or enjoyment can move these muscles into the proper happiness position. Ekman believes that the same analogy is true for several emotions, as shown in Table 3.2.

3.1.1.3 The Detection of Deceit

The detection of deceit is the practice of determining whether someone is lying. Activities of the body not easily controlled by the conscious mind are compared under different circumstances. Usually this involves asking the subject control questions where the answers are known to the examiner and comparing them to questions where the answers are not known.

Currently, the polygraph is commonly involved in deceit detection, which is an instrument that measures and records several physiological responses such as blood pressure, pulse, respiration and skin conductivity while the subject is asked and answers a series of questions, on the basis that false answers will produce distinctive measurements. The polygraph measures physiological changes caused by the sympathetic nervous system during questioning. A polygraph examination is also referred to as a psychophysiological detection of deception (PDD) examination. Several other technologies are also used in the field of lie detection, such as voice stress analysis, functional magnetic resonance imaging (fMRI), electroencephalography, and cognitive chronometry.

However, the most broadly used tool for deceit measurement is the polygraph. Nonetheless, it is a limited method as it suffers from human operator subjectivity and the fact that subjects are aware of their measurement. This reduces performance because subject behavior changes, making their deceit or verity more difficult to measure, in addition to the fact that counter-measures can be planned in advance.

Law enforcement and private investigators rely heavily upon the testimony of witnesses and suspects to solve criminal cases. Courts are centered upon the assumption that witnesses are credible. Agents from border patrol, airlines, and other government and corporate officials require accurate and truthful information from subjects in order to maintain proper safety for the benefit of society. Based upon analysis of face, voice and body behavior, training aids for humans to detect deceit have been developed in the psychology community. While these forms of training do increase humans' ability to detect deceit, humans are subjective and qualitative in nature.

A consensus of research in deceit detection indicates that the way people deceive is highly personal. There are no single tell-tale indicators that generalize across populations without normalizations for individual behavioral traits. Nonetheless,

there are a multitude of behavioral trends that are claimed to predict deceit with poor but slightly more than random performance in segments of the population.

The learning process has both a global and local component. Global learning is characterized by the analysis of behaviors in a large and diverse group of people, such that models can be created to aid in feature detection and recognition across the general population. Local learning is characterized by the act of analyzing recorded data of the targets, in order to build a model of their individual behavior, both during lies and truth-telling.

3.1.2 Related Work

Several research efforts are underway to replace human with an automatic system for deceit detection. Buddharaju et al. [14] proposed a methodology to compute the average periorbital temperature signal utilizing thermal video images to generate an estimate of stressful (deceptive) or non-stressful (non-deceptive) subjects on a large and realistic mock-crime interrogation experiment. They reported a successful classification rate of 87.2% for 39 subjects. While a promising area of research, it requires thermal video equipment, which is expensive and could potentially limit broad deployment. Lu et al. [66] presented a method of blob analysis for analyzing the movement of the head and hands based on the identification of skin color, and a proof-of-concept study of accessing behavioral indicators of deception and behavioral state based on the blob analysis of the head and hands was conducted. For their system to be able to screen and detect the behavioral state of people, an automated, near real-time system is necessary, which incurs challenges related to both software and hardware. The work seen in [87] and other efforts leveraging similar modalities, require active sensing, which could possibly be detected and counter-measured by the subject. Facial Action Coding System (FACS) is a framework created by Ekman et al. [41] for the study and classification of facial expressions, and it was widely utilized

in facial expression analysis and other related research fields. In FACS, expressions are represented as combinations of fundamental facial Action Units (AUs) based upon the underlying musculature of the face.

During the research in psychology of facial behavior, Ekman et al. [42] found that while culture and society affect voluntary use of facial expression, there exist expressions that arise as a result of inner felt emotion, and are thus involuntary. Naturally, these facial behaviors transcend culture, sex, and age. It was postulated that if voluntarily arising expressions are visibly different from those expressions arising from involuntary triggers, a contradiction can be detected, and deceit can be inferred.

In [35], based upon their experience in facial behavior psychology, Ekman proposed several deceit indicators brought on by these involuntary movements of the face. A few specific expressions were postulated to be useful when searching for evidence of suppressed emotions, which would imply deceit when identified. These expressions rely upon “reliable muscles”, which cannot be voluntarily controlled by the vast majority of people [35].

Table 3.2 shows the four expressions and their specific combinations of AUs that, according to Ekman’s belief, cannot be triggered involuntarily by majority of people. In the case of enjoyment, for example, there is a measurable difference between a genuine smile (coined Duchenne Smile) and a deceitful or “polite” one (coined Non-Duchenne Smile). Duchenne smiles stimulate both the zygomatic major muscle (AU 12) and the orbicularis oculi muscle (AU 6), while Non-Duchenne smiles only stimulate the zygomatic major muscle. The orbicularis oculi muscles that encircle each eye aid in restricting and controlling the skin around the eyes, and they cannot be moved into the correct smile position voluntarily by most of the population. Only a natural feeling of happiness or enjoyment can move these muscles into proper happiness position. Table 3.5 shows the details of AU 6, AU 12 and other AUs related to reliable expressions.

	Anger	Enjoyment	Fear	Sadness
Defined DIs	AU 23	AU 6+12	AU 2	AU 15
DI Presenting Rate in Verity	89.5%	98.4%	80.0%	97.7%
DI Presenting Rate in Deceit	2.7%	20.5%	33.3%	0.0%

Table 3.3. Manual test results of correlation between specific DI and instances of deceit/verity by Slowe et al. [86].

Several research groups [6, 21, 93, 105] have undertaken research to detect the most common facial AUs and their combinations defined by Ekman [41]. These systems are not tuned for specific application, and it is unclear how their systems would perform when tasked with solving the deceit and verity classification problem. Burgoon et al. [15] proposed an approach that measures deceit and verity from the whole body behavior, where body actions or gestures are measured overtime to produce an estimate of credibility.

The work presented by Slowe et al. [86] attempted to perform deceit detection through unobtrusively measuring facial expressions by computer vision analysis of standard color video. “Reliable expressions” were employed for deceit indication. Their work established credibility to the area of measuring deceit indication from facial behaviors. Through manual tests and basic algorithm implementations, a group of deceit indicators (DIs) were assessed on verified video data acquired by CUBRC and the Center for Unified Biometrics and Sensors (CUBS). Table 3.3 shows their results, which leveraged the feasibility of an automatic system based on reliable expressions that could detect deceit through those DIs.

3.1.3 Facial Action Coding System

During the research in psychology of facial behavior, Ekman et al. [42] found that while culture and society affect voluntary use of facial expression, there exist expressions that arise as a result of inner felt emotion, and are thus involuntary. Naturally,

AU Category	# of AUs	List of AUs
Upper face AUs	9	AU 1, 2, 4–7, 43, 45, 46.
Lower face AUs	15	AU 9–18, 20, 22–24, 28.
Miscellaneous AUs	4	AU 21, 31, 38, 39.
Lip Parting and Jaw Opening AUs	2	AU 25, 26.

Table 3.4. AUs related to contractions of specific facial muscles.

these facial behaviors transcend culture, sex, and age. It was postulated that if voluntarily arising expressions are visibly different from those expressions arising from involuntary triggers, a contradiction can be detected, and deceit can be inferred.

In order to create a framework for the study of expressions, in 1976, Ekman and Friesen [40] developed a system for classifying facial expressions, named the Facial Action Coding System (FACS), in which every conceivable human facial expression can be properly taxonomized. In FACS, facial expressions are represented as single or combinations of fundamental facial action units (AUs), which are contractions or relaxations of one or more facial muscles. Figure 3.1 illustrates the muscles of the head and neck, the contraction or relaxation of which could produce different facial expressions. Of 46 defined AUs in FACS, 30 AUs are anatomically related to the contractions of specific facial muscles as shown in Table 3.4.

AUs can occur either individually or in combinations for different facial expressions. When occur in combinations, AUs can be *additive*, in which the combination does not change the appearances of the constituent AUs, or *non-additive*, in which the combination does change the appearances of the constituent AUs. Although the number of individual/atomic action units is relatively small, more than 7,000 different AU combinations have been observed [81]. FACS provides the descriptive power necessary to describe the details of facial expression. Using FACS, human coders can manually code nearly any anatomically possible facial expression, decomposing it into the specific AUs and their temporal segments that produced the expression.

Muscles of the Head and Neck




Figure 3.1. The human muscles of the head and neck [1].

As AUs are independent of any interpretation, they can be used for any higher order decision making process including recognition of basic emotions, or pre-programmed commands for an ambient intelligent environment.

3.2 Dataset Acquisition and Preprocessing

As required by the nature of this part of work, a dataset of both genuine and deceitful facial expressions of certain number of subjects is essential. However, there is no such a dataset that could be accessed publicly. Therefore, CUBRC and Center for Unified Biometrics and Sensors (CUBS) acquired and verified a dataset that meet the requirements.

3.2.1 CUBRC-CUBS Dataset

The CUBRC-CUBS Dataset was extracted from the verified video data of Big Brother 3 television show episodes acquired by CUBRC and CUBS for the purpose of



Figure 3.2. The sample images of CUBRC-CUBS Dataset. First row from left: genuine anger, genuine enjoyment, genuine fear, genuine sadness. Second row from left: deceitful anger, deceitful enjoyment, deceitful fear, deceitful sadness

training and testing this system. Two experts (fans of this show) examined each episodes and manually labeled the starting and ending time of each sequence of instances of subjects showing expressions of our interests, including both deceitful instances and genuine instances. Then, each of these video sequence was verified manually as either genuine instance or deceitful instance. Lastly, frames of these video sequences were extracted automatically with a certain time interval. 344 facial images of 12 individuals, 6 males and 6 females, are acquired in this dataset, and some of the sample images are shown in Figure 3.2, where the first row shows faces with the four genuine expressions, and the second row shows faces with the four deceitful expressions. In this dataset, about $2/3$ of the images are related with genuine expressions, and the rest related with deceitful expressions.

The advantage of using this database is that each person participating in the show has multiple video appearances over a long period of time of one to three months and the expressed emotions are more natural compared to the other available expression



Figure 3.3. The genuine and deceitful smiles of one subject in the available dataset with the genuine smile shown in the left hand side and the deceitful shown in the right hand side. Notice that AU 6 is absent in the deceitful smile. 58 predefined facial points are shown as small blue squares linked with green lines in the faces of the subject. Original images are copyrighted to *Endemol USA Inc.*

datasets, which simply let the subjects perform certain expressions on cue. The disadvantage is that relatively fewer subjects were available, and the sequences or frames may not be in good lighting, and posing conditions.

3.2.2 Manual Preprocessing

Preprocessing of all the available images in the CUBRC-CUBS Dataset includes labeling of canonical facial points for each face in these images, and also the ground truth of expression information, action unit and major component information, and deceit/verity information of these images. The purpose of canonical facial point labeling is to provide tracking information of the faces in these images. The purpose of ground truth of that information is to facilitate the processes of training and testing of our system.

For each of the facial images in this dataset, 58 facial points are defined and labeled manually, shown as small blue squares in the face regions in Figure 3.3.

Ground truth of expression and deceit/verity were manually verified and input by the expert persons mentioned in the previous sub-section. Ground truth of appearances of action unit and major component were manually verified and input by at least two different people, who have studied the definition of these action units in FACS manual thoroughly.

3.3 Deceit Detection in the Face

For this part of work, we focused on four reliable expressions, proposed by Ekman [35], for the task of deceit detection in face. Descriptions of these expressions and their presentations in FACS are shown in Table 3.2 in Section 3.1. The approach described in this section is based on visible facial behaviors indicated as implying deceit by the psychology community. Deceit is detected based on reliable facial expressions through detecting deceit indicators.

In this approach, a small set of AUs related to the four reliable expressions are decomposed into major components (MCs), and each of major components is detected based on either distance based features or texture based features or both. Deceit indicators (DIs) will be detected based on the result of major component detections. Finally, a decision of deceit or verity will be made based on the result of DI detections. Figure 3.4 outlined this system. The input to this system should be facial images or frame sequences of some video clips. First two steps are face detection and facial feature localization, which are certainly not the major concerns of this part of work, and were not implemented as automated processes. After facial features are extracted, AU recognition will be performed to determine which of the four reliable expressions is shown in the given image. Then, for each of these reliable expression, the system tries to determine whether the predefined deceit indicators is presented. Finally, based on the result of detection of deceit indicators, a conclusion of “Deceit” or “Verity” of the expression shown in the face of target in the input images can be reached. If none




Figure 3.4. The framework of deceit detection system based on reliable facial expressions through DI detections.

AU	FACS Description
AU 1	Inner brow raiser
AU 2	Outer brow raiser
AU 4	Brows lower
AU 6	Cheek raiser and lid compressor
AU 12	Lip corner puller
AU 15	Lip corner depressor
AU 23	Lip tightener

Table 3.5. FACS descriptions of AUs of interest.

of the deceit indicator is triggered, the decision of the system would be “Verity”, otherwise, the decision would be “Deceit”.

3.3.1 Deceit Indicators

For the purposes of this part of work, it was necessary to limit analysis to a set of behaviors with great potential, but that could be most easily tested. As can be seen in Table 3.2, each of the four reliable expressions is made up of the fundamental facial action units (AUs) defined by Ekman et al. [41]. Because it has been postulated that these expressions cannot be accurately faked by a significant portion of the population, the goal of the algorithms developed within this part of work was to both detect, when the expression was present, and if it was genuine or not. *Major Components* (MCs) of AUs are introduced by interpretations of the AU definitions given in [41] for better understanding and facilitation of AU detections. For this project, seven specific AUs (AU 1, 2, 4, 6, 12, 15, and 23) cover our interest. Figure 3.5 illustrates the sample images [41] of these AUs, and the FACS descriptions of these AUs are shown in Table 3.5. Definitions and the interpretations in major components of these AUs of interest, as well as other optional components of these AUs, are shown in Table 3.6, where major components are numbered, and the optional ones are listed as bullets.




Figure 3.5. The sample images [41] of AUs of interest. First row: (a) AU 1; (b) AU 2; (c) AU 4; (d) AU 6. Second row: (e) AU 12; (f) AU 15; (g) AU 20; (h) AU 23.

AU	Definition in FACS
AU 1	1. Horizontal forehead wrinkle. 2. Inner eyebrows raiser.
	• Outer corners of eyebrows move medially, not upwards.
AU 2	3. Outer eyebrows raiser.
	• Arch-shaped eyebrows. • Stretch outer portion of the eye cover fold upwards. • Short horizontal wrinkles above the outer portions of the eyebrows. • Wrinkles in the medial portion of the forehead. • Inner corners of eyebrows move a little bit.
AU 4	4. Eyebrows lower. 5. Inner eyebrows raiser. 6. Vertical wrinkles between eyebrows. 7. Horizontal wrinkles at root of nose.
	• Oblique wrinkle in the middle of forehead. • Narrow eye aperture.
AU 6	8. Cheek raiser. 9. Eye aperture narrower. 10. Lower eyelid furrow deepen. 11. Crow's feet wrinkle.
	• Horizontal wrinkles at root of nose.
AU 12	12. Corners of lips up. 13. Nasolabial furrow deepen.
	• Deepen the infraorbital furrow.
AU 15	14. Corners of lips down. 15. Lower lip stretched horizontally.
	• Pouches/bags/wrinkles of the skin below lip corners. • Flatten or bulge chin boss. • Depression medially under the lower lip. • Deepen the lower portion of nasolabial furrow.
AU 23	16. Red parts of lips narrowed.
	• Small lip protrusion if lips are parted. • Roll the red parts of the lips inwards. • The red part of the lips disappear. • Small wrinkles above and below the red parts of lips. • Flatten or wrinkle chin boss. • Flatten only one lip.

Table 3.6. FACS definitions of AUs of interest and their representations in major components and optional components. Major components are listed as numbered items, and optional components are listed as bulleted items.

3.3.1.1 DI for Anger

In attempt to fake anger facially, people would perform multiple combined expressions that are meant to trick others into believing that they are angry. Nonetheless, it is rare that a person will actually produce AU 23 (as shown in Figure 3.5) without being truly angry. Naturally, the anger DI is characterized by AU 23, and the description of this action unit was shown in Table 3.6. The Anger DI is characterized by an observation that the straightness of line created by the mouth during execution of AU 23, indicates the level of verity in the subjects anger.

In our 58 facial points definitions, three points are defined on each of the lips. In order to detect AU 23 or MC 16, three distances between feature points located on the upper and lower lips are calculated.

3.3.1.2 DI for Enjoyment

In order to detect deceit in enjoyment, the combination of AU 6 and AU 12 (as shown respectively in Figure 3.5) is applied, as genuine smile or Duchenne smile should display both these AUs while fake smile or Non-Duchenne smile only displays AU 12. Thus, independent detections of these two AUs are required for this part of work. If it is detected that both AU 6 and AU 12 are evident, verity is declared. If AU 12 is detected without AU 6, deceit is declared. If AU 12 is not seen, the deceit/verity state is undetermined.

In order to detect AU6, several major components (MC 8–11) are defined, among which MC 9 is represented by distance based features. Three facial points are defined along each of the four eyelids. Six distances are calculated among those points to represent MC 9. Due to their natures, MC 8, 10 and 11 are represented by texture based features. Texture analysis is performed on two corresponding facial regions for each of these MCs. MC 12 and 13 are defined to detect AU 12. Eight facial points are defined around mouth region. Six distances are calculated among those points to

represent MC 12. For MC 13, texture of two facial regions besides nose are analyzed, and Gabor wavelet features are extracted.

3.3.1.3 DI for Fear

As shown in Table 3.2, two different expressions, AU combination 1+2+4 and AU 20 (as shown respectively in Figure 3.5), can be applied as DI for fear. Due to the lack of instances of AU 20 in our current CUBRC-CUBS dataset, only AU combination 1+2+4 is considered.

In order to detect AU 1, MC 1 and MC 2 are defined. For MC 1, texture analysis of the forehead region is performed, and Gabor wavelet features are extracted. For MC 2, two distances between two inner eyebrow tips and the line formed by the two inner eye corners are calculated. Similarly, two distances between two outer eyebrow tips and the line formed by the two inner eye corners are calculated to detect AU 2 or MC 3. In order to detect AU 4, several major components (MC 4–7) are defined. Three distances for each eyebrow are calculated, and six distances in total to represent MC 4. One distance between two inner eyebrow tips are calculated to represent MC 5. Texture of the region between two eyebrows is analyzed and Gabor wavelet features are extracted to represent MC 6. Texture analysis of the region at the root of nose is performed and Gabor wavelet features are extracted to represent MC 7.

3.3.1.4 DI for Sadness

The sadness DI is characterized by the frown expressions (AU 15) one frequently sees displayed in full form mostly in children, AU 1 and AU 4, as shown respectively in Figure 3.5. Research within this project has reinforced, work by researchers in the academic psychology community, which found that AU 15 is employed quite frequently by adults, but for very short periods of time, fractions of a second.

In order to detect AU 15, MC 14 and 15 are defined. Similar to MC 14, MC 15 is also represented by the same six distances among the facial points on mouth region. Distance between the two outer corners of mouth is calculated to represent MC 15.

3.4 Feature Definitions

Due to the nature of the major components, two types of features are applied in this approach: *distance based features* (DBF) and *texture based features* (TBF). Among the 16 defined major components, nine (MC 2, 3, 4, 5, 9, 12, 14, 15, and 16) can be represented with distance based features and the rest (MC 1, 6, 7, 8, 10, 11, and 13) can be represented with texture based features. In order to process these features, 58 facial points are defined, as shown in Figure 3.3, and manually labeled for all the images in the CUBRC-CEDAR dataset. The definitions and extractions of the features would be introduced in details in the following subsections.

3.4.1 Distance Based Features

The nine major components that are related with distance based features are mainly concentrated on two regions, namely eye region and mouth region. In this part of work, Euclidean distance is applied when calculating distance between two facial points or distance between one facial point to a certain line formed by the other two facial points. Relative distances are introduced to overcome the problem of faces with various sizes. Basically, the distance between two inner corners of eyes is used as reference distance when calculating the relative distances between two facial points or one facial point to a line formed with other two facial points. In the rest of the chapter, *distance* refers to relative Euclidean distance, if not specified.

3.4.2 Texture Based Features

For the major components that are related with texture based features, the images are first scaled and grayscale normalized to minimize the in between difference

between them. There are in all 7 major components that are based on texture based features. However, due to lack of data, MC 8 has not been studied or used here.

The approach proposed in this part of work involves obtaining the Gabor wavelets at selected points in the face, where maximum possible variation is found due to muscular involvement during facial expressions. They are calculated over a local neighborhood of the point selected for a particular major component. From these transforms, four moments are calculated for each point transform. The wavelets are calculated for different orientations and frequencies. These orientations and frequencies are optimized based on the prior knowledge of the nature of furrows, wrinkles, or creases in the particular point where the wavelets are being calculated. The classification for all the major components is binary, based on their presence or absence. The classification is done using SVM with RBF kernel. LIBSVM [18] was utilized in this part of work with its default parameters.

3.5 Experiment and Result

3.5.1 Experiment Results of DBFs

Due to the fact that only limited number of samples are available in the dataset, statistical analysis was conducted on all the samples to verify that the distributions of the distance based features are different and hence separable for the two classes, namely presence or absence of certain major component. Wilcoxon rank sum test was applied for this purpose, and according to the results of this test, all of the features, except two features for MC 4, have p values lower than 5%. These results confirmed that most of the distance based features can be applied to the task of detecting the presence of certain major components represented by distance based features.

In this part of experiment, half of all the available samples are selected randomly as training samples and the rest are used for testing purpose. Simple thresholding was applied to the major components that are represented by small number of dis-

Major Component	No. of Features	Accuracy
MC 2	2	68.67%
MC 3	2	74.07%
MC 4	6	63.79%
MC 5	1	77.71%
MC 9	6	68.51%
MC 12	6	78.60%
MC 14	6	77.05%
MC 15	1	53.01%
MC 16	3	71.44%

Table 3.7. Test results of detecting major components represented by distance based features.

tance based features, while supporting vector machines (SVM) are trained for major components that are represented by more than 3 distance based features.

Table 3.7 shows the detecting results of major components that are represented by distance based features. Among these results, MC 15 and MC 4 have the lowest accuracy. MC 15, being one of the weak major component for AU 15 and represented by distance between two outer corners of mouth, isn't reliable due to the fact that for AUs other than AU 15, this distance may also be big, for example, when mouth is open wide. The reason for MC 4 being unreliable could be the fact that different people have different distance between eyebrows and eyes. In fact, the results of Wilcoxon rank sum test on these two major components indicate that the distance based features represent them have larger p values than those of the rest of the major components.

One way to improve the performance of these distance based features is to substitute these distances of a certain subject in a given expression for the difference between these distances and the same set of distances from this subject in a neutral expression. Restricted to the available dataset, this approach has not been implemented.

MC	Accuracy
MC 1	78.33%
MC 6	82.50%
MC 7	92.86%
MC 10	71.15%
MC 11	88.68%
MC 13	97.18%

Table 3.8. Test results of detecting major components represented by texture based features.

3.5.2 Experiment Results of TBFs

In this part of experiment, roughly half of all the available samples were selected randomly as training samples and the rest were used for testing purpose. The results obtained from the classification of texture based features, for each major component, varied a lot depending on the size of the data set used, but over all they are quite optimistic. Due to limited size of the available dataset being used, even a difference of single data in testing sets may cause a huge variation in the output accuracies.

All the classifications were done using LIBSVM library, with Radial basis functions as kernels and default parameters. The images were scaled before the classification. Table 3.8 shows the results of detecting results of major components that are represented by texture based features.

3.5.3 Experiment Results of Deceit Indicators

The focus of this work is to establish credibility to the area of measuring deceit indication from involuntary facial expressions, therefore the experiments for deceit indicators were conducted separately for these four expressions, namely anger, enjoy, fear and sadness. For each expression type, samples of both deceit and verity in the CUBRC-CEDAR dataset were distributed randomly into the training and testing data sets. Distance based features and texture based features for each of these expression

Expression	Anger	Enjoyment	Fear	Sadness
Accuracy	86.02%	73.16%	80.46%	90.15%

Table 3.9. Test results of detecting instances of deceit from involuntary facial expressions.

were applied, and their results are combined. Presently they are being combined based on simple averaging.

Table 3.9 shows the testing results of detecting deceit from involuntary facial expressions based on combination of distance based features and texture based features.

3.6 Conclusion

In this chapter, we proposed a system that could detect deceit unobtrusively by measuring several previously identified deceit indicators (DIs) based upon the involuntary, or reliable, facial expressions through computer vision analysis of facial images. This approach recognizes and detects four reliable expressions, namely anger, enjoyment, fear, and sadness, by recognizing action units (AUs) associated with each of these expressions. In addition, each AU of interest is further interpreted as a set of major components (MCs) to facilitate its detection. Distance-based features and texture-based features are defined for each major component. The system was evaluated using a dataset of verified video data of 344 frames of facial images of 12 subjects. The system showed a decent performance with limited data, and a possibility to advance this work by enhancing the speed of the feature extraction methods and their further combination to predict deceit or verity.

CHAPTER 4

FACIAL EXPRESSION AS BIOMETRICS

In this chapter, we investigated a possibility of utilizing the information of face expression for the purpose of person biometrics. The foundation of this research is that the emotional face expressions of a person are repeatable, and face expression features can be employed for the purpose of person identification.

In order to avoid utilizing person specific geometric or textural features traditionally employed in face biometrics, in this part of work, we restrict ourselves to the defined tracker displacement features only. In contrast to previous research in facial expression biometrics, we extract features only from the pair of facial images for each subject, the image of neutral expression and the image showing the apex of emotion expression, instead of using the sequence of images or frames from video clips.

The experiments, conducted on two facial expression databases of the public Cohn-Kanade Facial Expression Database and the CUBRC-CUBS Database, confirm that the proposed features can indeed be employed for the purpose of person biometrics.

4.1 Introduction

4.1.1 Facial Expression Analysis

Facial expressions are the changes of facial appearance in response to a person's internal emotional states, intentions, or social communications. And facial expression is one of the most powerful, natural, non-verbal, and immediate means for human beings to communicate their emotions and express their intentions. It is sooner for human beings to express their emotions through facial expressions than through

verbalization, and people even express their expressions before they realize their own feelings.

The study of facial expressions was primarily a research subject for psychologists. However, with the advent of automatic face recognition and detection research pioneered by researchers like Pentland [97, 96] and Takeo Kanade [77, 78], the study of facial expressions to create automatic facial expression systems gained prominence. In the past couple of decades, a lot of research work [10, 11, 20, 32, 43, 46, 63, 76, 92, 106, 100, 99] has been conducted to investigate and implement computer systems that could understand and use this natural form of human communications with the accomplishments in the related areas such as psychological studies, human movement analysis, face detection, face tracking, and recognition make the automatic facial expression analysis possible. In 1978, Suwa et al. [90] presented an early attempt to analyze facial expressions automatically by tracking the motion of 20 identified spots on an image sequence. Mase and Pentland [68] pioneered the work in automatic facial expression recognition. They used the concept of optical flow estimation to observe and detect facial expressions. Essa and Pentland [43] used optical flow to create a mesh model of the face and used this face model to recognize different facial expressions.

The facial action units proposed by Ekman was used for automatic facial expression analysis by Tian et al. [94]. In their model for facial expression analysis first a facial feature tracking is performed to extract key points on the face using which action units are recognized. Further using a neural network, facial expressions are recognized. In [19], a HMM based classifier is used to recognize facial expressions based on geometric features extracted from a 3D model of the face. The use of appearance based model for feature extraction followed by classification using SVM-HMM is followed in [5]. Tian et al. [95] proposed a combination of appearance based and geometric features of face for automatic facial expression recognition system which uses



Figure 4.1. Sample images showing the prototypic expressions, from left to right: neutral, enjoyment, surprise, anger, sadness, fear, and disgust. Images are from the Cohn-Kanade Facial Expression Database [55]

Gabor filters for feature extraction and neural networks for classification. Abboud et al. [4, 3] propose a statistical model for facial expression analysis and synthesis based on Active Appearance Models (AAM) to model the face.

However, most of the research on facial expression have been focused on detecting, recognizing, and analyzing a small set of prototypic emotional expressions, i.e., enjoyment, surprise, anger, sadness, fear, and disgust, as shown in Figure 4.1. This approach may follow the work of Darwin [30, 40, 36, 81] as early as the year of 1872, and more recent work of Ekman and Friesen [39], Ekman [37], and Izard et al. [49] who proposed that basic emotions have corresponding prototypic facial expressions. However, in everyday life situations, such extreme prototypic expressions occur relatively less frequently. Instead, emotions are communicated more often through subtle changes in one or a few discrete facial features, such as a tightening of the lips in anger or obliquely lowering the lip corners in sadness [17], as shown in Figure 4.2. Certain changes in isolated facial features, particularly in the area of the eyelids and the eyebrows, are typical paralinguistic displays. For example, raising the eyebrows could signal greetings [34]. Automated systems that can recognize changes, especially fine-grained ones, in facial expression are needed to capture such subtlety of human emotion and paralinguistic communication.



Figure 4.2. Two sample images from the CUBRC-CUBS Database showing subtle changes in facial features. Face in the left shows a person tightening the lips (AU 23) in anger. Face in the right shows a person obliquely lowering the lip corners (AU 15) in sadness.

4.1.2 Related Work

The previous research into facial expression biometrics is very limited. Schmidt and Cohn [82] and Cohn et al. [22] describe the system performing biometric person authentication using the changes in action unit appearances. Such system measures the intervals between different phases of facial action units [40] and their sequence order. The action units and time intervals are measured with the help of special hardware. The reported performance is comparable with the performance of commercial face biometrics system. Another interesting research is presented in [71], where authors investigate if emotion expression is hereditary. The experiments conducted with born-blind subjects seem to indicate that face emotion expression of family members is correlated. The used features included sequences of 43 types of face movements.

In both above approaches long sequences of facial movements were used to produce a statistically significant person identification algorithm. In our research we investigate whether the information obtained from single images can serve for the

same purpose. Similar to these works we concentrated on the expressions associated with some emotions. We assumed that the same emotion of the same person is expressed as a similar set of action units of the similar intensity. Thus, using a single image of the person at the height of emotion expression might be sufficient for person discrimination.

4.2 Facial Expression as Biometrics

The way person behaves, and, in particular, the way person expresses some emotions, can serve as an indicator to person's identity. Previously Ekman [35] identified 18 types of different smiles. The type of smile expressed by the person is partly influenced by the current emotional state of the person and environment. At the same time we can speculate that cultural background of the person and constant psychological traits can determine the frequencies of each type appearance and their strength. If it is so, then the type of the smile can be used for biometric person identification.

Some psychological studies seem to confirm the individual differences in emotions, and in particular in smiles. Krumhuber et al. [60] provide an extensive overview of recent research on differences in smiles and perceptions of smiles in the field of psychology. As it is discussed there, the perception of smile strength can be influenced by the general belief or expectation of a person. These results imply that psychological studies involving human test subjects might not give objective picture of smile or expression individuality. On the other hand, it was noted before that women express smile more frequently than men [13] and such frequency can be measured rather objectively.

In our research we are interested in separating the expressions of different individuals automatically. Besides proving the individuality of facial expressions, our goal is to achieve an algorithm identifying the persons based on their expressions. Since

expressions might not provide enough discriminating power, our research might be considered as a soft biometrics [53].

4.3 Feature Definitions

The main difficulty that we had in this part of work was to produce features which are unique to face expressions and do NOT contain information traditionally used for face biometrics. For example, we did not want to use geometric distances between different points in face, or texture information which might give strong biometrical information about the person. Such information might be irrelevant for face expressions, and our results would greatly skewed if such features are utilized and involved in our system.

Therefore, we decided to restrict ourselves in utilizing only displacement distances between tracker points. The used tracker positions are described in [88] and illustrated in Figure 4.3. Though the tracker positions can be extracted automatically [88], we found out that algorithm does not work quite reliably for single frame images or very short video sequences that we used. Thus, we used the help of human expert to find the tracker points.

To find displacements we had to utilize two facial images of each person, namely one with neutral emotion expression and the other one at the apex of the emotion expression. The distances between these corresponding tracker points are indicative on the movement of the face, but not of the face geometrical form.

In order to account for face global transformation in the image frame, we searched for a frame of reference for each of the facial images, shown as a pair of perpendicular axes in red in Figure 4.3. The vertical axis and the direction of horizontal axis were found by using regression on the sums of corresponding left and right tracker points. The location of horizontal axis was found by averaging vertical positions of some




Figure 4.3. One example of face images from the Cohn-Kanade Facial Expression Database with tracker points and extracted reference frame used for normalization. Tracker points are shown as small blue squares, and the reference frame is shown as a pair of perpendicular axes in red.

stable points, in this case, tracker points of eyes and nose. The positions of tracker points were also scaled to account for different distances between face and the camera.

After normalization procedures in both neutral and emotion in apex facial images, the displacements between corresponding tracker positions can be recorded. The final result is 116 features corresponding to x and y coordinates of 58 tracker points. These features seem to not contain any geometric face information, but only the information about emotion expression. Though it is possible that some type of face geometry is favorable to specific movements of tracker points, we regard this very improbable.

Two facial images, neutral and emotion in apex, are utilized to construct a single feature vector of a person having one particular emotion expression. The genuine biometric match consists in comparison of two such vectors of the same person having the same emotion, so four images (two neutral and two emotional) are needed to derive a single match score. The impostor biometric match is produced by having two different people expressing the same emotion. Again, four images are required to produce a matching score. The matching score is an Euclidean distance between two 116-dimensional feature vectors.

In this part of work, we used only emotions of enjoyment and sadness. These emotions constituted the largest part of considered databases. Though for biometric experiments alone, images from only one emotion would have sufficed, we also wanted to verify if our features can separate emotion expressions. For this purpose, we also performed experiments comparing the matching distances of two cases: the distance between feature vectors of different persons having same emotion and the distance between feature vectors of different persons having different emotions.

4.4 Experiment and Result

Experiments were conducted on two face expression databases in this part of work. The first database is the publicly available Cohn-Kanade Facial Expression

Database [55], and the second database is the CUBRC-CUBS Database, the database of face images extracted by human experts from episodes of a television show “Big Brother 3”, as discussed in Section 3.2. In the following two subsections, setups and results of our experiments performed on these two databases are described separately.

4.4.1 Experiment on Cohn-Kanade Database

The Cohn-Kanade Facial Expression Database [55] contains sequences of facial images of 100 subjects performing 8 different emotional or non-emotional facial expression changes. All the images are frontal face images, which ideally suits our feature extraction method. Though the sequences contain a few frames of video illustrating a gradual change of a person’s expression, in these experiments conducted in this part of work, only two frames were utilized, namely the first frame, which shows a face with neutral expression and the last frame, which shows a face with emotion expression in its apex.

The only disadvantage for using this database was that there were too few sequences of the same person doing same emotion expression. The human expert was able to identify 13 sadness and 9 enjoyment emotion pairs of expression sequences from 17 different human subjects. Note, that some persons had recorded two pairs of the sadness and enjoyment emotions. So the total number of genuine match scores was 22. For impostor matching scores, we produced all possible combinations of the same emotion sequence produced by two different persons. As a result we had 312 pairs of sadness emotion and 144 pairs of enjoyment emotion, which summarized to 456 pairs, or impostor matching scores.

The statistics of these matching score sets is presented in Table 4.1. Same person and same emotion score set corresponds to genuine biometric match scores. Different persons and same emotion corresponds to the impostor biometric match scores. The average matching distances (μ) for genuine scores are a little lower than those dis-

Score Set	μ	σ
Same person, same emotion	0.8078	0.2394
Different persons, same emotion	0.8688	0.2253
Different persons, different emotions	0.9813	0.2143

Table 4.1. Means and standard deviations for different matching score sets of the Cohn-Kanade Facial Expression Database.

Score set separation	p-value
Biometric person identification	0.2234
Emotion identification	5.5×10^{-16}

Table 4.2. p-values of the Wilcoxon Rank-Sum test on corresponding score sets on the Cohn-Kanade Facial Expression Database.

tances (μ) for impostor scores, as we predicted. But the standard deviation (σ) for both sets of scores is rather high, and there is a concern that this biometric matching might not be reliable.

In the derivation of the utilized feature vectors, we assumed that these features are designed to well separate emotional expressions. In order to verify this, we performed a testing involving a set of matching scores between sequences of different people expressing different emotions. By mixing together 13×2 sequences of sadness emotion and 9×2 sequences of enjoyment emotion, we obtained 468 such pairs. The statistics of this score set is presented in Table 4.1 as well. The separation between means of different persons expressing same emotion and means of different persons expressing different emotions is higher than the difference in our previous comparison.

In order to verify the statistical significance of the difference between our matching score sets, Wilcoxon rank-sum test was conducted. This test verifies a null hypothesis that two sample sets originate from the same distribution versus the hypothesis that they originate from different distributions. The p-values of this test are presented in Table 4.2.

Projection dimension	Diff. Subject Same Expression		Diff. Subject Diff. Expression		p-values
	μ_{gen}	σ_{gen}	μ_{imp}	σ_{imp}	
$N = 20$	0.79	0.24	0.92	0.23	3.9×10^{-17}
$N = 10$	0.70	0.25	0.84	0.24	8.3×10^{-21}
$N = 5$	0.57	0.27	0.74	0.25	35.1×10^{-25}
$N = 2$	0.44	0.28	0.47	0.24	0.004

Table 4.3. Score statistics and p-values of the Wilcoxon Rank-Sum test on emotion identification score sets after PCA transform on the Cohn-Kanade Facial Expression Database.

The emotion identification means that we compare two distributions, i.e. distribution of matching scores from different persons with same emotion and distribution of matching scores from different persons with different emotions. The biometric person identification means that we compare distribution of matching scores from same persons with same emotion and distribution of matching scores from different persons with same emotion. The small p-value for emotion identification (5.5×10^{-16}) indicates that the difference between corresponding score distributions is statistically significant, and that we indeed have good features for emotion identification. On the other hand, high value of p-value for biometric person identification is more than traditionally used threshold of 5%, which indicates that corresponding distributions might not be statistically different.

Although the statistical significance can be achieved by increasing the number of testing samples, these samples are rather hard to obtain. Instead, we attempted to reduce the noise in utilized features by considering their projection into smaller dimensional space using principal component analysis (PCA). The PCA projection is derived using feature vectors obtained from all image sequences, i.e. pairs of neutral and emotional faces. Table 4.4 contains results of these experiments related to biometric person identification distributions. Table 4.3 shows the results of these experiments related to emotion identification distribution.

Projection dimension	Same Expression Same Subject		Same Expression Diff. Subject		p-values
	μ_{gen}	σ_{gen}	μ_{imp}	σ_{imp}	
$N = 20$	0.72	0.27	0.79	0.24	0.191
$N = 10$	0.63	0.25	0.70	0.25	0.113
$N = 5$	0.50	0.24	0.57	0.27	0.147
$N = 2$	0.37	0.23	0.44	0.28	0.189

Table 4.4. Score statistics and p-values of the Wilcoxon Rank-Sum test on biometric score sets after PCA transform on the Cohn-Kanade Facial Expression Database.

As can be seen from the p-values of rank-sum test, we obtained a better separation between genuine and impostor scores than before. Although the numbers are still higher than 5%, we see a consistency among means of the distances. The genuine distance scores are always lower than impostor distance scores, which demonstrates a positive support into our hypothesis that these scores come from different distributions.

4.4.2 Experiment on CUBRC-CUBS Database

The experiments on the Cohn-Kanade Facial Expression Database were not able to provide a statistical proof that tracker displacement features are really useful for biometric person identification. As mentioned before, one problem with those experiments is that one class, specifically the genuine matching scores, has only limited number of samples available through the Cohn-Kanade database. Therefore, we expanded our experiments using additional image database extracted from the episodes of “Big Brother 3” television show, or the CUBRC-CUBS Database as discussed in Section 3.2.

The advantage of introducing and utilizing this database is that each person participating in the show has multiple video appearances over a long period of time of 1 to 3 months and most of the expressed emotions are more natural or spontaneous. The disadvantage of this database as compared to the Cohn-Kanade Facial Expres-

Score set	μ	σ
Same person, same emotion	2.5733	1.8032
Different persons, same emotion	3.2252	1.6661
p-value of Wilcoxon rank-sum test	2.67×10^{-26}	

Table 4.5. Score statistics of the CUBRC-CUBS Database matching score sets.

sion Database is that the video sequences might not contain neutral expressions. As a consequence, neutral and emotional expression images may be extracted from different video sequences and matched in pairs randomly in order to obtain displacement features.

Using the help of human experts, we obtained 46 sadness expression images, 38 enjoyment expression images from 3 human subjects, as well as 4 neutral expression images per subject. Each emotional image was utilized only once, but neutral expression images were utilized multiple times in pairs. Such setup was rather necessary since it turned out that videos contain much more emotional expression sequences than neutral face sequences. We tried to select emotional expression images from different video sequences in order to avoid dependencies in matching scores.

Since each subject has many images with the same emotional expression, we are able to obtain a much larger number of genuine matching scores for our tests: 488 sadness genuine match pairs and 236 enjoyment genuine match pairs for a total of 724 pairs, or genuine matching scores. The numbers for impostor matching: 547 sadness emotion pairs and 467 enjoyment emotion pairs for a total of 1014 pairs, or impostor matching scores.

Since PCA feature selection showed an improvement in performance for the Cohn-Kanade Facial Expression Database, we used it also here to obtain 10 features instead of original 116. The match score corresponds to the Euclidean distance between two feature vectors in a projected space. The statistics of resulting genuine and impostor score set is presented in Table 4.5.

As we can see from the results, we get statistically significant separation between genuine and impostor score sets. Though there is still a significant overlap between genuine (same person expressing same emotion) and impostor (different persons expressing same emotion) score sets judging from the means and standard deviations, due to the larger size of test sets we can confirm that considered features are indeed useful for biometric person identification. Note, that the matching scores are generally much larger than the matching scores obtained in the Cohn-Kanade Facial Expression Database, which might be explained by lower quality images, longer distance from face to the camera and face rotations. Face rotations, which produce non-frontal face images, might have been the major culprit for the increased general matching distance, since our feature extraction method did not account for such rotations.

The ROC curves for proposed face expression based biometrics are shown in Figure 4.4 for both the Cohn-Kanade Facial Expression Database and the CUBRC-CUBS Database. The curves show similar performance of a little less than 0.4 equal error rate (EER). Note, that the curve for experiments on the Cohn-Kanade database has visible steps corresponding to fewer genuine matching pair samples. Though proposed method has only little discriminative ability, it still can be used along with other biometrics methods, e.g. traditional face biometrics. Also, as previous research suggests, using it for video sequences can result in further improvement.

4.5 Conclusion

In this chapter, we considered employing emotion expression face dynamics for the purposes of biometric person identification. If, at the enrollment state of a facial biometric system, we not only enroll a person's face into the biometric database, but also the way person expresses emotions, for example, smiles, such information might be useful for the purpose of identifying the person. In our experiments, we utilized the displacements of tracker points as our features, and tested our system




Figure 4.4. ROC performance curves for face expression biometrics on two databases.

on two face image databases, namely, the Cohn-Kanade Facial Expression Database and the CUBRC-CUBS Database. We assume that such features only convey the emotional expression information, but not traditional face biometrics information. The statistical testing we performed demonstrated that such features can indeed be utilized for the task of biometric person identification.

CHAPTER 5

CONCLUSION

The main contributions of this thesis are:

- Investigation of the utilization of facial skin mark information as a biometric trait for the purpose of biometric personal identification.
 - Presented the results of the study on employing PCA models for the detection of facial skin marks.
 - Presented a novel combination algorithm of conventional biometric algorithm, Eigenfaces, and our proposed facial skin mark matching algorithm for the task of personal identification.
- Exploration of an unobtrusive measurement of deceit detection by measuring several previously identified deceit indicators (DIs) based upon the involuntary, or reliable, facial expressions through computer vision analysis of facial images.
- Investigation of the utilization of emotion expression face dynamics for the purposes of biometric personal identification.

The results of the study of facial skin marks, including building a facial image dataset with ground truth of facial skin marks and statistical analysis of facial skin marks, was presented in Section 2.2. For the task of facial skin mark detection, an algorithm based on PCA modeling was presented in Section 2.3, where two PCA models were constructed for local facial skin patches - the PCA model trained on facial skin patches with facial skin marks in the center and the PCA model trained on

facial skin patches with no skin marks in the center. It seems to be beneficial to utilize both of these PCA models on the testing facial skin patch in order to determine whether there is a facial skin mark at the center of the patch. Extensive experiments were conducted with various combinations of different distance measurements between original facial skin patch images and their PCA projections, different sizes of PCA modeling and distance calculation facial skin patches, and different numbers of principal components in the PCA models. The performance of this system was shown as four ROC curves in Figure 2.7.

For the study of utilizing facial skin marks as a biometric trait, the position, size and color intensity of the facial skin marks are considered and represented as features for facial skin mark based face matching algorithm. Two different approaches were proposed and developed in Section 2.4 - one employing facial skin marks as sole biometric trait for the task of personal identification and the other one combining facial skin marks with a conventional biometric trait. Two sets of experiments were conducted accordingly, and Eigenfaces was adopted as the face recognition algorithm for the combined approach. Figure 2.10 and Figure 2.11 demonstrated the performance of these two approaches. The combined face matching system has universality property and delivers better performance than either of the two matching algorithms, Eigenfaces and facial skin mark, alone. Future work comprises expanding current study of facial skin marks by incorporating more face image data, especially images with high resolution, and introducing more detailed classification and analysis of different types of facial skin marks. Study of the pattern of long term changes of facial skin marks can provide useful information in further evaluation of the stability of facial skin mark as a biometric trait. Facial skin marks combined with other conventional models could also be an interesting problem to investigate.

The polygraph, being the most broadly used tool for deceit measurement, has its limitation which suffers from human operator subjectivity and its obtrusive nature,

which invites the opportunity for subjects to alter their behavior or plan counter-measures in advance. An attempt to circumvent these problems by unobtrusively and automatically measuring several prior identified Deceit Indicators (DIs) based upon involuntary, so-called reliable facial expressions through computer vision analysis of image sequences in real time was presented in Chapter 3. This approach recognizes and detects four reliable expressions by recognizing action units (AUs) associated with each of these expressions. In addition, each AU of interest is further interpreted as a set of major components (MCs) to facilitate its detection. Distance-based features and texture-based features are defined for each major component. The system was evaluated using a dataset of verified video data of 344 frames of facial images of 12 subjects, and a decent system performance was shown in Table 3.9.

An investigation of the possibility of utilizing the information of face expression for the purpose of person identification was proposed and developed in Chapter 4. The assumption of this part of work is that the emotional face expressions of a person are repeatable, and face expression features can be utilized for person identification. The scenario of the proposed system is that at the enrollment state of a facial biometric system, we not only enroll a person's face into the biometric database, but also the way person expresses certain emotions such as smile, and such information might be useful for the purpose of identifying the person. In our experiments, we used the displacements of tracker points as our features, and tested our system on two face image databases, the Cohn-Kanade Facial Expression Database and the CUBRC-CUBS Database. We assume that such features only convey the emotional expression information, but not traditional face biometrics information. The statistical testing we performed showed that such features can indeed be utilized for person identification.

BIBLIOGRAPHY

- [1] Illustration of muscles of head and neck. Image available at http://training.seer.cancer.gov/module_anatomy/images/illu_head_neck_muscle.jpg.
- [2] ANSI/NIST-ITL 1-2000 standard: American national standard for information systems - data format for the interchange of fingerprint, facial, & scar mark & tattoo (SMT) information, 1993.
- [3] Abboud, B., Davoine, F., and Dang, M. Statistical modeling for facial expression analysis and synthesis. *Image Processing, 2003. ICIP 2003. Proceedings. 2003 International Conference on 1* (September 2003), I-653-6 vol.1.
- [4] Abboud, B., Davoine, F., and Dang, M. Facial expression recognition and synthesis based on an appearance model. *Signal Processing: Image Communication* 19, 8 (September 2004), 723-740.
- [5] Bartlett, M., Braathen, B., Littlewort-Ford, G., Hershey, J., Fasel, I., Marks, T., Smith, E., Sejnowski, T., and Movellan, J. R. Automatic analysis of spontaneous facial behavior: A final project report. Tech. Rep. INC-MPLab-TR-2001.08, Machine Perception Lab, Institute for Neural Computation, University of California, San Diego, CA, December 2001.
- [6] Bartlett, M. S., Littlewort, G. C., Frank, M. G., Lainscsek, C., Fasel, I., and Movellan, J. R. Automatic recognition of facial actions in spontaneous expressions. *Journal of Multimedia* 1, 6 (2006), 22-35.
- [7] Becker, P., and Wetzell, R. F. *Criminals and their Scientists: The History of Criminology in International Perspective*. Cambridge Univ. Press, Cambridge, UK, 2006.
- [8] Belhumeur, P. N., Hespanha, J. P., and Kriegman, D. J. Eigenfaces vs. fisherfaces: recognition using class specific linear projection. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 19, 7 (July 1997), 711-720.
- [9] Bertillon, A. *Signaletic Instructions including the theory and practice of Anthropometrical Identification*, R. W. McClaughry ed. The Werner Company, 1896.
- [10] Black, M. J., and Yacoob, Y. Tracking and recognizing rigid and non-rigid facial motions using local parametric models of image motion. *Fifth International Conference on Computer Vision (ICCV'95)* (1995), 374-381.

- [11] Black, M. J., and Yacoob, Y. Recognizing facial expressions in image sequences using local parameterized models of image motion. *International Journal of Computer Vision* 25, 1 (October 1997), 23–48.
- [12] Blanz, V., and Vetter, T. Face recognition based on fitting a 3d morphable model. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 25, 9 (September 2003), 1063–1074.
- [13] Briton, N. J., and Hall, J. A. Gender-based expectancies and observer judgments of smiling. *Journal of Nonverbal Behavior* 19, 1 (March 1995), 49–65.
- [14] Buddharaju, P., Dowdall, J., Tsiamyrtzis, P., Shastri, D., Pavlidis, I., and Frank, M. G. Automatic thermal monitoring system (athemos) for deception detection. *Computer Vision and Pattern Recognition, 2005. CVPR 2005. IEEE Computer Society Conference on* 2 (June 2005), 1179 vol. 2–.
- [15] Burgoon, J., Adkins, M., Kruse, J., Jensen, M. L., Meservy, T., Twitchell, D. P., Deokar, A., Nunamaker, J. F., Lu, S., Tsechenakis, G., Metaxas, D. N., and Younger, R. E. An approach for intent identification by building on deception detection. *System Sciences, 2005. HICSS '05. Proceedings of the 38th Annual Hawaii International Conference on* (January 2005), 21a–21a.
- [16] Burma, J. H. Self-tattooing among delinquents: A research note. *Sociology and Social Research* 43 (1959), 341–435.
- [17] Carroll, J. M., and Russell, J. A. Facial expressions in hollywood’s portrayal of emotion. *Journal of Personality and Social Psychology* 72, 1 (1997), 164–176.
- [18] Chang, C., and Lin, C. *LIBSVM: a library for support vector machines*, 2001. Software available at <http://www.csie.ntu.edu.tw/~cjlin/libsvm>.
- [19] Cohen, I., Cozman, F.G., Sebe, N., Cirelo, M.C., and Huang, T.S. Semisupervised learning of classifiers: theory, algorithms, and their application to human-computer interaction. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 26, 12 (December 2004), 1553–1566.
- [20] Cohn, J., Zlochower, A., Lien, J., and Kanade, T. Automated face analysis by feature point tracking has high concurrent validity with manual facs coding. *Psychophysiology* 36 (1999), 35–43.
- [21] Cohn, J. F. Foundations of human computing: facial expression and emotion. *ICMI '06: Proceedings of the 8th international conference on Multimodal interfaces* (2006), 233–238.
- [22] Cohn, J. F., Schmidt, K., Gross, R., and Ekman, P. Individual differences in facial expression: stability over time, relation to self-reported emotion, and ability to inform person identification. *Multimodal Interfaces, 2002. Proceedings. Fourth IEEE International Conference on* (2002), 491–496.

- [23] Colmenarez, A. J., and Huang, T. S. Face detection with information-based maximum discrimination. *Computer Vision and Pattern Recognition, 1997. Proceedings., 1997 IEEE Computer Society Conference on* (June 1997), 782–787.
- [24] Cootes, T. F., Edwards, G. J., and Taylor, C. J. Active appearance models. In *Computer Vision - ECCV'98, 5th European Conference on Computer Vision* (Freiburg, Germany, June 1998), Hans Burkhardt and Bernd Neumann, Eds., vol. 2, pp. 484–498.
- [25] Cootes, T. F., Edwards, G. J., and Taylor, C. J. Active appearance models. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 23, 6 (June 2001), 681–685.
- [26] Cootes, T. F., and Taylor, C. J. Constrained active appearance models. *Computer Vision, 2001. ICCV 2001. Proceedings. Eighth IEEE International Conference on* 1 (2001), 748–754 vol.1.
- [27] Cootes, T. F., Taylor, C. J., Cooper, D. H., and Graham, J. Active shape models - their training and applications. *Computer Vision Image Understanding* 61, 1 (January 1995), 38–59.
- [28] Craw, I., Tock, D., and Bennett, A. Finding face features. In *European Conference on Computer Vision* (1992), pp. 92–96.
- [29] Dai, Y., and Nakano, Y. Face-texture model based on sgld and its application in face detection in a color scene. *Pattern Recognition* 29, 6 (1995), 1007–1017.
- [30] Darwin, C. *The Expression of Emotions in Man and Animals*. Filiquarian Publishing, LLC, 1985.
- [31] Davies, R. H., Cootes, T. F., Twining, C. J., and Taylor, C. J. An information theoretic approach to statistical shape modelling. *British Machine Vision Conference* (2001), 3–11.
- [32] Donato, G., Bartlett, M. S., Hager, J. C., Ekman, P., and Sejnowski, T. J. Classifying facial actions. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 21, 10 (1999), 974–989.
- [33] Edwards, G. J., Taylor, C. J., and Cootes, T. F. Interpreting face images using active appearance models. *Automatic Face and Gesture Recognition, 1998. Proceedings. Third IEEE International Conference on* (April 1998), 300–305.
- [34] Eibl-Eihesfeldt, I. *Human Ethology*. Aldine de Gruyter, New York, 1989.
- [35] Ekman, P. *Telling Lies: Clues to Deceit in the Marketplace, Politics, and Marriage*. W. W. Norton, New York, 1985.

- [36] Ekman, P. *Handbook of Social Psychophysiology*, H. Wagner & A. Manstead ed. Wiley, Chichester, England, 1989, ch. The Argument and Evidence about Universals in Facial Expressions of Emotion, pp. 143–164.
- [37] Ekman, P. Facial expression and emotion. *American Psychologist* 48, 4 (April 1993), 384–392.
- [38] Ekman, P. Darwin, deception, and facial expression. *ANNALS of the New York Academy of Sciences* 1000 (December 2003), 205–221.
- [39] Ekman, P., and Friesen, W. V. *Pictures of Facial Affect*. Consulting Psychologist Press, Palo Alto, CA, 1976.
- [40] Ekman, P., and Friesen, W. V. *The Facial Action Coding System: A Technique for the Measurement of Facial Movement*. Consulting Psychologist Press, Palo Alto, CA, 1978.
- [41] Ekman, P., Friesen, W. V., and Hager, J. C. *The Facial Action Coding System*. Research Nexus eBook, Salt Lake City, UT, 2002.
- [42] Ekman, P., Sorenson, E. R., and Friesen, W. V. Pancultural elements in facial displays of emotions. *Science* 164, 3875 (1969), 86–88.
- [43] Essa, I. A., and Pentland, A. P. Coding, analysis, interpretation, and recognition of facial expressions. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 19, 7 (July 1997), 757–763.
- [44] Etemad, K., and Chellappa, R. Discriminant analysis for recognition of human face images. *Journal of the Optical Society of America A* 14, 8 (1997), 1724–1733.
- [45] Frank, M. G., and Ekman, P. The ability to detect deceit generalizes across different types of high-stake lies. *Journal of Personality and Social Psychology* 72, 6 (June 1997), 1429–1439.
- [46] Fukui, K., and Yamaguchi, O. Facial feature point extraction method based on combination of shape extraction and pattern matching. *Systems and Computers in Japan* 29, 6 (1998), 49–58.
- [47] Huynh-Thu, Q., Meguro, M., and Kaneko, M. Skin-color extraction in images with complex background and varying illumination. *Applications of Computer Vision, 2002. (WACV 2002). Proceedings. Sixth IEEE Workshop on* (2002), 280–285.
- [48] Ivanov, Y., Serre, T., and Bouvrie, J. Error weighted classifier combination for multi-modal human identification. Tech. Rep. AI Memo 2005-035, Computer Science and Artificial Intelligence Laboratory, Massachusetts Institute of Technology, Cambridge, MA, December 2005.

- [49] Izard, C., Dougherty, L., and Hembree, E. A. A system for identifying affect expressions by holistic judgments. Unpublished manuscript, Univ. of Delaware, 1983.
- [50] Jain, A., Bolle, R., and Pankanti, S. *Biometrics: Personal Identification in Networked Society*. Springer, New York, 2005.
- [51] Jain, A., Chen, Y., and Park, U. Scars, marks & tattoos (SMT): Physical attributes for person identification. Tech. Rep. MSU-CSE-07-22, Department of Computer Science and Engineering, Michigan State University, East Lansing, MI, July 2007.
- [52] Jain, A., Dass, S., and Nandakumar, K. Soft biometric traits for personal recognition systems. In *International Conference on Biometric Authentication* (Hong Kong, China, July 2004), pp. 731–738.
- [53] Jain, A. K., Dass, S. C., and Nandakumar, K. Can soft biometric traits assist user recognition? In *Biometric Technology for Human Identification. Proceedings of the SPIE* (August 2004), Anil K. Jain and Nalini K Ratha, Eds., vol. 5404, pp. 561–572.
- [54] Kanade, T. *Picture Processing by Computer Complex and Recognition of Human faces*. PhD thesis, Kyoto University, 1973.
- [55] Kanade, T., Cohn, J. F., and Tian, Y. Comprehensive database for facial expression analysis. *Automatic Face and Gesture Recognition, 2000. Proceedings. Fourth IEEE International Conference on* (2000), 46–53.
- [56] Kelly, M. D. Visual identification of people by computer. Tech. Rep. AI-130, Stanford AI Project, Stanford, CA.
- [57] Kirby, M., and Sirovich, L. Application of the karhunen-loeve procedure for the characterization of human faces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 12, 1 (January 1990), 103–108.
- [58] Kjeldsen, R., and Kender, J. Finding skin in color images. *Automatic Face and Gesture Recognition, 1996., Proceedings of the Second International Conference on* (October 1996), 312–317.
- [59] Kotropoulos, C., and Pitas, I. Rule-based face detection in frontal views. *Acoustics, Speech, and Signal Processing, 1997. ICASSP-97., 1997 IEEE International Conference on* 4 (April 1997), 2537–2540 vol.4.
- [60] Krumhuber, E., Manstead, A. S. R., and Kappas, A. Temporal aspects of facial displays in person and expression perception: The effects of smile dynamics, head-tilt, and gender. *Journal of Nonverbal Behavior* 31, 1 (March 2007), 39–56.

- [61] Lanitis, A., Taylor, C. J., and Cootes, T. F. Automatic face identification system using flexible appearance models. *Image and Vision Computing* 13, 5 (June 1995), 393–401.
- [62] Leung, T. K., Burl, M. C., and Perona, P. Finding faces in cluttered scenes using random labeled graph matching. *Computer Vision, 1995. Proceedings., Fifth International Conference on* (June 1995), 637–644.
- [63] Lien, J. J., Kanade, T., Cohn, J., and Li, C. Detection, tracking and classification of action units in facial expression. *Journal of Robotics and Autonomous Systems* 31 (July 1999), 131–146.
- [64] Lin, D., and Tang, X. Recognize high resolution faces: From macrocosm to microcosm. *Computer Vision and Pattern Recognition, 2006 IEEE Computer Society Conference on* 2 (2006), 1355–1362.
- [65] Lombroso, C. *Crime, Its Causes and Remedies*. Patterson Smith, New Jersey, 1912.
- [66] Lu, S., Tsechpenakis, G., Metaxas, D. N., Jensen, M. L., and Kruse, J. Blob analysis of the head and hands: A method for deception detection. *System Sciences, 2005. HICSS '05. Proceedings of the 38th Annual Hawaii International Conference on* (January 2005), 20c–20c.
- [67] Martinez, A. M., and Benavente, R. The AR Face Database. Tech. Rep. #24, Computer Vision Center, University of Alabama at Birmingham, Birmingham, AL, June 1998.
- [68] Mase, K., and Pentland, A. Recognition of facial expression from optical flow. *IEICE transactions* 74, 10 (1991), 3474–3483.
- [69] McKenna, S., Gong, S., and Raja, Y. Modelling facial colour and identity with gaussian mixtures. *Pattern Recognition* 31, 12 (1998), 1883–1892.
- [70] Osuna, E., Freund, R., and Girosit, F. Training support vector machines: an application to face detection. *Computer Vision and Pattern Recognition, 1997. Proceedings., 1997 IEEE Computer Society Conference on* (June 1997), 130–136.
- [71] Peleg, G., Katzir, G., Peleg, O., Kamara, M., Brodsky, L., Hel-Or, H., Keren, D., and Nevo, E. From the cover: Hereditary family signature of facial expression. *Proceedings of the National Academy of Sciences of the United States of America* 103, 43 (October 2006), 15921–15926.
- [72] Pentland, A., Moghaddam, B., and Starner, T. View-based and modular eigenspaces for face recognition. *Computer Vision and Pattern Recognition, 1994. Proceedings CVPR '94., 1994 IEEE Computer Society Conference on* (June 1994), 84–91.

- [73] Pierrard, J. S., and Vetter, T. Skin detail analysis for face recognition. *Computer Vision and Pattern Recognition, 2007. CVPR '07. IEEE Conference on* (June 2007), 1–8.
- [74] Rajagopalan, A. N., Kumar, K. S., Karlekar, J., Manivasakan, R., Patil, M. M., Desai, U. B., Poonacha, P. G., and Chaudhuri, S. Finding faces in photographs. *Computer Vision, 1998. Sixth International Conference on* (January 1998), 640–645.
- [75] Rhodes, T. F. *Alphonse Bertillon: Father of Scientific Detection*. Abelard-Schuman, New York, NY, 1956.
- [76] Rosenblum, M., Yacoob, Y., and Davis, L. S. Human expression recognition from motion using a radial basis function network architecture. *Neural Networks, IEEE Transactions on* 7, 5 (September 1996), 1121–1138.
- [77] Rowley, H.A., Baluja, S., and Kanade, T. Neural network-based face detection. *Computer Vision and Pattern Recognition, 1996. Proceedings CVPR '96, 1996 IEEE Computer Society Conference on* (June 1996), 203–208.
- [78] Rowley, H.A., Baluja, S., and Kanade, T. Neural network-based face detection. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 20, 1 (January 1998), 23–38.
- [79] Samaria, F. *Face Recognition using hidden markov models*. PhD thesis, University of Cambridge, Cambridge, UK, 1994.
- [80] Samaria, F. S., and Young, S. Hmm-based architecture for face identification. *Image and Vision Computing* 12, 8 (October 1994), 537–543.
- [81] Scherer, K., and Ekman, P. *Handbook of Methods in Nonverbal Behavior Research*. Cambridge University Press, Cambridge, England, 1982.
- [82] Schmidt, K.L., and Cohn, J.F. Dynamics of facial expression: normative characteristics and individual differences. *Multimedia and Expo, 2001. ICME 2001. IEEE International Conference on* (August 2001), 547–550.
- [83] Schneiderman, H., and Kanade, T. Probabilistic modeling of local appearance and spatial relationships for object recognition. *Computer Vision and Pattern Recognition, 1998. Proceedings. 1998 IEEE Computer Society Conference on* (June 1998), 45–51.
- [84] Shakhnarovich, G., Viola, P. A., and Moghaddam, B. A unified learning framework for real time face detection and classification. *Automatic Face and Gesture Recognition, 2002. Proceedings. Fifth IEEE International Conference on* (May 2002), 14–21.

- [85] Sirovich, L., and Kirby, M. Low-dimensional procedure for the characterization of human faces. *Journal of the Optical Society of America A* 4, 3 (1987), 519–524.
- [86] Slowe, T. E., and Govindaraju, V. Automatic deceit indication through reliable facial expressions. *Automatic Identification Advanced Technologies, 2007 IEEE Workshop on* (June 2007), 87–92.
- [87] Staderini, E. M. An UWB radar based stealthy ‘Lie Detector’. Online technical report.
- [88] Stegmann, M. B. Analysis and segmentation of face images using point annotations and linear subspace techniques. Tech. Rep. IMM-REP-2002-22, Informatics and Mathematical Modelling, Technical University of Denmark, Lyngby, Denmark, August 2002.
- [89] Sung, K. K., and Poggio, T. Example-based learning for view-based human face detection. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 20, 1 (January 1998), 39–51.
- [90] Suwa, M., Sugie, N., and Fujimora, K. A complimentary note on pattern recognition of human emotional expression. *International Joint Conference on Pattern Recognition* (1978), 408–410.
- [91] Swets, D. L., and Weng, J. J. Using discriminant eigenfeatures for image retrieval. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 18, 8 (August 1996), 831–836.
- [92] Terzopoulos, D., and Waters, K. Analysis of facial images using physical and anatomical models. *Computer Vision, 1990. Proceedings, Third International Conference on* (December 1990), 727–732.
- [93] Tian, Y., Kanade, T., and Cohn, J. Recognizing action units for facial expression analysis. Tech. Rep. CMU-RI-TR-99-40, Robotics Institute, Carnegie Mellon University, Pittsburgh, PA, December 1999.
- [94] Tian, Y.-I., Kanade, T., and Cohn, J.F. Recognizing action units for facial expression analysis. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 23, 2 (February 2001), 97–115.
- [95] Tian, Y.-L., Kanade, T., and Cohn, J.F. Evaluation of gabor-wavelet-based facial action unit recognition in image sequences of increasing complexity. *Automatic Face and Gesture Recognition, 2002. Proceedings. Fifth IEEE International Conference on* (May 2002), 229–234.
- [96] Turk, M.A., and Pentland, A.P. Eigenfaces for recognition. *Journal of Cognitive Neuroscience* 3, 1 (June 1991), 71–86.

- [97] Turk, M.A., and Pentland, A.P. Face recognition using eigenfaces. *Computer Vision and Pattern Recognition, 1991. Proceedings CVPR '91., IEEE Computer Society Conference on* (June 1991), 586–591.
- [98] Wayman, J. L. Benchmarking large-scale biometric systems: Issues and feasibility. In *Proceedings of CardTech SecurTech Government'97* (September 1997).
- [99] Yacoob, Y., and Black, M. J. Parameterized modeling and recognition of activities. *ICCV '98: Proceedings of the Sixth International Conference on Computer Vision* (1998), 120–127.
- [100] Yacoob, Y., and Davis, L. S. Recognizing human facial expressions from long image sequences using optical flow. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 18, 6 (1996), 636–642.
- [101] Yang, G., and Huang, T. S. Human face detection in a complex background. *Pattern Recognition* 27, 1 (1994), 53–63.
- [102] Yang, J., and Waibel, A. A real-time face tracker. *Applications of Computer Vision, 1996. WACV '96., Proceedings 3rd IEEE Workshop on* (December 1996), 142–147.
- [103] Yang, M. H., Kriegman, D. J., and Ahuja, N. Detecting faces in images: a survey. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 24, 1 (January 2002), 34–58.
- [104] Yow, K. C., and Cipolla, R. Feature-based human face detection. *Image and Vision Computing* 15, 9 (1997), 713–735.
- [105] Zhang, Y., and Ji, Q. Active and dynamic information fusion for facial expression understanding from image sequences. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 27, 5 (May 2005), 699–714.
- [106] Zhang, Z. Feature-based facial expression recognition: Sensitivity analysis and experiments with a multilayer perceptron. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 13, 6 (1999), 893–911.
- [107] Zhao, W., Chellapa, R., and Phillips, P. J. Subspace linear discriminant analysis for face recognition. Tech. Rep. CAR-TR-914, Center for Automation Research, University of Maryland, College Park, MD, 1999.
- [108] Zhao, W., Chellappa, R., and Krishnaswamy, A. Discriminant analysis of principal components for face recognition. *Automatic Face and Gesture Recognition, 1998. Proceedings. Third IEEE International Conference on* (April 1998), 336–341.
- [109] Zhao, W., Chellappa, R., Phillips, P. J., and Rosenfeld, A. Face recognition: A literature survey. *ACM Computing Surveys* 35, 4 (2003), 399–458.