

# Studies in Individuality: Can Students, Teachers and Schools be determined from Children's Handwriting?

Sargur N. Srihari, Gang Chen, Zhen Xu and Lisa Hanson

CEDAR, Department of Computer Science and Engineering  
University at Buffalo, The State University of New York, USA  
{srihari}@buffalo.edu  
<http://www.cedar.buffalo.edu>

**Abstract.** The individuality of handwriting is the principal underpinning of forensic handwriting examination. Studies of individuality have considered different statistical extremes to obtain handwriting samples. The first is a representative population drawn from a country. The second is a population of twins— so as to reflect genetic similarity. A third approach is to study whether teachers and schools have an influence on individuality. This paper presents preliminary results of individuality studies with data from children's handwriting, in grades 2-4, to identify the school, teacher and student. Considering the single handwritten word *and* we evaluate the performances of two methods, one based on feature values assigned by human questioned document examiners and the other based on automatically computing image features. Results are given for determining the school, the teacher and the student from images using restricted Boltzmann machines. Results of identifying the school with human assigned features and support vector machines are also given.

**Keywords:** Computational Forensics, Handwriting Individuality, Questioned Document Examination, Restricted Boltzmann Machine

## 1 Introduction

Forensic identification based on handwriting rests on the premise: *no two people write the same way and no one person writes the same way twice* [10, 1, 4]. Various types of quantitative support for the hypotheses of identifiability have been proposed using computational methods. One of these is to determine error rates for the writer verification problem using writing samples from a representative human population [13]. While the accuracies achieved were high, it was felt that a diverse population would make the task unrealistically easy. A second approach was to factor-in genetic attributes and study the discriminability of the handwriting of twins [14]. A third approach takes the other side of the nature vs. nurture argument – one where the handwriting samples are from individuals taught by the same method. Taking this third approach we study here the handwriting traits of children.

Data for the present study consists of samples of handwriting of elementary school children. In the present paper we describe the analysis of the handwriting of children in Grades 2-4 using : (i) images of handwritten *and* and (ii) characteristic values assigned by forensic document examiners (FDEs) to the handwriting of each student. The tasks reported upon here are on whether it is possible to determine the student, the teacher and the school.

## 2 Data Sets

The handwriting samples are from a large number of students (approx. 1800) as they are learning (2nd grade) or have just learned (3rd and 4th grade) how to produce cursive and printed writing (2012). Five independent school districts were chosen to participate in this study. The students wrote a paragraph twice in cursive writing and twice by hand printing using the Zaner-Bloser style of handwriting taught to them. The Zaner-Bloser Copy Book Handwriting Style [5], Figure 1, is the hand printing / hand writing copy book style being taught in elementary schools in Minnesota to introduce children to writing. The paragraph con-



Fig. 1: Zaner-Bloser copy book style for word *and*: (a) cursive, and (b) printed.

sists of the following text: The brown fox went into the barn where he saw the black dog. After a second, the black dog saw the fox too. The brown fox was fast and quick. The black dog was not fast and he lost the fox. The fox hid in a hole and waited for the black dog to go home. After the black dog went home, the fox was able to go to the hole he called home and saw all the other foxes. The other foxes were glad to see him and they all asked him to tell them about his day.

A sample of printed handwriting of a student is shown in Figure 2. All the writing samples were collected using the same forms to control variation due to document size and/or format. All students received the same instructions, as each of the teachers read the same instruction paragraph prior to collecting the writing samples.

The word *and* appears five times in the paragraph and was chosen as the focus of this study. The word *and* was chosen because it is one of few words that children write over and over during their early writings and have therefore began to develop individual handwriting characteristics rather than words that are not written often. There are an average of 5 to 10 samples of the word *and*




Fig. 2: School children's writing sample: hand-printed.

per student in hand printing and in cursive (except for second graders). Five of the datasets were used in the analysis described here: *printed writing* from the 2nd, 3rd and 4th grade and *cursive writing* from the 3rd and 4th grade.

We studied two different tasks: (i) *verification*, which is the task of determining whether two input samples are from the same or different sources, and (ii) *identification*, which is the task of determining the source of a single input sample from among a (closed) set of sources [13]. The verification problem is a binary classification problem to determine whether two samples of writing are from the same source— whether they are from the same student, same teacher or same school. The identification problem is a multi-class problem, to determine the source of an input sample among one of several (individuals, teachers or schools).

Two types of inputs for each of verification and identification were conducted. The first type of input were whole images of *and* as described in Section 3 and in the second we used a vector of handwriting characteristics of *and* as provided by human FDEs (Section 4).

### 3 Image-based Approach

For the verification task, we took the approach of providing as input to the system raw images of each pair of *and* and leaving it to an automatic system to

learn the features. The classification algorithm was trained to produce as output whether or not the inputs are from the same source or from different sources.

### 3.1 Classifier

For the verification task we used the restricted Boltzmann machine (RBM), a cornerstone for many variant neural networks [8, 2, 6]. The RBM and its variants yield state-of-the-art results in various recognition tasks [7, 6, 11].

Given a training set  $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}$ , with the  $i$ -th pair: an input vector  $\mathbf{x}_i$  and a target class  $y_i$ , where  $\mathbf{x}_i \in \mathbb{R}^d$  and  $y_i \in \{1, C\}$ , a RBM with  $n$  hidden units is a parametric model of the joint distribution between a layer of hidden variables  $\mathbf{h} = (h_1, \dots, h_n)$  and the observations  $\mathbf{x} = (x_1, \dots, x_d)$  and  $y$ . The RBM joint likelihood takes the form:

$$p(y, \mathbf{x}, \mathbf{h}) \propto e^{-E(y, \mathbf{x}, \mathbf{h})} \quad (1)$$

where the energy function is

$$E(y, \mathbf{x}, \mathbf{h}) = -\mathbf{h}^T \mathbf{W} \mathbf{x} - \mathbf{b}^T \mathbf{x} - \mathbf{c}^T \mathbf{h} - \mathbf{d}^T \mathbf{y} - \mathbf{h}^T \mathbf{U} \mathbf{y} \quad (2)$$

with parameters  $\Theta = \{\mathbf{W}, \mathbf{b}, \mathbf{c}, \mathbf{d}, \mathbf{U}\}$  and  $\mathbf{y} = (1_{y=i})_{i=1}^C$  for  $C$  classes. And we can compute the following conditional likelihood:

$$p(\mathbf{h}|y, \mathbf{x}) = \prod_j p(h_j|y, \mathbf{x}) \quad (3a)$$

$$p(\mathbf{x}|\mathbf{h}) = \prod_i p(x_i|\mathbf{h}) \quad (3b)$$

$$p(y|\mathbf{h}) = \frac{e^{d_y + \sum_j U_{jy} h_j}}{\sum_{y^*} e^{d_{y^*} + \sum_j U_{jy^*} h_j}} \quad (3c)$$

$$p(x_i = 1|\mathbf{h}) = \text{logistic}(b_i + \sum_j W_{ji} h_j) \quad (3d)$$

where  $\text{logistic}(x) = 1/(1 + e^{-x})$ . To learn RBM parameters, we need to optimize the joint likelihood  $p(y, \mathbf{x})$  on training data  $\mathcal{D}$ . Note that it is intractable to compute  $p(y, \mathbf{x})$ , because it needs to model  $p(x)$ . Fortunately, Hinton proposed an efficient stochastic descent method, namely contrastive divergence (CD) [3] to maximize the joint likelihood.

For classification problem, we need to compute the conditional probability for  $p(y|\mathbf{x})$ . As shown in [12], this conditional distribution has explicit formula and can be calculated exactly, by writing it as follows:

$$p(y|\mathbf{x}) = \frac{e^d \prod_{j=1}^n (1 + e^{c_j + U_{jy} + \sum_i W_{ji} x_i})}{\sum_{y^*} e^{d_{y^*}} \prod_{j=1}^n (1 + e^{c_j + U_{jy^*} + \sum_i W_{ji} x_i})} \quad (4)$$




Fig.3: “and” samples cropped from grades 2, 3 and 4 text images on Print dataset. The first 2 rows are from grade 2, the middle 2 rows are from grade 3, and the last 2 rows are from grade 4.

Table 1: Distribution of students for handprint samples.

Number	Group Distribution		
	Grade 2	Grade 3	Grade 4
Students	193	324	336
Teachers	12	16	13
Schools	3	4	4

### 3.2 Input Images

We cropped the word “and” as our training samples from print dataset (see Fig. 3). We sampled a total of 7,782 images, which are distributed among grade 2 to grade 4 with 2241, 2752 and 2789 samples, respectively. In this subset, we have a total of 6 schools, 41 teachers and 1,184 students. Then, we divide students into groups according for each grade. Then, for each grade we categorize the verification problem into three levels: school level, teacher level and student level.

Considering the different sizes of “and” images, we first resize them into the same average width and height. Then, we do some preprocessing to all resized “and” images. For example, we binarize each image, and then vectorize it as its feature representation. Then, we construct pairs from all the given vectorized images. Basically, we concatenate the two corresponding feature vectors (see Figure 4 and give it a positive label if these two images from the same group, otherwise a negative label.




Fig. 4: Vectorization for image-based verification.

For student level, we have around 6-10 “and” images for each student, so we can construct positive pairs for all students. However, the negative pairs are very large, thus we random sample negative pairs so that the number of samples are roughly equal to that of positive pairs. Given sampled pairs, we can train RBM with 10-fold cross validation. For teacher level, each teachers have around 20 to 30 students, so the pairs grow rapidly. We random sample 10,000 pairs from both positive and negative pairs for each group, and then train RBM with 10-fold cross validation. For school level, it has the same situation as the teacher level. Thus we take the same strategy as what we did in the teacher level.

*Parameter setting* In all our experiments, we set the number of hidden units  $n = 50$  and learning rate  $\alpha = 0.1$  for RBM, and use 10-fold cross validation to evaluate performance.

*Results* We used RBM as the verification classifier and determined the error rates for each level in each group for handprint as shown in Table 2(a). The verification algorithm is unable to determine either teacher or school, since the error rate in this two-class problem is close to 50%. On the other hand the student can be determined with better than random chance. Although the error rate is 45%, it is promising in that we only used a single word as input.

Classification error rate into schools, using a multi-class RBM, is shown in Table 3 on both print and cursive datasets respectively. Here we see that the error rate gets progressively worse with each grade. This indicates higher degree of individualization with increasing grade.

Table 2: Results for handprinted (left) and cursive (right) images respectively. (a) Verification error rates for groups on Print dataset. (b) Verification error rates for groups on Cursive dataset.

Verification error rate				Verification error rate			
Levels	Grades			Levels	Grades		
	Grade 2	Grade 3	Grade 4		Grade 2	Grade 3	Grade 4
Student level	44.92%	43.24%	46.52%	Student level	NA	44.22%	45.39%
Teacher level	51.29%	47.92%	50.20%	Teacher level	NA	48.62%	49.93%
School level	46.12%	50.58%	53.66%	School level	NA	49.21%	54.79%

Table 3: Identification error rates for schools on Print (left) and Cursive (right) datasets respectively.

(a) Error rates on Print dataset.

Grade	Error Rate
2nd Grade (3 schools)	47.47%
3rd Grade (4 schools)	53.06%
4th Grade (4 schools)	68.76%

(b) Error rates on Cursive dataset.

Grade	Error Rate
3rd Grade (4 schools)	59.34%
4th Grade (4 schools)	68.35%

## 4 Characteristics-based Approach

### 4.1 Handwriting Characteristics

QDEs assign different characteristics to handwriting manually, depending on whether the writing is *cursive* or *hand-print*. A handwritten letter, or a combination of letters such as the word *and*, can be represented by a set of  $D$  characteristics,  $\mathbf{X} = \{X_i\}, i = 1, \dots, D$  where characteristic  $X_i$  takes one of  $d_i$  discrete values. Based on the characteristics defined in Figures 6, the Zaner-Bloser Copy Book style of writing letter construct features can be assigned values as illustrated in Figure 5.




Fig. 5: Characteristics of Handwritten *and* in Zaner-Bloser Copy Book Style as Specified by FDE.

Table 4: The number of handwriting samples for different schools.

School	Printed		Cursive	
	3rd	4th	3rd	4th
Liberty Ridge	67	65	82	77
Middleton	125	119	73	72
Royal Oaks	80	79	74	70
Red Rock	121	103	71	68
Woodbury	80	78	71	65

Table 5: Characteristics-based identification error for schools

Classification Error	Cursive	Handprint
3rd Grade	45.45%	51.19%
4th Grade	48.57%	58.33%

The characteristics assigned to children’s handwriting is represented in Figure 6. The characteristic values were assigned by QDEs using a *truthing tool* [9].

Initial stroke of "a"	staff right	staff left	staff center	
Formation of "a" staff	tented	retraced	looped	no staff
Number of "n" arches	one	two		
Shape of "n" arches	pointed	rounded	retraced	combination
Location of "n" mid	above base	below base	at base	
Formation of "d" staff	tented	retraced	looped	
Formation of "d" initial	overhand	underhand	straight across	
Formation of "d" terminal	curved up	straight	curved down	no obvious end stroke
Symbol	unusual		symbol	
a-n relationship	a taller	a equal	a smaller	
a-d relationship	a taller	a equal	a smaller	
n-d relationship	n taller	n equal	n smaller	

(a)

# strokes in "a"	one	two	three	uppercase
formation of "a" staff	tented	retraced	looped	no staff
# strokes in "n"	one	two	three	uppercase
formation of "n" staff	tented	retraced	looped	no staff
shape of arch of "n"	pointed	rounded		
# strokes in "d"	one	two	three	uppercase
formation of "d" staff	tented	retraced	looped	no staff
initial stroke of "d"	staff top	bulb		
Unusual formations	formation		symbol	
a-n relationship	a taller	a equal	a smaller	
a-d relationship	a taller	a equal	a smaller	
n-d relationship	n taller	n equal	n smaller	

(b)

Fig. 6: Twelve characteristics of *and* together with their possible values: (a) cursive and (b) hand-print.

Samples of handwritten *and* by children of grade 2, 3 and 4 and their respective feature values are shown in Figure 7. Out of these, the samples for Handprint and Cursive writing in Grade 4 were extracted from the paragraphs in Figure 2.

## 4.2 Classification

A support vector machine (SVM) was used to classify an input vector of characteristics into one of five schools: Liberty Ridge, Middleton, Royal Oaks, Red Rock, and Woodbury. An SVM is a two-class classifier which can be generalized to more than two classes using a one-versus-rest methodology.






Fig. 7: Samples of Handwritten *and* together with feature values assigned by QDEs.

The total number of samples are shown in Table 4. We randomly chose 90% of the data as training set and the remaining 10% as the testing data. The classification error is shown in Table 5. From the table we see that cursive handwriting has lower error or higher individuality.

### 4.3 Individual School Handwriting Characteristics

By constructing a probabilistic generative models for the characteristics data, we can get more insights. We generated Bayesian networks for each grade with different schools using a causal algorithm [15]. Using these Bayesian networks, we can find the common handwriting characteristics for each individual school. The images of most common handwritten styles of "and" are shown in Figure 8 and 9. We can find school handwriting characteristics by inference from Bayesian networks. Next we give some examples of what we have learned from the 3rd handwriting data.

#### *Printed Handwriting Characteristics*

- Students from Middleton are more likely to write tented 'n' (8 students), while for other 4 schools there are total 3 students writing in this way.
- Students from Middleton are more likely to write inconsistent 'a'- 'n' and 'n'- 'd' relationships (total 24 students), while for other schools the total number is 7.
- Only students from Royal Oaks write inconsistent number of strokes for 'a', 'n', and 'd'.

*Cursive Handwriting Characteristics*

- Students from Liberty Ridge are more likely to write pointed 'n' (9 students), while for other schools the biggest number is 2.
- Only students from Liberty Ridge write tented 'd'.
- Students from Middleton are more likely to write inconsistent number of 'n' arches (23 students), while for other schools the biggest number is 3.
- Only students from Red Rock write straight across 'd'.
- Students from Middleton are more likely to write no staff 'a' (23 students), while for other schools the biggest number is 4.
- Students from Woodbury are more likely to write no obvious end stroke of 'd' (9 students), while for other schools the biggest number is 2.
- Students from Middleton are more likely to write inconsistent formation of 'd' initial and terminal (total 32 students), while for other schools the total number is 7.

With printed handwriting, students in Liberty Ridge, 'a' is more likely to be smaller than 'd', while in other schools 'a' is usually taller than 'd'. For students in Middleton, 'n' is more likely tented. For students in Royal Oaks, the number of strokes for 'd' is usually larger. For students in Red Rock, the number of strokes for 'a' is usually larger. In addition, 'a' is more likely looped. For students in Woodbury, 'n' is more likely taller than 'd'.




Fig. 8: The most common style of hand-printed *and* from five schools: (a) Liberty Ridge; (b) Middleton; (c) Royal Oaks; (d) Red Rock; (e) Woodbury.




Fig. 9: The most common style of cursive *and* from five schools: (a) Liberty Ridge; (b) Middleton; (c) Royal Oaks; (d) Red Rock; (e) Woodbury.

## 5 Discussion

We have analyzed the handwriting of children using a single word of text, i.e., the word *and*. Both the verification task and the identification task were considered using (i) whole images and (ii) characteristics provided by FDEs.

Using image-based verification, we see that it is not possible to determine whether two samples are from the same school and teacher. On the other-hand, whether two samples are from the same student can be determined with better than random chance. This supports the individuality argument individuals are more distinctive than a collection of individuals. In image-based identification we see that the error rate increases with grade thereby supporting individuality with age as well.

Using characteristics-based identification the error rate is about 45%, while a random assignment to schools would have only resulted in 80%. This supports the hypothesis that schools have some distinctiveness which is captured by the characteristics specified by FDEs.

## Acknowledgement

The work was supported by Award No. 2010-DN-BX-K212 of the NIJ, Office of Justice Programs, U.S. DoJ. The opinions expressed are those of the author(s) and do not necessarily reflect those of the DoJ.

## References

1. Hilton, O.: Scientific Examination of Questioned Documents, Revised Edition. CRC Press (1993)
2. Hinton, G.E., Salakhutdinov, R.R.: Reducing the dimensionality of data with neural networks. *Science* 313(5786), 504–507 (Jul 2006)
3. Hinton, G.E.: Training products of experts by minimizing contrastive divergence. *Neural Comput.* 14(8), 1771–1800 (Aug 2002)
4. Huber, R.A., Headrick, A.M.: *Handwriting Identification: Facts and Fundamentals*. CRC Press (1999)
5. Kelly, J.S., Lindblom, B.: *Scientific Examination of Questioned Documents, Second Edition*. CRC Press (2006)
6. Krizhevsky, A., Sutskever, I., Hinton, G.E.: Imagenet classification with deep convolutional neural networks. In: *Advances in Neural Information Processing Systems* (2012)
7. Larochelle, H., Bengio, Y.: Classification using discriminative restricted Boltzmann machines. In: *Proceedings of the 25th International Conference on Machine Learning*. pp. 536–543. ICML '08, ACM, New York, NY, USA (2008)
8. LeCun, Y., Boser, B., Denker, J.S., Henderson, D., Howard, R.E., Hubbard, W., Jackel, L.D.: Backpropagation applied to handwritten Zip Code recognition. *Neural Comput.* 1(4), 541–551 (Dec 1989)
9. M.Puri, Srihari, S.N., Hanson, L.: Probabilistic modeling of children’s handwriting. In: *Document Recognition and Retrieval XX*. SPIE (2014)
10. Osborn, A.: *Questioned Documents*. Nelson Hall Pub (1929)
11. Rashid, S.F., Schambach, M.P., Rottland, J., von der Nüll, S.: Low resolution arabic recognition with multidimensional recurrent neural networks. In: *Proceedings of the 4th International Workshop on Multilingual OCR*. pp. 6:1–6:5. MOCR '13, ACM, New York, NY, USA (2013)

12. Salakhutdinov, R., Mnih, A., Hinton, G.: Restricted boltzmann machines for collaborative filtering. In: Proceedings of the 24th International Conference on Machine Learning. pp. 791–798. ICML '07, ACM, New York, NY, USA (2007)
13. Srihari, S.N., Cha, S., Arora, H., Lee, S.: Individuality of handwriting. *Journal of Forensic Sciences* 44(4), 856–872 (2002)
14. Srihari, S.N., Huang, C., Srinivasan, H.: On the discriminability of the handwriting of twins. *Journal of Forensic Sciences* 53(2), 430–446 (2008)
15. Xu, Z., Srihari, S.: Bayesian network structure learning using causality. In: Submitted (2014)