

Fuzzy Control Structures in Multiple Parameter Systems: An Application in Handwritten Address Interpretation Systems

Krassimir Ianakiev and Venu Govindaraju
Department of Computer Science & Engineering
University at Buffalo, Amherst, NY 14280
email: govind@cse.buffalo.edu

Abstract

Most practical software systems are a conglomerate of many modules, where each module has its own parameters that control the accuracy of the module. While each individual module can be optimized by tuning the relevant parameters, it is a non-trivial task to optimize the entire system. When the number of modules and the parameters are few, manual choosing of all parameters is possible by a "trial and error" mechanism. However, when the modules are many, other methods have to be adopted.

We use the Fuzzy set technology for the purpose in the particular application of a Handwritten Address Interpretation System. We use a fuzzy measure based on the topology of the "blind" set of handwritten addresses and a pre-determined neighborhood to construct the fuzzy membership function. This allows a non-linear partitioning of the results to maximize the correct rate. On a test set of 10,000 images, the fuzzy methodology accomplishes 5% higher accuracy.

1. Introduction

Most practical software systems are a conglomerate of many modules, where each module has its own parameters that control the accuracy of the module. While each individual module can be optimized by tuning the relevant parameters, it is a non-trivial task to optimize the entire system. Clearly, the optimal setting of parameters for the best performance of the entire system is not simply a choosing of the parameters that optimize the individual modules- for the modules could be competing.

When the number of modules and the parameters are few, manual choosing of all parameters is possible by a "trial and error" mechanism. However, when the modules are many, other methods have to be adopted. Further, most current systems take an approach of "if then else" rules where the parameters are linear and are compared with threshold values. Both of these issues must be addressed in

a methodical way. Neural networks have been suggested as one possible approach to this task. However, this calls for very large training samples which are difficult to come by at system level.

We use the Fuzzy set technology for the purpose in the particular application of a Handwritten Address Interpretation System. The modules that constitute the system are: (i) Address Block Location, (ii) Line separation module, (iii) Word Separation Module, (iv) ZIP Code recognition module, (v) Street number recognition module, and (vi) Street name recognition module. Each of these modules have sub-modules and face the same problems at a micro-level. The ZIP Code recognition and Street number modules invoke a numeral recognition module and a Street number recognition module invokes a character recognition module. Each of the modules and sub-modules are controlled by many parameters.

In the final analysis, a particular recognition of the address block is deemed either worthy of being accepted as correct or rejected as unreliable. The idea is to accept as high a percentage of addresses as possible while making a minimum of errors. A conservative setting of the thresholds at the final stage would cause many correct results to be rejected in order to keep the error rate low.

We will use a fuzzy measure based on the topology of the "blind" set of handwritten addresses and a pre-determined neighborhood to construct the fuzzy membership function. This will allow a non-linear partitioning of the results to maximize the correct rate.

2. Handwritten Address Interpretation

Determining the delivery location for mail pieces based on handwritten addresses is a problem that trained humans can normally solve. As a problem in machine reading and interpretation, it presents many challenges like word recognition, digit recognition, combining high level and low level information, control structure to satisfy mutual constraints.

The United States Postal Service sorts mail by utilizing an encoding of each mail piece by a string of digits, the first




Figure 1: Each graph shows a perspective of the 3-dimensional space of confidences returned by the ZIP Code recognition module, the Street Number recognition module and the Street Name module. The green points in the space represent addresses that were recognized correctly and the red ones represent the incorrect ones. Clearly a fuzzy boundary exists between the corrects and the errors.

Justin Lofgren
 480 Ellen St.
 East Amherst, NY
 14057

Encode: 14051-1144

Figure 2: A handwritten address has many fields that must be recognized in order to find the destination code. The fields of interest in this paper are the ZIP Code, the Street Number and the Street Name.

five of which are referred to as the ZIP Code, and together with the next four as the ZIP+4.

A complete system for unconstrained address interpretation needs several components. At the pre-processing level, the written matter from the handwritten address block image must be distinguished from the background, and irrelevant streaks such as underlines must be removed. The text line locations in the address must be determined, the text lines separated into words, and candidates for the ZIP Code, street number, and street name must be determined. Separating an address line into words is non-trivial because the distance between components is often misleading. The ZIP Code and street number are read next. The digit strings in these fields often have touching digits. Finally, the Postal directory is queried with the street number and the ZIP Code to obtain a lexicon of street names. The word recognition algorithm ranks the lexicon based on several features it extracts from the street name image. A correct recognition of the ZIP Code AND the Street Number AND the Street Name leads to a correct encoding of the entire address [2].

As is clear from the example of Figure 2, first and foremost, the accurate location of these modules is a challenge. Recognition of handwritten characters in an unconstrained environment as is presented by the postal domain, adds the difficulty.

The goal is to return an encode for an address only when the system is confident. The cost of rejecting an address image without any encode is less severe than returning an incorrect encode. Hence, each module is expected to return its recognition result along with a confidence measure. During the training phase, the optimal threshold on the confidence measure is chosen so that whenever the confidence exceeds the pre-determined threshold the recognition results of the module is accepted.

3. Topology, Measure and Membership of Fuzzy Sets

Let V be a "blind" set of handwritten addresses, that we will use to simulate the fuzzy boundaries between the two

classes ω_0 and ω_1 . V is partitioned into a disjoint union of subsets V_0 and V_1 , where subset V_1 contains all correctly recognized handwritten addresses in V and V_0 is the complement of V_1 in V , i.e it contains those addresses in V for which at least one of the recognition modules returns result, different from the truth.

Let $f_i(x)$ be the characteristic function of the set V_i , i.e.

$$f_i(x) = \begin{cases} 1 & \text{if } x \in V_i \\ 0 & \text{otherwise,} \end{cases}$$

Let $W = [0, 1]_0 \times [0, 1]_1 \times [0, 1]_2$, be a cartesian product of 3 copies of the interval $[0, 1]$. Here $[0, 1]_i$ denotes the i^{th} -copy of the interval $[0, 1]$. We can convert W into a topological space by introducing one of the following two topologies: finite or Euclidian.

1. Finite Topology:

Assume that each interval $[0, 1]_i$ is partitioned into finitely many disjoint sub-intervals $W_i^1, W_i^2, \dots, W_i^m$. Then the set B of neighborhoods $W_0^{i_0} \times W_1^{i_1} \times W_2^{i_2}$ forms a base of a topology in W . Let us enumerate the elements of B , i.e $B = \{B_1, B_2, \dots, B_M\}$, where $M = m^3$.

Let $W(i_1, i_2, \dots, i_j)$ be the union of the sets $B_{i_1}, B_{i_2}, \dots, B_{i_j}$, i.e

$$W(i_1, i_2, \dots, i_j) = B_{i_1} \cup B_{i_2} \cup \dots \cup B_{i_j}.$$

Let \mathcal{M} be the family of all such sets $W(i_1, i_2, \dots, i_j)$, i.e

$$\mathcal{M} = \{W(i_1, i_2, \dots, i_j) : j \in \{1, 2, \dots, M\},$$

$$1 \leq i_1 < i_2 < \dots < i_j \leq M\}.$$

Then \mathcal{M} is a topology of W .

2. Euclidian Topology:

In this case we will consider W with the topology induced by the Euclidian topology of the space \mathbb{R}^3 , i.e the topology that is generated by the collection of all balls in the set W [3].

Next step is to construct a σ -algebra, that includes the topology of the set W . Again we consider two cases.

In the finite case, it is apparent that

$$B_0 \cup B_1 \cup \dots \cup B_M = W.$$

Hence $W \in \mathcal{M}$. Moreover, since no two elements of the base B intersect, if the set $A \in \mathcal{M}$, then $A^c \in \mathcal{M}$, where A^c denotes the complement of A in W . Also, the union of any two sets from \mathcal{M} is a set from \mathcal{M} . This, together with the fact that \mathcal{M} is finite, implies that \mathcal{M} is a σ -algebra [3].

In the Euclidian case, we define \mathcal{M} to be Borel σ -algebra, generated by the Euclidian topology.

Now, we will introduce a positive σ -additive measure for the σ -algebra \mathcal{M} . Having defined the function $f(x)$, we can define functions $\mu_i : \mathcal{M} \rightarrow \mathbb{R}$, $i = 0, 1$ as follows:

$$\mu_i(A) = \sum_{\{x \in V_i : \Phi(x) \in A\}} f_i(x) \quad (1)$$

for all $A \in \mathcal{M}$. The values of functions μ_0 and μ_1 are non-negative. Moreover, functions thus defined have the additive property, i.e if $A_1 \in \mathcal{M}$ and $A_2 \in \mathcal{M}$, such that $A_1 \cap A_2 = \emptyset$, then $A_1 \cup A_2 \in \mathcal{M}$ and

$$\mu_i(A_1 \cup A_2) = \mu_i(A_1) + \mu_i(A_2),$$

for $i = 0, 1$. Indeed, if $x \in V$ is in $A_1 \cup A_2$, then $x \in A_1$ or $x \in A_2$, since $A_1 \cap A_2 = \emptyset$, that implies

$$\begin{aligned} \mu_i(A_1 \cup A_2) &= \\ &= \sum_{\{x \in V_i : \Phi(x) \in A_1 \cup A_2\}} f_i(x) = \\ &= \sum_{\{x \in V_i : \Phi(x) \in A_1\} \cup \{x \in V_i : \Phi(x) \in A_2\}} f_i(x) = \\ &= \sum_{\{x \in V_i : \Phi(x) \in A_1\}} f_i(x) + \sum_{\{x \in V_i : \Phi(x) \in A_2\}} f_i(x) = \\ &= \mu_i(A_1) + \mu_i(A_2). \end{aligned}$$

So, we can conclude that μ_i , $i = 0, 1$ is a positive σ -additive measure [3].

Let us also define the following measure

$$\mu(A) = \mu_0(A) + \mu_1(A).$$

In the finite case, we have a set of neighborhoods

$$B = \{B_1, B_2, \dots, B_M\}.$$

Let us notice that for every $y \in W$, there exists a unique neighborhood B_y , containing y . In Euclidian case, given a function $R : W \rightarrow \mathbb{R}$, the set of neighborhoods of y includes all balls of the forms

$$B_y = \{z \in W : \text{dist}(y, z) \leq R(y)\}.$$

For every $y \in W$, let $\chi_y : W \rightarrow \mathbb{R}$ be the characteristic function of its neighborhood B_y . Let us also define the function

$$\varphi(y) = \int_W \chi_y(z) d\mu(z) = |\{x \in V : \Phi(x) \in B_y\}|,$$

as well as the function

$$\varphi_i(y) = \int_W \chi_y(z) d\mu_i(z) = |\{x \in V_i : \Phi(x) \in B_y\}|,$$

for $i = 0, 1, \dots, 9$. Let us observe, that all functions $\varphi_i(x)$, $i = 0, 1, \dots, 9$, as well as $\varphi(x)$ are nonnegative. Let

$$\eta_i(y) = \begin{cases} \frac{\varphi_i(y)}{\varphi(y)} & \text{if } \varphi(y) \neq 0 \\ 0.5 & \text{otherwise} \end{cases}.$$

Let us observe, that $\eta_i(y)$ measures the proportion of the points from set V_i , which confidence vector is in the neighborhood B_y . The following relation

$$\varphi(y) = \varphi_0(y) + \varphi_1(y)$$

holds, due to the fact

$$\mu(A) = \mu_0(A) + \mu_1(A)$$

for all $A \in \mathcal{M}$. Hence, for every $y \in W$, $0 \leq \eta_i(y) \leq 1$ and $\eta_0(y) + \eta_1(y) = 1$.

Now, we are in a position to define the fuzzy sets corresponding to the different classes. Let x be an unknown handwritten address,

$$\Phi(x) = (\phi_0(x), \phi_1(x), \phi_2(x))$$

is its confidence vector. We can define the fuzzy membership functions as follows:

$$\xi_i(x) = \begin{cases} \eta_i(\Phi(x)) & \text{if } x \text{ is in the fuzzy area} \\ \phi_i(x) & \text{otherwise} \end{cases}$$

Each of these functions $\xi_i(x)$ is the membership function of the corresponding class ω_i . We say that the unknown pattern x belongs to the class ω_i , if $\xi_j(x) < \xi_i(x)$ for all $j \neq i$. Having defined our membership functions $\xi_i(x)$, $i = 0, 1, 2$ we are able to partition the space W into class regions and boundaries, that separates them in the following way. The set

$$\Omega_i = \{x : \xi_i(x) > \xi_j(x) \text{ for all } j \neq i\},$$

$i = 0, 1$ is the region, all points of which are in class ω_i . The set

$$D_{ij} = \{x : \xi_i(x) = \xi_j(x) \text{ and } \xi_i(x) > \xi_k(x)$$

$$\text{for all } k \neq i, j\},$$

$i, j = 0, 1$, $j \neq i$ is the implicitly defined surface, that is a part of the boundary between the family of correctly recognized images and all the rest.

4. Intuitive Understanding of Methodology

The heuristic method uses several thresholds on each confidence measure in order to find the addresses whose recognition results should be accepted. The thresholds

ZIP Code Coordinates		Street Number Coordinates		Street Name Coordinates		Majority		
x_1	x_2	y_1	y_2	z_1	z_2	Correct	Error	Accept / Reject
0.000	0.495	0.830	1.000	0.830	1.000	41	517	Reject
0.495	0.610	0.830	1.000	0.830	1.000	154	17	Accept
0.610	0.830	0.610	0.830	0.830	1.000	4	22	Accept
0.610	0.830	0.830	1.000	0.830	1.000	45	572	Accept
0.830	1.000	0.000	0.495	0.830	1.000	2	2	Reject
0.830	1.000	0.495	0.610	0.830	1.000	2	3	Accept
0.830	1.000	0.610	0.830	0.830	1.000	28	87	Accept
0.830	1.000	0.830	1.000	0.495	0.610	3	4	Accept
0.830	1.000	0.830	1.000	0.610	0.830	17	38	Accept
0.830	1.000	0.830	1.000	0.830	1.000	2016	426	Reject

Table 1: A grid is defined by the [x,y,z] coordinates. Each grid has addresses inside that are either correct or in error. The majority decides the label of the grid.

themselves are fixed during a training phase which is essentially a "trial and error" procedure. The fuzzy methodology on the other hand partitions the space of all the confidence measures under consideration into a grid. Each grid is labeled as an "Accept" grid or a "Reject" grid in the training phase using a majority rule, *i.e.*, if there are more number of addresses that fall in a grid that are correct, the grid is labeled as an "Accept" grid. The testing phase is a matter of finding the label of the grid a given address falls in.

5. Experiments

We used a training set of 4,000 handwritten address images. The size of the grids is determined by observing the spread of points in the 3D space. Table 1 shows the lookup table derived by the method described in this paper.

Table 2 shows the results on a test set of 10,000 handwritten address images. Of the many modules that are part of a handwritten address interpretation system, we have taken the three most important modules to show the viability of using a fuzzy control instead of a heuristic approach. The three important modules are the ZIP Code recognition module, the Street Number recognition module and the Street name recognition module. First, we manually set the thresholds on the confidence scores returned by the modules as shown in Table 2. For instance, when all three acceptance thresholds are 0.61, 7,988 addresses are accepted and the remaining are rejected as at least one of the three modules has confidence below the threshold. Of the ones accepted, 6,527 (65.27%) are correct. The fuzzy approach described in this paper has an acceptance rate of 64.62% and a correct rate of 84.73%. For an equivalent acceptance rate the heuristic method has a correct rate of 79.97%, almost 5% lower.

Thresholds			Results	
ZIP Code	Street Number	Street Name	Accept Rate	Correct Rate
0.61	0.61	0.61	79.88	65.27
0.83	0.61	0.61	63.69	79.97
0.83	0.83	0.61	60.73	82.73
0.83	0.83	0.83	59.47	84.03
Fuzzy			64.62	84.73

Table 2: Results from manual setting of thresholds on the ZIP Code, Street Number, and Street Name yield results which are inferior to the results from the fuzzy methodology.

References

- [1] D. Bouchaffra, V. Govindaraju, and S. Srihari, "A Methodology for determining probability of correctness of recognizer scores", Proceedings of IEEE Conference on Computer Vision and Pattern Recognition, Santa Barbara, June 1998.
- [2] S. Madhvanath, E. Kleinberg, and V. Govindaraju, "Empirical Design of a Multi-classifier Thresholding/ Control Strategy for Recognition of Handwritten Street Names", Int. Journal of Pattern Recognition and Artificial Intelligence, 1997.
- [3] James R. Munkres, "Topology, a first course", Prentice Hall, 1975.