

Multi-experts for Touching Digit String Recognition

Xian Wang, Venu Govindaraju, and Sargur Srihari

Center of Excellence for Document Analysis and Recognition
State University of New York at Buffalo, Buffalo, NY 14260, U.S.A.
Xianwang@cedar.buffalo.edu

Abstract

84.6% of touching digit strings have only two digits touching, 12.3% have three digits touching, and 3.1% have more than three digits touching. We present a multi-experts approach to recognize touching digit pairs (TDP) and touching digit triples (TDT). We combine holistic and traditional segmentation methods. 25,686 TDP training samples and 2778 TDP testing samples collected from USPS mail are used in our experiment. Holistic method outperforms the traditional segmentation based methods. The multi-experts combination has the best performance, a correct rate of 91.1% on TDP.

1. Introduction

When adjacent digits in a digit string are touching the recognition task becomes particularly challenging. Researchers have relied upon segmenting touching digit strings into individual digits [2,3,4,5,6]. However, improper segmentation tends to leave some of the newly separated digits with artifacts. A digit might lose a piece of a stroke to the adjacent digit or might be attached to ligature. Either way, subsequent recognition of the digit is rendered inaccurate. Furthermore, finding the precise splitting path that separates the touching digits is non-trivial.

There are many applications that require the recognition of touching digit strings, such as reading bank checks, reading tax forms and interpretation of addresses. In the mail stream there are many numeric strings – ZIP codes, street numbers, apartment and suite numbers, and PO. box numbers. An analysis of 27,619 address reveals that about 15.5% of digit strings have touching digits. 13.1% are Touching Digit Pairs (TDP) and 1.9% are Touching Digit Triples (TDT).

The holistic approach poses the problem as labeling a TDP pattern as one of 100 classes (00, 01, ... 99). Another method combines two segmentation based methods [3,9]. A multi-experts TDP recognizer combines both.

2. Background of Segmentation Based Methods

A survey of segmentation strategies is provided by Casey and Lecolinet [7]. Common approaches are often heuristic. While they have the advantage of efficiency, their accuracy is limited. Vertical histograms have been widely used for segmentation but are error-prone.

Another method uses the upper and lower profiles in conjunction with a set of heuristics to determine the segmentation points [4]. A segmentation path is constructed upward from the highest point on the lower profile of a numeral or downward from the lowest point in the upper profile. The approach is further refined in [5]. A graph based method has been described in [6]. This method analyzes the contours of the connected numerals. Vertically oriented edges derived from adjacent strokes form the vertices of the graph, which are potential points of segmentation. There are other methods where a recognizer is used to aid in the segmentation process [8]. Potential segmentation points are validated by submitting the resulting segments to a digit recognizer. The recognizer provides a means of quantifying the "goodness" of a segmentation point, otherwise unavailable to methods using heuristics alone. However, frequent calls to a recognizer during the course of segmentation makes the process inefficient.

3. Holistic TDP recognizer

There are various ways in which two digits can touch, Yu [10] working on single touching, and Zhao [11] focus on the ligature that joins the digits. After analysis of TDP sample images collected from real mail pieces, we have classified TDP into 6 categories. Examples and frequency of each category are shown in Figure 1.

Since the character recognizer chosen does not in anyway limit the holistic paradigm presented in this paper, we will describe the methodology using the GSC character recognizer [1]. The Gradient, Structural, Concavity, (GSC) features are symbolic multi-resolution features. Gradient of the image contour captures the local shape of a

character. The Gradient features are extended to Structural features by encoding the relationships between strokes. Concavity features capture the global shape of characters. Features at the 3 levels, **G**, **S**, **C** are combined in a k-nearest neighbor classification method to produce a multi-resolution digit recognizer. **G** features are the finest and the **C** features are the coarsest.

Several modifications are made to the GSC isolated character recognizer to support the holistic recognition of TDPs.

We use a 4x6 grid instead of the 4x4 grid used for isolated character recognition (Table 1). Since the pattern of concern is two characters side by side, the width of the pattern is going to be larger than the height.

If the width of the pattern is divided into three zones, it is our conjecture that the most useful features are present in the left and right zones, while the central zone merely contains the ligature that joins the two characters (Figure1). Further, given the various ways in which the joining of two characters can occur (Figure1), it is best to disregard the central portion altogether. To this purpose, we weight the contribution of different zones of the pattern to minimize the effects of the central zone. We can suppress the 3rd and 4th columns of the grid based on the observation that it carries little useful information.

Variable weights to the G, S, and C features was also experimented. Recognition rates are shown in Table 2. Best results are achieved by giving the maximum weight to the Concavity features. Given the complex shape of the TDP pattern, this result does seem reasonable. The coarsest features are the most important. Furthermore, the computation of score de-emphasizes the 3rd and the 4th columns and emphasizes the 1st, 2nd, 5th, and 6th columns.

G-Weight	S-Weight	C-Weight	Correct	Error
W_g	W_s	W_c		
0	0	0	82.3%	17.7%
0.5	0	1.0	84.1%	15.9%
0.5	0.1	1.0	84.5%	15.5%
0.5	0.2	1.2	85.0%	15.0%

Table 2: Recognition rates with weighted values for the G, S, and C features based on 2,488 learning samples and 226 testing samples.

4. Multi-segments TDP recognizer

We combine the method described by Fenrich [9] and the method described by Shi and Govindaraju [3]. Fenrich describes a recognition aided iterative method is used. The number of digits in the numeric string is first estimated from the aspect ratio of the digit string and successive estimates are obtained by a linear regression model with

high confidence are removed after each iteration. The effective contribution of the removed digits to the density of the digit string is recorded. This information is fed to a least squares linear model. By setting the density to zero (all digits are removed), the least squares equation can estimate the number of digits in the string. Connected digit components are split into required number of digits. The segmenter has a correct segmentation rate of 93.33% when the input is specified as a 5 or 9 digit ZIP Code, and is 83.03% correct when the number of digits has to be estimated.

Shi and Govindaraju describe a method of splitting digits that follows the contours of the strokes. Significant right turning points together with their opposite contour points are located to divide the contour into contour pieces. Contour pieces are then classified as belonging to one or the other digit. A vertical line bisecting the image is use as the guide. A contour piece is classified as part of the left digit if the center of mass of the piece is on the left of the line, otherwise, as part of the right digit. In most cases, the two digits have similar widths and the touching strokes lie close to the center line. Images of segmented digits may be recovered from the segments by drawing line segments from each contour point to its opposite contour point, or the modified opposite contour point if the line segment to the opposite point is too long.

TDP consists of two digits denoted as left digit and right digit. In the multi-segments method we mark segmentation points by each method. Thus we form more than one left and right image. The combination logic is as follows.

- a. *If the top two choices of either method matches the other then accept the result.*
- b. *Otherwise, select the result with the higher confidence.*

5. Multi-experts TDP recognition

A rule-based combination is used.

- a. *if two of three recognizers give the same recognition result then accept the result.*
- b. *OR if a recognizer's top choice is the same as the second choice of another then accept.*
- c. *OR if the confidence of the holistic recognizer is greater than a threshold accept the result.*
- d. *OR choose the left and right digit results based on confidences of method [3] and method [9].*

6. Experimental Results

Touching digit pairs were manually collected from postal images. 28464 TDP samples are collected from more than 200,000 USPS real mail addresses. A comparison of the holistic, multi-segments, and multi-expert methods is described in Table 3. The holistic method outperforms the traditional segmentation based methods. And the multi-segments method which combines

two of traditional segmentation based methods outperforms the individual methods. Multi-experts approach reaches 91.1% top choice correct rate.

Table 4 shows the testing results across various categories of TDPs. Multi-expert method outperforms the other methods in all categories. For Multiple Points Touching category, holistic method is more than 10% higher than traditional methods.

539 TDT were collected from USPS mail stream. Table 5 shows the results. Multi-segments method is more than 3% higher than the traditional segment based methods.

Methods	Methods Described in [9]	Methods Described in [3]	Multi-segments Method
Testing samples	539	539	539
Top Choice correct	62.52%	60.39%	65.73%
Top + Second Choices correct	71.33%	70.03%	76.88%

Table 5: Recognition result of 3 digit touching of multi-segments method

7. Summary

We have demonstrated that the holistic, multi-segments and multi-expert methods of recognizing touching digit strings are the effective approaches. The holistic method outperforms segmentation based methods. Multi-segments method outperforms the individual methods in both TDP and TDT. Multi-expert approach achieves 91.1% TDP recognition.

References

- [1]. John T. Favata and Geetha Srikantan, A multiple Feature/Resolution Approach to Handprinted Digit and Character Recognition, International Journal of Imaging Systems and Technology, vol. 7, 304-311, 1996.
- [2]. Oivind Due Trier, Anil K. Jain and Torfinn Taxt, Feature Extraction Methods for Character Recognition - A Survey, Pattern Recognition, Vol.29, No.4, pp.641-663, 1996.
- [3]. Z. Shi and V. Govindaraju, Segmentation and Recognition of Connected Handwritten Numeral Strings, Pattern Recognition, Vol. 30, No. 9, pp. 1501-1504, 1997.
- [4]. M. Shridhar and A. Badreldin, Recognition of isolated and simply connected handwritten numerals, Pattern Recognition, Vol. 19, pp. 1-12, 1986.
- [5]. F. Kimura and M. Shridhar, Segmentation-recognition algorithm for handwritten numeral strings, Machine Vision Applications, No. 5, pp. 199-210, 1992.
- [6]. J. M. Westall and M. S. Narasimha, Vertex directed segmentation of handwritten numerals, Pattern Recognition, Vol. 26, No. 10, pp. 1473-1486, 1993.
- [7]. R. G. Casey and E. Lecolinet, Strategies in character segmentation: A survey, Proc. of the Int. Conference on Document Analysis and Recognition, Montreal, Canada, pp. 1028-1033, 1995.
- [8]. S. Seshadri and D. Sivakumar, A technique for segmenting handwritten digits, Proc. of the Int. Workshop on Frontiers in Handwriting Recognition III, Buffalo, New York, USA, May 25-27, pp. 443-448, 1993.
- [9]. R. Fenrich, Segmentation of Words, Proc. of the Int. Workshop on Frontiers in Handwriting Recognition II, Bonas, France, 1991.
- [10]. D. Yu and H. Yan, Separation of single-touching handwritten numeral strings based on structural features, Pattern Recognition, Vol. 31, No. 12, pp. 1835-1847, 1998
- [11]. B. Zhao, H. Su, and S. Xia, A new method for segmenting unconstrained handwritten numeral string, Proc. of the Int. Conference on Document Analysis and Recognition, Ulm, Germany, pp. 524-527, 1997

Grid Size	G Vector	S Vector	C Vector	Total Vector	Correct recognition	Weighted
4x4	192	192	128	512	79.2%	--
4x6	288	288	192	768	82.3%	85%
6x9	648	648	432	1728	78.8%	--
4x8	384	384	256	1024	79.2%	81.4%
4x7	336	336	224	896	79.6%	--
6x6	432	432	288	1152	77.0%	--

Table 1: Recognition result of GSC features in different grid size based on 2,488 learning samples and 226 testing samples.

Total Testing Images	Methods Described in [9]	Methods Described in [3]	Holistic Method	Multi-segments Method	Multi-experts Method
2778	81.6%	83.5%	85.1%	87.8%	91.1%

Table 3: Comparison of 2778 TDP testing sample results by different methods

Category	Images	Methods Described in [9]	Methods Described in [3]	Holistic Method	Multi-segments Method	Multi-experts Method
Single Point Touching	1537	83.9%	85.4%	86.4%	90.6%	93.0%
Ligature Touching	484	82.2%	85.5%	86.0%	87.4%	91.9%
Multiple Points Touching	272	75.0%	73.5%	85.3%	80.5%	89.0%
Overlaps	175	87.4%	92.0%	86.3%	92.0%	93.7%
Noise	256	68.8%	72.7%	73.0%	76.2%	78.5%
Broken	54	88.9%	87.0%	90.7%	90.7%	90.7%

Table 4: Recognition rate comparison across various categories of TDPs by different methods

Category	Examples			Frequency
Single Point Touching				55%
Ligature Touching				18%
Multiple Points Touching				10%
Overlaps				6%
Noise				10%
Broken				2%

Figure 1: Categories of TDP based on the manner in which the two digits touch and their frequency of occurrence in a set of 2,778 samples