

USE OF CHARACTER RECOGNITION AND SYNTAX IN  
LOCATING ADDRESS PARAGRAPHS IN COMPLEX DOCUMENTS

by

Jenchyou Lii

A dissertation submitted to the  
Faculty of the Graduate School of  
State University of New York at Buffalo  
in partial fulfillment of the requirements for the degree of  
Doctor of Philosophy

June 20, 1995

©Copyright by Jenchyou Lii, 1995  
All rights Reserved

### Committee Members

Chairman: Dr. Sargur N. Srihari  
Computer Science, SUNY at Buffalo

Members: Dr. Jonathan J. Hull  
Ricoh California Research Center

Dr. Raj Acharya  
Electrical Engineering, SUNY at Buffalo

Outside Reader: Dr. Rangachar Kasturi  
Computer Science & Engineering,  
The Pennsylvania State University

This dissertation was defended on May 26, 1995.

To my parents for their love and support.

## Acknowledgements

I would like to express my gratitude to those people who helped me successfully complete this dissertation.

Dr. Sargur N. Srihari, my advisor, inspired me to conduct research in document image analysis. He gave me guidance and assistance throughout my entire Ph.D. studies, e.g. many hours spent in helping me improve the slides for my dissertation defense. I am grateful for his kindness and advice.

Dr. Jonathan J. Hull and Dr. Raj Acharya, my committee members, provided me with valuable comments on this research. Their advice and encouragement helped me complete my dissertation writing. I would like to thank Dr. Rangachar Kasturi, my outside reader, for his time and effort examining my dissertation.

Paul Palumbo, my ABL project manager at CEDAR, led me into the address block location project and offered me much technical assistance. His criticism on my dissertation was very constructive. Dr. Ronald Curtis, my UMRS project manager at CEDAR, helped me carry out the experiments on fax address block location. He has been very friendly and supportive. I enjoyed working with all members in both ABL and UMRS research groups.

Many Thanks to Heike Berlind, Eugenia Smith, and Natalie Leaver for their excellence in the administrative tasks at CEDAR. I wish to thank Eloise Benzal, Sally Elder, and Gloria Koontz, department secretaries, for their friendly help in many student affairs.

It was enjoyable to discuss in private seminars with a few friends, including Dr. Chun-Shi Chang, Dr. Jiah-Shing Chen, Dr. E-Ren Chuang, Dr. Dar-Shyang Lee, Chain-Wu Lee, Giovanni Seni, and Dr. May Yuan.

Finally, I am indebted to my parents for their love and support. They encouraged me to pursue my doctorate and helped me overcome many hurdles. From the bottom of my heart, I am sincerely grateful to them.

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Problem Statement and the Scope of the Thesis . . . . .	7
1.2	Overview of the Proposed Approach . . . . .	8
1.3	Outline of the Dissertation . . . . .	10
<b>2</b>	<b>Background</b>	<b>11</b>
2.1	Syntactic Methods in Pattern Recognition . . . . .	11
2.1.1	Formal Grammars and Recognition of Languages . . . . .	13
2.1.2	Relational Models and Structural Matching . . . . .	14
2.2	Document Image Analysis . . . . .	19
2.2.1	Document Image Analysis and Syntactic Methods . . . . .	20
2.3	Address Block Location . . . . .	21
2.3.1	Region Segmentation on Mail Pieces . . . . .	22
2.3.2	Feature Extraction . . . . .	24
2.3.3	Address Block Selection . . . . .	25
<b>3</b>	<b>A Computational Model for Locating Address Paragraphs</b>	<b>27</b>
3.1	Physical Boundaries and Logical Boundaries . . . . .	27
3.2	Text Recognition and Locational Information . . . . .	31
3.2.1	Difficulties of Block Segmentation . . . . .	31
3.2.2	Integration of Text Recognition and Page Segmentation . . . . .	32
3.3	Use of Syntax and Context in Address Block Location . . . . .	33

4.1	Computational Model . . . . .	34
<b>4</b>	<b>Theory of the Consistent Labeling Problem</b>	<b>45</b>
4.1	Definition of the Consistent Labeling Problem . . . . .	45
4.2	Examples and Previous Studies . . . . .	46
4.3	Address Block Location as a Consistent-Labeling Problem . . . . .	50
4.4	Problem Decomposition . . . . .	53
<b>5</b>	<b>Locating Address Paragraphs on Envelopes</b>	<b>70</b>
5.1	Overview of the Method . . . . .	71
5.2	Preprocessing and Character Segmentation . . . . .	72
5.3	Spatial Information Map and its Application . . . . .	72
5.3.1	Construction of Spatial Information Map . . . . .	73
5.3.2	Skew Correction . . . . .	75
5.4	Word Segmentation . . . . .	75
5.5	Character Recognition . . . . .	76
5.6	Keyword Matching . . . . .	78
5.7	Locating Destination Address Paragraph . . . . .	80
5.8	Use of Address Syntax in Postprocessing . . . . .	80
5.9	Experimental Results . . . . .	81
<b>6</b>	<b>Location of Name and Address on Fax Cover Pages</b>	<b>85</b>
6.1	Introduction . . . . .	85
6.2	Method . . . . .	90
6.2.1	Page Orientation Detection . . . . .	90
6.2.2	Location and Recognition of Keywords . . . . .	94
6.2.3	Location of the Address Region . . . . .	96
6.3	Results . . . . .	100
<b>7</b>	<b>Conclusions</b>	<b>104</b>





## Abstract

Locating address paragraphs on complex documents is an important problem in document image analysis. Automatic extraction and interpretation of addresses has useful applications in mail sorting, database compiling, fax routing, etc. Many methods have been proposed for address block location on mail pieces, and most of them used global geometric and topological features. However, their methods showed difficulties in locating destination addresses on machine-printed envelopes to achieve high success rate. In addition, their methods were not suitable for locating addresses on other types of documents such as fax cover pages and advertisements.

This thesis provides a computational model for locating address paragraphs on complex documents. The model uses text recognition to derive locational information which facilitates address segmentation. Locational information can be extracted in two ways: (1) through detection of address syntax; (2) through the understanding of semantic constraints imposing on an address. The adoption of character recognition and keyword matching in the scheme opens the door to take advantage of the linguistic nature of address paragraphs and their environments.

Two types of documents were used in our experiments. The first one was letter mail. We proposed a method of using character recognition and syntax in address block location. To discriminate an address block from other extraneous material, address syntax can be used as a salient feature. The aggregation of text objects which demonstrate address syntax suggests the location of an address region. Therefore, by recognizing characters and analyzing address syntax, the system is able to identify a more plausible address region in a complex environment. In addition, the syntax information can also be utilized to better

delineate the address block boundaries.

The second kind of documents used in our research was fax cover pages. On fax cover pages handwritten addresses are difficult to locate by direct recognition of addresses themselves. However, since a recipient's address is strongly constrained by keywords such as TO and COMPANY, keyword recognition can provide locational information for address blocks. The positions of keywords not only narrow down search for the address to the area where an address is likely to appear, but also reveal the layout of the document and help address segmentation.

In summary, this thesis illustrates a novel approach to tackle address block location. The methodology is general and applicable to different types of documents. Our experimental systems showed good performance on machine-addressed letter mail and fax cover sheets.

# Chapter 1

## Introduction

Paper has conventionly been used as the major media to record and disseminate information. Since the advent of the computer age, many forms of computer media offer alternatives to store vast amounts of information. Despite great advances in computer technology during the last few decades, paper documents remain the easist and most comfortable means of obtaining information by humans without auxiliary machinery. The sheer volume of existing paper documents and new ones calls for efficient methods of manipulating them through computers. Information contained in these documents needs to be stored, retrieved, queried, and processed in many intelligent ways. This leads to a growing research area “document image analysis”, whose objective is to make a computer perform high level understanding of paper documents [12, 84].

Locating address paragraphs in complex documents is one problem in document image analysis. Address paragraphs appear on letters, advertisements, business cards, mail pieces, facsimile cover page, and other documents (Figure 1.1 to Figure 1.5). Since an address is one type of useful information present on paper documents, the ability to extract and process it electronically is desired for various purposes. One application of using address information is to build databases of personal and company records. Another application is mail sorting, where machines are used to identify addresses. One more example to use address is fax

**FREE**  
**ESTATE PLANNING SEMINAR**

*Sponsored by*



**ARTHRITIS  
FOUNDATION®**



**Metro  
Community  
News**

**LEARN FROM LEGAL SPECIALISTS HOW TO:**

- Avoid probate and maintain the privacy of your financial and personal affairs
- Reduce or eliminate death taxes
- Increase your personal income for life and eliminate capital gains on appreciated property
- Preserve and pass your wealth on to your children

**JULY 1, 1993**  
**7:00-9:00 pm**  
NOCO Building - 3rd Floor  
2440 Sheridan Drive  
Tonawanda, NY 14150

**RESERVATIONS  
REQUIRED  
CALL  
1-800-286-0608**

**SPEAKERS**  
DAVID BEARCHELL *Arthritis Foundation Regional Director Planned Giving*  
WAYNE S. LANDESMAN *General Agent, New England Insurance*  
ROGER B. SIMON, *Esq. Saperston & Day*

Learn Proven Techniques To Dramatically Improve Your Financial Future!

Figure 1.1: Address blocks appear in several document types: (a) advertisement.



## UNIVERSITY AT BUFFALO

STATE UNIVERSITY OF NEW YORK

### **Sargur N. Srihari**

Director, Center of Excellence  
for Document Analysis and Recognition (CEDAR)  
UB Commons  
520 Lee Entrance, Room 202  
Buffalo, New York 14228-2567  
Office: (716) 645-6162, FAX: (716) 645-6176  
E-mail: [srihari@cs.buffalo.edu](mailto:srihari@cs.buffalo.edu)

---

Figure 1.2: Address blocks appear in several document types: (b) business card.

**YES! I MISS MY TV GUIDE!**

- Please reinstate my subscription right away for the special short term (30 issues) and bill me later in 4 easy monthly installments of just \$5.99 each.
- SAVE MORE!** Send me 52 issues and bill me in 4 easy monthly installments of only \$9.99.

**SPECIAL  
LIMITED TIME  
OFFER!**

*Detach and mail  
this card at once.*


MRS NORA LEE SMITH  
RR 1 BX 80  
GOREVILLE IL 62939-9707

16405A9\*B8

Figure 1.3: Address blocks appear in several document types: (c) postcard (reverse side).

Motorola • Xerox • Kodak • Wang • Boeing • GTE  
IBM • Hewlett-Packard • Good Samaritan Hospital  
Tennant Company • Globe Metallurgical • Velcro  
Westinghouse • First National Bank of Chicago  
Maryland Bank • Ford • IDS • American Express  
Federal Express • Milliken • Florida Power & Light  
National Tool & Die • Sewell Cadillac • Zytec  
Corning • Apple Computer • Procter & Gamble  
Toro • Honda • Toyota • Maytag • General Electric  
Bell Cell  
United T  
General  
Texas In  
United Van Lines • Thomson Consumer Electronics  
Shelly-Ragon Inc. • AMP Inc. • Pratt & Whitney

MR. CHARLES DEER III X245  
NY100  
1576 SWEET HORN RD  
BUFFALO, N. Y. 14228



**INSIDE: What You Must  
Learn From America's  
Most Quality-Conscious  
Companies To Compete -  
And Win - In The Nineties**

12,112 125,112 (07555)

Figure 1.4: Address blocks appear in several document types: (d) envelope.

DEC-05-1994 16:02 FROM CEDAR: (716) 645-6176 TO 251 P.01

**FAX**

Date 10/18/94

Number of pages including cover sheet 6

TO: Thoms Vaught  
1 Niagara Sq.  
Buffalo, NY 14202

FROM: Vanito Grant  
25 B St.  
Buffalo, NY 14211

Phone 716-461-8047  
Fax Phone 716-481-4348

Phone 716-274-5150  
Fax Phone 716-427-2989

CC:

REMARKS:  Urgent  For your review  Reply ASAP  Please Comment

Gary:

I wonder if Gleason would be interested in this Microstation (for PC) support?

Mark M.

OCT 18 '94 18:27

7164272989 PAGE 001  
TOTAL P.01

Figure 1.5: Address blocks appear in several document types: (e) fax cover page.



routing. In a fax routing system, a fax can be delivered to individuals through recognition of the recipient's name and address on the fax cover page.

## 1.1 Problem Statement and the Scope of the Thesis

The problem studied in this thesis is locating address blocks in complex documents. An address block is a paragraph of text that consists of several lines (sentences) of text. Each sentence consists of numbers, words, and phrases that identify a meaningful geographical region. Addresses are typically present in documents with other text and graphics. The problem of address block location is to segment and identify the subimage corresponding to the address paragraph from the entire document image.

Two types of documents are chosen for our research on address block location. One is envelopes and the other is fax cover pages. These documents have huge variety and complexity in their own domains. Since an address can be placed at an unpredictable region on these documents, address block location has been a challenging task for a document analysis system.

In mail sorting application, address block location is a pre-processing step for address interpretation. The task of address interpretation is to read the destination address in determining the destination code (e.g. ZIP + 4 Code) [17, 64]. About half of the mail sent through mail sorters installed in the U.S. ends with being rejected. Failure in finding address regions on envelope images is one of the major reasons. The problem of address block location has been tackled by many researchers [2, 14, 37, 43, 53, 63, 78, 90, 101]. Though each of them emphasized on different aspects, the issue of using character recognition and syntax in address block location has not been seriously studied until recently [45, 46].

There are two types of address print methods for letter mail. One is machine-printed and the other is handwritten. We focus our research on machine-printed letter mail, owing

to the fact that 83% of all letter mail is machine-printed and 17% handwritten [16]. It is also because that in practice the address block location performance on machine-printed mail is required to be much higher than on handwritten mail, e.g. 95% - 98% versus 90%. Since handwritten mail usually contains much less non-address material than machine-printed mail, address block location on handwritten mail has performed well in present systems.

Sending fax is another way of transporting messages. Unlike letters being delivered as paper documents, a fax is transmitted in the form of image. As use of fax machines is getting popular, it calls for the need to process fax images more intelligently. There are several scenarios that an automatic fax routing system can improve fax handling. One example is to automate incoming fax distribution in a company or institution. A fax routing system can read an incoming fax cover sheet and route the fax to the receiver's electronic mail box.

Another example is to handle fax by means of electronic postal service. A third party can serve as a trusted agent for government or company for collecting documents. People submit documents to the third party through fax machines. A fax handling system is used to collect these documents, classify them according to the recipient, and store them in a high capacity medium (e.g. hard disk). These document images can later be accessed by their intended receivers through computer network.

In these fax applications, the recipient's name and address need to be located and recognized. In this thesis, our focus is on location of name and address on fax cover pages. Both machine-printed and handwritten fax cover sheets are used in our experiments.

## 1.2 Overview of the Proposed Approach

Generally speaking, an object can be located by two means. First is through its detectable properties. Second is through its environments. In the first case, certain salient features

are used to identify the target. The location of the object is confirmed as soon as it is recognized. Sometimes direct recognition of the target is not easy; however, we may resort to using its context to locate the object. If the existence of the object is strongly constrained by its context, it is possible to begin with identifying the unique pattern of its environments and then find the object.

This thesis investigates the issue of using character recognition and syntax in address block location. Although it is assumed that address interpretation is performed after the address block is located, it does not exclude the possibility of using some address recognition to aid the location. For address block location, a complete interpretation of the address need not be performed to determine the destination code, but address recognition can be used for a better understanding of the nature of the objects present on a document. To discriminate an address block from other extraneous material, address syntax can be used as a salient feature. The aggregation of text objects which demonstrate address syntax indicates the location of an address region. Therefore, by recognizing characters and analyzing address syntax, the system is able to identify a more plausible address region in a complex environment. In addition, the syntax information can also be utilized to better delineate the address block boundaries.

On the other hand, attempt is made to locate an address block through its environments. On fax cover pages, handwritten addresses are difficult to locate by direct recognition of addresses themselves. However, since a recipient's address is strongly constrained by keywords such as TO and COMPANY, keyword recognition can provide locational information for address blocks. The information regarding the positions of keywords not only narrows down search for the address to the area where an address is likely to appear, but also reveals the layout of the document and facilitates address segmentation.

### 1.3 Outline of the Dissertation

The outline of the remaining thesis is as follow. In Chapter 2 we will describe some background and review previous work. Chapter 3 provides a computational model of our thesis. Since address block location can be formulated as a consistent labeling problem, Chapter 4 discusses our research work on that topic. There are two types of documents used for our experiments: one is envelopes and the other is fax cover pages. Chapter 5 depicts a method of locating destination address block on envelopes. Chapter 6 represents a scheme to locate recipient's name and address on fax cover pages. Chapter 7 gives conclusions.

## Chapter 2

# Background

### 2.1 Syntactic Methods in Pattern Recognition

Use of syntactic (structural) methods is one of the major approaches to solving pattern recognition problems [10, 23, 26, 54, 69]. The syntactic approach is applicable to problems where the structure of an object is salient and can be used for classification and description. The syntactic approach attempts to describe patterns in terms of pattern primitives. A complex pattern is hierarchically decomposed into a small set of pattern primitives. These primitives together with their structural relations can be used for both recognition and description of a given pattern.

A syntactic pattern recognition system (Figure 2.1) can be looked at through its training and recognition stages [23]. In the training phase, we need to determine a set of structural elements and their relations out of a training set of images. Then grammars or relational models are constructed to represent the structural information exhibited by the structural elements and their relations. The recognition phase starts with preprocessing on the input image. The system then performs segmentation or decomposition, extracts structural elements, and computes relations among structural elements. A symbolic representation (e.g. a string, a tree or a graph) is derived to describe the structural elements and their relations.

Finally syntax or structural analysis is performed on the symbolic representation to achieve classification and description.




Figure 2.1: Block diagram of a syntactic pattern recognition system. (From Fu, 1982.)

Many successful results have been reported as to applying syntactic methods to a wide range of problems, such as shape analysis, recognition of mathematical equations, chromosome image analysis, texture analysis, bubble chamber picture identification, Chinese character recognition, and automatic inspection.

Representational schemes and analysis procedures are two major components in the syntactic approach. These two issues are related. Representational schemes attempt to give a quantitative representation of structural information contained in patterns. Structural information can be captured in two ways in the syntactic approach. One is use of formal grammars and the other is use of relational models. After representational schemes have been constructed, analysis procedures are developed to recognize structures. If grammars are used, parsing algorithms or automata are employed as analysis procedures. If relational models are used, matching is the technique of analyzing pattern structures.

### 2.1.1 Formal Grammars and Recognition of Languages

Formal grammars have been extensively used to represent pattern classes in the syntactic approach. The production rules of a grammar capture the way of constructing a complex pattern from pattern primitives. String grammars are one-dimensional grammars operating on strings of symbols which represent pattern primitives. In this type of grammars, concatenation is the only relation between symbols. Patterns with more complex interconnections need to use higher-dimensional grammars. Examples of higher-dimensional grammars are array grammars, tree grammars, web grammars, plex grammars, shape grammars, and graph grammars. Recognition of languages defined by formal grammars can be carried out by either automata or parsing algorithms.

Automata are abstract models of computation devices. An automaton operates on a pattern and accepts or rejects the pattern depending on if the pattern is a member of a specific language. Automata commonly seen are finite automata for regular grammars, push-down automata for context free grammars, and frontier-to-root automata for tree grammar.

Parsing is to determine if a given string belongs to one of the languages defined by the grammars. If the parser succeeds in parsing, it will provide a sequence of how to derive the given string from the start symbol of the grammar. Parsing algorithms do not need to have the form of an automaton. CYK algorithm and Earley's algorithm are two well-known parsers for context free grammars.

We may consider formal grammars which describe perfect patterns to be exact version of formal grammars. Automata or parsing algorithms on the basis of exact formal grammars reject patterns that have any errors. In order to deal with imperfect patterns and tolerate some errors, inexact version of formal grammars along with their parsers and au-

tomata have been proposed. The inexact formal grammars incorporate error production rules by introducing edit operations into the grammars. The error production rules allow the grammars to derive erroneous patterns. Inexact version of language recognizers include error-correcting string parsers for string languages and error-correcting tree automata for tree grammars.

Another approach to handle distorted and noisy patterns is use of stochastic grammars and recognizers. The distorted and noisy patterns cause the problem of overlapping pattern classes. In other words, a noisy pattern may be derived from two or more grammars and therefore the languages defined by the grammars are not disjoint. This ambiguity can not be resolved by normal syntax analysis procedures. It leads to the introduction of stochastic process, which uses the statistical information about the pattern noise and distortion, into the syntactic approach. Stochastic grammars are inferred to describe both statistical and structural information about the patterns. Stochastic recognizers are used to perform the classification and description of patterns.

### **2.1.2 Relational Models and Structural Matching**

Another way to represent structural information is use of special data structures, such as strings, trees, and relational descriptions. Both the input pattern and the prototypes are represented by a special data structure. Structural matching is then performed on these representations to compare an input pattern with each model pattern and compute their likeness. A similarity measure is appropriately chosen during this process. Common matching methods are string to string matching [9], tree to tree matching [67], and matching between relational descriptions [92].



### 2.1.2.1 Matching of Strings

The matching of strings concerns the computation of similarity between two strings [9]. One basic algorithm used for string matching is based on the weighted Levenshtein distance [27, 44]. The weighted Levenshtein distance is defined as the minimum weighted cost of edit operations needed to transform a string  $x$  to another string  $y$ . There are three types of edit operations: substitution, insertion, and deletion. This algorithm uses dynamic programming as an optimization procedure, and the computation gives  $O(mn)$  regarding both time and space complexity, where  $m$  and  $n$  are the length of the two strings.

Various modifications to the basic algorithm have been reported in the literature. Sze and Yang [80] proposed a simplified approach whose similarity measure mainly depended on the number of identities between two strings. This method, whose computational complexity is  $O(\max(m, n))$ , is faster than the basic algorithm, but it has a restricted application. Wagner and Fischer [93] proposed a similarity measure in terms of the longest common subsequence. The time complexity of their method is of order  $O(mn)$ . Warping and elastic matching [1] is one method proposed to include two properties, expansion and compression, into the basic algorithm. This method allows the expansion of one symbol into  $k$  consecutive copies as well as the compression of  $k$  consecutive identical symbols into one without any cost. Another method uses a string distance based on generalized substitutions. A string  $u$  can be replaced by another string  $v$  where  $u$  and  $v$  have a length greater than or equal to zero. In contrast to all the abovementioned methods that assume cost functions are context-independent, Tanaka [83] proposed a context-dependent method where the cost assigned to each edit operation is dependent on the symbols in the neighborhood. In addition, one faster algorithm for computing string-edit distances was reported by Masek and Paterson [51]. This algorithm has a time complexity of  $O(mn/\min(m, \log n))$ .

One way to enhance the representational power of strings is use of attributed strings [24,

86]. Given a string  $x = x_1 \dots x_n$ , we can associate an attribute vector  $a(x_i) = (a_1^i, \dots, a_k^i)$  with each symbol  $x_i$  in the string, where  $i = 1, \dots, n$  and  $k$  is the length of the vector. Each attribute vector is a list of real numbers describing certain properties, such as length of a line and area of a region. In the matching of attributed strings, the distance between two strings is dependent on both the difference of symbols and the distance of attribute vectors.

### 2.1.2.2 Matching of trees

Problems of tree to tree matching [67] can be grouped into three categories. The first category is the isomorphism of tree to tree matching [15]. The second is partial matching [48], which is to determine if one tree is a subtree of another tree. The third one is generic tree matching [49, 72, 81, 82, 85, 100], and this type of problems is to measure the similarity between two trees. Several methods used in generic tree matching are briefly described as follows.

The difference between two trees can be viewed as being caused by two kinds of distortions, i.e. local and structural distortions. The local distortion makes trees be different in some of their node labels, but does not affect the tree structure. The structural distortions are changes made on trees regarding node labels and/or structure. Since the tree structure remains the same in the local distortion, the distance measure is only dependent on the node labels which are not the same between two trees. The matching can be done in  $O(N)$ , where  $N$  is the total number of tree nodes.

The principle of measuring the structural distortion is to compute the cost of transforming the input tree into a prototype tree by modifying the tree structure. There are five commonly used edit operations for tree correction, including node insertion, node deletion, node label substitution, node merging, and node splitting. A distance measure can be defined as follow.

$$d(T_i, T_j) = \min\{|s| \mid s \text{ is a sequence of edit operations needed to transform } T_i \text{ to } T_j, \\ \text{and } |s| \text{ is the number of operations in } s\}$$

The upper bound of the time complex of computing the similarity measure is  $O((5N)^d)$ , where  $N$  is the size of  $T_i$  and  $d$  is the distance between two trees. Two groups of methods were proposed to reduce the time complexity. One group of methods restricts itself to use of three edit operations which are node insertion, node deletion, and node label substitution. Tai [81] proposed a basic algorithm of utilizing dynamic programming. His algorithm gives a time complexity of  $O(N_i N_j D_i^2 D_j^2)$ , where  $N_i$  and  $N_j$  are the total number of nodes in each trees and  $D_i$  and  $D_j$  are the heights of the two trees. The other group of methods only considers node merging and node splitting. Lu [49] proposed a divide and conquer method applying four edit operations, including two versions of node merging and two versions of node splitting, to unlabeled trees. His method has a time complexity of  $O(NM^2)$ , where  $N$  and  $M$  are the sizes of the two trees.

### 2.1.2.3 Matching of Relational Descriptions

The relational descriptions are a formalism of describing the structural information of patterns by means of relations. At a high level abstraction each of the input image and the object prototypes is represented by a set of interrelationships among parts. Matching between two relational descriptions is known as relational matching. The goal of relational matching is to find the best mapping from the constituent parts in the input image to those in the object prototypes.

The definition of relational description was first given by Shapiro and Haralick [74]. Let the set of components constituting an object be denoted by  $X$ . A relational description  $D_X$  is a collection of relations and is formally written as  $D_X = \{R_1, \dots, R_i, \dots, R_M\}$ , where the relations  $R_i \subseteq X^{n_i}$  with  $i = 1, \dots, M$ .

Given two relational descriptions  $D_P = \{R_1, \dots, R_M\}$  and  $D_Q = \{S_1, \dots, S_M\}$ , a relational distance can be defined as follows [73]. Let  $f$  be an arbitrary one-to-one, onto mapping from  $P$  to  $Q$ . The distance  $E^i(f)$  between the  $i$ th pair of relations in  $D_P$  and  $D_Q$  as well as the total distance  $E(f)$  between  $D_P$  and  $D_Q$  by using  $f$  are expressed as

$$E^i(f) = |R_i \circ f - S_i| + |S_i \circ f^{-1} - R_i|$$

$$E(f) = \sum_{i=1}^M E^i(f).$$

Since  $f$  is arbitrary, there exist many  $E(f)$ 's. Therefore, the relational distance  $d(D_P, D_Q)$  between  $D_P$  and  $D_Q$  is defined as the  $E(f)$  with the minimal value, i.e.

$$d(D_P, D_Q) = \min_f E(f).$$

The relational descriptions can be extended by considering various properties associated with components, the relationships among components, or the whole object. This generalization leads to the formulation of attributed relational description and relational distance. The basic method to compute the (attributed) relational distance is based on the backtracking tree search. The time complexity of the backtracking tree search is exponential, and many discrete relaxation techniques, e.g. forward checking, are used to improve the tree search.

Sanfeliu and Fu [68] proposed a distance measure between attributed relational graphs. The distance measure is a function of the cost of node recognition and the cost of structural transformation. The cost functions are defined as

$$C_x = \sum_{k=1}^m w_{xk} g_{xk} \text{ with } \sum_{k=1}^m w_{xk} = 1$$

where  $g_{xk}$  and  $w_{xk}$  are the cost and the weight regarding the operation "x" (e.g. node recognition). The similarity measure between attributed relational graphs  $G_P$  and  $G_Q$  is given as

$$d(G_P, G_Q) = \min_{\text{configuration}} (w_{nr}C_{nr} + w_{ni}C_{ni} + w_{nd}C_{nd} + w_{bi}C_{bi} + w_{bd}C_{bd} + w_{ns}C_{ns} + w_{bs}C_{bs})$$

where  $nr, ni, nd, bi, bd, ns,$  and  $bs$  are node recognition, node insertion, node deletion, branch insertion, branch deletion, node label substitution, and branch label substitution. The computation of the similarity distance is also based on a tree search.

In addition, two similarity measures based on the information theory were proposed. Boyer and Kak [7] introduced a similarity measure whose cost function used the logarithm of transition probabilities. The transition probabilities are conditional probabilities modeling the information transfer through a communication channel. Vosselman [92] defined a similarity measure using a merit function. The merit function measures the support of the mapping given by two relational descriptions.

## 2.2 Document Image Analysis

One definition of document image analysis is given as follows. A document image is a two-dimensional pixel representation of a printed document. Document images can be acquired from various sources including newspapers, maps, forms, journals, etc. The contents of document images may have text, graphics, and pictures. Document image analysis aims at automatically converting pixel representation to symbolic representation which facilitates high level information processing.

Some authors make a distinction between document image analysis and document image understanding [76, 84]. They define document image analysis as the task of low level processing mainly deriving geometric structure of a document. Document image understanding is defined as the task of high level processing such as mapping from geometric structure to logical structure, text recognition, interpreting pictures, understanding line drawings etc.

Others simply use document image analysis (or document analysis) to mean all levels of information processing on document images [12, 70]. Similar to the concept of “document image analysis and understanding”, the term “document image analysis and recognition” is also seen in literature.

Examples of research domains in document image analysis are: character and word recognition [33, 35], interpretation of line drawing [39], converting maps into a cartographic database [55, 79], transforming printed chemical structure diagrams into a chemical database [34, 52], extracting data from forms [11, 66], analysis of technical journals [57], understanding newspapers [97], and locating addresses on documents (e.g. mail pieces) [96, 101].

### 2.2.1 Document Image Analysis and Syntactic Methods

Documents are often highly structured, both logically and geometrically. Journals are an example. The logical structure of a journal article consists of a title, authors, an abstract, and a body. The body is composed of sections and references. A section may be recursively decomposed into subsections, subsubsections, etc. Each of a section and its recursively decomposed units normally have headings, paragraphs, tables, figures, etc. References contain a list of publications. On the other hand, the geometric structure of pages from journals can be divided into a number of rectangular regions which contain uniform data. The contents of rectangular regions may be text, tables, or figures. If a rectangular region is composed of text, some typographic properties, including spacing, font, size, etc., are required to be consistent. The rectangular regions on a page can be grouped into a hierarchical structure based on some spatial or locational properties.

Since hierarchical representation is suitable to describe the contents of such documents [56], syntactic methods can be used for layout analysis. Viswanathan [91] applied a set of block-grammars to identifying the spatial structure of document images scanned from pages

of technical journals.

A text image has several levels of symbolic representation, including character, word, phrase, sentence, and paragraph levels. Many structural methods have been used in character recognition [98, 41]. Since words are strings of characters, matching between strings are widely used in the postprocessing of word recognition [8]. Phrases and sentences are products of syntactic rules and are subject to the description of formal grammars. A paragraph consists of sentences which are correlated in meanings. The sentences in certain type of paragraphs (e.g. addresses) are organized according to some rules. Syntactic analysis is useful in understanding such paragraphs.

Syntactic methods have been applied to many applications in document image analysis. Dori [19] used a context-free dimensioning grammar in understanding engineering drawings. Searls and Taylor [71] applied Definite Clause Grammars to several applications, such as address interpretation on mail. Lee and Lee [42] proposed a mathematical expression recognition system using two stages of matching. Hrechak and McHugh [32] developed a data model of fingerprints, which was based on local structural relations among features. Parizeau and Plamondon [61] experimented with several signal matching algorithms, including regional correlation, dynamic time warping, and skeletal tree matching, on signature verification.

### 2.3 Address Block Location

The subject of address block location has been studied by many researchers since early 1980s due to its important role in mail sorting. A comparison of various approaches can be seen in [40]. There are three categories of mail pieces where address block location is needed for the automatic sorting. They are letters, flats (e.g. large envelopes), and irregular parcels and pieces (IPPs). Earlier researchers tried to design a system capable of handling

all three classes of mail pieces with two types of address print methods, machine-printed and handwritten [4, 5, 13, 38, 78]. Recent efforts have concentrated on either one particular mail piece category [2, 14, 99] or multiple categories of the same address print method [25].

Generally speaking, address block location may be viewed as a three-phase problem. The three phases are region segmentation, feature extraction and region classification/ranking. The purpose of the first stage is to segment the entire mail piece image into a number of uniform regions such as the return address, stamp, the destination address, advertising text, graphics, and so on. The goal of the second stage is to compute a sufficient set of salient features from the segmented regions. The aim of the last stage is then to label the segmented regions, based on the extracted features, for selecting the most likely destination address block. Many distinct system designs have been proposed and they do not always follow the three-phase scheme one stage after another. Nevertheless, these stages are three main elements in address block location. Through the understanding of various solutions in each stage, we can gain insight into the problem of address block location.

### **2.3.1 Region Segmentation on Mail Pieces**

Region (block) segmentation is an important process in document image analysis and has been intensively studied [94, 97]. Almost every document segmentation method, with certain modification, has a potential of being used in dividing a mail piece image into blocks. We select a number of representative schemes, most of which have been used in address block location, and briefly describe as follows.

Downton and Leedham [20] experimented with run-length smearing [94] to connect characters, words, and lines into a text region. In this method, the horizontal or vertical runs of white pixels between black pixels were converted to black if the run length was less than the smearing value. The characters and words could be linked into lines by selecting



an appropriate horizontal smearing value. Furthermore, the lines could be clustered by choosing a proper vertical smearing value.

Jain and Bhattacharjee [36] implemented a texture-based segmentation method for address block location. Four Gabor filters, corresponding to the two highest image radial frequencies for each of 0 and 90 degrees, were used to compute texture features. These texture features were fed into a one-layer feed-forward neural network for classifying pixels into text and non-text categories. The resulting connected components, after certain elimination, were grouped together to form blocks on the mail piece image.

Gardin et al. [25] investigated a recursive top-down address block segmentation scheme. Their approach was to compute the horizontal and vertical histograms based on the count of connected components. The valleys in the histograms were then used for splitting the mail piece image into subregions. This procedure, applied on each of segmented subregions, iterated until certain conditions were satisfied.

Oriot et al. [58] developed a segmentation method based on transition analysis of textural regions. Two distances,  $d_{++}$  and  $d_{+-}$ , were computed in their textual-like analysis. They defined  $d_{++}$  ( $d_{+-}$ ) as the distance between two following transitions 01 (10). Distances  $d_{++}$  and  $d_{+-}$  were then used to characterize the text along the horizontal and vertical directions, respectively. The information obtained from the analysis of distances  $d_{++}$  and  $d_{+-}$  consequently produced word-type segmentation. With a set of topological features, such as distances, alignment, etc., the relation between words were calculated and led to merging a group of words into lines. Finally, the task of merging lines into blocks was accomplished by checking the consistency of some measurements computed on each line.

Pavlidis and Zhou [62] proposed a page segmentation technique for segmenting a document page into column blocks, such as text, halftone, graphics, etc. The vertical projection profile was used to compute the white streams on the document page. The white streams

were formed by sequences of wide blank spaces on contiguous scan lines. Instead of using the vertical projection profile over the entire page image, the projections were taken only over a short height of scan lines each time. In such a way, their method was capable of handling tilted document pages, since skew did not shadow the gap between column blocks.

Yeh et al. [101] designed a way of segmenting out blocks from machine-addressed envelop images. The grey-scale envelop image was segmented into two types of connected components: the light components and the dark components. They were separated by zero-crossings of a digital Laplacian operator. Some properties with respect to the dark connected components were computed and then used to cluster the components into uniform regions. The grouping of components was based on the proximity tree, a data structure similar to the dendrogram [21].

The common problems arisen from the address block segmentation are under segmentation, which leaves out part of the address contents, and over segmentation, which includes excess non-address material. One example of the under segmentation problems is missing part or all of the critical information, defined as the combination of city, state, and ZIP Code. Since machine-printed address blocks often have extra space between the city/state names and the state/ZIP Code, this excessive space results in text being excluded from the main body of the address. Therefore, other measures are often needed to refine the preliminary segmentation results.

### 2.3.2 Feature Extraction

Many features, extracted at character, word, line, and block levels, have been used for classifying regions and ranking candidate destination address blocks [4, 5, 13, 38, 77, 96, 101]. Some basic geometric features are computed at all levels, including location (the minimum and maximum x-y coordinates of the enclosing box), length, height, enclosing box area, and

aspect ratio. Other features are roughly organized as follows:

- Component/character level features: average grey levels, stroke thickness, pixel density;
- Word level features: number of characters in a word, variance of character widths, variance of character heights;
- Line level features: number of words in a line, variance of word orientations, variance of word heights, skew angle;
- Block level features: number of lines in a block, average height of lines, variance of line heights, average gap between lines, justification of lines, print method (handwriting or machine printing), block orientation, background color of a block, texture of a block;
- Miscellaneous features: overlap between blocks, spatial relationship between blocks, labels, windows, isolated ZIP Codes, density of edge points;

Though many geometric and topological features have been experimented with and have shown certain usefulness, they seem insufficient for the task of address block location at high success rates (e.g. 95%). In many situations, address syntactic features appear to be the only plausible features for locating the correct address region.

### 2.3.3 Address Block Selection

While some researchers [20, 36] used simple heuristics to select the destination address block among candidate blocks, others [4, 5, 13, 38, 96, 101] adopted more sophisticated expert systems, AI techniques, and pattern classification methods.

Bergman et al. [6] used a nearest-neighbor pattern classifier to rank the candidate address blocks. There were eight features extracted from each candidate block and then

they were fed into the classifier. They included the number of text lines, the normalized area of the block, variance of word orientations, variance of character heights, the pixel area of the candidate address block, three features measuring the overlap between the candidate address blocks, and a destination address block locational probability distribution.

Caviglione et al. [13] designed a rule-based system in ranking the candidate destination address blocks. The rule-based system used three kinds of reasoning models and one knowledge base. The reasoning models included the probabilistic theory based on the Bayes theorem, the fuzzy set theory, and the combining functions theory. The knowledge base contained five levels of rules about mail characteristics. These rules were associated with the local, context, orientation, and (weak/strong) global features.

Wang and Srihari [96] chose an evidence combination scheme based on the Dempster-Shafer theory in their blackboard problem-solving architecture. The knowledge sources in the blackboard model generated pieces of evidence to be combined for locating the destination address. The categories of evidence included size, layout, color, shape, postage, location, print method, texture, compatibility, ZIP Code, and heuristics.

Yeh et al. [101] considered several alternative approaches for the inference procedure of their system, including the Bayesian classification, the rule-based system, and the hierarchical ambiguity resolution. An integration of the last two approaches was finally chosen for the implementation. The combined approach contained a set of IF-THEN rules using various information, including the inclusion tree, line orientation, domain knowledge of an address block, and the secondary properties for an address field, such as the size of components.

It is our observation that without a set of good features, the more complicated reasoning process does not guarantee the better decision-making outputs. On the other hand, a simple reasoning mechanism can produce satisfactory results if a set of power features is being used.

## Chapter 3

# A Computational Model for Locating Address Paragraphs

### 3.1 Physical Boundaries and Logical Boundaries

Humans are very good at analysis of patterns. We perform object segmentation and recognition in everyday life without much thinking. Studies in Cognitive Psychology [3] reveal that humans perform segmentation before perceptual pattern matching. Our segmentation is a kind of perceptual organization which is greatly influenced by the Gestalt principles. Figure 3.1 illustrates the Gestalt principles, including the principle of proximity, the principle of similarity, the principle of good continuation, and the principle of closure and good form. Part (a) is perceived as four pairs of lines, instead of eight individual lines. The principle of proximity says that we tend to organize objects which are close in space. Part (b) demonstrates the principle of similarity. The patterns are not viewed as five columns of mixed symbols, but as five rows of uniform symbols, although the vertical space in columns is smaller than the horizontal space in rows. Part (c) is perceived as one curve from A to B and one straight line from C to D. The principle of good continuation prevents us from perceiving other configurations which have bad curvature, e.g. one path from A to C and the other from D to B. Part (d) demonstrates the principle of closure and good form. The drawing consists of two overlapping objects and we intuitively think the object at the

bottom is a circle. However, the occluded part of the object is not necessarily an arc and may have other shapes.




Figure 3.1: Illustrations of the Gestalt principles of organization: (a) the principle of proximity; (b) the principle of similarity; (c) the principle of good continuation; (d) the principle of closure. (From Anderson, 1990.)

Take a glance at the character string `TheTaskOfSegmentationIsNotEasy`. Although the space between words is eliminated, people can still read the sentence without much difficulty. This is because our segmentation is influenced by the visual discontinuity created by capitalization of the first letter of each word. The discontinuity happens to correspond to correct word segmentation which leads to meaningful pattern matching. In contrast, it is very difficult to read the character string `ThEtAsKoFsEgMeNtAtIoNiSnOtEaSy`. The reason is that we are affected by the visual discontinuity which does not correspond to correct word segmentation. Therefore, our pattern matching does not give us any meaningful results.

A close look at the two character strings discloses that they are made of the same sequence of characters except the effect of capitalization. While the intuitive segmentation

on the second string does not lead to sensible interpretation, we may read it with more effort using high level reasoning. One way to read the second sentence is to intentionally ignore the effect of capitalization and use recognition based segmentation. We try to read the first few characters and come up with a meaningful word matching. Then we scan the next few characters and guess the meaning of the second word. As this procedure is executed repeatedly until the end of the string, the contents of the sentence becomes comprehensible.

When humans perform segmentation, the initial results are not necessarily be correct, since our functionality of perceptual organization is subject to the Gestalt principles. With bad segmentation, we may fail to understand the meaning of a pattern. In that case, we need to resegment the pattern and use high level reasoning in order to recognize the pattern.

Furthermore, the Gestalt principles concern only physical or geometrical properties of a pattern. It does not involve any recognition or inference. Thus segmentation resulted from the Gestalt principles gives the physical boundaries of the pattern. When segmentation based on the Gestalt principles fails, we may resort to logical or linguistic properties of the pattern to perform segmentation. It then gives us the logical boundaries of the pattern. As far as understanding is concerned, what we need is the logical boundaries, not the physical boundaries.

Although the above example is made of two simple character strings, it does manifest some characteristics of our visual information processing. When a document image is presented to us for a few tenths of second, our initial response of segmentation may not be precisely correct. During such a short time, our segmentation is primarily under the influence of the Gestalt principles and can only make us aware of the physical boundaries of patterns on the image. While we look at the image for longer time with activation of recognition and inference, we will then see the logical boundaries of patterns.

We use another example to illustrate the difference between physical boundaries and

托 羅 必 考 文 法

主 編—— 劉 毅

發 行 所—— 學 習 出 版 公 司

台北市大安區 10667 通化街 200 巷 11 號 4 樓

電話：7045525

郵 政 特 准 掛 號—— 0512727-2

印 刷 所—— 裕 強 彩 色 印 刷 有 限 公 司

登 記 證—— 局 版 台 業 2179 號

售 價—— 新 台 幣 二 百 八 十 元 正

一 九 八 六 年 六 月 二 十 日 新 版

台灣地區總經銷

• 華英文化事業公司 電話：3946693

香港地區出版權·發行權

• 香港學習出版公司 電話：5-293283

香港灣仔區佛蘭士街秀華坊 23 號地下

• 有成圖書貿易公司 電話：5-293283

香港灣仔區佛蘭士街秀華坊 23 號地下

美國總經銷：Evergreen Book Store

136 S. Atlantic Blvd. Monterey Park,

Ca. 91754

版 權 所 有 • 翻 印 必 究

※ 如有破損或缺頁，請寄回本公司更換 ※

Figure 3.2: A page containing both English and Chinese addresses.



logical boundaries. Figure 3.2 is a page containing mixed English and Chinese text. It is obvious that there is an English address located close to the bottom. However, for people who do not understand Chinese, it is difficult to answer the following questions. Does there exist any Chinese addresses on the document? If the answer is yes, how many and where? People who do not know Chinese can see clearly the physical edges and boundaries of the image, but not the logical (semantic) boundaries of addresses.

## 3.2 Text Recognition and Locational Information

While building a document analysis system to perform a task such as address block location, we need to ponder what we should encode into the system so that it can carry out the task as well as humans. The goal of address block location is to obtain the address boundaries. An intuitive approach to address block location is to perform block segmentation on an image and then select the address block from the segmented regions.

### 3.2.1 Difficulties of Block Segmentation

Block (page) segmentation is a process of dividing a document image into coherent regions which contain uniform data. For a journal article page, the regions are text, figures, tables, icons, halftone, etc. For an envelope, the regions are the return address, the destination address, postage, cancellation mark, barcode, graphics, non-address text, etc. For a fax cover page, the regions are the source address, the recipient's address, fax/telephone numbers, message, date, data field indicators such as TO and FROM, etc. Most methods in block segmentation are based on the concept of distance. If a group of objects (black pixels, connected components, or subregions) are "close" on the basis of some measurements, they are considered belonging to the same block; otherwise, they are considered belonging to different blocks. Several representative techniques are recursive X-Y cuts [56], segmentation

based on white stream [62], and run-length smoothing algorithm [94].

Due to the varieties of documents, page segmentation is often domain dependent. Prior information (domain knowledge) is used to help design algorithms and adjust parameters. There are several factors which make page segmentation difficult. First is the layout of the document. The more regularity of the document layout, the less difficulty of page segmentation. Second is the complexity of the contents. A document page becomes complex if it contains many objects of different nature such as machine printed text, handwriting, graphics, etc. Third is the compactness of the contents. If the objects on the document are tightly close to each other, spacing alone is not sufficient to separate these objects.

### 3.2.2 Integration of Text Recognition and Page Segmentation

Page segmentation is conventionally considered as a task performed before text recognition. The advantage of separating these two tasks is that they can become independent and modularized. But page segmentation should not exclude any use of recognition for certain applications. As we mentioned earlier, page segmentation is difficult on complex documents. If text recognition can offer useful information in page segmentation, page segmentation should take advantage of text recognition.

Most documents contain text and text can provide locational information. In newspaper, captions are used to identify human faces in the photos [75]. Words such as left, center, right, front, rear, etc, indicate the positions of people. In a journal article, headings and section numbers provide landmarks of the article layout. On a fax cover page, indicators (such as TO, FROM, and COMPANY) are located at the starting position of their associated data fields. In addition, for special types of text with unique structures, text recognition and structural analysis can directly identify their location. Examples are addresses, telephone numbers, social security numbers, credit card numbers, and ZIP Codes. In summary, text

recognition allows use of syntax and contextual information to locate the target object.

In addition, address block location is an instance of goal-directed location problem. Goal-directed location is the task of locating a particularly interested object. Since the emphasis is on the interested object, the main concern is how to locate the object and segment its boundaries. Therefore, block segmentation on other objects is not very important or necessary. While a generic block segmentation makes equal efforts to segment all objects, segmentation based on text recognition can focus on only the regions where evidence regarding the existence of an address is prominent.

### 3.3 Use of Syntax and Context in Address Block Location

Object location can use two sources of information. One is information regarding the nature of the object and the other is information revealed by its environment. An object can be located directly through its inherent features and structural properties. On the other hand, an object can be located indirectly through its environment which indicates the existence of the object. Often both sources of information are used in object location with emphasis on one or the other.

**Use of syntax:** In address block location, the information regarding the nature of the object include geometrical features and syntactic structure. Many geometrical features have been surveyed in literature review. Here we focus on use of syntactic structure. Since address is a paragraph of text which has unique syntactic structure, the system can identify it by searching for objects which possess address syntax.

A typical address is composed of three parts: firm/person name, street or PO Box information, and the critical information (i.e. city, state, and ZIP Code). Since our task is not address interpretation, we do not attempt to analyze every variety of address syntax. Only a subset of address syntax will be used in helping the address location. The following

three types of phrases have been proven useful.

- (1) the critical information phrase: state + ZIP Code;
- (2) the street phrase: number + ... + street suffix + ...;
- (3) the PO Box phrase: PO + Box + number;

Besides, keywords such as Dr., Mr., Mrs., Co., etc. are used to locate the possible sentences of firm/person names.

**Use of context and domain knowledge:** Knowledge about a problem domain can be incorporated into an address block location system. Prior information about a particular problem domain can confine the area to be searched for the desired address. In a letter, addresses appear on the top portion of the page. On a mail piece, destination addresses can be anywhere except on the top horizontal zone, which is often occupied by the sender's address, cancellation mark, and postage. On a business card, the address most likely appear on the middle or bottom of the card.

Contextual information is quite useful when an address is strongly constrained by its environment. Fax cover pages are one type of documents where contextual information can be extensively used to locate addresses. The recipient's addresses are indicated by keywords such as TO, ATTENTION (or ATTN), and COMPANY.

### 3.4 A Computational Model

The computational model for address block location is shown in Figure 3.3 and Figure 3.4. There are five processes in the computational model, including image analysis, keyword matching, graph construction, graph matching, and address segmentation. In addition, the

computational model contains four components of models/knowledge, including internal keyword list, external keyword list, spatial/syntactic relationship rules, and address models.




Figure 3.3: A computational model for address block location: (a) processes and models.

In the first stage of the computation, the main task is to convert a raw image into an ASCII map, e.g. Figure 3.5. This is carried out by three modules, including connected component analysis, word segmentation, and character recognition.




Figure 3.4: A computational model for address block location: (b) data flow.

Connected component analysis is a task of performing connected component labeling, measuring properties of the connected component regions, and classifying the connected components. Connected component analysis is a way of converting an image from the pixel representation to the segment (region) representation. In connected component representation, an image is abstracted and described by a list of labels each of which associated with a set of attributes, such as bounding rectangle, area, etc. Connected component analysis provides basic data to be used in several computational tasks in the model.

There are a few reasons for using connected component analysis in our model. First, the bounding boxes of connected components can reasonably represent the layout of an address and pre-printed keywords. In addition, extraordinary large or very tiny connected components resulting from graphics and other non-address material can be easily filtered out. This helps reduce the amount of the data to be processed. Furthermore, methods of image analysis using connected component rectangles normally cost less time than those directly dealing with pixels.

Word segmentation is to produce word boundaries and the parent-child relations between words and characters. For machine-printed text, it is reasonable to assume that each connected component corresponds to one character. Neighboring connected components can be grouped into words by using a measure based on geometric features such as distance, size, height, and width. The focus of segmentation is on machine-printed words because recognition will be performed only on them, not other material (e.g. handwriting). Furthermore, the information regarding the logical relations between words and characters are stored. For each word the labels of its constituent characters are recorded with that word. Besides, a word label is assigned to each connected component and the label uniquely identifies the word to which that connected component belongs.

The computation of spatial relations between words is also very important. From a

human point of view, objects present on a document have clear two-dimensional spatial relations. A word is either isolated or has other words or objects surrounding it. A region on the document is either empty or occupied. It is desirable to make a document analysis system mimic this type of ability. Specifically, we need to design a data structure to organize the objects so that the system can easily compute spatial relations among the objects whenever necessary. A spatial information map which stores the locational information of connected components is a data structure we use to achieve this purpose. The construction of a spatial information map will be detailed in Chapter 5.

One more task carried out in the first stage of the computation is character recognition. Connected component bounding boxes are used to extract subimages from the raw image. Then character recognition performs feature extraction and pattern classification on those subimages, and attempts to associate an ASCII value with each subimage. The collection of the results is an ASCII map (see Figure 3.5).

The second stage of the computation is to perform keyword matching. Keyword matching takes every word in the ASCII map and compares it against keywords in a lexicon. The lexicon is made of an internal keyword list, which contains address keywords, and an external keyword list, which contains non-address keywords. While keyword matching attempts to assign a syntactic category to an input word, words in the ASCII map which are not numbers and have no match in the lexicon will be discarded. The remaining words are collected in the filtered ASCII map (see Figure 3.6).

Our approach using syntactic structure in address block location is to formulate this task as a consistent labeling problem. In this formulation words extracted from the raw image are to be matched against two address models (Figure 3.7 and Figure 3.8) on the basis of syntactic and spatial relationships. The formalism of consistent labeling problem will be detailed in the next chapter. In the computational model, graph construction (Figure 3.9



```

      4
                                     4   4
                                           4
          9
                                     John BOreck
                                     17 Van Buren St
                                     Jame5toWm NY 14701 3343

      9
                                     Membareh4n e 3141606

```


Figure 3.5: Intermediate data in the computational model for address block location: ASCII map.

and Figure 3.10) corresponds to converting address block location into a consistent labeling problem, and graph matching corresponds to solving the consistent labeling problem.

The last stage of the computation is address segmentation. Address segmentation performs the task of locating the exact address boundaries and extracting the address subimage from the raw image. This process can use two sources of information. One is information regarding the address itself and is provided by the output of graph matching. The other is information obtained from non-address keywords which constrain the existence of addresses. In Chapter 6, we will show how to use non-address keywords in locating addresses on fax cover sheets.







Spatial relationship r:

e.g.

$r(\text{PO}, \text{BOX}):$

$$(1) \quad x(\text{PO}) - x(\text{BOX}) > D11 \quad \text{and} \\ x(\text{PO}) - x(\text{BOX}) < D12$$

$$(2) \quad y(\text{PO}) - y(\text{BOX}) > D13 \quad \text{and} \\ y(\text{PO}) - y(\text{BOX}) < D14$$

Figure 3.8: Two address models: model 2.





Figure 3.9: Graph construction: spatial / syntactic relationship rules.

## Graph Representation:



## Text Representation:

The label set  $L = \{ \text{words in the filtered ASCII map} \}$

The unit-label constraint relation  $R$ :

$\{((\text{State, NY}), (\text{ZIP-Code, 14701})), ((\text{State, NY}), (\text{Add-on, 3343})),$   
 $((\text{State, NY}), (\text{Street-suffix, St})), ((\text{State, NY}), (\text{Street-number, 17})),$   
 $((\text{ZIP-Code, 14701}), (\text{Add-on, 3343})), ((\text{ZIP-Code, 14701}), (\text{Street-suffix, St})),$   
 $((\text{ZIP-Code, 14701}), (\text{Street-number, 17})), ((\text{Add-on, 3343}), (\text{Street-suffix, St})),$   
 $((\text{Add-on, 3343}), (\text{Street-number, 17})), ((\text{Street-number, 17}), (\text{Street-suffix, St}))\}$

The unit-constraint relation  $T$ :

$\{(\text{State, ZIP-Code}), (\text{State, Add-on}), (\text{State, Street-suffix}), (\text{State, Street-number}),$   
 $(\text{ZIP-Code, Add-on}), (\text{ZIP-Code, Street-suffix}), (\text{ZIP-Code, Street-number}),$   
 $(\text{Add-on, Street-suffix}), (\text{Add-on, Street-number}), (\text{Street-number, Street-suffix})\}$

The unit set  $U = \{ \text{all the syntactic categories used in } T \}$

Figure 3.10: Graph construction result.

## Chapter 4

# Theory of the Consistent Labeling Problem

The consistent labeling problem (CLP) represents a general class of problems appearing in various fields, including computer vision, graph theory, database research, and artificial intelligence. We shall show that address block location can be formulated as a consistent labeling problem. Due to its broad applications and strong relationship with address block location, we have done some research on the theoretical aspect of this subject. A few interesting results regarding problem decomposition will be presented in this chapter.

### 4.1 Definition of the Consistent Labeling Problem

The definition of the consistent-labeling problem is adopted from Haralick and Shapiro [29]. An  $N$ -ary CLP is a problem composed of a collection of units, a set of labels, a unit-constraint relation, and a unit-label constraint relation. The collection of units contains the interested objects to be labeled. The set of labels is a list of possible names for those objects. The unit-constraint relation is an  $N$ -ary relation over the set of units specifying which objects are mutually constrained. The unit-label constraint relation, an  $N$ -ary relation over the set of unit-label pairs, restricts the permissible labelings of subsets of the unit set. The task of CLP is to find labelings of the unit set such that for any  $N$  mutually constrained

objects, their name assignment is consistent with the unit-label constraint relation. A formal definition is stated as follows:

An  $N$ -ary consistent-labeling problem is a 4-tuple  $CLP = (U, L, T, R)$

$U = \{1, \dots, M\}$ , is a set of  $M$  units

$L$  is a set of possible labels

$T \subseteq U^N$  is called unit-constraint relation, whose elements have the form  $(u_1, \dots, u_N)$

$R \subseteq (U \times L)^N$  is called unit-label constraint relation, whose elements

have the form  $((u_1, l_1), \dots, (u_N, l_N))$

A labeling  $f$  of  $\tilde{U} = \{u_1, \dots, u_n\} \subseteq U$  is a function  $f: \tilde{U} \rightarrow L$

A labeling  $f$  of  $\tilde{U} \subseteq U$  is consistent if and only if

$$\begin{aligned} \forall u_1 \dots \forall u_N \{u_1, \dots, u_N\} \subseteq \tilde{U} \text{ and } (u_1, \dots, u_N) \in T \\ \Rightarrow ((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R \end{aligned}$$

The task of  $CLP$  is to find one or all consistent labelings of the unit set  $U$ .

## 4.2 Examples and Previous Studies

Many problems can be formulated as consistent labeling problems, including the N-queen problem, the Latin square puzzle, the graph matching problem, the graph coloring problem, the relational-homomorphism problem, the scene labeling problem, the edge-orientation problem, temporal reasoning, AI planning, scheduling problems, natural language parsing, query optimization in database research, and so on [29, 31, 87].

Backtracking tree search is a basic method to solve consistent labeling problems. Additional procedures, such as forwarding checking [28] and discrete relaxation [88, 89, 95], can be incorporated to improve the tree search. When used alone, discrete relaxation procedures



may reduce the complexity of the problem. One discrete relaxation procedure called the psi operator was defined by Haralick and Shapiro [29, 30]. They explored its mathematical properties and showed that many operators used by other researchers were special cases of the psi operator.

Solution synthesis and exploitation of problem-specific features are two other approaches [87]. Freuder [22] introduced the first solution synthesis algorithm, which is a variation of breadth-first search. Though the consistent labeling problem is an NP-complete problem, some problems can be solved efficiently by exploiting their problem structures. For example, the tree-clustering method [18] is effective in problems where every unit is constrained by only a few others.

Figure 4.1 and Figure 4.2 give an example of formulating graph matching as a consistent labeling problem. There are two graphs, graph  $A$  and graph  $B$ , in part (a). The task of graph matching in this example is to find a subgraph  $B_s$  of graph  $B$  so that  $B_s$  is isomorphic to graph  $A$  (see Definition 1). The formulation of graph matching as a consistent labeling problem  $CLP = (U, L, T, R)$  is expressed by specifying the four components  $U$ ,  $L$ ,  $T$ , and  $R$  by means of graph  $A$  and graph  $B$  (see part (b)). The unit set  $U$  is the collection of all vertices in graph  $A$ . The label set  $L$  is the set of all vertices in graph  $B$ . Since every edge of graph  $A$  must find a corresponding edge in graph  $B$ , every edge of graph  $A$  is a unit-constraint on its two incident vertices. Therefore, the unit-constraint relation  $T$  is the set of all edges in graph  $A$ . The table in part (a) is used to define the unit-label constraint relation  $R$ . Because an edge in graph  $A$  can be matched to any edge in graph  $B$ , every entry in the table is a valid unit-label assignment for two adjacent vertices in graph  $A$ . As a result, the unit-label constraint relation  $R$  is the set of all entries in the table. It is also shown in part (b) that backtracking tree search generates a few solutions to this problem.

**Definition 1** Let  $G_1 = (V_1, E_1)$  and  $G_2(V_2, E_2)$  be two graphs, where  $V_i$  is the set of vertices




Figure 4.1: Graph matching is a consistent labeling problem: part (a).

$CLP = (U, L, T, R)$   
 $U = \{ 1, 2, 3, 4, 5, 6 \}$   
 $L = \{ a, b, c, d, e, f, g, h, i, j, k \}$   
 $T = \{ (1,2), (1,3), (2,4), (2,5), (3,4), (3,5), (4,6), (5,6) \}$   
 $E = \{ (a,b), (a,g), (b,a), (b,e), (c,e), (c,f), (c,g), (d,e), (d,f), (d,g), (e,b), (e,c),$   
 $(e,d), (f,c), (f,d), (f,h), (g,a), (g,c), (g,d), (g,h), (h,f), (h,g), (h,k), (i,k),$   
 $(i,j), (j,i), (j,k), (k,h), (k,i), (k,j) \}$   
 $R = \{ ((u_1, l_1), (u_2, l_2)) \mid (u_1, u_2) \in T \text{ and } (l_1, l_2) \in E \}$




Figure 4.2: Graph matching is a consistent labeling problem: part (b).

of  $G_i$  and  $E_i$  is the set of edges of  $G_i$  with  $i = 1, 2$ .  $G_1$  is said to be isomorphic to  $G_2$  iff there exists a one-to-one, onto mapping  $f : V_1 \rightarrow V_2$  such that it is true  $\forall v, v' (v, v') \in E_1$  iff  $(f(v), f(v')) \in E_2$ .

### 4.3 Address Block Location as a Consistent-Labeling Problem

In one phase of address block location, certain matching procedure is required. Given a list of words extracted from an image and a few address models, the task is to find all address regions. Here, the task involves only symbolic computation, no pixel-level operations. Each word is associated with two attributes: location and character recognition results. An address model is composed of interested units, each of which is a syntactic category. Two address models are shown in Figure 3.7 and Figure 3.8. For any two units in a model, some rules are used to specify the spatial relationships. For example, street suffix should follow street number on the same line with a few words apart. Add-on must be adjacent to ZIP Code. Locating an address region is then to determine which words can reasonably match one of the address models.

To formulate address block location as a consistent-labeling problem  $CLP = (U, L, T, R)$ , we need to clearly define its four components,  $U, L, T$ , and  $R$ . The set of units  $U$  is a collection of all the syntactic categories used in the address models. In addition, we impose an ordering on the units in  $U$ . One possible ordering " $>$ " on  $U$  is "State"  $>$  "ZIP-Code"  $>$  "Add-on"  $>$  "Number"  $>$  "Street-suffix"  $>$  "PO"  $>$  "BOX"  $>$  "Person-name"  $>$  "Firm-name". The set of labels  $L$  is an ensemble of words extracted from an image. The unit-label constraint relation  $R$  is a binary relation over the set of unit-label pairs. A tuple  $((u_1, w_1), (u_2, w_2))$  belongs to  $R$  if and only if  $u_1 > u_2$ , and the pair  $u_1$  and  $u_2$  is a feasible interpretation of the pair  $w_1$  and  $w_2$ . The feasible interpretation is based on two crite-

ria. One is the character recognition results of  $w_1$  and  $w_2$  should be compatible with the syntactic categories  $u_1$  and  $u_2$ . The other is the spatial relationship between  $w_1$  and  $w_2$  should be compatible with that between  $u_1$  and  $u_2$ . The unit-constraint relation  $T$  is a binary relation over the set of units. For each tuple  $((u_1, w_1), (u_2, w_2))$  belonging to  $R$ , the tuple  $(u_1, u_2)$  is said to be a member of  $T$ . Since it may occasionally happen in real world application that some syntactic categories in  $U$  are not used in  $R$  and  $T$ , we need to define a subset  $\tilde{U}$  of the unit set  $U$  so that  $\tilde{U}$  contains only those categories in use. Whenever a  $(u, v)$  or  $(v, u)$  is in  $T$ , we say  $u$  is a member of  $\tilde{U}$ . The task is then to find all consistent labelings of  $CLP = (\tilde{U}, L, T, R)$ . We summarize the formulation of address block location as a consistent-labeling problem below.

$$U = \{ \text{"State"}, \text{"ZIP-Code"}, \text{"Add-on"}, \text{"Number"}, \text{"Street-suffix"}, \text{"PO"}, \text{"BOX"}, \\ \text{"Person-name"}, \text{"Firm-name"} \}$$

$$L = \{ w \mid w's \text{ are words extracted from an image} \}$$


$$R = \{ ((u_1, w_1), (u_2, w_2)) \mid u_1, u_2 \in U \wedge u_1 > u_2 \wedge w_1, w_2 \in L \wedge \text{the couple of } u_1 \text{ and } u_2 \\ \text{is a feasible interpretation of the couple of } w_1 \text{ and } w_2 \}$$

$$T = \{ (u_1, u_2) \mid \text{there exists } ((u_1, w_1), (u_2, w_2)) \in R \}$$

$$\tilde{U} = \{ u \mid \text{there exists } (u, v) \in T \text{ or } (v, u) \in T \}$$

$$\text{Find } F = \{ f \mid f: \tilde{U} \rightarrow L \text{ is a consistent labeling of } CLP = (\tilde{U}, L, T, R) \}$$

An example is given in Figure 4.3 to illustrate the formulation of address block location as a consistent labeling problem  $CLP = (U, L, T, R)$ . The figure at the top shows the words extracted from an image. All these words constitute the label set  $L$ . The unit-label constraint relation  $R$  is computed based on both locational and syntactic attributes. The unit-constraint relation  $T$  is then derived from the unit-label constraint relation  $R$ . The unit set  $U$  is the collection of syntactic categories being used in the the unit-constraint relation  $T$ . It is not difficult to verify that  $\{(State, NY), (ZIP-Code, 14701), (Add-on, 3343),$



$CLP=(U,L,T,R)$

The label set  $L = \{ \text{words in the filtered ASCII map above} \}$

The unit-label constraint relation  $R$ :

$\{((\text{State, NY}), (\text{ZIP-Code, 14701})), ((\text{State, NY}), (\text{Add-on, 3343})),$   
 $((\text{State, NY}), (\text{Street-suffix, St})), ((\text{State, NY}), (\text{Street-number, 17})),$   
 $((\text{ZIP-Code, 14701}), (\text{Add-on, 3343})), ((\text{ZIP-Code, 14701}), (\text{Street-suffix, St})),$   
 $((\text{ZIP-Code, 14701}), (\text{Street-number, 17})), ((\text{Add-on, 3343}), (\text{Street-suffix, St})),$   
 $((\text{Add-on, 3343}), (\text{Street-number, 17})), ((\text{Street-number, 17}), (\text{Street-suffix, St}))\}$

The unit-constraint relation  $T$ :

$\{(\text{State, ZIP-Code}), (\text{State, Add-on}), (\text{State, Street-suffix}), (\text{State, Street-number}),$   
 $(\text{ZIP-Code, Add-on}), (\text{ZIP-Code, Street-suffix}), (\text{ZIP-Code, Street-number}),$   
 $(\text{Add-on, Street-suffix}), (\text{Add-on, Street-number}), (\text{Street-number, Street-suffix})\}$

The unit set  $U = \{ \text{all the syntactic categories used in } T \}$

Consistent-labeling:

$\{(\text{State, NY}), (\text{ZIP-Code, 14701}), (\text{Add-on, 3343}), (\text{Street-number, 17}),$   
 $(\text{Street-suffix, St})\}$

Figure 4.3: An example of consistent labeling problem.

(Street-number, 17). (Street-suffix, St)} is the only consisting labeling of this problem.

#### 4.4 Problem Decomposition

If a consistent labeling problem possesses specific features, it may be useful to decompose the problem into several subproblems. Solving the subproblems lends themselves to solving the main problem. Since a consistent labeling problem is composed of four sets,  $U, L, T$ , and  $R$ , problem decomposition has something to do with their structures. For the purpose of studying the problem structure of a  $CLP = (U, L, T, R)$ , we define three connected relations,  $J_U, J_L$  and  $J_T$ , on  $U, L$  and  $T$ , respectively. It is easy to see that the connected relations are three equivalence relations on their own domains.

**Definition 2** Given  $CLP = (U, L, T, R)$ , we define a connected relation  $J_U$  on  $U$ . For any two units  $u, v \in U$ , we say  $uJ_U v$  if there exists a path  $r_1, \dots, r_k$  in  $R$  with  $u$  appearing in  $r_1$  and  $v$  appearing in  $r_k$  such that for any two consecutive  $r_j = ((u'_1, l'_1), \dots, (u'_N, l'_N))$  and  $r_{j+1} = ((u''_1, l''_1), \dots, (u''_N, l''_N))$ ,  $j = 1, \dots, (k-1)$ , it is true that  $\{u'_1, \dots, u'_N\} \cap \{u''_1, \dots, u''_N\} \neq \emptyset$ .

**Definition 3** Given  $CLP = (U, L, T, R)$ , we define a connected relation  $J_T$  on  $T$ . For any two tuples  $x = (u_1, \dots, u_N) \in T, y = (\bar{u}_1, \dots, \bar{u}_N) \in T$ . we say  $xJ_T y$  if there exists a path  $r_1, \dots, r_k$  in  $R$  with  $r_1 = ((u_1, l_1), \dots, (u_N, l_N))$  and  $r_k = ((\bar{u}_1, \bar{l}_1), \dots, (\bar{u}_N, \bar{l}_N))$  such that for any two consecutive  $r_j = ((u'_1, l'_1), \dots, (u'_N, l'_N))$  and  $r_{j+1} = ((u''_1, l''_1), \dots, (u''_N, l''_N))$ ,  $j = 1, \dots, (k-1)$ , it is true that  $\{u'_1, \dots, u'_N\} \cap \{u''_1, \dots, u''_N\} \neq \emptyset$ .

**Definition 4** Given  $CLP = (U, L, T, R)$ , we define a connected relation  $J_L$  on  $L$ . For any two labels  $l, \bar{l} \in L$ , we say  $lJ_L \bar{l}$  if there exists a path  $r_1, \dots, r_k$  in  $R$  with  $l$  appearing in  $r_1$  and  $\bar{l}$  appearing in  $r_k$  such that for any two consecutive  $r_j = ((u'_1, l'_1), \dots, (u'_N, l'_N))$  and  $r_{j+1} = ((u''_1, l''_1), \dots, (u''_N, l''_N))$ ,  $j = 1, \dots, (k-1)$ , it is true that  $\{l'_1, \dots, l'_N\} \cap \{l''_1, \dots, l''_N\} \neq \emptyset$ .

**Lemma 1**  $J_U, J_L, J_T$  are equivalence relations on  $U, L$  and  $T$ , respectively.

One special case where problem decomposition is possible is when the unit set is not connected. That means the unit set can be divided into more than one connected groups and each group corresponds to one subproblem. Since there are no constraints among units belonging to different groups, each subproblem can be solved independently and the union of the subsolutions makes up the overall solution.

**Definition 5** Let  $f : A \rightarrow B$  be a function. For any subset  $A' \subseteq A$ , we define  $f_{A'} : A' \rightarrow B$  as  $f_{A'} = \{(a, b) \mid a \in A' \text{ and } (a, b) \in f\}$ . We call  $f_{A'}$  a subfunction of  $f$ .

**Theorem 1** Given  $CLP = (U, L, T, R)$ , suppose  $U$  is not connected under  $J_U$  and is partitioned into  $U_1$  and  $U_2$ . Let

$$R_1 = \{(u_1, l_1), \dots, (u_N, l_N) \in R \mid \{u_1, \dots, u_N\} \subseteq U_1\}$$

$$R_2 = \{(u_1, l_1), \dots, (u_N, l_N) \in R \mid \{u_1, \dots, u_N\} \subseteq U_2\}$$

$$T_1 = \{(u_1, \dots, u_N) \in T \mid \text{there exists } ((u_1, l_1), \dots, (u_N, l_N)) \in R_1\}$$

$$T_2 = \{(u_1, \dots, u_N) \in T \mid \text{there exists } ((u_1, l_1), \dots, (u_N, l_N)) \in R_2\}$$

$$L_1 = \{l \mid \text{there exists } r \in R_1 \text{ such that } l \text{ appearing in } r\}$$

$$L_2 = \{l \mid \text{there exists } r \in R_2 \text{ such that } l \text{ appearing in } r\}$$

The following statements are true.

(a)  $f$  is a consistent labeling of  $CLP = (U, L, T, R)$

$\Rightarrow f_{U_1}$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$  and

$f_{U_2}$  is a consistent labeling of  $CLP = (U_2, L_2, T_2, R_2)$

(b)  $f'$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$  and

$f''$  is a consistent labeling of  $CLP = (U_2, L_2, T_2, R_2)$

$\Rightarrow f' \cup f''$  is a consistent labeling of  $CLP = (U, L, T, R)$



Proof of Theorem 1:

(a):

Since  $f$  is a consistent labeling of  $CLP = (U, L, T, R)$  and  $T_1 \subseteq T$ ,

for any  $(u_1, \dots, u_N) \in T_1$ , there exists  $((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R$ .

We claim  $((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R_1$ ; therefore,

$f$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$ .

Suppose our claim is false and  $((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R_2$ .

It implies  $(u_1, \dots, u_N) \in T_2$  and  $T_1 \cap T_2 \neq \emptyset$ .

This gives a contradiction.

(b):

For any  $(u_1, \dots, u_N) \in T$ ,

if  $(u_1, \dots, u_N) \in T_1$ ,

then  $((u_1, f_1(u_1)), \dots, (u_N, f_1(u_N))) \in R_1$  and also  $((u_1, f_1(u_1)), \dots, (u_N, f_1(u_N))) \in R$ .

if  $(u_1, \dots, u_N) \in T_2$ ,

then  $((u_1, f_2(u_1)), \dots, (u_N, f_2(u_N))) \in R_2$  and also  $((u_1, f_2(u_1)), \dots, (u_N, f_2(u_N))) \in R$ .

So  $f_1 \cup f_2$  is a consistent labeling of  $CLP = (U, L, T, R)$ .

We use an example to illustrate Theorem 1 (see Figure 4.4 and Figure 4.5). Part (a) shows a consistent labeling problem  $CLP = (U, L, T, R)$ . It can be solved directly and there are two consistent labelings as shown in part (a). On the other hand, its answers can be obtained by taking the union of the solutions to its subproblems. This problem is suitable to be decomposed since the connection graph of  $U$  is not connected. The connection graph of  $U$  is produced by drawing a complete subgraph consisting of  $u_1, u_2$ , and  $u_3$ , for every  $(u_1, u_2, u_3) \in T$ . There are two connected components in the connection graph of  $U$ , and each of them corresponds to one subproblem as shown in part (b). These two subproblems

$$CLP=(U, L, T, R)$$

$$U = \{ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 \}$$

$$L = \{a, b\}$$

$$T = \{ (1,3,4), (1,5,6), (2,3,4), (2,4,5), (3,5,6), (7,8,9), (7,9,10) \}$$

$$R = \{ ((1,a),(3,b),(4,a)), ((1,b),(3,b),(4,a)), \\ ((1,a),(5,b),(6,b)), ((1,b),(5,a),(6,a)), \\ ((2,a),(3,b),(4,a)), ((2,b),(3,b),(4,b)), \\ ((2,a),(4,a),(5,b)), ((2,b),(4,a),(5,a)), \\ ((3,a),(5,b),(6,b)), ((3,b),(5,b),(6,b)), \\ ((7,b),(8,a),(9,a)), ((7,b),(8,b),(9,a)), \\ ((8,a),(9,a),(10,b)), ((8,b),(9,a),(10,a)) \}$$

Consistent Labelings:

$$\{ (1,a), (2,a), (3,b), (4,a), (5,b), (6,b), (7,b), (8,b), (9,a), (10,a) \}$$

$$\{ (1,a), (2,a), (3,b), (4,a), (5,b), (6,b), (7,b), (8,a), (9,a), (10,b) \}$$

$$\forall (u_1, u_2, \dots, u_N) \in T \\ \Rightarrow \text{draw a complete subgraph consisting of } u_1, u_2, \dots, u_N$$

Connection graph of U:





Figure 4.4: An example of problem decomposition based on a disconnected unit set: part (a).

$CLP=(U_1, L_1, T_1, R_1)$   
 $U_1 = \{ 1, 2, 3, 4, 5, 6 \}$   
 $L_1 = \{ a, b \}$   
 $T_1 = \{ (1,3,4), (1,5,6), (2,3,4), (2,4,5), (3,5,6) \}$   
 $R_1 = \{ ((1,a),(3,b),(4,a)), ((1,b),(3,b),(4,a)),$   
 $((1,a),(5,b),(6,b)), ((1,b),(5,a),(6,a)),$   
 $((2,a),(3,b),(4,a)), ((2,b),(3,b),(4,b)),$   
 $((2,a),(4,a),(5,b)), ((2,b),(4,a),(5,a)),$   
 $((3,a),(5,b),(6,b)), ((3,b),(5,b),(6,b)) \}$




Consistent Labeling:

{ (1,a), (2,a), (3,b), (4,a), (5,b), (6,b) }

Connection graph of U1

$CLP=(U_2, L_2, T_2, R_2)$   
 $U_2 = \{ 7, 8, 9, 10 \}$   
 $L_2 = \{ a, b \}$   
 $T_2 = \{ (7,8,9), (7,9,10) \}$   
 $R_2 = \{ ((7,b),(8,a),(9,a)), ((7,b),(8,b),(9,a)),$   
 $((8,a),(9,a),(10,b)), ((8,b),(9,a),(10,a)) \}$



Consistent Labelings:

{ (7,b), (8,b), (9,a), (10,a) }  
 { (7,b), (8,a), (9,a), (10,b) }

Connection graph of U2

Figure 4.5: An example of problem decomposition based on a disconnected unit set: part (b).

can be solved separately. The union of their consistent labelings is the same as the solutions to the original problem.

Another situation where problem decomposition is adequate is when the set of labels is disjointed. Whenever the label set of a CLP is not connected and can be divided into more than one groups, the problem is suitable to be decomposed. In this case, each individual group corresponds to an independent subproblem. Theorem 2 states that the solutions to the subproblems are also the solutions to the original problem.

**Theorem 2** *Given CLP = (U, L, T, R), suppose (a) U is connected under  $J_U$ . (b) L is not connected under  $J_L$  and is partitioned into  $L_1$  and  $L_2$ . Let*

$$R_1 = \{((u_1, l_1), \dots, (u_N, l_N)) \in R \mid \{l_1, \dots, l_N\} \subseteq L_1\}$$

$$R_2 = \{((u_1, l_1), \dots, (u_N, l_N)) \in R \mid \{l_1, \dots, l_N\} \subseteq L_2\}$$

$$T_1 = \{(u_1, \dots, u_N) \in T \mid \text{there exists } ((u_1, l_1), \dots, (u_N, l_N)) \in R_1\}$$

$$T_2 = \{(u_1, \dots, u_N) \in T \mid \text{there exists } ((u_1, l_1), \dots, (u_N, l_N)) \in R_2\}$$

$$U_1 = \{u \mid \text{there exists } t \in T_1 \text{ such that } u \text{ appearing in } t\}$$

$$U_2 = \{u \mid \text{there exists } t \in T_2 \text{ such that } u \text{ appearing in } t\}$$

*The following statements hold.*

(0)  $T_1 \cup T_2 = T$ , and  $T$  is connected under  $J_T$ .

(1) If  $T_1, T_2 \subset T$ , then

*there is no consistent labeling for the problem CLP = (U, L, T, R).*

(2) If  $T_1 = T, T_2 \subset T$ , then

*f is a consistent labeling of CLP = (U, L, T, R)*

$\Leftrightarrow$  *f is a consistent labeling of CLP = (U<sub>1</sub>, L<sub>1</sub>, T<sub>1</sub>, R<sub>1</sub>).*

(3) If  $T_1 = T_2 = T$ , then

*f is a consistent labeling of CLP = (U, L, T, R)*

$\Leftrightarrow$  *f is a consistent labeling of CLP = (U<sub>1</sub>, L<sub>1</sub>, T<sub>1</sub>, R<sub>1</sub>) or CLP = (U<sub>2</sub>, L<sub>2</sub>, T<sub>2</sub>, R<sub>2</sub>).*

Proof of Theorem 2:

(0):

It is straightforward from the definitions of connected relations  $J_U$  and  $J_T$ .

(1):

Assume there is a consistent labeling  $f$  for  $CLP = (U, L, T, R)$ .

Let  $(\bar{u}_1, \dots, \bar{u}_N) \in (T_2 - T_1)$  and  $(u_1, \dots, u_N) \in (T_1 - T_2)$ .

$(T_1 \cup T_2 = T \wedge T_1, T_2 \subset T \Rightarrow (T_2 - T_1) \neq \emptyset \wedge (T_1 - T_2) \neq \emptyset)$

Naturally,

$r = ((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R_1$ ; otherwise  $(u_1, \dots, u_N) \in T_2$ .

$\bar{r} = ((\bar{u}_1, f(\bar{u}_1)), \dots, (\bar{u}_N, f(\bar{u}_N))) \in R_2$ ; otherwise  $(\bar{u}_1, \dots, \bar{u}_N) \in T_1$ .

Since  $T$  is connected, there exists a path  $r_1, \dots, r_k$  with  $r_1 = ((u_1, l_1), \dots, (u_N, l_N))$  and

$r_k = ((\bar{u}_1, \bar{l}_1), \dots, (\bar{u}_N, \bar{l}_N))$  such that for any two consecutive  $r_j = ((u'_1, l'_1), \dots, (u'_N, l'_N))$

and  $r_{j+1} = ((u''_1, l''_1), \dots, (u''_N, l''_N))$ ,  $j = 1, \dots, (k-1)$ , it is true that

$\{u'_1, \dots, u'_N\} \cap \{u''_1, \dots, u''_N\} \neq \emptyset$ .

It implies that there exists a path  $r = \tilde{r}_1, \dots, \tilde{r}_k = \bar{r}$  such that for any two consecutive

$\tilde{r}_j = ((u'_1, f(u'_1)), \dots, (u'_N, f(u'_N)))$  and  $\tilde{r}_{j+1} = ((u''_1, f(u''_1)), \dots, (u''_N, f(u''_N)))$ ,

$j = 1, \dots, (k-1)$ , it is true that  $\{f(u'_1), \dots, f(u'_N)\} \cap \{f(u''_1), \dots, f(u''_N)\} \neq \emptyset$ .

By the definition of connected relation  $J_L$  on  $L$ , we know

$f(u_1), \dots, f(u_N), f(\bar{u}_1), \dots, f(\bar{u}_N)$  belong to the same equivalence class.

Because  $f(u_1), \dots, f(u_N) \in L_1$ , it leads to  $f(\bar{u}_1), \dots, f(\bar{u}_N) \in L_1$ .

As a result,  $(\bar{u}_1, \dots, \bar{u}_N) \in T_1$  and we come to a contradiction.

(2):

$\Leftarrow$  : Obvious, since  $T_1 = T$  and  $R_1 \subseteq R$ .

$\Rightarrow :$

Given  $T_2 \subset T_1$ , let  $(u_1, \dots, u_N) \in (T_1 - T_2) \neq \emptyset$

Since  $f$  is a consistent labeling of  $CLP = (U, L, T, R)$ , there exists

$$r = ((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R.$$

It must be true that  $f(u_1), \dots, f(u_N) \in L_1$ ; otherwise,

it would get a contradiction that  $(u_1, \dots, u_N) \in T_2$ .

Now, for any  $(\bar{u}_1, \dots, \bar{u}_N) \in T_1$ , we want to show  $\bar{r} = ((\bar{u}_1, f(\bar{u}_1)), \dots, (\bar{u}_N, f(\bar{u}_N))) \in R_1$

and our proof will be done.

Since  $T_1$  is connected, there exists a path  $r_1, \dots, r_k$  with  $r_1 = ((u_1, l_1), \dots, (u_N, l_N))$  and

$r_k = ((\bar{u}_1, \bar{l}_1), \dots, (\bar{u}_N, \bar{l}_N))$  such that for any two consecutive  $r_j = ((u'_1, l'_1), \dots, (u'_N, l'_N))$

and  $r_{j+1} = ((u''_1, l''_1), \dots, (u''_N, l''_N)), j = 1, \dots, (k-1)$ , it is true that

$$\{u'_1, \dots, u'_N\} \cap \{u''_1, \dots, u''_N\} \neq \emptyset.$$

It implies that there exists a path  $r = \tilde{r}_1, \dots, \tilde{r}_k = \bar{r}$  such that for any two consecutive

$\tilde{r}_j = ((u'_1, f(u'_1)), \dots, (u'_N, f(u'_N)))$  and  $\tilde{r}_{j+1} = ((u''_1, f(u''_1)), \dots, (u''_N, f(u''_N))),$

$j = 1, \dots, (k-1)$ , it is true that  $\{f(u'_1), \dots, f(u'_N)\} \cap \{f(u''_1), \dots, f(u''_N)\} \neq \emptyset$ .

By the definition of connected relation  $J_L$  on  $L$ , we know

$f(u_1), \dots, f(u_N), f(\bar{u}_1), \dots, f(\bar{u}_N)$  belong to the same equivalence class.

Because  $f(u_1), \dots, f(u_N) \in L_1$ , it must be true that  $f(\bar{u}_1), \dots, f(\bar{u}_N) \in L_1$ .

As a result,  $\bar{r} = ((\bar{u}_1, f(\bar{u}_1)), \dots, (\bar{u}_N, f(\bar{u}_N))) \in R_1$ .

(3):

$\Leftarrow :$  Obvious, since  $T_1 = T_2 = T$  and  $R_1, R_2 \subseteq R$ .

$\Rightarrow :$

Let  $(u_1, \dots, u_N)$  be an arbitrary member in  $T$ .

Since  $f$  is a consistent labeling of  $CLP = (U, L, T, R)$ , there exists

$$r = ((u_1, f(u_1)), \dots, (u_N, f(u_N))) \in R.$$

Without loss of generality, assume  $f(u_1), \dots, f(u_N) \in L_1$ , which means

$$r \in R_1 \text{ and also } (u_1, \dots, u_N) \in T_1.$$

Now, we need to show for any other  $(\bar{u}_1, \dots, \bar{u}_N) \in T_1$ , it is true that

$$\bar{r} = ((\bar{u}_1, f(\bar{u}_1)), \dots, (\bar{u}_N, f(\bar{u}_N))) \in R_1 \text{ and our proof will be done.}$$

Since  $T_1 = T$  is connected, there exists a path  $r_1, \dots, r_k$  with  $r_1 = ((u_1, l_1), \dots, (u_N, l_N))$

and  $r_k = ((\bar{u}_1, \bar{l}_1), \dots, (\bar{u}_N, \bar{l}_N))$  such that for any two consecutive

$$r_j = ((u'_1, l'_1), \dots, (u'_N, l'_N)) \text{ and } r_{j+1} = ((u''_1, l''_1), \dots, (u''_N, l''_N)), j = 1, \dots, (k-1),$$

it is true that  $\{u'_1, \dots, u'_N\} \cap \{u''_1, \dots, u''_N\} \neq \emptyset$ .

It implies that there exists a path  $r = \tilde{r}_1, \dots, \tilde{r}_k = \bar{r}$  such that for any two consecutive

$$\tilde{r}_j = ((u'_1, f(u'_1)), \dots, (u'_N, f(u'_N))) \text{ and } \tilde{r}_{j+1} = ((u''_1, f(u''_1)), \dots, (u''_N, f(u''_N))),$$

$j = 1, \dots, (k-1)$ , it is true that  $\{f(u'_1), \dots, f(u'_N)\} \cap \{f(u''_1), \dots, f(u''_N)\} \neq \emptyset$ .

By the definition of connected relation  $J_L$  on  $L$ , we know

$$f(u_1), \dots, f(u_N), f(\bar{u}_1), \dots, f(\bar{u}_N) \text{ belong to the same equivalence class.}$$

Because  $f(u_1), \dots, f(u_N) \in L_1$ , it must be true that  $f(\bar{u}_1), \dots, f(\bar{u}_N) \in L_1$ .

As a result,  $\bar{r} = ((\bar{u}_1, f(\bar{u}_1)), \dots, (\bar{u}_N, f(\bar{u}_N))) \in R_1$ .

One example (Figure 4.6 and Figure 4.7) is used to illustrate Theorem 2. Part (a) gives a consistent labeling problem  $CLP = (U, L, T, R)$  and its solutions. Because the connection graph of  $L$  consists of two connected components, this problem can be decomposed into two subproblems. The connection graph of  $L$  is derived by plotting a complete subgraph among  $l_1, l_2$ , and  $l_3$ , for every  $((u_1, l_1), (u_2, l_2), (u_3, l_3)) \in R$ . Each connected component in the connection graph of  $L$  corresponds to one subproblem as shown in part (b). The consistent labelings of the subproblems are valid solutions to the original problem.

In addition, the issue of problem decomposition can be addressed on the structure of the unit-label constraint relation  $R$  in a CLP. Should the relation  $R$  be decomposed into two subrelations  $R_1$  and  $R_2$  consistent with some rules (see Definition 6), it is appropriate to

$$CLP=(U, L, T, R)$$

$$U = \{ 1, 2, 3, 4, 5 \}$$

$$L = \{ a, b, c, d, e, f, g, h, i, j, k, l, m \}$$

$$T = \{ (1,2,4), (1,4,5), (2,3,4), (2,3,5) \}$$

$$R = \{ ((1,a),(2,i),(4,d)), ((1,e),(2,m),(4,h)), ((1,i),(2,d),(4,f)), ((1,l),(2,h),(4,b)), ((1,a),(4,d),(5,k)), ((1,c),(4,f),(5,k)), ((1,j),(4,m),(5,g)), ((1,l),(4,b),(5,e)), ((2,a),(3,c),(4,d)), ((2,g),(3,j),(4,l)), ((2,h),(3,g),(4,b)), ((2,i),(3,c),(4,d)), ((2,b),(3,m),(5,j)), ((2,f),(3,i),(5,c)), ((2,h),(3,g),(5,e)), ((2,i),(3,c),(5,k)) \}$$

Consistent Labelings:

$$\{ (1,a), (2,i), (3,c), (4,d), (5,k) \}, \{ (1,l), (2,h), (3,g), (4,b), (5,e) \}$$

$$\forall ((u_1,l_1), (u_2,l_2), \dots, (u_N,l_N)) \in R \\ \Rightarrow \text{draw a complete subgraph consisting of } l_1, l_2, \dots, l_N$$

Connection graph of L:




Figure 4.6: An example of problem decomposition based on a disconnected label set: part (a).




CLP=(U<sub>1</sub>, L<sub>1</sub>, T<sub>1</sub>, R<sub>1</sub>)

U<sub>1</sub> = { 1, 2, 3, 4, 5 }

L<sub>1</sub> = { a, c, d, f, i, k }

T<sub>1</sub> = { (1,2,4), (1,4,5), (2,3,4), (2,3,5) }

R<sub>1</sub> = { ((1,a),(2,i),(4,d)), ((1,i),(2,d),(4,f)),  
 ((1,a),(4,d),(5,k)), ((1,c),(4,f),(5,k)),  
 ((2,a),(3,c),(4,d)), ((2,i),(3,c),(4,d)),  
 ((2,f),(3,i),(5,c)), ((2,i),(3,c),(5,k)) }



Connection graph of L<sub>1</sub>

Consistent Labeling:

{ (1,a), (2,i), (3,c), (4,d), (5,k) }


CLP=(U<sub>2</sub>, L<sub>2</sub>, T<sub>2</sub>, R<sub>2</sub>)

U<sub>2</sub> = { 1, 2, 3, 4, 5 }

L<sub>2</sub> = { b, e, g, h, j, l, m }

T<sub>2</sub> = { (1,2,4), (1,4,5), (2,3,4), (2,3,5) }

R<sub>2</sub> = { ((1,e),(2,m),(4,h)), ((1,l),(2,h),(4,b)),  
 ((1,j),(4,m),(5,g)), ((1,l),(4,b),(5,e)),  
 ((2,g),(3,j),(4,l)), ((2,h),(3,g),(4,b)),  
 ((2,b),(3,m),(5,j)), ((2,h),(3,g),(5,e)) }



Connection graph of L<sub>2</sub>

Consistent Labeling:

{ (1,l), (2,h), (3,g), (4,b), (5,e) }

Figure 4.7: An example of problem decomposition based on a disconnected label set: part (b).

decompose the problem into two subproblems. Theorem 3 states the relationships between the solutions to the subproblems and the solutions to the original problem.

**Definition 6** Let  $R \subseteq (U \times L)^N$  be a unit-label constraint relation in  $CLP = (U, L, T, R)$ . If  $R$  can be decomposed into  $R_1$  and  $R_2$  with the following properties, then we denote  $R = R_1 \oplus R_2$ .

- (1) There exist three numbers  $k, N_1$ , and  $N_2$ , satisfying (a)  $k \neq 0$ , (b)  $k < N_1, N_2 < N$ ,  
(c)  $N_1 + N_2 = N + k$ .
- (2) For every  $(x'_1, \dots, x'_k, \dots, x'_{N_1}) \in R_1$ ,  
there exists  $(x'_1, \dots, x'_k, \dots, x'_{N_1}, x_{N_1+1}, \dots, x_N) \in R$ .
- (3) For every  $(x''_1, \dots, x''_k, x''_{k+1}, \dots, x''_{N_2}) \in R_2$ ,  
there exists  $(x''_1, \dots, x''_k, x_{k+1}, \dots, x_{N_1}, x''_{k+1}, \dots, x''_{N_2}) \in R$ .
- (4) For every  $(x_1, \dots, x_k, x_{k+1}, \dots, x_{N_1}, x_{N_1+1}, \dots, x_N) \in R$ ,  
there exists  $(x_1, \dots, x_k, x_{k+1}, \dots, x_{N_1}) \in R_1$ , and  
there exists  $(x_1, \dots, x_k, x_{N_1+1}, \dots, x_N) \in R_2$ .
- (5) For every pair of  $(x'_1, \dots, x'_k, x'_{k+1}, \dots, x'_{N_1}) \in R_1$ , and  
 $(x'_1, \dots, x'_k, x''_{k+1}, \dots, x''_{N_2}) \in R_2$ ,  
there exists  $(x'_1, \dots, x'_k, x'_{k+1}, \dots, x'_{N_1}, x''_{k+1}, \dots, x''_{N_2}) \in R$ .

Note that each variable (e.g.  $x'_1$ ) in tuples denotes a unit-label pair.

**Theorem 3** If  $R = R_1 \oplus R_2$ , it is true that

- (a)  $f$  is a consistent labeling of  $CLP = (U, L, T, R)$   
 $\Rightarrow f_{U_1}$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$  and  
 $f_{U_2}$  is a consistent labeling of  $CLP = (U_2, L_2, T_2, R_2)$
- (b)  $f'$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$  and  
 $f''$  is a consistent labeling of  $CLP = (U_2, L_2, T_2, R_2)$  and

$$f'_{U_1 \cap U_2} = f''_{U_1 \cap U_2}$$

$\Rightarrow f' \cup f''$  is a consistent labeling of  $CLP = (U, L, T, R)$

where,

$$L_1 = \{l \mid \text{there exists } r \in R_1 \text{ such that } l \text{ appearing in } r\}$$

$$L_2 = \{l \mid \text{there exists } r \in R_2 \text{ such that } l \text{ appearing in } r\}$$

$$T_1 = \{(u_1, \dots, u_N) \in T \mid \text{there exists } ((u_1, l_1), \dots, (u_N, l_N)) \in R_1\}$$

$$T_2 = \{(u_1, \dots, u_N) \in T \mid \text{there exists } ((u_1, l_1), \dots, (u_N, l_N)) \in R_2\}$$

$$U_1 = \{u \mid \text{there exists } t \in T_1 \text{ such that } u \text{ appearing in } t\}$$

$$U_2 = \{u \mid \text{there exists } t \in T_2 \text{ such that } u \text{ appearing in } t\}$$

Proof (a):

For every  $(u'_1, \dots, u'_{N_1}) \in T_1$ , there exists  $((u'_1, l'_1), \dots, (u'_{N_1}, l'_{N_1})) \in R_1$

by Definition 6 (2)

$$\exists((u'_1, l'_1), \dots, (u'_{N_1}, l'_{N_1}), (u_{N_1+1}, l_{N_1+1}), \dots, (u_N, l_N)) \in R$$

Since  $f$  is a consistent labeling of  $CLP = (U, L, T, R)$

$$\exists((u'_1, f(u'_1)), \dots, (u'_{N_1}, f(u'_{N_1})), (u_{N_1+1}, f(u_{N_1+1})), \dots, (u_N, f(u_N))) \in R$$

by Definition 6 (4)

$$\exists((u'_1, f(u'_1)), \dots, (u'_{N_1}, f(u'_{N_1}))) \in R_1$$

Since  $f_{U_1}$  is a subfunction of  $f$  on the domain  $U_1$ , we can rewrite the previous step as

$$\exists((u'_1, f_{U_1}(u'_1)), \dots, (u'_{N_1}, f_{U_1}(u'_{N_1}))) \in R_1$$

Therefore,  $f_{U_1}$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$

Similarly, we can prove  $f_{U_2}$  is a consistent labeling of  $CLP = (U_2, L_2, T_2, R_2)$

Proof (b):

For every  $(u_1, \dots, u_k, u_{k+1}, \dots, u_{N_1}, u_{N_1+1}, \dots, u_N) \in T$ ,

there exists  $((u_1, l_1), \dots, (u_k, l_k), (u_{k+1}, l_{k+1}), \dots, (u_{N_1}, l_{N_1}), (u_{N_1+1}, l_{N_1+1}), \dots, (u_N, l_N)) \in R$

by Definition 6 (4)

$\exists((u_1, l_1), \dots, (u_k, l_k), (u_{k+1}, l_{k+1}), \dots, (u_{N_1}, l_{N_1})) \in R_1$  and

$\exists((u_1, l_1), \dots, (u_k, l_k), (u_{N_1+1}, l_{N_1+1}), \dots, (u_N, l_N)) \in R_2$

Since  $f'$  is a consistent labeling of  $CLP = (U_1, L_1, T_1, R_1)$  and

$f''$  is a consistent labeling of  $CLP = (U_2, L_2, T_2, R_2)$ ,

$\exists((u_1, f'(u_1)), \dots, (u_k, f'(u_k)), (u_{k+1}, f'(u_{k+1})), \dots, (u_{N_1}, f'(u_{N_1}))) \in R_1$  and

$\exists((u_1, f''(u_1)), \dots, (u_k, f''(u_k)), (u_{N_1+1}, f''(u_{N_1+1})), \dots, (u_N, f''(u_N))) \in R_2$

Since  $f'_{U_1 \cap U_2} = f''_{U_1 \cap U_2}$ , we can define  $f = f' \cup f''$  and rewrite the previous step as

$\exists((u_1, f(u_1)), \dots, (u_k, f(u_k)), (u_{k+1}, f(u_{k+1})), \dots, (u_{N_1}, f(u_{N_1}))) \in R_1$  and

$\exists((u_1, f(u_1)), \dots, (u_k, f(u_k)), (u_{N_1+1}, f(u_{N_1+1})), \dots, (u_N, f(u_N))) \in R_2$

by Definition 6 (5)

$\exists((u_1, f(u_1)), \dots, (u_k, f(u_k)), (u_{k+1}, f(u_{k+1})), \dots, (u_{N_1}, f(u_{N_1})), (u_{N_1+1}, f(u_{N_1+1})), \dots, (u_N, f(u_N))) \in R$

Therefore,  $f = f' \cup f''$  is a consistent labeling of  $CLP = (U, L, T, R)$

Figure 4.8 and Figure 4.9 show an example illustrating Theorem 3. Part (a) gives a consistent labeling problem  $CLP = (U, L, T, R)$ . The unit-label constraint relation  $R$  is rewritten as a table shown at the upper right. After the table is put into a compact form, it is easy to see that the table can be decomposed into two smaller tables according to Definition 6. Each small table corresponds to a subproblem and their solutions are indicated at the bottom of part (b). Since there are multiple solutions, they are expressed in solution tables. If we take the intersection of the two solution tables, the result is identical to the solution table which is located at the upper right of part (b) and is obtained by solving the original problem.

CLP=(U, L, T, R)

U = { a, b, d, e }

L = { 1, 2, 3 }

T = { (e,a,b), (e,a,d), (d,b,a), (d,b,e) }

R = { ((e,1),(a,1),(b,1)), ((e,1),(a,1),(b,2)),  
 ((e,1),(a,1),(d,1)), ((e,1),(a,1),(d,2)),  
 ((e,1),(a,2),(b,1)), ((e,1),(a,2),(b,2)),  
 ((e,1),(a,2),(d,1)), ((e,1),(a,2),(d,2)),  
 ((e,1),(a,3),(b,1)), ((e,1),(a,3),(b,2)),  
 ((e,1),(a,3),(d,1)), ((e,1),(a,3),(d,2)),  
 ((d,1),(b,1),(a,1)), ((d,1),(b,1),(a,2)),  
 ((d,1),(b,1),(e,1)), ((d,1),(b,1),(e,2)),  
 ((d,1),(b,2),(a,1)), ((d,1),(b,2),(a,2)),  
 ((d,1),(b,2),(e,1)), ((d,1),(b,2),(e,2)) }

field 1	field 2	field 3
(e,1)	(a,1)	(b,1)
(e,1)	(a,1)	(b,2)
(e,1)	(a,1)	(d,1)
(e,1)	(a,1)	(d,2)
(e,1)	(a,2)	(b,1)
(e,1)	(a,2)	(b,2)
(e,1)	(a,2)	(d,1)
(e,1)	(a,2)	(d,2)
(e,1)	(a,3)	(b,1)
(e,1)	(a,3)	(b,2)
(e,1)	(a,3)	(d,1)
(e,1)	(a,3)	(d,2)
(d,1)	(b,1)	(e,1)
(d,1)	(b,1)	(e,2)
(d,1)	(b,1)	(a,1)
(d,1)	(b,1)	(a,2)
(d,1)	(b,2)	(e,1)
(d,1)	(b,2)	(e,2)
(d,1)	(b,2)	(a,1)
(d,1)	(b,2)	(a,2)

⇒

field 1	×	field 2	×	field 3
(e,1)		(a,1)		(b,1)
		(a,2)		(b,2)
		(a,3)		(d,1)
				(d,2)
(d,1)		(b,1)		(e,1)
		(b,2)		(e,2)
				(a,1)
				(a,2)

⇓

field 1	field 2	⊕	field 1	field 2
(e,1)	(a,1)		(e,1)	(b,1)
(e,1)	(a,2)		(e,1)	(b,2)
(e,1)	(a,3)		(e,1)	(d,1)
(d,1)	(b,1)		(e,1)	(d,2)
(d,1)	(b,2)		(d,1)	(e,1)
			(d,1)	(e,2)
			(d,1)	(a,1)
			(d,1)	(a,2)

Figure 4.8: An example of problem decomposition based on unit-label constraint relation: part (a).




Figure 4.9: An example of problem decomposition based on unit-label constraint relation: part (b).

## Chapter 5

# Locating Address Paragraphs on Envelopes

This chapter describes a method of using syntax for locating machine-printed destination addresses on letter mail. We have been researching on use of address understanding in address block location. Specifically, address understanding entails performing character recognition and address syntax analysis. The prominent address syntactic features, such as state, ZIP Code, street number, street suffix, and their derivatives, offer valuable information with respect to address block location. Their appearance not only reveals the site of an address region but also indicates where the address boundaries should be defined.

Figure 5.1 is a typical example where a destination address block is embedded in a complex environment on a machine-printed mail piece. In this case, several text blocks together with graphics are present on the mail piece and they pose a challenge for a system to locate the correct destination address block. Humans identify an address block by means of mixed knowledge. Best of all is the postal address syntax. A text block with address syntax distinguishes itself from non-address blocks. Therefore, it is attractive to bring character recognition and syntax analysis into an address block location system to help destination address block identification.






Figure 5.1: A complex letter mail piece.

## 5.1 Overview of the Method

The strategy of the proposed method is to search through the entire mail piece image for the text objects showing address syntactic features. It starts with producing connected components and applying character recognition on each of the character-sized components. Then word segmentation is carried out by grouping adjacent connected components. The syntactic processing at word level relies on a keyword matching algorithm. After comparing the input word against a dictionary, the keyword matching algorithm assigns each input word a syntactic tag. Since address block location can be formulated as a consistent labeling problem as described in Chapter 4, locating address paragraphs is equivalent to finding all consistent labelings. In cases where more than one consistent labeling and several address paragraphs are produced, a selection mechanism is activated to determine the ranking of the candidates. Finally, syntactic features are used in the postprocessing module to improve block segmentation on the top-ranked destination address paragraph.

More details about the method are provided in the following sections.

## 5.2 Preprocessing and Character Segmentation

The experimental system accepts grey scale images as its input. One image processing tool [59, 60], based on local adaptive thresholding, is used to convert a grey scale image to a binary image. The local adaptive thresholding first convolves an 8 x 8 filter kernel with a grey scale image. Based on a look up table, the convolution image is then thresholded to generate a binary image.

After the image has been converted to binary form, character segmentation is accomplished by producing connected components. Connected components are formed by grouping black pixels which are eight-connected together [50, 65]. For machine-printed text, one connected component is more or less likely corresponding to one character. We implemented a connected component labeling algorithm which used run-length encoding and a local equivalence table [65]. To simplify the computation of various tasks in our system, the connected component rectangles are used to represent the physical shape and location of their connected components. Hereafter, we will interchange connected components with connected component rectangles if no confusion occurs.

## 5.3 Spatial Information Map and its Application

One important task the system executes is the topological processing. The main functions of the topological processing is (1) organizing the primitive objects (characters) into a special data structure, called the spatial information map, for the convenience of data retrieval; (2) constructing the composite objects (words, lines, ...) from the primitive objects; (3) computing the spatial relationships between the text objects (characters, words, ...) to be used in the syntactic processing.

As mentioned in Chapter 3, the spatial information map is used to preserve the spatial relationships between text objects. This map with a grid-based data structure facilitates the computation of the geometric and topological features requested by the syntactic processing and other computational tasks. In the following, we describe the construction of the spatial information map and its application to skew correction.




Figure 5.2: An example of spatial information map obtained from an envelope.

### 5.3.1 Construction of Spatial Information Map

The spatial information map is constructed as follows. Let the length and the height of an image be  $L$  and  $H$ , respectively. An image (Figure 5.2) is evenly partitioned along both horizontal and vertical directions and is thus divided into a fixed number of rectangular cells. Each cell has an equal size of  $l$  by  $h$ . One possible choice is to use the average size of connected component rectangles as the cell size. There exists a linked list associated with every cell to record the information with respect to the occupying connected components. For each connected component with any portion of its bounding box appearing within one cell, the index of the connected component will be added into the linked list of that cell. As a result, a cell may be empty, containing just one connected component, or shared by more than one connected components. The spatial relationships between connected components

are thus embedded into these cells.

As easily seen from the spatial information map, locational information regarding individual connected components can be directly retrieved from the map. For example, given a connected component  $\alpha$ , what are its neighboring connected components within a distance of  $d$ ? Suppose the center of the connected component  $\alpha$  falls into a cell called  $j$ . An area surrounding  $j$  is then searched on the map and each cell in this area is checked. The size of the search area depends on the distance  $d$ . For non-empty cells, their occupying connected components are potentially close enough to the connected component  $\alpha$ . Finally, a measurement is performed to determine which occupying connected components are close to the connected component  $\alpha$  within a distance of  $d$ .

Many operations can be defined in a similar way on the spatial information map. Some of them are:

- (1) looking for all objects in a specified rectangular region;
- (2) computing the existence of alignments;
- (3) searching for objects in the neighborhood of a given object;
- (4) testing whether an object is isolated;
- (5) detecting if there is any large blank space on the left-hand (right-hand) side of an object.

One point to mention is that it is possible for a connected component to occupy more than one cell. In that case, its index is recorded into all linked lists of cells which the connected component overlaps. During a search in a specified region, duplication of connected component indices may be reported. This issue is resolved after the search by applying a sorting algorithm (e.g. quick sort) and then eliminating duplicated indices in sequence.

### 5.3.2 Skew Correction

The task of skew correction is to find the skewed text lines and rotate them back to the horizontal direction. This effort is one of the important preprocessings for the syntactic analysis. Three steps are taken in skew correction. The first step is to group together the collinear connected components into lines and compute their skew angles. The next step is to cluster the lines into blocks. The last step is to rotate the skewed blocks individually to the normal orientation. The spatial information map can be used in locating text lines. For a given connected component, its neighboring connected components are retrieved from its adjacent cells on the spatial information map. A grouping function needs to be defined in determining if two connected components should be merged into one line. The function variables may include horizontal distance, height similarity, and other geometric features. The skew angle of the collinear connected components is computed by fitting a straight line with least square error through the centroids of the connected components. Furthermore, another grouping function can be defined at line level to cluster lines into blocks with the same skew direction. The standard rotation transformation is finally applied on each block to counteract the skew.

## 5.4 Word Segmentation

The task of word segmentation is carried out by grouping horizontally neighboring connected components into words. This process makes use of the above-mentioned spatial information map. For a given connected component, its horizontally neighboring connected components can be retrieved from its adjacent cells. Depending on the gap between two connected components and some geometric properties, the decision can be made as to whether they should be grouped together.

Meanwhile, the parent-child relationships between words and their constituent connected

components are retained. Each word data structure records the indices of connected components belonging to that word. At the same time, each connected component data structure records the index of its parent. These relationships can be viewed as bi-directional links between words and their children (i.e. characters). Since the locational information of connected components is stored in a spatial information map, the locational information regarding words can also be derived from the map (Figure 5.3).




Figure 5.3: The relations between words, characters, and a spatial information map.

## 5.5 Character Recognition

Character recognition is currently performed at resolution of 100 ppi. It is a gradient-based feature and neural network based classification approach. Since this algorithm appeared to work well at higher resolution (300 ppi) in the Machine-Print Character Recognition project at CEDAR, the CEDAR Address Block Location (ABL) group explored the use of this algorithm at lower resolution. It is possible to switch to another algorithm if the new method is proven better.

The gradient-based feature approach utilizes the grey-level change in the intensity of various pixels to perform machine-printed character recognition. For each character image, a gradient map of the entire image is calculated. The gradient map depicts the gradient magnitude and direction of each pixel; in other words, it depicts the magnitude and direction of maximum change in grey-level intensity for each image point. The Sobel operator is used to calculate the gradient map of the image. Once the gradient map is obtained, the "character" image is partitioned along both horizontal and vertical directions and is thus divided into a fixed number ( $3 \times 3$ ) of rectangular cells. The gradient directions are also quantized into a fixed number,  $k = 16$ , of gradient angle bins and each bin covers a range of  $360/k$  gradient angles. Every gradient angle bin in each cell corresponds to one feature. Therefore, the total number of features is one hundred and forty four which is equal to the product of the number of vertical divisions, the number of horizontal divisions, and  $k$ . Note that each pixel in the "character" image can be assigned to an appropriate gradient angle bin in a cell according to its position and its quantized gradient direction. A feature is said to be present if the corresponding bin of that feature contains pixels which have a gradient magnitude greater than a threshold value. Otherwise, the feature is considered to be absent. The collection of these features is regarded as a feature vector, and the feature vector is to be fed into a neural network for character classification.

A multi-layer perceptron neural network (Figure 5.4) is employed for pattern classification. This feedforward neural network consists of 144 units in the input layer, 104 units in the hidden layer, and 64 units in the output layer. Given an input "character", the neural network generates a confidence value for each of sixty-four classes, including all upper and lower characters, ten digits, number sign, and comma. The class with the highest confidence value will be taken as the object output for the input "character". If the confidence value of the object output is lower than a threshold, the input "character" will be classified into the sixty-fifth class, i.e. the reject class.




Figure 5.4: A method of performing character recognition.

## 5.6 Keyword Matching

Once the results of character recognition and word segmentation are available, the syntactic features at word level can be extracted by keyword matching. A keyword matching tool is designed to process each input word and assign it a syntactic tag (e.g. state tag, numeral tag, street suffix tag, and so on). If the majority of the characters in an input word are digits, a numeral tag will be attached to that word. Otherwise, the keyword matching tool proceeds to match the input word against the keywords stored in a dictionary and labels it an appropriate tag when a match is found. For short words with 2, 3, or 4 characters, an exact match of the character recognition results and a keyword is required. For longer words, a variation of longest common subsequence algorithm is used to compare the input word against the keywords. A mismatch of one or more characters is allowed in the long word matching. If more than one keyword is acceptable, a ranking mechanism is activated to



determine the best matched word. However, if no keyword is close enough to be compatible with the input word, an unknown tag will be assigned.

The keyword dictionary is constructed in a special way to minimize the keyword matching process. The keywords are first sorted according to number of characters. The words of the same length constitute a partition of the dictionary. Words inside each partition are then arranged in lexicographical order. The advantage of making such an arrangement is that not every keyword needs to be compared with a given input word. Only keywords whose length approximates the length of the input word deserve matching consideration. As we know, it does not make too much sense to compare a two-character word with a ten-character word. Therefore, the search domain in the dictionary is reduced to a few continuous partitions, compared to the whole dictionary otherwise. To reduce the computation time further, a binary search is used to search a particular partition of the dictionary whenever exact matching is required.

So far, we have used the state tag, the numeral tag, and tags denoted for P.O. Box, street suffix, and title in the keyword dictionary as seen in Table 5.1. There are about 500 entries in the keyword dictionary. More keywords and syntactic tags can be added into the dictionary as the system is being developed.

Table 5.1: Syntactic tags.

syntactic tag	meaning
pw	P.O.
pi	box
ss	street suffix
sw	state word
tn	title
#	number
-	unknown

## 5.7 Locating Destination Address Paragraph

The problem of finding the clustering of address text is tackled by solving its equivalent consistent-labeling problem (see Chapter 4). Each solution to the consistent-labeling problem is a potential destination address paragraph. A selection process may be needed to pick up the best looking destination address among several candidates provided by the consistent labelings. If there is more than one address paragraph, the selection module classifies the paragraphs into groups based on the overlap of block regions and chooses the group close to the lower right corner on the mail piece. The address paragraph demonstrating the most syntactic features in that group will be favored as the top-ranked destination address.

## 5.8 Use of Address Syntax in Postprocessing

Another application of using address syntactic features is to improve destination address block segmentation. The preliminary address paragraph may not be perfect destination address block. It may lose part of address owing to insufficient syntactic information. Therefore, one operation, called block expansion, is necessary to enlarge the block boundaries and recover the lost address information. It is the presence or absence of the address syntactic features in the preliminary address paragraph which dictates how much the block expansion operation should be carried out.

In the event that all address syntactic features are detected, including title, street, and the critical information, no block expansion is actually needed. Otherwise, the block expansion operation is activated to recover the lost information. In particular, if both the street and the critical information are already known, the expansion operation will just merge title-like text onto the top of the current block. If the critical information alone is detectable, the expansion operation will look for the missing address text on the top region

of the critical information and merge them. However, if only the street syntactic feature is present, the expansion operation has to search the downward region to recover the plausible critical information and search the upward region to recover the title line. It should be noted that all of the geometric and topological computations on text objects utilize the spatial information map.

## 5.9 Experimental Results

The proposed system has been implemented for locating the destination address block on machine-printed letter mail. Since the experimental system accepted only mail pieces whose address syntax information could be detected, another system developed at CEDAR was conjoined for handling the reject images of the syntax-based system. A set of 1996 machine printed images had been used to evaluate the combined system performance. About 81% of the mail pieces were accepted by the experimental system and the success rate was 96.9%. The other address block location system, which did not use any recognition data, processed the rest 19% of the images and the success rate was 82.0%. As a result, the combined system performance was 94.1%. On the other hand, when acting alone on the whole image set, the success rate of the address block location system without using character recognition was 91.7%. The experiments showed that there was a net gain 2.4% in using character recognition (see Table 5.2). The complete failure analysis of the combined system performance on 1996 images is shown in Table 5.3.

Table 5.2: Address block location performance on 1996 images with and without character recognition.

	Success Images	Success Rate
with character recognition	1878	94.1%
without character recognition	1831	91.7%

Some experiments were also carried out to evaluate the top 3 candidate destination address blocks on the same image set. The system performance of the top N candidates

Table 5.3: Error analysis of the combined system performance on 1996 images

Block type	Number of Images	% of All Failures
Minor oversegmented address	43	36.4%
Person name/Firm name part/all missing	18	15.2%
Undersegmented address	14	11.9%
No address produced	10	8.5%
Other text picked	10	8.5%
Critical information part/all missing	8	6.8%
Oversegmented address picked	7	5.9%
Return address included	4	3.4%
Other errors	4	3.4%
Total	118	100.0%

is the success rate of at least one candidate destination address block among the top  $N$  choices being correct. Since the best version of address block location system was the one using character recognition, we investigated the performance of this address block location system on the top 3 candidates. As shown in Table 5.4, the success rate of the top candidate was 94.1%. The system performance increased to 96.1% and 96.3% for the top 2 and top 3 candidates, respectively.

Table 5.4: Address block location performance on 1996 testing images with character recognition.

Top candidate	Top 2 candidates	Top 3 candidates
94.1%	96.1%	96.3%

Two examples are provided to illustrate how to use character recognition and syntax to help locate the destination address block. One example is given in Figure 5.5 and Table 5.5. Figure 5.5 shows a test mail piece and the system final result. Table 5.5 shows the character recognition and keyword matching results for the candidate destination address block, where each word is labeled with either a syntactic tag or an unknown tag. Since address syntax is detected through recognition of street number, state name, and ZIP Code, the block on the bottom right of Figure 5.5 is identified as the destination address block. The other example is given in Figure 5.6 and Table 5.6, where the system was able to locate the correct destination address by using syntax information.




Figure 5.5: Address block location final result using character recognition.




Figure 5.6: Address block location final result using character recognition.

Table 5.5: Character recognition and keyword matching results.

L	A	N A P e O	S R e
(-)	(-)	(-)	(-)
9 7	S H E F F I E L D		
(#)	(-)		
8 U F F A L O	N Y	1 4 2 2 o	
(-)	(sw)	(#)	

Table 5.6: Character recognition and keyword matching results.

3 W A - o	6 2	
(-)	(#)	
P S Y C H I A T R I C	C - R	
(-)	(-)	
W D 0	F O R E S T	A V
(-)	(-)	(ss)
B U - F A L O	N Y	- 4 3 3 4 1 2 0 7
(-)	(sw)	(#)

## Chapter 6

# Location of Name and Address on Fax Cover Pages

### 6.1 Introduction

Documents transmitted through fax machines are received as images. Like many document images obtained from such sources as journals, maps, engineering drawings, etc., fax images are desirable to be converted to computer editable form. A fax cover page (Figure 6.1 to Figure 6.4) usually accompanies the documents being transmitted and it carries information regarding sender, recipient, comments, date, fax and phone numbers, etc. At present a fax machine needs to be attended by humans who read the fax cover page and then know who should receive the documents. It would be nice if this process can be automated by a document analysis system which functions as a mail routing system. The ideal system can understand the incoming fax cover page and know whom the documents should be sent to. This chapter reports our research as part of an effort to realize such a system and focuses on location of the recipient's name and address on fax cover pages [47]. The name and address regions will later be extracted from the image and sent to an address interpretation unit, which is beyond the scope of this thesis, for further processing.

SEP-06-1994 11:21 FROM CEDAR: (716) 645-6176 TO 251 P.01

<b>FACSIMILE TRANSMISSION</b>	
<b>To:</b> ENRIQUE MENDEZ 550 BUSTI AVE BUFFALO NY 14201	
<b>From:</b> DARLENE TINNELL 448 4 <sup>th</sup> ST. BUFFALO, NY 14201	
<b>Message:</b> COPY OF MY TESTIMONIAL Darlene.	
(sender's name here)	

TOTAL P.01

Figure 6.1: A fax cover page.



OCT-17-1994 18:35 FROM UNISOURCE OF WY, INC. TO 6456164-251 P.01

# UNISOURCE

Computers · Peripherals · Software

## Fax Transmission

Date: 10/17/94  
To: STEVE YOUNG  
of: CEDAR  
Fax Number: \_\_\_\_\_  
From: Christopher Braisted  
Account Manager  
Our Phone: (716) 634-8200  
Our Fax: (716) 634-3310

Ask about our



Energy Star Computers  
from EPS, Zaos,  
Gateway, and Infotell

No. of pages including cover page: 2

Comments: Steve,  
Please find following quote  
on Seagate drive. I spoke with our man  
on your fiber optic install. He has done it  
in the past, but would have to rent install  
equipment. He does however have supported  
sources which I will forward to you this  
afternoon when he gets to his desk. Thanks Steve  
Please call if you have any questions *Respectfully*  
*Chris*

Figure 6.2: A fax cover page.

DEC-05-1994 14:29 FROM CEDAR:(716) 645-6176 TO 251 P.01

GLEASON WORKS  
1000 University Avenue  
Rochester, NY 14892

FAX COVER SHEET

DATE: September 27, 1994 TIME: 9:40 AM  
TO: *Carroll Ballou* PHONE: 532-1456  
*505 Elmwood Ave. Genoa* FAX: 532-1458  
*Rochester, NY 14622*  
FROM: *Karen Ballou* PHONE: (716) 593-1966  
*300 Elmwood Ave.* FAX: (716) 593-1967  
*Rochester, NY 14613*  
RE: November Conference

NUMBER OF PAGES INCLUDING COVER SHEET: 1

Message

I have confirmed the System Manager's afternoon session with Tom Hager of Intergraph for November 17, 1994.

He will need the following equipment:

- Clipper workstation
- TD/Windows NT workstation
- Overhead display panel and screen
- Laser printer

Here is a description of Tom's session:

Tom Hager will continue and expand upon his Windows NT session from the June conference. The session will cover interoperability between CLIX and NT. He will also cover NT Advanced Server, and the concepts of NT Domain and Trusted Domain features of NT. Tom will also demonstrate plotting in a heterogeneous environment.

Remember that I will not be able to attend the November 17th conference, as I will be in Detroit. Andy Loconte should hold elections for System Manager Sig chairman for next year and introduce Tom.

TOTAL P.01

Figure 6.3: A fax cover page.

DEC-05-1994 14:37 FROM CEDAR:(716) 645-6176 TO 251 P.01

<p><b>THE WORLD BANK/IFC/MIGA PERSONNEL SERVICES &amp; COMPENSATION DEPARTMENT</b> 1818 H Street, N.W. Washington, D.C. 20433 U.S.A. Tel. No. (202) 477-1234 - FAX No. (202) 477-4548 Telex No. RCA 248423</p> <p><b>FACSIMILE TRANSMITTAL FORM</b></p>	
Date: October 13, 1994	Number of pages:
To: Paul Seminary 1183 Elmwood Ave Buffalo NY 14222 Fax Nos. 562-9344	From: Donald Blum 24 Cedar St, 2nd Fl Buffalo NY 14203 Tel. No. 543-2140
Subject/Comments: <i>Hold in a test fax.</i>	
If you experience any problems in receiving this transmission, please inform: at telephone number	

TOTAL P.01

Figure 6.4: A fax cover page.

## 6.2 Method

The proposed method uses a scheme (Figure 6.5) which strongly couples text recognition and block segmentation. Text recognition focuses on keyword identification. The system attempts to locate and recognize keywords which are data field indicators so as to figure out the positions of such keywords as "TO" and "COMPANY". The information regarding the positions of "TO" and "COMPANY" indicators is used as reference in block segmentation to segment out their associated data regions.

In the following we first present page orientation detection in Subsection 6.2.1. In Subsection 6.2.2, we elaborate on how to perform keyword recognition and locate recipient indicator (e.g. "TO") and address indicator (e.g. "COMPANY"). The segmentation of the recipient's name and address is described in Subsection 6.2.3.

### 6.2.1 Page Orientation Detection

An effort has been made to detect the orientation of an incoming fax cover page. Since it may happen that people accidentally transmit upside-down fax cover pages, our system should be able to handle those cases as well. We found a good feature for detecting the page orientation. This feature is based on connected component analysis on the local regions of colons (Figure 6.6). It was motivated by the following observation. In the normal page orientation, for a given colon there is a machine-printed character closely located on the left-hand side of the colon. On the other hand, the character (either machine-printed or handwritten) located on the right-hand side of the colon has a larger gap from the colon. Therefore, by examining the connected components in the left and the right neighborhood of colons, the system can obtain pieces of evidence regarding the page orientation. A majority vote is then taken among all colons to make the final decision. The pseudo algorithm is described as follows.





Figure 6.5: Fax address block location system design.

Connected component analysis on the local regions of colons:



$\alpha, \beta$  : connected components

$d1 < d2 \Rightarrow$  page orientation is normal

$d1 > d2 \Rightarrow$  page orientation is upside-down

$d1 = d2 \Rightarrow$  inconclusive

## F A X   C O V E R   S H E E T

DATE:	September 27, 1994	TIME:	9:40 AM
TO:	Janis Vandever 58 Trinity Pl A. Buffalo, NY 14201	PHONE:	
		FAX:	
FROM:	William Washington 10 7th St. Dpt 622 Buffalo, NY 14201	PHONE:	
		FAX:	
RE:	November Conference		

NUMBER OF PAGES INCLUDING COVER SHEET: 1

Fig: A subimage of a fax cover page

Figure 6.6: Page orientation detection.

For each colon  $i$ , do

begin

Define a rectangular region on the left-hand side of the colon  $i$ .

Search the region for the connected component  $\alpha$  which is closest to the colon  $i$ . Let the distance between the connected component  $\alpha$  and the colon  $i$  be  $d1$ . If no connected component exists in the rectangular region, set  $d1 = W$ , where  $W$  is the width of the page.

Define a rectangular region on the right-hand side of the colon  $i$ .

Search the region for the connected component  $\beta$  which is closest to the colon  $i$ . Let the distance between the connected component  $\beta$  and the colon  $i$  be  $d2$ . If no connected component exists in the rectangular region, set  $d2 = W$ , where  $W$  is the width of the page.

If  $d1 < d2$ , we say the evidence from the local region of the colon  $i$

supports the decision that the page orientation is normal;

else if  $d1 > d2$ , we say the evidence from the local region of the colon  $i$

supports the decision that the page is upside-down;

else we say the evidence is inconclusive.

end

The final result regarding the page orientation is based on a majority vote taken among all colons.

### 6.2.2 Location and Recognition of Keywords

The system uses the same technique as described in Chapter 5 to produce connected components and then group them into words. After selecting a set of candidate keywords, the system applies character recognition on their constituent components. A keyword matching module is used to compare the character recognition results of the candidate keywords against a lexicon. The subgoal is to find out the locations of recipient indicator (e.g. "TO") and address indicator (e.g. "COMPANY").

No attempt was made to read every word on the fax cover page. Instead, character recognition was applied only on restricted areas. Based on analysis of the geometric features and the spatial relationships extracted from connected components, a few candidate words were hypothesized as keywords. Character recognition was then performed on these candidate words to recognize their constituent components. The classifier for character recognition is a two-layer back propagation neural network using chaincode features.

One good feature used to locate the candidate keywords is the presence of colons. As we know, a keyword is usually followed by a colon. Since a colon is composed of a pair of two tiny components separated by a short vertical distance, the system recognizes colons by analyzing connected components based on their size and spatial relationship. For each recognized colon, the system uses its position as a reference point on the spatial information map (Figure 6.7) and searches for the keyword appearing on the left-hand side of the colon.

If it happens that the fax cover page does not have colons following keywords, the system uses another technique to find the locations of the candidate keywords. This technique uses the fact that a keyword normally has a large blank space on its left neighborhood. For each word the system checks the spatial information map and determines whether the word has an empty region adjacent on its left-hand side. Those words that satisfy the above criterion






Figure 6.7: An example of spatial information map obtained from a fax cover sheet.

will be considered as candidate keywords.

Table 6.1: Category Tags.

Category Tag	Keywords
Recipient	TO            ATTN            ATTENTION
Address	COMPANY    LOCATION    ADDRESS    OF
Sender	FROM            FR

In order to generate semantic information, a keyword matching module is employed to do word level processing. The function of keyword matching is to compare the character recognition results of each candidate word against a lexicon. The lexicon is of small size and contains interested keywords such as TO, ATTENTION, FROM, COMPANY, MESSAGE, PAGES, etc. The keyword matching module outputs a category tag or an unknown tag for each input word. Three types of category tags (Table 6.1), including recipient tag, address tag, and sender tag, are most useful for our current task. Examples of keywords associated

with a recipient tag are TO, ATTN, and ATTENTION. The sender tag is assigned to the keyword FROM or FR. Keywords such as COMPANY, LOCATION, ADDRESS, and OF, are given the address tag. The method of keyword matching is based on longest common subsequence algorithm [93].

### 6.2.3 Location of the Address Region

Fax cover pages may be classified into two categories. In the first category, the fax cover pages contain only recipient indicator, whose data field carries the recipient's name and address. In the second category, the fax cover pages contain both recipient and address indicators. The name and address are filled in the data fields of the recipient and address indicators respectively. Hereafter, we assume the fax cover page belongs to the first category and the goal is to locate the address region. The fax cover pages belonging to the second category are handled in a similar fashion.

**Preliminary location of the address region:** The position of the recipient indicator is used as the reference point marking the upper left corner of the address region. In addition, the keyword immediately below the recipient indicator is searched for on the spatial information map and its location is used to suggest the bottom boundary of the address. We may assume the right extent of the address is the right edge of the fax cover page if the fax cover page is in a one-column format. The colon information can tell the system whether the fax cover page is in a one-column or semi two-column format. On a semi two-column fax cover page (Figure 6.8), if there exists a colon on the right-hand side of the colon which follows the recipient indicator, the position of the keyword just before the right colon can be used as the temporary right boundary of the address.

**Refinement of the address region:** At this moment the system defines an address container with preliminary address boundaries. Underlines is one problem needing to be

DEC-05-1994 15:58 FROM CEDAR: (716) 645-6176 TO Z51 P.01

GLEASON WORKS  
1000 University Avenue  
Rochester, NY 14892

FAX COVER SHEET

DATE: September 27, 1994 TIME: 9:40 AM  
TO: *Janis Vandorst* PHONE:  
*56 Trinity PL A.* FAX:  
*Buffalo, NY 14201*  
FROM: *William Washington* PHONE:  
*10 7th St. Apt 602* FAX:  
RE: November Conference  
*Buffalo, NY 14201*

NUMBER OF PAGES INCLUDING COVER SHEET: 1

**Message**

I have confirmed the System Manager's afternoon session with Tom Hager of Intergraph for November 17, 1994.

He will need the following equipment:

- Clipper workstation
- TD/Windows NT workstation
- Overhead display panel and screen
- Laser printer

Here is a description of Tom's session:

Tom Hager will continue and expand upon his Windows NT session from the June conference. The session will cover interoperability between CLIX and NT. He will also cover NT Advanced Server, and the concepts of NT Domain and Trusted Domain features of NT. Tom will also demonstrate plotting in a heterogeneous environment.

Remember that I will not be able to attend the November 17th conference, as I will be in Detroit. Andy Loconte should hold elections for System Manager Sig chairman for next year and introduce Tom.

TOTAL P.01

Figure 6.8: A fax cover page.


dealt with during the refinement process. Some data regions are preprinted with underlines and it is often seen that handwriting touches or overlaps the underlines. The presence of underlines makes address refinement difficult because handwriting is connected to underlines. Therefore, an effort was made to remove underlines from the preliminary address region.

The technique to remove underlines includes two passes. The first pass is to detect the underline regions and the second pass is to clean up the underlines. In the first pass, the system scans every line in the address container subimage and records black streams which are longer than a threshold  $t_1$ . All pixels of the recorded black streams are then being horizontally projected. Each mode of the profile whose accumulating pixels are greater than a threshold  $t_2$  is deemed to be resulted from an underline. Therefore, the upper and lower boundaries of these modes define a set of strips across the address container subimage and each strip is called a detected underline region. In the second pass, the system scans every line in all detected underline regions and removes black streams whose length is longer than the threshold  $t_1$ .

After underlines are removed from the address container region, the system performs refinement on the boundaries of the container. In the following, we describe a method of improving segmentation on the top and the bottom boundaries of an address.


An example shown in Figure 6.9 is used to illustrate our method. Part (a) is the preliminary address region extracted from a fax cover page (Figure 6.8). The system first performs connected component labeling on this subimage. Part (b) is the set of connected components associated with black pixels in part (a). Note that some connected components have been removed such as those belonging to keywords and those with infinitesimal size. The system then proceeds to do line segmentation which is based on the horizontal projection of the connected component image.

TE: September 27, 1994  
Janis Vandever  
56 Trinity Pl A.  
Buffalo, NY 14201  
FM: William Washington




(a)

(b)



(c)



(d)

Janis Vandever  
56 Trinity Pl A.  
Buffalo, NY 14201

(e)

Figure 6.9: Locating the top and the bottom boundaries of an address.

The horizontal projection can be regarded as a one-dimensional function  $f(y)$  defined on the vertical  $y$ -axis. For a connected component with vertical extent from  $y_1$  to  $y_2$  and horizontal extent from  $x_1$  to  $x_2$ , it contributes to  $f(y)$  a weight equal to  $x_2 - x_1 + 1$  for every point  $y$  in the interval of  $y_1$  to  $y_2$ . Therefore, the function value  $f(y)$  at the point  $y$  is the sum of all weights contributed from connected components whose vertical extent covers the point  $y$ . Part (c) is the histogram of all connected components in part (b) and the contour of the histogram depicts the horizontal projection  $f(y)$ .

The histogram can be smoothed by applying an operator which averages the projection function values at neighboring points. An operator with a length of three points is adopted and part (d) shows the smoothed histogram. If the smoothed histogram is rotated counter-clockwise 90 degrees, it can be viewed as composed of mountain peaks and valleys. Line segmentation points are obtained by processing those peaks and valleys through the following three steps. First, find the positions of peaks and valleys in the smoothed histogram. Second, delete spurious peaks whose height and width are not prominent. Third, the remaining peaks give the line locations and their neighboring valleys are taken as the line segmentation points.

Part (d) indicates there are five prominent peaks corresponding to five lines. Because the first line and the last line have keywords on their left and are considered to be non-address material, those two lines are removed from part (a). Part (e) shows the remaining lines, which help the system determine the top and the bottom boundaries of the address.

### 6.3 Results

Our system handles two types of fax cover pages, machine-printing and handwriting. After fax cover pages are transmitted through a fax machine, the images captured for processing has resolutions of 200 PPI by 100 PPI in the horizontal and vertical directions. The cur-

rent system appeared to work slightly better on machined-printed fax cover pages than on handwritten ones. The success rates on the two different types of images were 82% versus 80%. This test was based on a sample set composed of 112 machined-printed images and 115 handwritten images. There were 43 different fax cover page formats in the data set. Two examples of locating the recipient's name and address on fax cover pages are given in Figure 6.10 and Figure 6.11. Table 6.2 and Table 6.3 are error analysis of address block location on handwritten and machined-printed fax cover pages.

Table 6.2: Error analysis of address block location on 115 handwritten fax cover pages.

Reason for failure	% of All Failures
Handwriting overlapping keywords	33%
Invalid data filling	28%
Undersegmentation	22%
Oversegmentation	11%
Keyword recognition error	6%
Total	100.0%

Table 6.3: Error analysis of address block location on 112 machine-printed fax cover pages.

Reason for failure	% of All Failures
Keyword location/recognition error	52%
Undersegmentation	16%
Oversegmentation	16%
Colon detection error	16%
Total	100.0%

OCT-03-1994 08:31 FROM CEDAR:(716) 645-6176 TO 251 P.01

**FAX**  
**TRANSMITTAL**

**To:** Jose Rivera  
248 Whitney Pl.  
Buffalo, NY 14201-1602.

**From:** O. J. McDuffie  
98 Sudbury Ln # A  
Williamsville, NY 14221.


**Message:** Copy of agreement enclosed.

TOTAL P.01

Figure 6.10: Location of the recipient's name and address on fax cover pages.



MAR-02-1995 14:25 FROM CEDAR: (716) 645-6176 TO 251 P.03



Rochester Postal Employees Credit Union

From: Costainrossnretr  
104 Maryland St.  
Buffalo NY 14201

FACSIMILE TRANSMISSION COVER SHEET

DATE: Feb, 13, 1995  
TO: Millie Casillias  
60 Ruspia Ave  
Buffalo NY 14215  
RE: \_\_\_\_\_  
\_\_\_\_\_

NO. OF PAGES 3 (including cover page)

Figure 6.11: Location of the recipient's name and address on fax cover pages.

## Chapter 7

# Conclusions

Locating address paragraphs on complex documents is an important problem in document image analysis. Automatic extraction and interpretation of addresses has useful applications in mail sorting, database compiling, fax routing, etc. Many methods have been proposed for address block location on mail pieces, and most of them used global geometric and topological features. However, their methods showed difficulties in locating destination addresses on machine-printed envelopes to achieve high success rate. In addition, their methods were not suitable for locating addresses on other type of documents such as fax cover pages and advertisements.

It was pointed out that address location was a problem of finding the logical or semantic boundaries of a particular type of paragraphs. Segmentation based only on geometric features often gave results regarding the physical edges of patterns, which might not correspond to the logical boundaries of the interested object. Our arguments were supported by studies in Cognitive Psychology. Their experiments showed that the segmentation of human visual processing was strongly influenced by the Gestalt principles. Since the Gestalt principles mainly involve geometric and topological features, they make humans see the physical edges of a scene. When the physical edges are not in accordance with the logical boundaries and become useless in understanding patterns, people fall back on recognition

and inference to find the logical boundaries. Furthermore, since addresses are products of a written language, their semantic boundaries are not visible to people who have no knowledge in the language. While building a document image analysis system to perform the task of address location, we should keep in mind that the nature of this task is to find the logical boundaries of address paragraphs.

This thesis provided a computational model for locating address paragraphs on complex documents. The model uses text recognition to derive locational information which facilitates address segmentation. Locational information can be extracted by two ways: (1) through detection of address syntax; (2) through the understanding of semantic constraints imposing on an address. The adoption of character recognition and keyword matching in the scheme opens the door to take advantage of the linguistic nature of address paragraphs and their environments.

Use of syntax in locating address paragraphs has been formalized in this thesis. With two address models being defined, address block location was formulated as a consistent labeling problem. We also showed some interesting results with regard to decomposing a consistent labeling problem into several subproblems based on its problem structure. The understanding of a problem's characteristics helps us design an efficient problem solver. This is especially important when a very large consistent labeling problem is being attempted to solve.

Two types of documents were used in our experiments. The first one was letter mail. We proposed an approach of using character recognition and syntax in locating address paragraphs on machine-printed envelopes. Performing character recognition at low resolution (100 PPI) was desirable for implementing a real-time system. In addition, an efficient keyword matching algorithm was designed. It matched input words against a dictionary of about 500 keywords and assigned a syntactic tag to each word segmented out from a mail

piece. These syntactic tags were subsequently used in the consistent labeling problem solver to detect the aggregation of address text. Furthermore, syntactic features extracted from keywords were used to improve segmentation on address boundaries. It was shown that our system had advantages over a system without using character recognition in locating destination address blocks.

The second kind of documents used in our research was fax cover pages. A document analysis system which understands the incoming fax cover sheets can serve as a mail routing system. This thesis reported our research on locating the recipient's name and address on fax cover sheets. Fax cover pages are one type of documents which have changeable layout, contain many objects of different nature, and possess compact contents. Our method used a scheme which strongly coupled text recognition and block segmentation and integrated them into a coherent framework. Recognition of keywords such as "TO" and "COMPANY" helps the system determine a preliminary address region. Meanwhile, the spatial information map was constructed to facilitate the task of locational analysis in word and block segmentation. Our system worked reasonably well on both machine-printed and handwritten fax cover pages, and it can be easily extended to locating other types of information.

In summary, this thesis has illustrated a novel approach to tackle address block location. The methodology is general and applicable to different types of documents (Appendix A). Our experimental systems showed good performance on machine-addressed letter mail and fax cover sheets.

## Appendix A

# Address Block Location on Advertisements

Advertisements are one type of complex documents which carry address information. Although our address block location system was not intentionally designed to process advertisements, we did some experiments to find out how our system worked on this type of document images. Five advertisements were taken from Yellow Pages for the test. Figure A.1 to Figure A.5 show the address block location results. There are three cases, including Figure A.1, Figure A.3, and Figure A.4, where minor oversegmentation results are produced. The address block location result in Figure A.2, regarded as oversegmentation, is a region containing both the address and lots of non-address material. Figure A.5 is an example of success.

Generally speaking, the system was able to include addresses into its final results but tended to incorporate more material than necessary. One reason was that the system was tuned to process letter mail pieces where most addresses had at least three lines of text. For those advertisements with a two-line address, the system was too aggressive in doing address segmentation.

**TRANSMISSION**  
**EXCHANGE**

FAMILY OWNED &  
OPERATED  
SINCE 1959

STANDARD & AUTOMATIC  
TRANSMISSION SPECIALISTS

ONE OF THE LARGEST SUPPLIERS OF MANUAL TRANSMISSIONS IN N.Y.

**EXPERTLY REBUILT PROFESSIONALLY INSTALLED**

- Autos • Trucks • Fleet Service Available • Front Wheel Drive Service • New - Used Parts • 4X4
- Towing Available • Automatics & Standard • Clutches & Transfer Cases • Foreign & Domestic
- Over 100 Rebuilt Transmissions In Stock • Same Day Service Upon Request
- Ask About Our Conditional Guarantee • Installed Or Sold Outright

**FREE ESTIMATES**

 333 Ridge Road  
Lackawanna, NY

**824-2600**

Figure A.1: Address block location result on an advertisement: minor oversegmentation.

**Magic Carpet Tours & Travel Ltd.**

Full Service Travel Agency  
- At No Cost To You! -

**CORPORATE & LEISURE TRAVEL**

- Disney • Cruises • Weekend Getaways
- Honeymoon Packages • Sporting Events
- Group Tours

Specializing In Group Tours And Senior Travel

1443 HERTEL AVE.  
BUFFALO, NY 14216

838-9800

FAX:  
(716) 838-9802

See Our Offer In the Coupon Section



Figure A.2: Address block location on result an advertisement: oversegmentation.

**MSC** **McMAHON**  
**SCALE CO. INC.**

*"Serving W.N.Y. for over 44 years"*

**SALES - SERVICE - RENTALS**  
**NEW & REBUILT COUNTING & WEIGHING SCALES**  
RICE LAKE WEIGHING SYSTEMS - WEIGH - TRONIX  
ELECTROSCALE - DIGI MATEX - A&D ENGINEERING  
EXACT WEIGHT - CONSOLIDATED CONTROLS  
ISHIDA, OHAUS, FLEX-WEIGH, MSI  
PRECISION LABORATORY BALANCES  
SERVICE & REPAIRS ON MOST MAKES  
EMERGENCY SERVICE 24 HOURS A DAY - 7 DAYS A WEEK

**873-6017** 1901 MILITARY RD  
KENMORE, NY 14217

Figure A.3: Address block location result on an advertisement: minor oversegmentation.



**AFFORDABLE**  
**MORTGAGEE CORPORATION**



**We're Available Anytime - Day Or Night**

<input type="checkbox"/> Easy Qualifying Programs	<input type="checkbox"/> Fixed & Adj. Rates	<input type="checkbox"/> No Point Loans
<input type="checkbox"/> Refinancing	<input type="checkbox"/> Conventional	<input type="checkbox"/> Investors Loans
<input type="checkbox"/> Quick Approvals	<input type="checkbox"/> FHA & VA Loans	<input type="checkbox"/> Branches Statewide

Call Anytime For  
Free Information  
& Qualification


Licensed Mortgage Banker  
NYS Banking Department


**633-3550**

475 International Dr.  
Williamsville, NY 14221

Figure A.4: Address block location result on an advertisement: minor oversegmentation.

**BUFFALO**  
**LIFT TRUCKS**  
NEW ◦ USED  
RENTAL ◦ LEASING  
PARTS ◦ SERVICE

**balkancar**   
EST. 1978 AMERICA



**Schaeff** INC.

**895-1035**

**75 LATHROP ST**  
**BUFFALO, NY**  
**14212**

**EMERGENCY SERVICE**  
**7 DAYS A WEEK**

Figure A.5: Address block location result on an advertisement: success.

# Bibliography

- [1] K. Abe and N. Sugita. Distances between strings of symbols-review and remarks. In *Proceedings of the International Conference on Pattern Recognition*, pages 172-174, 1982.
- [2] R. L. Allen and F. A. Kamangar. Pose space search for address block location in letter mail. In *Proceedings of USPS Advanced Technology Conference*, pages 1271-1282, 1992.
- [3] J. R. Anderson. *Cognitive Psychology and its Implications*. W. H. Freeman and Company, New York, 1990.
- [4] T. Antognini, L. Turnbaugh, and A. Lehar. An expert system for the location of destination address in mail of arbitrary complexity. In *Proceedings of USPS Advanced Technology Conference*, pages 279-293, 1988.
- [5] N. Bartneck. Knowledge-based address block finding using hybrid knowledge representation schemes. In *Proceedings of USPS Advanced Technology Conference*, pages 249-263, 1988.
- [6] A. Bergman, E. Bracha, P. G. Mulgaonkar, and T. Shaham. Advanced research in address block location. In *Proceedings of USPS Advanced Technology Conference*, pages 218-232, 1988.

- [7] K. L. Boyer and A. C. Kak. Symbolic stereo from structural descriptions. Technical Report TR-EE 86-12, School of Electrical Engineering, Purdue University, West Lafayette, Indiana, February, 1986.
- [8] R. Bozinovic and S. N. Srihari. A string correction algorithm for cursive script recognition. *IEEE Trans. Pattern Anal. Machine Intell.*, 4:655-663, 1982.
- [9] H. Bunke. String matching for structural pattern recognition. In H. Bunke and A. Sanfeliu, editors, *Syntactic and Structural Pattern Recognition: Theory and Applications*, pages 119-144. World Scientific, Singapore, 1990.
- [10] H. Bunke and A. Sanfeliu, editors. *Syntactic and Structural Pattern Recognition: Theory and Applications*. World Scientific, Singapore, 1990.
- [11] R. Casey, D. Ferguson, K. Mohiuddin, and E. Walach. Intelligent forms processing system. *Machine Vision and Applications*, 5:143-155, 1992.
- [12] R. G. Casey and K. Y. Wong. Document analysis systems and techniques. In R. Kasturi and T. Trivedi, editors, *Image Analysis Applications*, pages 1-35. Marcel Dekker, New York, 1990.
- [13] M. Caviglione, A. De Gaetano, and P. N. Scaiola. A knowledge-based vision system for address block location oriented to real-time implementation. In *Proceedings of USPS Advanced Technology Conference*, pages 687-704, 1988.
- [14] V-G. Christian and B. Dominique. Robust extraction of destination address block using a multi-level segmentation. In *Proceedings of USPS Advanced Technology Conference*, pages 1257-1270, 1992.
- [15] D. G. Corneil and C. C. Gotlieb. An efficient algorithm for graph isomorphism. *J. ACM.* 17:51-64. 1970.

- [16] Kenan Systems Corporation. *Mail Characteristics Study Findings*, volume 2, page 76. Kenan Systems Corporation, 1991.
- [17] P. B. Cullen, T. K. Ho, J. J. Hull, M. Prussak, and S. N. Srihari. Contextual analysis of machine printed addresses. In *Proceedings of the SPIE Conference on Machine Vision Application in Character Recognition and Industrial Inspection*, volume 1661, pages 257–268, 1992.
- [18] R. Dechter and J. Pearl. Tree clustering for constraint networks. *Artificial Intelligence*, 38:353–366, 1989.
- [19] D. Dori. Self-structural syntax-directed pattern recognition of dimensioning components in engineering drawings. In H. S. Baird, H. Bunke, and K. Yamamoto, editors, *Structured Document Image Analysis*, pages 356–384. Springer-Verlag, 1992.
- [20] A. C. Downton and C. G. Leedham. Preprocessing and presorting of envelope images for automatic sorting using ocr. *Pattern Recognition*, 23(4):347–362, 1990.
- [21] R. Dubes and A. K. Jain. Clustering methodologies in exploratory data analysis. In *Advances in Computers*, volume 19, pages 113–228. Academic Press, New York, 1980.
- [22] E. C. Freuder. Synthesizing constraint expression. *Communications of the ACM*, 21:958–966, 1978.
- [23] K. S. Fu. *Syntactic Pattern Recognition and Applications*. Prentice-Hall, Englewood Cliffs, N.J., 1982.
- [24] K. S. Fu. A step towards unification of syntactic and statistical pattern recognition. *IEEE Trans. Pattern Anal. Machine Intell.*, 5:200–205, 1983.
- [25] A. Gardin, Z. Bichri, and H. Pham Le. A real time address block location system for handwritten letter and flat mail. In *Proceedings of USPS Advanced Technology Conference*, pages 1221–1240, 1992.

- [26] R. C. Gonzalez and M. G. Thomason. *Syntactic Pattern Recognition*. Addison-Wesley, Reading, Massachusetts, 1978.
- [27] P. A. V. Hall and G. R. Dowling. Approximate string matching. *ACM Computing Surveys*, 12:381-402, 1980.
- [28] R. M. Haralick and G. Elliott. Increasing tree search efficiency for constraint satisfaction problems. *Artificial Intelligence*, 14:263-313, 1980.
- [29] R. M. Haralick and L. G. Shapiro. The consistent labeling problem: Part i. *IEEE Trans. Pattern Anal. Machine Intell.*, 1:173-184, 1979.
- [30] R. M. Haralick and L. G. Shapiro. The consistent labeling problem: Part ii. *IEEE Trans. Pattern Anal. Machine Intell.*, 2:193-203, 1980.
- [31] R. M. Haralick and L. G. Shapiro. *Computer and Robot Vision*, volume 2, pages 379-426. Addison-Wesley, New York, 1993.
- [32] A. K. Hrechak and J. A. McHugh. Automated fingerprint recognition using structural matching. *Pattern Recognition*, 23(8):893-904, 1990.
- [33] J. J. Hull. *A Computational Theory of Visual Word Recognition*. PhD thesis, State University of New York at Buffalo, 1988.
- [34] P. Ibrison et al. Chemical literature data extraction: The clide project. *Journal of Chemical Information and Computer Sciences*, 33:338-344, 1993.
- [35] S. Impedovo, I. Ottaviano, and S. Occhinegro. Optical character recognition - a survey. *International Journal of Pattern Recognition and Artificial Intelligence*, 5:1-24, 1991.

- [36] A. K. Jain and S. K. Bhattacharjee. Address block location on envelopes using gabor filters: Supervised method. In *Proceedings of the International Conference on Pattern Recognition*, pages 264–267, 1992.
- [37] A. K. Jain and Y. Chen. Address block location using color and texture analysis. *CVGIP: Image Understanding*, 60:179–190, 1994.
- [38] J. Jelinek, K. Schaper, and A. Patani. A knowledge-based image understanding system for address block location. In *Proceedings of USPS Advanced Technology Conference*, pages 264–278, 1988.
- [39] R. Kasturi et al. A system for interpretation of line drawings. *IEEE Trans. Pattern Anal. Machine Intell.*, 12:978–992, 1990.
- [40] J. T. Koljonen and F. R. Glickman. Comparative study of artificial intelligence techniques as applied to the location of address blocks on mail pieces. In *Proceedings of the SPIE Conference on Applications of Artificial Intelligence VII*, volume 1095, pages 489–502, 1989.
- [41] L. Lam and C. Y. Suen. Structural classification and relaxation matching of totally unconstrained handwritten zip-code numbers. *Pattern Recognition*, 21:19–31, 1988.
- [42] H.-J. Lee and M.-C. Lee. Understanding mathematical expressions in a printed document. In *Proceedings of Second International Conference on Document Analysis and Recognition*, pages 502–505, 1993.
- [43] A. F. Lehar, R. Gonsalves, J. Weaver, and L. Turnbaugh. Pattern recognition techniques for finding the address on letters and parcels. In *Proceedings of the SPIE Conference on Image Pattern Recognition: Algorithm Implementations, Techniques, and Technology*. volume 755, pages 132–140, 1987.

- [44] A. Levenshtein. Binary codes capable of correcting deletions, insertions, and reversals. *Sov. Phy. Dokl*, 10:707-710, 1966.
- [45] J. Lii, P. W. Palumbo, and S. N. Srihari. Address block location using character recognition and address syntax. In *Proceedings of Second International Conference on Document Analysis and Recognition*, pages 330-335, 1993.
- [46] J. Lii and S. N. Srihari. Use of character recognition and syntax in locating address paragraphs in complex documents. In *Proceedings of the International Conference on Pattern Recognition*, pages 374-376, 1994.
- [47] J. Lii and S. N. Srihari. Location of name and address on fax cover pages. In *Proceedings of Third International Conference on Document Analysis and Recognition*, 1995. Accepted.
- [48] S. Y. Lu. A tree to tree distance and its applications to tree analysis. *IEEE Trans. Pattern Anal. Machine Intell.*, 1:219-224, 1979.
- [49] S. Y. Lu. A tree matching algorithm based on node splitting and merging. *IEEE Trans. Pattern Anal. Machine Intell.*, 6:249-256, 1984.
- [50] R. Lumia, L. Shapiro, and O. Zuniga. A new connected components algorithm for virtual memory computers. *Computer Vision, Graphics, and Image Processing*, 22:287-300, 1983.
- [51] W. J. Masek and M. S. Paterson. A faster algorithm for computing string-edit distances. *Journal of Computer and System Sciences*, 20:18-31, 1980.
- [52] J. R. McDaniel and J. R. Balmuth. Kekule: Ocr - optical chemical (structure) recognition. *Journal of Chemical Information and Computer Sciences*, 32:373-378, 1992.



- [53] K. Mersereau, M. Kuhner, and D. Grieser. Hybrid techniques for postal address location. In *Proceedings of the SPIE Conference on Hybrid Image and Signal Processing*, volume 939, pages 132–139, 1988.
- [54] L. Miclet. *Structural Methods in Pattern recognition*. North-Oxford Academic, 1986.
- [55] M. T. Musavi et al. A vision-based method to automate map processing. *Pattern Recognition*, 21(4):319–326, 1988.
- [56] G. Nagy and S. Seth. Hierarchical representation of optically scanned documents. In *Proceedings of the International Conference on Pattern Recognition*, pages 347–349, 1984.
- [57] G. Nagy, S. Seth, and M. Viswanathan. A prototype document image analysis system for technical journals. *IEEE Computer*, 25(7):10–22, 1992.
- [58] J.-C. Oriot, D. Barba, and J.-C. Salome. Address block location method based on transition analysis approach: Design and evaluation on flat objects. In *Proceedings of First International Conference on Document Analysis and Recognition*, pages 665–673, 1991.
- [59] P. W. Palumbo, P. Swaminathan, and S. N. Srihari. Document image binarization: Comparison of techniques. In *Proceedings of the SPIE Conference on Digital Image Processing*, volume 697, pages 278–285, 1986.
- [60] P.W. Palumbo, S.N. Srihari, J. Soh, R. Sridhar, and V. Demjanenko. Postal address block location in real time. *IEEE Computer*, 25:34–42, 1992.
- [61] M. Parizeau and R. Plamondon. A comparative analysis of regional correlation, dynamic time warping, and skeletal tree matching for signature verification. *IEEE Trans. Pattern Anal. Machine Intell.*, 12:710–717, 1990.

- [62] T. Pavlidis and J. Zhou. Page segmentation by white streams. In *Proceedings of First International Conference on Document Analysis and Recognition*, pages 945–953, 1991.
- [63] J. Platt and R. Wolf. Convolutional neural networks for address block location. In *Proceedings of USPS Advanced Technology Conference*, pages 1283–1293, 1992.
- [64] M. Prussak and J. J. Hull. A multi-level pattern matching method for text image parsing. In *IEEE Conference on Artificial Intelligence Applications*, pages 183–189, 1991.
- [65] C. Ronse and P. A. Devijver. *Connected Components in Binary Images: The Detection Problem*. John Wiley, Letchworth, UK, 1984.
- [66] R. Fritson S. L. Taylor and J. A. Pastor. Extraction of data from preprinted forms. *Machine Vision and Applications*, 5:211–222, 1992.
- [67] A. Sanfeliu. Matching tree structures. In H. Bunke and A. Sanfeliu, editors, *Syntactic and Structural Pattern Recognition: Theory and Applications*, pages 145–178. World Scientific, Singapore, 1990.
- [68] A. Sanfeliu and K. S. Fu. A distance measure between attributed relational graphs for pattern recognition. *IEEE Trans. SMC*, 13:353–362, 1983.
- [69] R. J. Schalkoff. *Pattern Recognition: Statistical, Structural and Neural Approaches*. John Wiley & Sons, Inc., New York, 1992.
- [70] J. Schurmann et al. Document analysis - from pixels to contents. *Proceedings of the IEEE*, 80(7):1101–1119, 1992.
- [71] D. B. Searls and S. L. Taylor. Document image analysis using logic-grammar-based syntactic pattern recognition. In H. S. Baird, H. Bunke, and K. Yamamoto, editors, *Structured Document Image Analysis*, pages 520–545. Springer-Verlag, 1992.

- [72] S. M. Selkow. The tree to tree editing problem. *Information Processing Letters*, 6:184-186, 1977.
- [73] L. G. Shapiro and R. M. Haralick. A metric for comparing relational structures. *IEEE Trans. Pattern Anal. Machine Intell.*, 7:90-94, 1985.
- [74] L. G. Shapiro and R. M. Haralick. Matching relational structures using discrete relaxation. In H. Bunke and A. Sanfeliu, editors, *Syntactic and Structural Pattern Recognition: Theory and Applications*, pages 179-195. World Scientific, Singapore, 1990.
- [75] R. K. Srihari. *Extracting Visual Information from Text: Using Captions to Label Faces in Newspaper Photographs*. PhD thesis, State University of New York at Buffalo, 1992.
- [76] S. N. Srihari. Document image understanding. In *Proceedings of ACM-IEEE Fall Joint Computer Conference*, pages 87-96, 1986.
- [77] S. N. Srihari. Feature extraction for locating address blocks on mail pieces. In J. C. Simon, editor, *From Pixels to Features*, pages 261-273. Elsevier Science Pub., 1989.
- [78] S. N. Srihari, C.-H. Wang, P. W. Palumbo, and J. J. Hull. Recognizing address blocks on mail pieces: Specialized tools and problem-solving architecture. *AI Magazine*, 8(4):25-40, 1987.
- [79] S. Suzuki and T. Yamada. Maris: Map recognition input system. *Pattern Recognition*, 23(8):919-933, 1990.
- [80] T. W. Sze and Y. H. Yang. A simple contour matching algorithm. *IEEE Trans. Pattern Anal. Machine Intell.*, 3:676-678, 1981.
- [81] K. C. Tai. The tree to tree correction problem. *J. ACM*, 26:422-433, 1979.

- [82] E. Tanaka. A computing algorithm for the tree metric based on structure preserving mapping. *Trans. IECE*, E68:317-324, 1985.
- [83] E. Tanaka. A string correction method based on the context-dependent similarity. In G. Ferrate et al., editors, *Syntactic and Structural Pattern Recognition, NATO ASI Series*, pages 3-17. Springer, 1987.
- [84] Y. Y. Tang, C. Y. Suen, C. D. Yan, and M. Cheriet. Document analysis and understanding: A brief survey. In *Proceedings of First International Conference on Document Analysis and Recognition*, pages 17-30, 1991.
- [85] J. W. Thatcher. Tree automata: an informal survey. In A. V. Aho, editor, *Currents in the Theory of Computing*. Prentice-Hall, Englewood Cliffs, N.J., 1973.
- [86] W. H. Tsai and K. S. Fu. Attributed string matching with merging for shape recognition. *IEEE Trans. Pattern Anal. Machine Intell.*, 7:453-462, 1985.
- [87] E. Tsang. *Foundations of Constraint Satisfaction*, pages 1-29. Academic Press, New York, 1993.
- [88] J. R. Ullman. Parallel recognition of idealized line characters. *Kybernetik*, 2:221-226, 1965.
- [89] J. R. Ullman. Associating parts of patterns. *Information and Control*, 9:583-601, 1966.
- [90] C. Viard-Gaudin and D. Barba. Address block location method based on a multi-resolution approach. In *Proceedings of First International Conference on Document Analysis and Recognition*, pages 954-962, 1991.
- [91] M. Viswanathan. Analysis of scanned documents - a syntactic approach. In H. S. Baird, H. Bunke, and K. Yamamoto, editors, *Structured Document Image Analysis*, pages 115-136. Springer-Verlag, 1992.

- [92] G. Vosselman. *Relational Matching*. Springer-Verlag, Berlin, 1992.
- [93] R. A. Wagner and M. J. Fischer. The string-to-string correction problem. *J. ACM*, 21:168-173, 1974.
- [94] F. M. Wahl, K. Y. Wong, and R. G. Casey. Block segmentation and image extraction in mixed text/image document. *Computer Graphics and Image Processing*, 20:375-390, 1982.
- [95] D. L. Waltz. Understanding line drawings of scenes with shadows. In P. Winston, editor, *The Psychology of Computer Vision*, pages 19-92. McGraw-Hill, New York, 1970.
- [96] C.-H. Wang and S.N. Srihari. A framework for object recognition in a visually complex environment and its application to locating address blocks on mail pieces. *International Journal of Computer Vision*, 2:125-151, 1988.
- [97] D. Wang and S. N. Srihari. Classification of newspaper image blocks using texture analysis. *Computer Vision, Graphics, and Image Processing*, 47:327-352, 1989.
- [98] P. S. P. Wang and A. Gupta. An improved structural approach for automated recognition of handprinted characters. *International Journal of Pattern Recognition and Artificial Intelligence*, 5:97-121, 1991.
- [99] J. Wen, A. J. Baerveldt, and F. Ade. Location of address labels on postal parcels using neural networks based on multifeatures. In *Proceedings of International Conference on Industrial Electronics, Control and Instrumentation*, volume 2, pages 1480-1484, 1991.
- [100] R. Wilhelm. A modified tree to tree correction problem. *Information Processing Letters*, 12:127-132, 1981.

- [101] P-S. Yeh, S. Antoy, A. Litcher, and A. Rosenfeld. Address location on envelopes.  
*Pattern Recognition*, 20(2):213-227, 1987.