

Bank Check Recognition using Cross Validation between Legal and Courtesy Amounts

Gyeonghwan Kim and Venu Govindaraju

Center of Excellence for Document Analysis and Recognition (CEDAR)
Department of Computer Science
State University of New York at Buffalo
520 Lee Entrance
Amherst, New York 14228-2567
U. S. A.

Abstract

A bank check reading system using cross validation of both the legal and the courtesy amounts is presented in this paper. Some of the challenges posed by the task are (i) segmentation of the legal amount into words, (ii) location of boundaries between dollars and cents amounts, and (iii) high accuracy in terms of recognition performance. Word segmentation in the legal amount is a serious issue because of the nature of the data and patrons' writing habits which tend to clump the words together. We have developed a word segmentation algorithm based on the character segmentation results to address this issue. The list of possible amounts generated by the word segmentation hypotheses is used as lexicon for the courtesy amount recognition. The order of magnitude of the amount is estimated during legal amount recognition. We treat the courtesy amount as a numeral string and apply the same word recognition scheme as used for the legal amount.

Our approach to check recognition differs from traditional methods in two significant aspects: First, our emphasis on both the legal and the courtesy amounts is balanced. We use an accurate word recognizer which performs equally well on alpha words and digit strings. Second, our combination strategy is serial rather than the commonly used parallel method. Experimental results show that 43.8 % of check images are correctly read with an error rate of 0 %.

Keywords:

Bank check recognition, Handwriting recognition, Segmentation, Cross validation

1 Introduction

Reading unconstrained handwriting by the use of a computer program is a challenging task. Recent research in recognition of general handwritten text has revealed a number of complex problems.¹ Systems that read handwriting in constrained domains include address interpretation from mail pieces,² processing of census forms,^{3,4} processing of tax forms,⁵ and recognition of bank checks.^{6,7}

It is estimated that Americans write about 50 billion bank checks a year.⁸ The banks in Unites States therefore have to deal with processing many million checks everyday. The present protocol requires a bank employee to manually enter the check amount while a second employee verifies the entry. Recent advances in automated recognition of bank checks have attempted to minimize the manual effort involved.

Automation of bank check recognition has several salient aspects. Wide variations in handwriting style exist not only in terms of cursive or discrete but also in the manner in which amounts are represented. For example, “*one thousand and five hundred dollars*” and “*fifteen hundred dollars*” are different ways of representing the amount \$1,500. Moreover, the absence of constraints on the number of digits that can appear in the numeral amount and the need for high recognition performance^{6,9} compound the difficulty of the task. The one advantage that this application offers is the redundancy between the legal field (text) and the courtesy field (numeral) as they both convey the same information.¹⁰

Bank check recognition systems can be divided into two categories: (i) systems that read only one of the amounts – legal or courtesy,^{7,9,11–13} and (ii) systems that read both amounts and use a combination of the results.^{6,10} In this paper, we introduce a novel method for assigning the amount value of bank checks by using *both* the legal field and the courtesy field. Input to the system is a binary image of a bank check. Output is a list of choices for the value of the check. A lexicon driven handwritten word recognizer¹⁴ constitutes the main

engine of the system. Table 1 outlines the problems specific to the recognition of the legal and courtesy amounts.

Issues	Legal	Courtesy
Amount Extraction	○	○
Touching digits		○
Touching characters	○	
Decimal point detection		○
Presence of dollar and cent amounts in the same field	○	○

Table 1. Issues specifically related to reading each field

Organization of this paper is as follows. Section 2 presents an overview of bank check recognition and outlines general challenges of the task. Section 3 describes a strategy for locating word breaks in the legal amounts. Section 4 outlines the recognition procedures for the legal and courtesy amounts using a word recognizer and a cross validation method. Section 5 details our experiment results and error analysis. Summary of the work and some concluding remarks are presented in Section 6.

2 System overview

Fig. 1 illustrates the components of a typical bank check. The objective of the check reading system is to obtain the value of the check by reading the legal and courtesy amounts. In the subsequent sections we describe the main challenges of this task: (i) strategies for reading the two fields and cross validation of one field with the other, and (ii) segmentation of the text phrase in the legal amount field into its constituent words.

Fig. 2 illustrates the system architecture. The legal amount is segmented into words and recognized by a lexicon driven word recognizer.¹⁴ A list of hypothesized amounts is




Fig. 1. The components of a typical bank check

passed onto the courtesy amount recognizer. A numeral string word recognizer uses the list of hypotheses as its lexicon. It should be noted that the numeral string recognizer operates in exactly the same way as the legal phrase recognizer. In the final phase, the confidence of match from the recognition of both the fields is used to minimize error rate.

The legal and courtesy fields are located by an analysis of the check image. Cues, such as presence of two long horizontal lines near the legal amount, the dollar sign ('\$'), and a box near the courtesy amount are used.

Pre-processing includes noise removal, underline removal, box removal, slant correction, and converting the sub-images into chain code¹⁵ representation. Underline and box images are removed by the analysis of connected components represented by run-length coding.¹⁶ Handwriting strokes crossing the lines are saved. Small components (compared to the average stroke width) are regarded as noise and removed. Vertical strokes are extracted and the slant angle is estimated by averaging the angles of the strokes based on their vertical length. Slant correction is performed according to the estimated angle directly on the chain code representation.¹⁷

The legal amount is regarded as a text phrase of one or more words. Word segmentation is performed to divide the phrase into its constituent words which can be subsequently






Fig. 2. Check reading system architecture

recognized.

Detection of the boundary between dollar and cent amounts is another serious issue that must be addressed during the recognition of both fields. The different ways of representing amounts makes exact location of the boundaries difficult (Fig. 3).



(a)



(b)

Fig. 3. Examples of amounts in which it is difficult to locate the boundary between dollar and cent amounts: (a) courtesy amounts and (b) legal amounts

3 Segmentation

The goal of this module is to separate the words in the legal amount. The input to this module is the set of connected components forming the image of a legal amount. The output is a list of hypotheses, where each hypothesis is a partition of the original image into sub-images. A sub-image can correspond to exact words or sub-words.

3.1 Previous work in word segmentation

Most of the previous work on recognition of handwriting assumes that the words are already isolated or that isolation is trivial (*e.g.*, words are separated by large amounts of white space),¹⁸ or that words are written in boxes whose location is known.¹⁹ There are limited number of research reports that present a comprehensive discussion on this topic.^{20–22}


Deriving a computational methodology for word segmentation is quite complex. Humans use several cues to perform word separation: (i) spatial separation between components, (ii) presence of punctuation marks, (iii) presence of upper case characters following a string of lower case characters, (iv) transition between numerals and alpha characters, and (v) actual recognition of words prior to word separation. Among these, the cue of spatial separation is most commonly used.

Methods based on spatial cues alone have limited success for two reasons. First, handwriting does not necessarily adhere to the rule of placing larger gaps between words than between characters. Second, the perceived space between components cannot be easily estimated by a 1-dimensional scalar metric.

Word segmentation in the legal field of bank checks is made difficult by the nature of the data and patrons' writing habits. The number of words in the fields is not known and hard to predict. Furthermore, patrons tend to clump the words together so that additional words are not illegally squeezed (Fig. 4(a, b)). Also, a long horizontal line is drawn at the end of the amount to use up the entire space in the field (Fig. 4(c)).

3.2 Word segmentation based on character segmentation

In the following subsections we describe our approach to word segmentation method which uses spatial distance as well as a recognition engine. This method captures the author's writing style by characterizing the variation of spacing between adjacent characters as a



(a)



(b)



(c)

Fig. 4. Examples of legal amount make segmentation difficult: (a - b) not enough spaces between words, and (c) long horizontal line at the end of the field

function of the corresponding characters themselves. The notion of expecting greater space between characters with leading or trailing ligature is encoded into the segmentation scheme. Furthermore, we make the additional assumption that character segments must have at least one significant vertical stroke, a fair assumption given the structure of the English alphabet.

Our approach has proved to be efficient and powerful in the application of bank checks mainly for the following reasons: (i) size of the lexicon is small, (ii) the character segmentation is the necessary step for word recognition, and (iii) word recognition is used to drive the word segmentation process.

3.2.1 Character segmentation

Consider the legal amount image of Fig. 5(a). The image is converted into a contour representation and the slant is estimated and corrected. A long horizontal stroke at the end of the amount (which is drawn to use up the entire space in the amount field) hinders the

extracting of information of the author's writing style in terms of spacing between characters. The stroke is removed based on the density of components obtained by computing the ratio between the number of contour pixels and the length of the components. The character segmentation algorithm¹⁷ segments the image into characters and sub-characters (Fig. 5(b)).




Fig. 5. Word segmentation (based on character segmentation): (a) original input image, (b) character segmentation result after slant correction, (c) centerline of each segment after merging, and (d) word segmentation result

Two reference lines are defined: *base line* and *middle line*. The base line is the best-fit line of concavities in the lower contour. The middle line is the best-fit line of y-coordinates of the center of mass of each character segment. Based on the two reference lines, segments are examined. Rules are developed to determine which segments can be merged. Fig. 5(c)

shows bounding boxes after the merge.

A vertical line is located based on the distribution of pixels inside the box. The intervals between two adjacent boxes characterize the author’s writing style in terms of inter-character and inter-word spacing. The intervals are normalized, and average and standard deviation are computed based on which word gaps are defined (Fig. 5(d)). The letter “*d*” in the word “*hundred*”, which is classified as a segment, is eventually combined with the word “*hundred*” during the recognition phase.


one	two	three	four	five
six	seven	eight	nine	ten
eleven	twelve	thirteen	fourteen	fifteen
sixteen	seventeen	eighteen	nineteen	twenty
thirty	forty	fifty	sixty	seventy
eighty	ninety	hundred	thousand	dollars
dollar	and	only		

Table 2. Lexicon entries used for the recognition of the legal amount

Word segments are submitted to a word recognizer along with the lexicon shown in Table 2 and recognition results are collected as shown in Fig. 6(b). The numbers in left and top side of the figure correspond to the segment numbers of Fig. 6(a), and define the beginning and ending segment number of combined segments, respectively. For example, a block at row position 1 and column position 2 represents the recognition result obtained by submitting to a word recognizer a combination of segments one and two which in turn correspond to the first and the second parts of the word ‘*hundred*’. Matching confidences are used for determining the global matching score for each meaningful amount.

3.2.2 Word segmentation

Exhaustive search of all possible amounts that can be derived from the recognition results minimizes the risk of missing the true word in the list. However, this increases the size of



	0	1	2	3	4	5	6	7
0	3.6: three 4.1: five 5.1: four 5.1: one 5.4: nine	9.0: thousand 6.0: thirteen 6.0: fourteen 6.1: twelve 6.2: nineteen	9.0: thousand 6.1: fourteen 6.1: thirteen 6.2: nineteen 6.3: hundred	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen
1		4.8: nine 5.1: hundred 5.2: dollars 5.3: eleven 5.6: thirty	4.1: hundred 4.7: dollars 4.9: eleven 5.0: thousand 5.2: seven	6.6: nineteen 6.6: seventeen 7.1: thirteen 7.1: thousand 7.2: eighteen	9.0: seventeen 9.0: dollar 9.0: and 9.0: eight 9.0: dollars	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen
2			9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	5.2: twenty 5.5: seventy 6.1: ninety 6.2: eighty 6.6: sixteen	6.6: seventeen 7.3: nineteen 7.3: eighteen 7.3: fourteen 7.6: thousand	6.7: seventeen 7.4: eighteen 7.4: fourteen 7.7: nineteen 7.8: thousand	9.0: seventeen 9.0: fourteen 9.0: thousand 9.0: dollars 9.0: dollar	9.0: seventeen 9.0: dollar 9.0: and 9.0: eight 9.0: dollars
3				4.8: twenty 6.0: ninety 6.1: seventy 6.2: forty 6.4: thirteen	7.0: seventy 7.0: seventeen 7.0: fourteen 7.1: nineteen 7.2: thousand	7.2: seventeen 7.2: fourteen 7.5: nineteen 7.6: thousand 7.6: thirteen	8.1: seventeen 9.0: fourteen 9.0: nineteen 9.0: thirteen 9.0: thousand	9.0: seventeen 9.0: dollar 9.0: and 9.0: eight 9.0: dollars
4					5.7: sixty 6.4: forty 6.5: fifty 6.6: nine 7.2: only	7.1: sixteen 7.4: sixty 7.4: eight 7.5: ninety 7.5: seven	7.1: nineteen 7.4: eighteen 7.5: sixteen 7.5: fifteen 7.6: thirteen	7.2: nineteen 7.6: eighteen 7.7: fifteen 7.7: seventeen 7.8: sixteen
5						9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen	8.0: two 8.1: dollar 8.2: thirty 8.2: forty 8.2: three	7.5: dollars 7.6: fifty 7.7: dollar 7.7: thirty 7.7: twelve
6							7.2: six 9.0: ten 9.0: one 9.0: and 9.0: two	6.9: six 6.9: two 7.2: five 7.3: one 7.5: sixty
7								9.0: and 9.0: dollar 9.0: dollars 9.0: eight 9.0: eighteen

(b)

Fig. 6. Recognition of the segments: (a) word segmentation result and (b) recognition results of the segments. The number before each word represents the matching distance. (A smaller value indicates a better match and 9.0 means no matching was performed.)

the lexicon processed by the courtesy amount recognition. Following heuristics are used to determine which results are to be used to form a list as the lexicon to the subsequent stage of courtesy amount recognition (boxes in Fig. 6(b)). The decision is made based on only the confidence of the top choice.

1. If the distance score is less than 3.0 (very high confidence) then select that column alone from the corresponding row.
2. If the difference of confidences of the best and the second best columns is within 20% of the best one select both columns (*e.g.*, the second row in the figure).
3. If the difference in step 2 is greater than 20% then select only the best column (*e.g.*, the first row in the figure).
4. Groups with very low confidence (9.0 in our scale) are ignored in the selection.

Based on the above rules, only a few strings are hypothesized. It should be noted that we do not allow an overlap between two adjacent segments during the generation of hypotheses. We obtained the following 4 hypothesized strings for the example illustrated in Fig. 6.

1.

(0,0): <i>Three</i>

(1,2): <i>hundred</i>

(3,3): <i>twenty</i>

(4,4): <i>nine</i>

(5,7): <i>£80</i>

2.

(0,0): <i>Three</i>

(1,2): <i>hundred</i>

(3,3): <i>twenty</i>

(4,4): <i>nine</i>

(5,6): <i>£8</i>

3.

(0,0): <i>Three</i>

(1,1): <i>hundre</i>

(2,3): <i>dtwenty</i>

(4,4): <i>nine</i>

(5,7): <i>£80</i>

4.

(0,0): <i>Three</i>

(1,1): <i>hundre</i>

(2,3): <i>dtwenty</i>

(4,4): <i>nine</i>

(5,6): <i>£8</i>

4 Recognition of Amounts

Our approach to check amount recognition differs from traditional methods in two significant ways. First, our emphasis on both the legal amount and the courtesy amount is balanced.

Previous approaches have largely focused on courtesy amount alone because of the greater reliability of recognizing numerals. However, we have developed an accurate word recognizer which performs equally well on alpha words and digit strings.¹⁴ Second, our combination strategy is serial rather than the more commonly used parallel methods. The recognition engine first process the legal amount and outputs a list of hypotheses which are submitted to the courtesy amount recognizer as a lexicon. This strategy of serial combination using a single word recognition engine, we believe, is unique to our methodology to check recognition.

4.1 Word recognizer background

Our lexicon driven handwritten word recognition algorithm is based on dynamic programming and has been described in detail elsewhere.¹⁴ In the matching procedure of the algorithm, comparisons between feature vectors of several possible combinations of segments and reference feature vectors of codewords are made to find the best match. Since codewords are trained at the character level and a character can be composed of up to four segments (based on our character segmentation criteria), a segment or a combination of segments is compared to the codewords of reference characters within a permissible window. For each match, the minimum distance value of each comparison is retained and the best path is searched.

In the training phase, segmentation statistics of each character are obtained. The segmentation statistics represent the possible ways in which a training character can be split into segments.²³ We use the statistics to define the size of the matching window.

To minimize the computational complexity, which is serious issue in this type of approach, we take the advantage of the word recognizer in many aspects. For each entry, the number of characters and the maximum number of segments allowed (computed based on the segmentation statistics obtained during the training phase) are compared with the number of character segments in the word segment before the match is performed. Eq. (1) shows a way of minimizing the computational complexity using the information obtained during the

training phase.

$$\begin{aligned}
max_seg &= \sum_{j=0}^{N_c(i)-1} dur(lex_entry[j]) \\
&\text{if (} num_seg_of_word > max_seg \text{) reject;} \\
&\text{else continue;}
\end{aligned} \tag{1}$$

$N_c(i)$ represents the number of characters in i -th entry in the lexicon, $lex_entry[\cdot]$ represents character string of the lexicon entry, $dur(\cdot)$ returns variable duration of a character,^{14,24} and $num_seg_of_word$ is the number of segments in a word obtained by the character segmentation algorithm. If a case is reject by Eq. (1), the match is skipped and the lowest confidence value is assigned (*e.g.*, 9.0 in blocks (0,3), (0,4), ..., (0,7), (1,5) in the Fig. 6(b)).

Furthermore, if a part of the word segment has been compared with a particular character in a lexicon entry, the same comparison against the same character is avoided (or minimized) by saving the matching results. For example, if the lexicon entry “*two*” has been compared to the word segment “*three*”, a part of computation is not duplicated when the entry “*three*” is compared to the word segment because the character “*t*” in the first position is common. It has been proven that the statistical information can be used to improve recognition accuracy as well as speed.²⁴

Character segments obtained in the early stage of word segmentation are used once again in the recognition phase.

4.2 Legal amount recognition

The recognition results of word segments collected from Fig. 6 are shown in a lattice in Fig. 7. The lattice is traversed, and meaningful *dollar* amounts are generated. We use a transition table to denote the legal bigram transitions and an exhaustive tree search algorithm to determine all possible dollar amounts. In Fig. 7, a subset of the possible paths are indicated.

Some example dollar amounts generated by the paths are: “*three hundred twenty nine*”, “*three hundred ninety nine*”, “*five hundred twenty nine*”, and “*five hundred ninety nine*”.




Fig. 7. Recognition results of word segments for a hypothesis form a lattice

In addition to generating the possible paths, we also generate prefixes of valid legal amounts (for example, the amount “*three*” in “*three hundred*” is a prefix and considered valid outputs). The reason for including the prefixes is that we do not know the exact boundaries of the dollar amount in the image. Thus in certain cases, the sub-images corresponding to the cents part are recognized as valid words, and the longest valid path through the lattice may not be correct.

We keep a record of occurrences of words during the traversing to estimate the order of magnitude of the amount. Six bit flags are assigned for this purpose as shown in Fig. 8. Based on the recognized words from the legal amounts, corresponding flags are set. Only the top choice of each segment(s) with high confidence (less than 6.0 in our scale) is considered while setting the flags. In our example, “*three*” set the flag **S1** which means a single digit is in the first position. Next possible transition to “*hundred*” sets the flag **H**. For all hypothesized amounts, this process is repeated and saved along with the amount. Two types of flags are provided for the single and the double digits to identify whether it is detected in the first position of the legal amount. Rules for interpreting the flags are explained in the following

section. The confidence in recognition of a dollar amount is computed as the average of the recognition confidences of each word in the legal field. The list of amounts along with the confidences and flags is then submitted to the courtesy amount recognizer as the lexicon.




Fig. 8. Flags for estimating the order of magnitude of the legal amount

4.3 Courtesy amount recognition

The list of amounts recognized from the legal amount are converted into the corresponding digit strings and used as lexicon entries for courtesy amount recognition. The alpha character segmentation algorithm applied to the legal amount is applied to handle touching digits as well. Therefore a segment obtained by the segmenter can be a digit or a part of a digit. Since we do not attempt to locate the boundary between dollar and cents amount (in this paper), the combined segments are submitted to the recognizer by adding one character segment at a time. Fig. 9 shows the matching results between segment(s) against the lexicon entries. Top two choices from each match are saved for the purpose of cross validation.

4.4 Cross validation between the legal and courtesy amounts

Based on the recognition results of both amounts using the methods described above, we try to solve the cross validation problem. While estimating the number of digits in the check




Fig. 9. Matching between amount candidates from the legal amount recognition and segments in the courtesy amount

amount, the legal amount is more tractable than the courtesy amount because of the fact that components of the legal amount contain the information both implicitly and explicitly. For example, the words “*hundred*” and “*thousand*” provide the information explicitly.

The flags saved during the phase of parsing the legal amount are used for determining the number of digits. First, the lexicon for the courtesy amount recognition is sorted based on the confidence and then the flags of top N (10 in our case) choices are examined. The top N choices reflect the characteristics of the amount in terms of the number of digits. N is chosen depending on the number of word segmentation hypotheses and the number of words per segment involved in the amount generation. Flags for all N amounts are logically *OR*ed and the result is analyzed based on the definition of each flag. Table 3 shows how the flags are interpreted. The 10 choices from the legal amount recognition result in our example are listed below:

rank	amount	confidence	flags (hex)
0	3	3.5851	10
1	300	3.8606	14
2	5	4.1358	0
3	500	4.1360	4
4	320	4.1695	16
5	3000	4.3170	10
6	520	4.3531	6
7	3020	4.4738	12
8	390	4.5613	14
9	5000	4.5923	0

After performing the *OR* operation the flags we obtain 16 in hexadecimal number as the final flags. Although, the true value (329) is not present in the list, the final flags imply: (i) there should be keyword “*hundred*” (**H** is set), and (ii) single digit number is placed at the first position of the amount (**S1** is set).

Strict rules are applied in the interpretation of the flags. If there is any indication of confusion in terms of estimating the number of digits, the image is rejected. As we can see in the example, the role of flags **T** and **H** is crucial. Let us assume that the combined segment “*hundred*” is recognized as the second choice and the **H** flag is not set. The result flags after *OR*-operation will be 12 instead of 16. Based on the Table 3 the case is rejected. As an another example, consider the true amount \$300 and that only the flag **S1** is set by recognition of “*hundred*” as the second choice in the position. In the courtesy amount recognition, there is a possibility for both 3 and 300 as top choices in each digit position. Therefore, in this case (*i.e.*, only the flag **S1** or **D1** is set) we examine the top choices in the corresponding digit number to see if following two digits are 0s. If the following two are 0s we reject the case since the flag **H** is not set and there is a confusion between 3 and 300.

Once the number of digits is estimated, the following three items are used to finalize the amount: (i) number of digits estimated, (ii) confidence values of top two choices of the courtesy amount consistent with the number of estimated digits, and (iii) confidence of the legal amount which is selected as top choice in the above step (ii).

flags	no. of digits	examples
XX1XXX	4 or 5	fifteen thousand, three thousand
011XXX	4	three thousand
101XXX	5	fifteen thousand
001XXX	4 or 5	<i>see note below</i>
XXX1XX	3 or 4	fifteen hundred, three hundred
01X1XX	3	three hundred
10X1XX	4	fifteen hundred
00X1XX	4	<i>see note below</i>
010000	1	three
10000X	2	fifteen
11000X	1 or 2	<i>see note below</i>
others	reject	

Table 3. Interpretation of the flags used for estimating number of digits in the amount. **note:** confidence values of the top choices are also examined for the amounts with questionable number of digits

If the top choice of the courtesy amount has high confidence the corresponding legal amount with reasonable confidence is accepted. On the other hand, if the confidence of the top choice of courtesy amount is marginal but the confidence of the corresponding legal amount is high, then difference between the top two choices of the courtesy amounts is examined. If the distance is big enough to separate them the image is accepted.

5 Experiments and Results

Because bank checks have confidential information, such as names, address, and account numbers, we were unable to use real bank checks. Instead, as part of our data collection effort we artificially created blank copies of checks (Fig. 1) and requested students and employees in the State University of New York at Buffalo to fill out the legal amount and courtesy amount with imaginary numbers. 235 check images were collected from 91 participants.

No image was rejected by visual inspection. We expected our system to properly reject inconsistent checks (legal and courtesy amounts do not match).

The word recognizer was trained on data from addresses in mail pieces. To provide reference feature vectors to the matching procedure, a codebook was constructed. The codewords are trained using 20,529 character images extracted from handwritten images of city names.

5.1 Segmentation

Performance of the word segmentation algorithm was measured using the recognition results of the legal amount. We applied the word segmentation algorithm explained in Section 4 and the list of amount candidates was examined to see whether the true value was present. 80.0% of cases contained the true amount in the list. Average size of the list was 107.

5.2 Recognition

The 235 check images were submitted to the system. Some of them have inconsistency in the amounts, unexpected amounts (*e.g.*, zero dollar), and very poor image quality. In cross validation phase of both amounts, there are two steps: Step 1 is about estimating the number of digits in the legal amount. In step 2 the confidence values of the legal and courtesy amounts, and distance between the top two choices of the courtesy amount are used.

Table 4 shows the performance of each step. Among 183 images accepted in step 1, 132 cases contain the true amount in the lexicon for the courtesy amount recognition. Step 2 is expected to reject the cases which do not contain true amounts based on the confidences.

Because of the nature of the application, we allowed a strict error rate in the experiments. Lower half of Table 4 shows the performance of our system for two different error rates by changing the thresholds applied in the step 2.

step 1	accept	reject
	183	132
	(77.9 %)	(22.1 %)
step 2	error rate	acceptance rate
	0.0 %	43.8 % (103)
	1.8 %	47.2 % (111)

Table 4. Recognition performance

We made analysis for the 29 cases which have true amounts after the legal amount recognition but rejected in the cross validation (Table 5).

source	instances
low confidence of the legal amount recognition	10
low confidence of the courtesy amount recognition	20
not enough gaps between two top choices	4

Table 5. Sources of the rejection

Fig. 10 shows some examples of amounts processed by our system indicating that we can handle various writing styles (Fig. 10 (a - d)), poor quality (Fig. 10 (e)), incorrect syntax (Fig. 10 (f)), unexpected format (Fig. 10 (g)), and word segmentation error (Fig. 10 (h)).

6 Summary

In this paper, we have introduced a strategy for recognition of bank check amounts. A word segmentation algorithm (driven by recognition) was designed to overcome the problem of separating words in the legal amount field. The characteristics of the word recognizer we have developed and the small size of the lexicon make the segmentation process efficient.

Two hundred and thirty five $\frac{67}{100}$ 235.67
(a)

One hundred Twenty. and $\frac{50}{100}$ 120.50
(b)

Two Hundred Fifty Six & $\frac{16}{100}$ 256.16
(c)

One hundred seventeen and $\frac{85}{100}$ — 117.~~85~~
(d)

one thousand dollars and $\frac{62}{100}$ 1000.00
(e)

Seventy eighty and $\frac{21}{100}$ 78,21
(f)

Two thousand Two hundred
and twenty nine 2229.00
(g)

Three hundred twenty six and $\frac{23}{100}$ 326 23
(h)

Fig. 10. Examples of amounts images : (a - d) correctly recognized and (e - h) rejected cases

Based on top choice confidences, a few word segmentation hypotheses are made. The order of magnitude of the amounts are estimated from the legal amount and forms the first step of the cross validation. In the second step, simple rules, based on confidence values of both amount fields and the distance between top two choices, are applied to reject inconsistent cases. In the experiment, we can correctly read 43.8 % of check images with 0 % error rate.

Acknowledgments

The authors would like to thank Uma Mahadevan, CEDAR, for providing the tree search code presented in Section 4 and the discussion on word segmentation issues. Furthermore, Uma Mahadevan was instrumental in bringing the importance of word separation in text recognition applications to our attention.

References

1. V. Govindaraju, R. K. Srihari, and S. N. Srihari, "Handwritten Text Recognition," in *Proceedings of the conference on Document Analysis System, Kaiserslautern, Germany*, pp. 157–171, 1994.
2. V. Govindaraju, A. Shekhawat, and S. N. Srihari, "Interpretation of Handwritten Addresses in US Mail Stream," in *The third International Workshop on Frontiers in Handwriting Recognition, Buffalo, New York*, pp. 197–206, 1993.
3. T. M. Breuel, "Design and Implementation of a System for the Recognition of Handwritten Responses on US Census Forms," in *Proceedings of the conference on Document Analysis System, Kaiserslautern, Germany*, pp. 109–134, 1994.
4. S. Madhvanath, V. Govindaraju, V. Ramanaprasad, D.-S. Lee, and S. N. Srihari, "Reading Handwritten US Census Forms," in *Third International Conference on Document Analysis and Recognition (ICDAR-95), Montreal, Canada*, pp. 82–85, 1995.
5. S. N. Srihari, Y.-C. Shin, V. Ramanaprasad, and D.-S. Lee, "Name and Address Block Reader System for Tax Form Processing," in *Third International Conference on Document Analysis and Recognition (ICDAR-95), Montreal, Canada*, pp. 5–10, 1995.
6. J.-V. Moreau, B. Plessis, O. Bougeios, and J.-L. Plagnaud, "A Postal Check Reading System," in *Proceedings of the First International Conference on Document Analysis and Recognition, St. Malo, France*, pp. 758–766, 1991.
7. J. C. Simon, O. Baret, and N. Gorski, "A System for the Recognition of Handwritten Literal Amounts of Checks," in *Proceedings of the conference on Document Analysis System, Kaiserslautern, Germany*, pp. 135–155, 1994.
8. S. S. John, "Checking Checks," *Technology Review*, vol. 95, pp. 15–16, May/June 1992.

9. T. Paquet and Y. Lecourtier, "Handwriting Recognition: Application on Bank Cheques," in *Proceedings of the First International Conference on Document Analysis and Recognition, St. Malo, France*, pp. 749–757, 1991.
10. E. Cohen, "Computational theory for interpreting handwritten text in constrained domains," *Artificial Intelligence*, vol. 67, pp. 1–31, 1994.
11. D. Guillevic and C. Y. Suen, "Cursive Script Recognition applied to the Processing of Bank Cheques," in *Proceedings of the Third International Conference on Document Analysis and Recognition, Montreal, Canada*, pp. 11–14, 1995.
12. J.-P. Dodel and R. Shinghal, "Symbolic/Neural Recognition of Cursive Amounts on Bank Cheques," in *Proceedings of the Third International Conference on Document Analysis and Recognition, Montreal, Canada*, pp. 15–18, 1995.
13. A. Agarwal, L. Granowetter, K. Hussein, and A. Gupta, "Detection of Courtesy Amount Block on Bank Checks," in *Proceedings of the Third International Conference on Document Analysis and Recognition, Montreal, Canada*, pp. 748–751, 1995.
14. G. Kim and V. Govindaraju, "Handwritten Word Recognition for Real-Time Applications," in *Third International Conference on Document Analysis and Recognition (ICDAR-95), Montreal, Canada*, pp. 24–27, August 1995.
15. H. Freeman, "Techniques for the Digital Computer Analysis of Chain-Encoded Arbitrary Plane Curves," in *Proceedings of the National Electronics Conference*, vol. 17, pp. 412–432, 1961.
16. T. Pavlidis, *Algorithms for Graphics and Image Processing*. Rockville, MD: Computer Science Press, 1982.
17. G. Kim and V. Govindaraju, "Efficient Chain Code Based Image Manipulation for Handwritten Word Recognition," in *Proc. of the SPIE symposium on electronic imaging sci-*

- ence and technology (*Document Recognition III*), San Jose, CA, vol. 2660, pp. 262–272, February 1996.
18. H. Baird and K. Thompson, “Reading chess,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 12, pp. 552–559, 1990.
 19. R. O. Duda and P. E. Hart, “Experiments in Recognition of Hand-printed Text,” in *AFIPS Conference Proceedings*, pp. 1139–1149, 1968.
 20. E. Cohen, J. Hull, and S. N. Srihari, “Understanding Handwritten Text in a Structured Environment : Determining ZIP codes from addresses,” *International Journal of Pattern Recognition and Artificial Intelligence*, vol. 5, no. 1&2, pp. 221–264, 1991.
 21. G. Seni and E. Cohen, “External Word Segmentation of Off-Line Handwritten Text Lines,” *Pattern Recognition*, vol. 27, no. 1, pp. 41–52, 1994.
 22. U. Mahadevan and R. C. Nagabushnam, “Gap Metrics for Word Separation in Handwritten Lines,” in *Third International Conference on Document Analysis and Recognition (ICDAR-95)*, Montreal, Canada, pp. 124–127, 1995.
 23. M.-Y. Chen, A. Kundu, and J. Zhou, “Off-Line Handwritten Word Recognition Using a Hidden Markov Model Type Stochastic Network,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 16, pp. 481–496, May 1994.
 24. G. Kim, V. Govindaraju, and S. N. Srihari, “Handwritten Word Recognition using Dynamic Matching with Variable Duration,” in *IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP96)*, Atlanta, vol. 6, pp. 3454–3457, May 1996.