

A Systematic Approach for Feature Extraction in Fingerprint Images

Sharat Chikkerur, Chaohang Wu, Venu Govindaraju

Center for Unified Biometrics and Sensors (CUBS), University at Buffalo, NY, U.S.A
{ssc5,cwu3,govind}@cedar.buffalo.edu

Abstract. Fingerprint image enhancement and feature extraction are the most important stages in fingerprint verification. The robustness of the system depends entirely upon its ability to enhance bad quality images and reliably extract minutiae from it. In this paper we propose two original algorithms for the extraction of global and local features in fingerprint images. A global feature extraction and enhancement algorithm based on Fourier analysis that is simultaneously able to extract local ridge orientation, ridge frequency and ridge quality measure is proposed. A novel algorithm for minutiae feature extraction and post processing based on chain coded contour following is also presented.

1 Introduction

This paper introduces new algorithms for fingerprint image enhancement, and feature extraction from fingerprint images. Fingerprints are characterized by global and local features. The global features include the ridge orientation map, core and delta locations. The minutiae points form the local features. The estimation of local ridge orientation and the local ridge frequency play an important role in all subsequent stages of a fingerprint verification system [14]. The ridge orientation map is used in image enhancement [14,8], detection of singular points [16], minutiae post processing and fingerprint classification [7]. The map of local ridge frequency has been found to be useful in fingerprint image enhancement [8].

There have been several approaches to estimate the orientation map of a fingerprint image. These include the use of gradients [8], template comparison [7], and ridge projection based methods [14]. The orientation estimation obtained by these methods is noisy and has to be processed further. The post processing methods can be based on vector averaging [6], relaxation methods [14], or mathematical orientation models [15]. In particular, the orientation models depend on reliable detection of the core and delta points in the fingerprint image. However, many of the methods used for singular point extraction [7,16,1] depend on a reliable orientation map, therefore requiring that the orientation map be estimated accurately to begin with.

The local ridge frequency indicates the average inter ridge distance within a block. This can be estimated based on the projection sum [8], or variation of gray level in different directions [11]. These two methods also depend upon the reliable extraction of the local ridge orientation.

The robustness of the verification system depends on its ability to enhance poor quality images. General-purpose image processing algorithms are not very useful in this regard but serve as a preprocessing step in the overall enhancement scheme [10]. A majority of the techniques are based on the use of contextual filters whose parameters depend on the local ridge frequency and orientation. The filters themselves may be spatial [8,4] or based on Fourier domain analysis [14,18].

Feature extraction algorithms can be categorized as those based on gray level and those dealing with binarized images. Approaches working with binary images proceed with detection of the minutiae after thinning the binary image. The binarization approaches include peak detection [13], adaptive and optimal thresholding. Approaches working with gray level images are mostly based on ridge following [12].

The rest of the paper is organized as follows: Section 2 presents a scheme to extract local ridge orientation and frequency using Fourier domain analysis. Segmentation and enhancement schemes are also introduced. Section 3 gives details of the minutiae extraction and post processing methods. Section 4 presents an objective evaluation of the algorithm. The summary of the paper is outlined in Section 5.

2 Global Feature Extraction

2.1 Fourier Domain Analysis

With the exception of the singularities such as core and delta any local region in the fingerprint image has a consistent orientation and frequency. Therefore, the local region can be modeled as a surface wave that is characterized completely by its orientation ϕ and frequency f . The parameters of the surface wave (f, ϕ) may be easily obtained from its Fourier spectrum that consists of two impulses whose distance from the origin indicates the frequency and its angular location indicates the orientation of the wave.




Fig. 1. (a) Local region in a fingerprint image (b) Surface wave approximation (c,d) Fourier spectrum of Fig. 2a, Fig. 2b. The symmetric nature of the Fourier spectrum arrives from the properties of the Fourier transform for real signals [3]

2.2 Directional Field Estimation

In reality the surface wave model is only an approximation, and the Fourier spectrum of the real fingerprint images is characterized by a distribution of energies across all frequencies and orientations. To approximate each block by a single orientation and frequency, a probabilistic approximation is used. We can represent the Fourier spec-

trum in polar form as $F(r, \phi)$. Using this, we can define a probability density function $f(r, \phi)$ and the marginal density functions $f(\phi), f(r)$ as

$$f(r, \phi) = \frac{|F(r, \phi)|^2}{\int_r \int_\phi |F(r, \phi)|^2 d\phi dr} \quad (1)$$

$$f(\phi) = \int_r f(r, \phi) dr, f(r) = \int_\phi f(r, \phi) d\phi \quad (2)$$

We assume that the orientation ϕ is a random variable that has the probability density function $f(\phi)$. The expected value of the orientation may then be obtained by

$$E\{\phi\} = \int_\phi \phi \cdot f(\phi) d\phi \quad (3)$$

2.3 Ridge Frequency Estimation

The average ridge frequency is estimated in a manner similar to the ridge orientation. We can assume the ridge frequency to be a random variable with the probability density function $f(r)$ as in Eqn. (2). The expected value of the ridge frequency is given by

$$E\{r\} = \int_r r \cdot f(r) dr \quad (4)$$

The frequency map so obtained is smoothened by applying a 3x3 gaussian mask.

2.4 Energy Map and Segmentation

The fingerprint image may be easily segmented based on the observation that the surface wave model does not hold in regions where ridges do not exist. In the areas of background and noisy regions, there is very little structure and hence very little energy content in the Fourier spectrum. We define an energy image $E(x, y)$ (Eqn. 5) where each value indicates the energy content of the corresponding block. The fingerprint region may be differentiated from the background by thresholding the energy image. We take the logarithm values of the energy to obtain a linear scale. Fig 4 illustrates the energy map obtained by this method.

$$E = \sum_u \sum_v |F(u, v)|^2 \quad (5)$$

2.5 Enhancement

We propose a Fourier domain based block-wise contextual filter approach for enhancing fingerprint images. The image is divided into 16x16 overlapping blocks that is filtered in the Fourier domain by a frequency and orientation selective filter whose parameters are based on the estimated local ridge orientation and frequency. Block-wise approaches have problems around the singularities where direction of the ridges cannot be approximated by a single value. The bandwidth of the directional filter has to be increased around these regions. We propose to use the directional histogram obtained in the estimation of the orientation image for this purpose. We assume that $f(\phi)$ is unimodal and centered around $E\{\phi\}$ and define the bandwidth as the angular extent where $P\{|\phi - E\{\phi\}| < \phi_{BW}\} = 0.5$. Thus, the angular bandwidth of the filter adapts itself in regions of high curvature. The filters are defined as specified in [14] and are given by

$$H_r(r) = \sqrt{\frac{(rr_{BW})^{2n}}{(rr_{BW})^{2n} + (r^2 - r_{BW}^2)^{2n}}} \quad (6)$$

$$H_\phi(\phi) = \begin{cases} \cos^2 \frac{\pi(\phi - \phi_c)}{2\phi_{BW}} & \text{if } |\phi - \phi_c| \leq \phi_{BW} \\ 0 & \text{otherwise} \end{cases}$$

r_{BW} : radial bandwidth, ϕ_{BW} : angular bandwidth, ϕ_c : mean orientation.

3 Chain Code Based Minutiae Detection and Post Processing

Commonly used minutiae extraction algorithms that are based on thinning are iterative, computationally expensive and produce artifacts such as spurs and bridges. We propose a chain coded contour following method for this purpose. Chain codes are a loss less representation of contours and yield a wide range of information about the contour such as curvature, direction, length etc [5]. As the contour of the ridges is traced consistently in a counter-clockwise direction, the minutiae points are encountered as locations where the contour has a *significant* turn. Specifically, the ridge end occurs as significant left turn and the bifurcation as a significant right turn in the contour. Analytically the turning direction may be determined by considering the sign of the cross product of the incoming and outgoing vectors at each point. The product is right handed if the sign of Eqn.(7) is positive and left handed if the sign is negative. The turn is termed significant only if $x_1y_1 + x_2y_2 \leq T$. The threshold T is chosen to have a small value. In practice a group of points along the turn satisfy this condition. We define the minutia point as the center of this group.

$$\text{sgn}(\vec{P}_{in} \times \vec{P}_{out}) = \text{sgn}(x_1y_2 - x_2y_1) \quad (7)$$




Fig. 2. (a) Minutiae marked by significant turn in the contour (b) Left turn (c) Right turn

The feature extraction results in two forms of errors. The enhancement process may introduce artifacts that are detected as spurious minutia or may miss some of the genuine minutiae (Fig. 3). We use heuristics based on the structural properties of the minutiae to eliminate the false features. Similar approaches are outlined in [10]. We use the following rules to eliminate false minutiae (i) We merge the minutiae that are within a certain distance of each other and have similar angles. This is to merge the false positives that arise out of discontinuities along the significant turn of the contour. (ii) If the direction of the minutiae is not consistent with the local ridge orientation, then it is discarded. This removes minutiae that arise out of noise in the contour. (iii) We discard all minutiae that are within a distance of the border of the fingerprint area. The border is determined based on the energy map. This rule removes spurious minutiae that occur along the border of the fingerprint image (iv) We remove the pair of opposing minutiae that are within a certain distance of each other. This rule removes the minutiae that occur at either ends of a ridge break.




Fig. 3. Post processing: (a) Fingerprint image with locations of spurious minutiae marked (b) Types of spurious minutiae removed by applying heuristic rules (i-iv)

4 Testing and Evaluation

The efficiency of the feature extraction can be measured by how well it meets the objective of detecting the minutiae features from the original image. We use the evaluation method proposed in [14]. We measure two quantities namely ‘‘Sensitivity’’ and ‘‘Specificity’’ to evaluate the algorithm. The sensitivity and specificity indicates the

ability of the algorithm to detect the true minutiae and reject false minutiae respectively. We manually identified the minutiae features on a subset of FVC2002 DB1 [2] database to establish the ground truth of the minutiae. The minutiae features were then detected using our algorithm and the sensitivity and specificity were measured over the entire database. The algorithm was executed on a PC with AMD Athlon 1.1GHz processor running Windows XP. The algorithm takes an average of 0.98s over the test images.

4.1 Results




Fig. 4. (a) Original print (b) Orientation Image (c) Energy map (The brighter regions indicate regions with higher energy) (d) Frequency Image (Bright regions indicate higher frequencies)




Fig. 5. Results of the contextual filtering algorithm (a) Good quality print. (b) Medium quality print (c) Bad quality dry print.

Table 1. Performance over FVC2002 (DB1) database

	Sensitivity(%)	Specificity(%)
Mean Value	79.40	85.29
Std Deviation	7.86	12.91

5 Conclusion

We have proposed a unified frequency domain analysis based algorithm for the enhancement and extraction of global features from fingerprint images. The enhancement algorithm uses the full context information obtained from the Fourier domain analysis of the fingerprint image. We have also proposed a novel algorithm for the extraction of minutiae points from the fingerprint image using the chain coded contour ridge following method. Heuristic rules specifically suitable for our algorithm have been presented.

References

1. Bazen and Gerez, "Extraction of Singular Points from Directional Fields of Fingerprints", Annual CTIT Workshop, Enschede, The Netherlands, 2001.
2. Fingerprint Verification Competition, <http://bias.csr.unibo.it/fvc2002/>
3. Gonzalez R. C and R. E. Woods, "Digital Image Processing", Prentice Hall, Upper Saddle River, NJ, 2002.
4. Gormann L. and J. V. Nickerson, "An Approach to Fingerprint Filter Design", *Patt. Recogn.*, Vol. 22, No. 1, pp. 29-38, 1989.
5. Govindaraju V., Z. Shi and J. Schneider, "Feature Extraction Using a Chaincoded Contour Representation", International Conference on Audio and Video Based Biometric Person Authentication, Surrey, UK, 2003.
6. Kaas M. and A. Witkin, "Analyzing Oriented Patterns", *Comp. Vision Graphics Image Process.* Vol. 37, No. 4, pp. 362-385, 1987.
7. Kawagoe M., A. Tojo, "Fingerprint Pattern Classification", *Pattern Recognition*, Vol. 17, No 3, pp 295-303, 1987.
8. Ling H., Y. Wan and A. K. Jain, "Fingerprint Image Enhancement: Algorithm and Performance Evaluation", *PAMI*, Vol. 20, No. 8, pp. 777-789, Aug. 1998.
9. Madhavanth S., Kim, and V. Govindaraju, "Chaincode Processing for Hand-written Word Recognition", *IEEE Trans. On Pattern Analysis and Mach. Intell* 19, pp. 27-40, 1997.
10. Maltoni D., D. Maio, A. K. Jain, S. Prabhakar, "Hand book of Fingerprint Recognition", Springer-Verlag, 2003.
11. Maio D. and D. Maltoni, "Neural Network Based Minutiae Filtering in Fingerprints", *Proc. 14th International Conf. Pattern Recognition*, Brisbane, Australia, pp. 1654-1658, 1998.
12. Maio D. and D. Maltoni "Direct Gray Scale Minutiae Detection in Fingerprints", *IEEE Trans. On Patt. Analysis and Machine Intell.* Vol.19, No.1, 1997.
13. Ratha N. K., S. Y. Chen and A. K. Jain, "Adaptive Flow Orientation Based Feature Extraction in Fingerprint Images", *Patt. Recogn.* Vol. 28, No. 11, pp. 1657-1672, 1995.
14. Sherlock B. G., D. M. Monro, K. Millard, "Fingerprint Enhancement by Directional Fourier Filtering", *IEEE Proc. Vis. Image Signal Process.*, Vol 141., No 2, pp. 87-94, April 1994.
15. Sherlock B. G., D. M. Monro, "A Model for Interpreting Fingerprint Topology", *Pattern Recognition*, Vol. 26, No. 7, pp 1047-1055, 1993.
16. Srinivasan V.S. and N. N. Murthy, "Detection of Singular Points in Fingerprint Images", *Pattern Recognition*, Vol. 25, No. 2, pp. 139-153, 1992.
17. Viscaya, Gerhardt, "A Nonlinear Orientation Model for Global Description of Fingerprints", *Pattern Recognition*, Vol.29, No.7, pp 1221-1231, 1996.
18. Watson C. I., G. T. Candela and P. J. Grother, "Comparison of FFT Fingerprint Filtering Methods for Neural Network Classification", NISTIR 5493, 1994.