

Fusion of Biometric Matchers

Venu Govindaraju

Sergey Tulyakov

University at Buffalo


venu@cubs.buffalo.edu

Outline

- **Multimodal Biometric Fusion**
 - Heuristic Rules vs. Learnable Functions
 - Biometric Identification Systems
 - General Framework
 - Sequential Binning

Multibiometrics

- **Single biometric may not be**
 - Secure
 - Provide sufficient coverage
 - Accurate
 - Efficient




Fusion

- **Multiple Modalities:**
 - Integrated authentication: e.g., face and fingerprint
 - Multiple fingers is a special case (e.g., ten fingers)
- **Multiple Samples:**
 - E.g., “Three chances and you are out”
 - Allow upper time limit for authentication
- **Multiple Sensors**
 - E.g., Fingerprint sensor based on optical and capacitance
- **Multiple Matchers**
 - Different algorithms/features used on same biometric
 - E.g., NN approach vs SVM
 - E.g., Minutiae based and Correlation based
- **Multiple Tokens**
 - Combination with PINs, Knowledge

Multiple Modalities: Verification


- Person A: “I am Alice. Here is my biometric data.”
- Retrieve enrolled biometric templates for Alice and match them with person A’s biometric data



- Combine scores:
- Decide if $A == \text{Alice}$ (genuine) or $A \neq \text{Alice}$ (impostor)

Biometric Identification

- Person X: “No claim made OR I don’t believe the claim.”
- Match all enrolled biometric templates with X’s biometric data



- Combine scores:

- **Identify** X: $X == \text{Alice}$ or $X == \text{Bob}$ or ...

Objective

- **We will explore:**
 - What are the advantages and disadvantages of Heuristic Combination rules vs. a Second stage pattern classification?
 - What type of biometric matchers lend themselves to combination functions that can be learnt?
 - How can the combination methods take advantage of the independence of the biometric matchers?
 - How should the combination methods be different when dealing with Identification Systems vs. Verification Systems?

Example Heuristic Rules

- Weighted Sum Rule

$$f(s_1, s_2) = w_1 s_1 + w_2 s_2$$
$$= \frac{s_1}{\sigma_1^2} + \frac{s_2}{\sigma_2^2}$$

- RMS Rule

$$f(s_1, s_2) = \sqrt{(s_1^2 + s_2^2)}$$

- Boolean Rules: AND, OR

$$\text{score} \sim P(\omega | s) + \varepsilon$$

- Product Rule: assume score is posterior probability
- Sum Rule: assume score is log (posterior probability)

Sum rule and Product Rule assume independence of scores.
If scores are not independent then these rules are suboptimal

Questions

- How to normalize scores before applying the rule?
 - Linear mapping, Z-normalization, Histogram normalization

-What is the meaning of the scores?


$$score \sim P(\omega | s) + \varepsilon$$

$$score = \frac{\text{No. of matched minutia}}{\text{Total no. of minutia}} \times \text{Average match conf}$$


- How should the weights be chosen?
- What happens with correlated matchers? (e.g., ensemble classifiers)

Theorem: Symmetric smooth combination functions result in similar combination results for ensemble classifiers [Tulyakov 2006].

Product Rule




Sum Rule



General pattern classification in the score space addresses these drawbacks

2nd stage Pattern Classification Task

- Treat a set of scores as a feature vector, and solve a pattern classification problem with two classes: genuine and impostor.



Given “enough” truthed data estimate joint class conditional pdf


$$p(s_1, s_2 | \text{genuine}) \quad p(s_1, s_2 | \text{imposter})$$

Use non parametric methods [Jain & Prabhakar] *Decide on ~*

$$\frac{p(s_1, s_2 | \text{genuine})}{p(s_1, s_2 | \text{imposter})}$$

- Use independence knowledge

Neyman Pearson Likelihood Ratio



Utilizing Independence

Approximate densities for Bayesian classification:

- Not using independence – approximate 2-dimensional score densities by 2-dimensional Parzen kernels

$$p(s_1, s_2) \approx \hat{p}(s_1, s_2) = \frac{1}{N} \sum_{i=1}^N \left(\frac{1}{h} \varphi \left(\frac{x_1(i) - s_1}{h}, \frac{x_2(i) - s_2}{h} \right) \right)$$

- Using independence - approximate 2-dimensional score densities by products of 1-dimensional Parzen kernel approximations

$$p(s_1, s_2) = p(s_1)p(s_2) \approx \hat{p}(s_1)\hat{p}(s_2)$$

$$\hat{p}(s_1) = \frac{1}{N} \sum_{i=1}^N \left(\frac{1}{h} \varphi \left(\frac{x_1(i) - s_1}{h} \right) \right)$$

Subscripts *gen* and *imp* have been dropped.

h is estimated using Maximum Likelihood criterion in each case

Estimation Errors using Parzen Kernels

Mean integrated squared error (MISE) is a measure of pdf estimation:

$$MISE(\hat{p}) = E \left(\int_{-\infty}^{\infty} (p - \hat{p})^2(x) dx \right)$$

n = no. of training samples

d = no. of dimensions

k = no. of parameters in derivation;
consider a constant

For d -dimensional kernel estimation of pdf the order of error is:

$$MISE(\hat{p}) \sim n^{-\frac{2k}{2k+d}} \quad \text{W. Hardle "Smoothing techniques with implementation in S"}$$

Known: lower dimension d results in better asymptotic pdf approximation. In particular, error for approximating 1-dimensional pdf is less than error for approximating 2-dimensional pdf given same no. of training samples

$$n^{-\frac{2k}{2k+1}} < n^{-\frac{2k}{2k+2}}$$

For given n (usually small and fixed) training samples; and constant k

Theorem: Product of approximations has the same order of error as individual 1-dimensional approximations.



Experiments

- NIST BSSR1 biometric score set
- 517 enrollees and 517 user authentication attempts =>
- 517 genuine and 517 x 516 impostor scores

- Leave-one-out testing procedure

- Score for test sample (Likelihood Ratio) :


$$\frac{p(s_1, s_2) | \text{genuine}}{p(s_1, s_2) | \text{impostor}}$$



Biometric Identification

- Person X: “No claim made OR I don’t believe the claim.”
- Match all enrolled biometric templates with X’s biometric data

Previous Work



- Combine scores:

- **Identify** X: $X == \text{Alice}$ or $X == \text{Bob}$ or ...


Previous Models in Identification

Model the background (enrolled database)

Non-class specific

Model average over all genuine and impostor classes

1 1D pdf score pair




Low
Complexity

Class specific

Model genuine and impostor scores for each class separately

N 1D pdf score pairs

[Jain & Ross 02]




Medium I
Complexity

Neighborhood specific

Cohort normalization

Choose different thresholds for different test attempts

[Colombi & Reider 97]




Medium - High

1:N Identification Model

Example of scores produced by a 'perfect' identification system matcher:

| Identification attempt | Gen score | Impostor scores |
|------------------------|-----------|-----------------|
| 1 | 1.0 | 0.8, 0.4, -0.1 |
| 2 | 2.2 | 1.9, 1.3, 0.7 |
| 3 | 0.5 | 0.1, -0.3, -1.1 |

Score distributions do not preserve all information due to score dependence:




- ID Model reflects the relationships between 1 genuine and N-1 impostor scores on each attempt.

- ID Model uses second-best matching score as a statistic about current identification attempt.

- Approximation

- 1:1 vs 1:N



Identification Model

[Grother 04]

z-normalization

$$z_i = \frac{x_i - m}{s}$$

$$m = \frac{1}{G} \sum_{i=1}^G x_i, \quad s = \frac{1}{G-1} \sum_{i=1}^G (x_i - m)^2$$

On each test attempt all class scores are considered

Not trainable

Genuine and impostor scores on each trial are dependent-

Learn this dependency

[Tulyakov 06]



Training: Genuine distribution: N score pairs

Alice: $(s_{\text{Alice}}, s_{\text{best of remaining}})$

Bob: $(s_{\text{Bob}}, s_{\text{b of r}})$

....N

Training: Impostor distribution: N x N-1 score pairs

Atpt 1: Alice: $(s_{\text{Bob}}, s_{\text{b-of-r}}), (s_{\text{Frank}}, s_{\text{b of r}}), \dots N..1$

Atpt 2: Bob: $(s_{\text{Alice}}, s_{\text{b of r}}), (s_{\text{Frank}}, s_{\text{b of r}}), \dots N..1$

Attempt N:

Combination in Identification Models

Model the joint pdf of the genuine scores and best of remaining scores

$$(s_g, sbr(s_g))$$

and the same for impostor score distributions

$$(s_i, sbr(s_i))$$

where

$$sbr(s)$$

is the second best score besides s

Using Independence Assumption model distributions of 2 biometrics

$$\hat{p}((s_{g1}, sbr(s_{g1})), (s_{g2}, sbr(s_{g2}))) \approx$$

$$\hat{p}((s_{g1}, sbr(s_{g1}))) \times \hat{p}((s_{g2}, sbr(s_{g2})))$$

$$\hat{p}((s_{i1}, sbr(s_{i1})), (s_{i2}, sbr(s_{i2}))) \approx$$

$$\hat{p}((s_{i1}, sbr(s_{i1}))) \times \hat{p}((s_{i2}, sbr(s_{i2})))$$

Estimate 2D pdfs instead of 4D pdfs

Identification Algorithm

Statistic t_k^j is 'second best score' among all scores besides s_k^j in the current identification attempt

Traditional - Likelihood Ratio $\arg \max_k \prod_j \frac{p(s_k^j | C_k)}{p(s_k^j | \bar{C}_k)}$

Density





$$\arg \max_k \prod_j p(\{s_i^j\}_{i=1,\dots,N} | C_k) \xrightarrow{t_k^j} \arg \max_k \prod_j p(s_k^j, t_k^j | C_k)$$

Posterior Class Probability

$$\arg \max_k \prod_j \frac{p(\{s_i^j\}_{i=1,\dots,N} | C_k)}{p(\{s_i^j\}_{i=1,\dots,N} | \bar{C}_k)} \xrightarrow{t_k^j} \arg \max_k \prod_j \frac{p(s_k^j, t_k^j | C_k)}{p(s_k^j, t_k^j | \bar{C}_k)}$$

Experiments

BSSR1: fingerprint x face





BSSR1 score set, fingerprint r_i and face C scores.



BSSR1 score set, fingerprint r_i and face G scores.

Experiments

BSSR1: fingerprint x face



| Configuration | Traditional | Density | PosterProb |
|--------------------|-------------|---------|------------|
| li & C / 516 users | 5 | 7 | 4 |
| li & G / 517 users | 9 | 11 | 6 |
| ri & C / 516 users | 3 | 3 | 2 |
| ri & G / 517 users | 3 | 2 | 2 |



BSSR1 score set, fingerprint ri and face C scores.


BSSR1 score set, fingerprint ri and face G scores.

Experiments with Identification Model

Correlations between genuine and impostor scores

Positive correlations between genuine and impostor scores indicate the score dependencies and justify the use of identification model in decision making and combinations

| | 1 st Imp | 2 nd Imp | 3 rd Imp | mean |
|----|---------------------|---------------------|---------------------|-------|
| li | .3164 | .3400 | .3389 | .2961 |
| ri | .3536 | .3714 | .3785 | .3626 |
| C | .1419 | .1513 | .1562 | .1440 |
| G | .1339 | .1800 | .1827 | .1593 |



Choose random 50 impostors from 6000 on each attempt

New experiments on identification model for fusion

Identification model (utilizing second best score statistic) improves performances of both Bayesian and Weighted Sum combination algorithms (shown are numbers of failed identification attempts out of 6000 with 50 randomly chosen impostors)

| Configuration | Bayesian No ID Model | Bayesian ID Model | Weighted Sum No ID Model | Weighted Sum ID Model |
|---------------|----------------------|-------------------|--------------------------|-----------------------|
| li & C | 75 | 74 | 70 | 65 |
| li & G | 101 | 92 | 122 | 95 |
| ri & C | 37 | 31 | 30 | 25 |
| ri & G | 52 | 41 | 67 | 48 |

General Framework

1. Low

$$S_i = f(s_i^1, s_i^2, \dots, s_i^M)$$

Class generic combination function Parameter set

2. Medium I

$$S_i = f_i(s_i^1, s_i^2, \dots, s_i^M)$$

Class specific combination function


3. Medium II

$$S_i = f(s_i^1, s_i^2, \dots, s_i^M, \{s_k^1, s_k^2, \dots, s_k^M\}_{k \neq i})$$

Parameter set


4. High

$$S_i = f_i(s_i^1, s_i^2, \dots, s_i^M, \{s_k^1, s_k^2, \dots, s_k^M\}_{k \neq i})$$




Complexity of Trainable Functions

$C_f(k)$ - complexity of the family of functions f accepting k dimensional input – VC (Vapnik-Chervonenkis) dimension




(a) Low

(b) Medium I



(c) Medium II

(d) High



M biometrics; N users

Low $C_f(M)$

Medium I $NC_f(M)$


Medium II $C_f(NM)$

High $NC_f(NM)$

Score Dependencies


2-class identification problem, each classifier produces 2 match scores – 1 genuine score and 1 impostor score.

Classifier 1



In each identification attempt of classifier 1: $s_{imp}^1 = s_{gen}^1 - 1$

Classifier 2



In each identification attempt of classifier 2 s_{imp}^2 and s_{gen}^2 are sampled independently from $p_{imp}(x)$ and $p_{gen}(x)$


Result of Improper Combination Choice

Assume also that classifiers are independent.

Low complexity combination:

Low complexity combinations operate in score space (s^1, s^2) and their training set consists of pairs (s_{gen}^1, s_{gen}^2) and (s_{imp}^1, s_{imp}^2)

Optimal decision surfaces \Rightarrow




- Low complexity combinations do not account for the relationships between scores produced by single classifier during identification attempt.
- Improper combination choice can actually hurt

Outline

- **Multimodal Biometric Fusion**
 - ✓ Heuristic Rules vs. Learnable Functions
 - ✓ Biometric Identification Systems
 - ✓ General Framework
 - Sequential Binning

Sequential Fusion



Search Space Analysis

- We can improve performance by reducing the search space during identification
- Let P_{SYS} – Penetration rate [between 0.0 and 1.0]
 - Penetration rate is the average fraction of the database searched during identification
 - Effective size = $N * P_{SYS}$

- For a 1:N matching,

$$FAR_{P_{SYS}N} = 1 - (1 - FAR)^{P_{SYS} \times N} \approx P_{SYS} \times N \times FAR$$

$$FRR_{P_{SYS}N} = FRR$$


- The total number of False Accepts is given by

$$\text{False accepts} = N \times FAR_N \approx N^2 \times P_{SYS} \times FAR$$

- State of the art fingerprint systems has $P_{SYS}=0.5$



Binning

- Binning can be used to achieve a smaller P_{SYS}
 - Partition the feature space
 - Each bin is represented by a cluster center C_K
 - Records are compared with only N_B cluster centers



- Bin representatives are computed offline during training

Binning



11 – Dimensional Signature data
Best Penetration: 16.65% for 17 bins
FRR = 0%

$$P_{SYS} = \frac{N_S T_B}{N_D}$$

N_S : Number of bins to search, T_B : Average templates in bin


N_B : Number of bins, N_D : Size of the database

Dataset 400 Training Set & 400 Testing Set

27 – Dimensional Hand Geometry data
Best Penetration: 14.60% for 9 bins
FRR = 0%

$$Comparisons = \frac{N_S T_B + N_B}{N_D}$$

Speed Analysis



$$P_{SYS} = \frac{N_S T_B}{N_D}$$

Best combined penetration rate of 8.93% at 0% FRR using 6 bins

N_S : Number of bins to search

T_B : Average templates in bin

N_D : Size of the database

Dataset 400 Training Set & 400 Testing Set

Time for 1:N identification $\Theta(N)$

Time for identification using binning system $\Theta(C \times M) + C \times \Theta(A_M)$

C – Closest bins to be searched

M – Total number of bins

A_M – Average bin density

Time to find C closest bin $\Theta(C \times M)$

Time to search within C bins $C \times \Theta(A_M)$

If $C < M \ll N$ and $AM < N$, then:

$$\Theta(C \times M) + C \times \Theta(A_M) < \Theta(N)$$

Summary

- Use combination complexity type based on the problem
 - Can learn class information => use medium I or high
 - Can learn classifier behavior => use medium II or high
- Usually there are too many classes (persons) and too few samples per class to have individually trained combination functions for each class.
 - Use low and medium II combination complexity types.
 -
- If there is a dependence between scores produced by a classifier during one identification attempt, low complexity combinations might not work.
 - Use medium II or high complexity combinations if possible.
- The performance of the system might decrease with additional classifiers, even if optimal combination is constructed, but of the wrong type.
- Increasing the number of bins improves the penetration rate but increases computations for locating closest bins