Knowledge-Based Derivation of Document Logical Structure

Debashish Niyogi and Sargur N. Srihari

Center of Excellence for Document Analysis and Recognition (CEDAR)
State University of New York at Buffalo, Buffalo, NY 142228-2567, U.S.A.
{niyogi,srihari}@cedar.buffalo.edu

Abstract

The analysis of a document image to derive a symbolic description of its structure and contents involves using spatial domain knowledge to classify the different printed blocks (e.g., text paragraphs), group them into logical units (e.g., newspaper stories), and determine the reading order of the text blocks within each unit. These steps describe the conversion of the physical structure of a document into its logical structure. We have developed a computational model for document logical structure derivation, in which a rule-based control strategy utilizes the data obtained from analyzing a digitized document image, and makes inferences using a multi-level knowledge base of document layout rules. The knowledge-based document logical structure derivation system (DeLoS) based on this model consists of a hierarchical rule-based control system to guide the block classification, grouping and read-ordering operations; a global data structure to store the document image data and incremental inferences; and a domain knowledge base to encode the rules governing document layout.

1 Introduction

Standard printed documents generally conform to a certain geometric structure that dictates that the document be composed of a set of interconnecting rectangular printed regions, or blocks. The layout of the blocks varies among different types of documents and depends on the layout conventions for each document type. However, there is an underlying structure for standard printed documents that is governed by certain basic constraints: (1) the physical blocks into which printed documents can be spatially divided represent meaningful physical divisions of the document; (2) each physical block can be classified into a basic category like "text", "photograph", "line-drawing", etc.; (3) these physical blocks can be grouped into units that represent meaningful logical entities in a document, e.g., a newspaper story, magazine article, etc.; and (4) the text blocks within each unit must be read in a specific "reading order" for the information in the unit to make sense syntactically and semantically.

Constraints 1 and 2 are met by performing image segmentation followed by identification of the different blocks. This is the process of extraction of the physical structure of the document from the image, and is known as *document layout analysis*. Constraints 3 and 4 are met by performing block classification, logical grouping, and ordering. This is the process of extraction of the logical structure of the document, which we will call *logical structure derivation*.

The *physical* layout of a document page consists of the geometric structure and spatial relationships of the different blocks of printed matter, and its *logical* structure consists of the logical groupings of related blocks into composite units. The logical structure is defined in terms of the logical entities (e.g., stories, titles, captions, photographs, etc.) into which a document is divided. Thus, a typical document's logical structure would be a tree in which the root node represents the entire document, the intermediate nodes represent units and sub-units, and the leaf nodes represent individual blocks. The transformation of the physical structure of a document into the logical structure is a critical component of document image understanding. Therefore, our objective has been to develop a methodology for this transformation (i.e., from a digitized document image to an editable file containing a complete symbolic description of the document).

The steps involved in the transformation of a scanned image of a document into its logical description are: (a) physical segmentation of the image into its constituent printed "blocks"; (b) categorization of each of these blocks into block types; (c) labeling of these blocks, using domain knowledge, according to their specific identities; (d) logical grouping of these blocks, using further domain knowledge, into logical "units"; and (e) determining the reading order of text blocks within each unit, also using domain knowledge.

The domain used for this work is that of newspaper images. Newspapers provide a wide variety of layouts that are determined according to editorial conventions. The formats of newspaper pages are more complex than office documents or journal pages, and provide an opportunity for developing more generalized techniques.

2 Background

The application of knowledge-based techniques to document image understanding has been discussed by several researchers. For example, Kubota et al. [3] describe the application of a production system concept to an experimental document understanding system, and Fisher et al. [2] describe a rule-based system for segmenting a document image into text and non-text blocks. Rule-based systems used in the document image domain, however, have not fully exploited the depth and breadth of knowledge that is available about specific document domains.

Research on document layout analysis includes the interpretation of office documents through the classification of the blocks in a document image (Dengel & Barth [1]). Other approaches to document image understanding include those by Taylor et al. [8], who use multiple knowledge sources and a blackboard control architecture to derive document structure, Luo et al. [4], who use a rule-based approach to interpreting the physical and logical structure of Japanese newspaper pages, and Tsujimoto & Asada [9], who have suggested a rule-based method for deriving the physical and logical structures of a multi-articled document.

Our approach uses layout heuristics to infer the classes and labels of the blocks in a document image, and also combines these blocks to make up logical units comprising related blocks. However, unlike previous approaches, we also determine the logical reading order of the text blocks in each unit, thus enabling a document reader to read the different blocks comprising a story or article in the appropriate order. Also, most previous work deals with office documents, or with pages from technical journals (Japanese newspapers have been used by some researchers, as mentioned above, but they have stopped at logical labeling). Our approach deals with newspaper images, which are structurally complex, since a newspaper page typically contains multiple articles which are structurally, but not necessarily logically, related.

3 Analysis of document structure

The basic element of the physical structure of a document is a "block", which is defined as a homogeneous geometric region of printed matter in the document (i.e., each connected component within a block is of similar type and size). Blocks are separated from one another by regions of white space. Newspapers are examples of complex documents. Each page of a newspaper typically contains many blocks of textual or graphical information, arranged so that each rectangular block of information is interconnected with its adjacent blocks so as to make a grid-like pattern. The syntax of the physical structure of a typical newspaper page is shown (in Extended BNF format) in Figure 1 (a).

```
<document> ::= { <page> }
<page>     ::= { <block> }
<block>    ::= <large-text> | <medium-text> |
                 <small-text> | <line-drawing> |
                 <half-tone> | <boundary>
<boundary> ::= <horizontal-line> | <vertical-line> |
                 <line-rectangle>
```

(a) Physical structure

```
<document info>   ::= { <unit> }
<unit>            ::= <title> | <graphical area> |
                        <story> | <photoblock>
<photoblock>      ::= [ <title> ] <photo> <caption>
<graphical area>  ::= <page banner> | <horizontal band> |
                        <other graphics>
<story>           ::= [ <sub-story> ] |
                        <title> [ <sub-title> ]
                      { <text-para> } [ <photoblock> ]
                      [ [ <title> ] <chart> <caption> ]
                      [ [ <title> ] <table> <caption> ]
<sub-story>       ::=  <story>
```

(b) Logical structure

Figure 1: Syntax of a typical newspaper.

The logical structure of a document reflects the hierarchy of logical units that comprise the document. Each logical unit is itself a composite of text or graphics elements. Logical structure is layout-independent; i.e., the contents of a newspaper story and of the various components in the story (e.g., text, photograph, caption, etc.), as well as the semantic relations between these components, are not affected by the manner in which the story is geometrically arranged on the newspaper page. The syntax of the logical structure of a typical newspaper page is shown in Figure 1 (b).

Layout rules may vary widely among different types of documents, and even among different examples of the same type of document. For example, a rule that says, "the author's name block is centered below the title block" may apply to the title page of a paper but not to a newspaper page. Thus, a knowledge base of layout rules for document logical structure derivation will contain some global rules that apply to a majority of documents and some domain-specific rules that apply only to the type of document being analyzed. In the case of newspaper images, for example, a knowledge base of layout rules will contain spatial rules that can be inferred from newspaper layouts. Examples are:

1. Multi-line headlines are left-justified.
2. A thin line rectangle around a set of blocks signifies an independent story or unit.

We have developed a computational model for the derivation of logical structure of a document. The model involves strategies for extracting the physical structure of a document (i.e., layout analysis), translating into the logical structure (i.e., logical structure derivation), and representing the logical structure in an appropriate symbolic form suitable for use by other processes that perform deeper levels of document understanding (e.g., text reading). The formalisms used in the design of this computational model are discussed in detail in Niyogi [5]. The computational model has the following components: (a) a procedure for classifying all the distinct blocks in an image, (b) a procedure for grouping these blocks into logical units, (c) a procedure for determining the read-order of the text blocks within each logical unit, (d) a control mechanism that monitors the above processes and creates the logical representation of the document, (e) a knowledge base containing knowledge about document layout and structure, and (f) a global data structure that maintains the domain and control data.

4 A logical structure derivation system

We have developed and implemented a knowledge-based system for the derivation of document logical structure based on the computational model described in Section 3. This system, called DeLoS ("**De**rivation of **Lo**gical **S**tructure") takes as input the digitized image of a newspaper page and produces as output a symbolic description of the logical structure of the page. Various image processing operations are performed to extract basic properties of the components of the image, and this data is analyzed under the control of a rule-based system, which operates in conjunction with a global data structure to monitor the entire classification, grouping, and block-ordering process. The rule-based system is an enhancement of the one described in Niyogi [6]. Details on the design and implementation of the system have been given in Niyogi [5].

Figure 2 shows the components of the DeLoS system. DeLoS consists of a multi-level rule-based reasoning system, an image processing sub-system, and a partitioned global data structure. The rule-based system utilizes a top-down, backward-chaining strategy. An inference engine within the rule-based system makes deductions about the document using a hierarchical knowledge base that contains rules describing all the identifiable characteristics of document images. The global data structure facilitates the transfer of information between the image processing modules and the rule-based system. A common data area stores all intermediate computation results (including incremental inferences), and other control information. The sub-processes that access and modify the data are sets of rules that are activated within the system's rule-invocation structure. The image-processing modules directly access the document image to extract various kinds of information about the document. Intrinsic properties of the different printed blocks as well as the spatial relationships between the blocks constitute the information that is passed to the control structure through the global data structure.



Figure 2: The DeLoS system.

The rule-based system consists of three levels of rules: knowledge rules (level 1), control rules (level 2), and strategy rules (level 3). The *knowledge rules* comprise the knowledge base, and contains all the domain knowledge for the system, expressed in terms of first-order predicates. These rules define the general characteristics expected of the components of a document image and the relationships between such components in the image. Thus, all common characteristics of different types of document blocks (e.g., text blocks, photographs, etc.), as well as spatial constraints commonly followed in document layout (e.g., the positioning of captions relative to photographs, etc.), are encoded into the knowledge base. These knowledge rules can be used for block classification, block grouping, or text block ordering as and when required according to the control strategy. An example knowledge rule is shown in Figure 3 (a).

The control structure for the rule-based system contains an inference engine which contains two levels of rules: *control rules* and *strategy rules*. These rules regulate the analysis of the document image, and decide when a consistent interpretation of the document has been obtained. The rules comprising the inference engine are also formulated in terms of first-order predicates. The control structure determines the order of execution of these rules.

Control rules regulate the invocation of the knowledge rules, based on appropriate data configurations or processing states. They can be further categorized into *focus-of-attention rules* or *meta-rules*. An example control rule is shown in Figure 3 (b). Strategy rules guide the search in a more general way, i.e., they determine what control strategy is to be followed for analyzing the image. Thus, strategy rules regulate the invocation of the control rules. Strategy rules also determine the stopping criteria for the system, i.e., whether a consistent interpretation of the document image has been achieved (as determined by the absence of incomplete block or unit data in the global data structure, and by the completeness of the logical structure tree). The system control strategy algorithms are thus directly translated into a set of strategy rules. An example strategy rule is shown in Figure 3 (c).

```
IF a block Z is of type "large-text",
  OR IF it satisfies the following three conditions:
      {it is of type "medium-text",
         AND it is below another block W,
         AND block W is not of type "large-text"
               or "medium-text"},
THEN block Z is a major headline.
```

(a) Knowledge Rule

```
IF the grouping mode is on,
  AND a block has been selected,
THEN find all the immediate neighbors
       of the selected block.
```

(b) Control Rule

```
IF any partially grouped units remain,
THEN apply all unit-related control rules
       for each of these units
     until there are no more partial units.
```

(c) Strategy Rule

Figure 3: Examples of rules in DeLoS.

5 Implementation of DeLoS

DeLoS has been implemented on a Sun SPARC-2 workstation running the SunOS 4.1.3 operating system. Document images are scanned using a flatbed scanner at a resolution of 300 pixels per inch (ppi). The rule-based control structure, the knowledge base, and the global data structure are all implemented in Prolog. The image processing routines which provide the inputs to the system are implemented in C. The interaction between these sub-systems is handled via system routines and scripts which perform tasks such as translation of formats, consolidation of image data, and document-structure reconstruction.

Currently the DeLoS system's knowledge base contains 160 individual rule clauses describing the structure of newspapers and other documents. Of these, 114 are specific to newspapers, and the rest describe general characteristics of structured documents.

The basic image processing operations performed on the scanned gray-level document image include binarization, connected component analysis, image segmentation, and block type categorization. Segmentation is performed by *K*-nearest-neighbor clustering of connected components using an implementation of "docstrum" (O'Gorman [7]). The result of segmentation is that each of the printed blocks on the image is isolated and categorized as text or graphics. Further processing of the blocks information, using block size and connected component characteristics, results in the categorization of each block into a block *type*, i.e., "small-text", "medium-text", "large-text", "line-drawing", or "half-tone". The list of all the blocks in the image, giving the coordinates of their enclosing rectangle as well as the basic block type, is the input to the document logical structure derivation system.

The output from this knowledge-based system is a data representation of the logical structure of the document, i.e., a tree showing all the classified blocks in the document image, giving all the relevant extracted feature details for each block, and details of the logical unit to which the particular block belongs, as well as an ordered listing of all the text blocks in each unit. This data structure is output in the form of an editable text file that contains information about the identity, position, and other relevant properties of all the blocks and units in the image, as well as pointers between blocks to represent the reading order of the text blocks within each unit.

6 Experimental Results for DeLoS

The DeLoS system has been trained using data from page images of *The Buffalo News*, and extensively tested on data from digitized images of pages from *The Buffalo News* and *USA Today* newspapers. A test set of 44 binary images of newspaper pages (12 pages of *USA Today* and 32 pages of *The Buffalo News*) were analyzed through the system. Overall, the DeLoS system performed fairly well for images from both newspapers. Table 1 shows the performance of the system for the *USA Today* newspaper pages, in terms of percentages of the original blocks correctly classified, grouped and read-ordered. Performance results for *The Buffalo News* followed a similar pattern (and are described in detail in Niyogi [5]). The presence of noise in the original images leading to inaccurate block segmentation and type-categorization was the major reason for erroneous classification, grouping and read-ordering in our test images.

Document ID	Block Classif.	Block Grouping	Read-Ordering
Page01	96.1 %	73 %	72.7 %
Page02	96.7 %	80.6 %	92.3 %
Page03	85.1 %	100 %	100 %
Page04	84.2 %	73.6 %	87.5 %
Page05	91.3 %	82.6 %	71.4 %
Page06	85.1 %	66.6 %	80 %
Page07	88.4 %	84.6 %	100 %
Page08	100 %	94.4 %	100 %
Page09	70.3 %	85.1 %	57.1 %
Page11	100 %	97.1 %	86.6 %
Page12	82.6 %	69.5 %	83.3 %
Page13	84 %	48 %	75 %

```
BLOCK CLASSIF. = % of blocks correctly classified
BLOCK GROUPING = % of blocks correctly grouped
READ-ORDERING = % of text blocks correctly read-ordered
```

Table 1: Performance of DeLoS on *USA Today* pages.

7 Summary

We have presented a computational model for the derivation of logical structure in a document using domain knowledge about document layout. The model allows mixed-mode analysis of a document, and thus is more powerful than a simple top-down or bottom-up system. The rule-based structure is flexible enough to allow the addition of more knowledge rules to facilitate the analysis of additional document features, and the global data structure can allow the addition of more complex tree frames representing documents with varying levels of complexity or the results of more detailed document understanding methods. The multi-level rule structure also ensures efficiency in computation, since the computational time and effort required to fully analyze a document image is proportional to its quality and structural complexity. As mentioned, the approach described here has been implemented in DeLoS, a system that can derive the logical structure of a document. In doing so, we have shown that document logical structure can be represented and analyzed using layout and structural rules.

The most obvious use of the document logical structure derivation system is as a part of a comprehensive document understanding system that uses the logical structure output by our system to read the information in the individual units in a document. Applications include document browsers and document archival systems. In addition, the applications of document image understanding systems in creating intelligent digital libraries are manifold. Systems that can extract logically linked parts of a document and retrieve them on demand can significantly improve the usefulness and performance of digital document libraries.

References

[1] A. Dengel and G. Barth. ANASTASIL: A hybrid knowledge-based system for document layout analysis. In *Proc. of 11th IJCAI*, volume 2, pages 1249–1254, Detroit, MI, Aug. 20–25, 1989.

[2] J.L. Fisher, S.C. Hinds, and D.P. D'Amato. A rule-based system for document image segmentation. In *Proc. of 10th ICPR*, volume 1, pages 567–572, Atlantic City, NJ, June 16–21, 1990.

[3] K. Kubota, O. Iwaki, and H. Arakawa. Document understanding system. In *Proc. of 7th ICPR*, pages 612–614, Montreal, Canada, July 30–Aug. 2, 1984.

[4] Q. Luo, T. Watanabe, and N. Sugie. A structure recognition method for Japanese newspapers. In *Proc. of Symposium on Doc. Analysis and Info. Retrieval*, pages 217–234, Las Vegas, NV, March 16–18, 1992.

[5] D. Niyogi. *A Knowledge-Based Approach to Deriving Logical Structure from Document Images*. PhD thesis, State University of New York at Buffalo, 1994.

[6] D. Niyogi and S.N. Srihari. A rule-based system for document understanding. In *Proc. of AAAI-86*, volume 2, pages 789–793, Philadelphia, PA, August 15–22, 1986.

[7] L. O'Gorman. The document spectrum for page layout analysis. In *IAPR International Workshop on Structural and Syntactic Pattern Recognition*, Bern, Switzerland, August 1992.

[8] S.L. Taylor, M. Lipshutz, and C. Weir. Document structure interpretation by integrating multiple knowledge sources. In *Proc. of Symposium on Doc. Analysis and Info. Retrieval*, pages 58–76, Las Vegas, NV, March 16–18, 1992.

[9] S. Tsujimoto and H. Asada. Understanding multi-articled documents. In *Proc. of 10th ICPR*, volume 1, pages 551–556, Atlantic City, NJ, June 16–21, 1990.