Using domain knowledge to derive the logical structure of documents

Debashish Niyogi and Sargur N. Srihari

Center of Excellence for Document Analysis and Recognition
State University of New York at Buffalo, Buffalo, NY 14228-2567
{niyogi,srihari}@cedar.buffalo.edu

ABSTRACT

An important aspect of document understanding is document logical structure derivation, which involves knowledge-based analysis of document images to derive a symbolic description of their structure and contents. Domain-specific as well as generic knowledge about document layout is used in order to classify, logically group, and determine the read-order of the individual blocks in the image, i.e., translate the physical structure of the document into a layout-independent logical structure. We have developed a computational model for the derivation of the logical structure of documents. Our model uses a rule-based control structure, as well as a hierarchical multi-level knowledge representation scheme in which knowledge about various types of documents is encoded into a document knowledge base and is used by reasoning processes to make inferences about the document. An important issue addressed in our research is the kind of domain knowledge that is required for such analysis. A document logical structure derivation system (DeLoS) has been developed based on the above model, and has achieved good results in deriving the logical structure of complex multi-articled documents such as newspaper pages. Applications of this approach include its use in information retrieval from digital libraries, as well as in comprehensive document understanding systems.

Keywords: Document understanding, Logical structure analysis, Knowledge-based reasoning, Layout analysis, Image interpretation, Rule-based systems, Digital libraries.

1. INTRODUCTION

A *document image* is a visual representation of a printed page such as a journal article page, a magazine cover, a newspaper page, etc. Typically a document consists of blocks of text, i.e., letters, words, and sentences, that are interspersed with half-tone pictures, line drawings, and symbolic icons. A document image is therefore a digital two-dimensional array representation of a document obtained by optically scanning and raster digitizing a hard copy document. Document image *analysis* is the task of recognizing objects in an image by using techniques that extract homogeneous regions within the image. Document image *understanding* is the goal-oriented task of deriving a symbolic representation of the contents of a document image, which involves detecting and interpreting different blocks (like photographs, text, line drawings, etc.), accounting for the interactions of the different components, and coordinating the interpretations to achieve an end result.

The majority of standard printed documents conform to a certain geometric structure that dictates that the document be composed of a set of interconnecting rectangular printed regions, or blocks. Thus, there is an underlying structure for standard printed documents that is governed by certain basic constraints. First, the physical blocks into which printed documents can be spatially divided represent meaningful physical divisions of the document. Second, each of the physical blocks of printed matter can be classified according to certain basic categories like "text", "photograph", "line-drawing", etc. Third, these physical blocks can be logically grouped to make up units that represent meaningful logical entities in a document, e.g., a newspaper story, magazine article, etc. Fourth, there exists a specific order in which the text blocks within each unit must be read in order for the information in the block to make sense syntactically and semantically.

Of the above constraints, the first two are met by performing image segmentation followed by identification of the different blocks in an image. This refers to the extraction of the physical structure of the document from the image, and is known as *document layout analysis*. The last two constraints are met by performing the classification, logical grouping, and ordering of blocks. This refers to the extraction of the logical structure of the document, and is known as *logical structure derivation*.

Document layout analysis and logical structure derivation enable us to determine the relationship between the *physical* layout of a document page (consisting of the geometric structure and spatial relationships of the different blocks of printed matter) and its *logical* layout (consisting of the logical groupings of related blocks into composite units). This can then be used to actually "translate" a physical document into its logical symbolic representation.

The logical structure of a document is independent of the physical layout of the printed document, and is defined in terms of the logical entities into which a document is divided. Figure 1 shows the graphical representation of the logical structure for a typical document.



Figure 1: Logical structure of a document.

The transformation of the physical structure of a document into the logical structure is a critical component of document image understanding. Currently this transformation process is not very well defined, especially for complex multi-articled documents such as newspapers. Therefore, our objective has been to develop a methodology for the physical-to-logical structure transformation of a document (i.e., from a digitized image to an editable file containing a complete symbolic description of the document).

The steps involved in transforming a scanned image of a physical document into its logical description are:

1. Physical segmentation of the image into its constituent "blocks".
2. Categorization of each of these blocks into block types or categories.
3. Labeling of these blocks according to their specific identities.
4. Logical grouping of these blocks into logical "units".
5. Determining the reading order of text blocks within each unit.
6. Translation of the block and unit information into an editable symbolic description of the logical structure of the document.

The logical description of a document is represented as a tree structure (with the entire document as the root node and individual blocks as leaf nodes), and is contained in a text file that can be edited using a standard text editor.

Document logical structure derivation is also a crucial step in the development of *digital document libraries*. Extraction of the logical structure of a document will enable individual logical components to be stored separately in digital libraries, thus making their indexing and access much faster and easier.

The domain used for this work is primarily that of newspaper images. Newspapers provide a wide variety of layouts that are determined according to editorial conventions and are therefore extremely interesting for our analysis purposes. The formatting of newspaper pages is more complicated than, for instance, office documents, and provides an opportunity for developing a wider variety of interesting techniques.

2. BACKGROUND

The application of knowledge-based techniques to document image understanding has been discussed by several researchers. For example, Kubota et al.[4] describe the application of a production system concept to an experimental document understanding system, and Fisher et al.[3] describe a rule-based system for segmenting a document image into text and non-text blocks. Rule-based systems used in the document image domain, however, have not fully exploited the depth and breadth of knowledge that is available about specific document domains.

Document layout analysis involves the extraction of the physical structure of a document. Various researchers have worked on the interpretation of office documents through the classification of the blocks in a document image, including Dengel & Barth.[2] Layout analysis has also long been an area of interest to magazine and newspaper editors. Books by Arnold[1] and White,[16] among others, provide important heuristics about the structural make-up of different kinds of published documents.

Document image understanding involves the syntactic and semantic interpretation of the various components of a document image, and requires domain knowledge about document features and characteristics. Nagy[6] describes the types of knowledge required for document image understanding. Also, various approaches to the solution of this problem have been proposed, such as those by Taylor et al.,[14] who have used multiple knowledge sources and a blackboard control architecture to derive document structure and then used linguistic knowledge to label various document components. Luo et al.[5] have used a rule-based approach to interpreting the physical and logical structure of Japanese newspaper pages, and Tsujimoto & Asada[15] have suggested a rule-based method for deriving the physical and logical structures of a multi-articled document.

Our approach not only infers the labels of the blocks in the image and groups these blocks, but also determines the logical reading order of the text blocks in each unit, thus enabling a document reader to read the different blocks comprising a story or article in the appropriate order. Also, most previous work deals with office documents, or with pages from technical journals (Japanese newspapers have also been used by some, but only for logical labeling). We have analyzed newspaper images, which are structurally more complicated than office documents, since a newspaper page typically contains several units which are structurally related but not logically related to one another.

3. A FRAMEWORK FOR DOCUMENT STRUCTURE ANALYSIS

The physical structure of a document reflects the layout of different geometrical units within the document in a specific presentation format. The basic element of the physical structure of a document is a "block", which is defined as a homogeneous geometric region of printed matter in the document (i.e., each connected component within a block is of similar type and size). Blocks are separated from one another by regions of white space.

Newspapers are examples of complex documents. Each page of a newspaper typically contains many blocks of textual or graphical information, arranged so that each rectangular block of information is interconnected with its adjacent blocks so as to make a grid-like pattern of blocks on the page. The syntax of the physical structure of a typical newspaper page is shown (in Extended BNF format) in Figure 2 (a).

```
<document>  ::=  { <page> }
<page>      ::=  { <block> }
<block>     ::=  <large-text> | <medium-text> | <small-text> |
                           <line-drawing> | <half-tone> | <boundary>
<boundary>  ::=  <horizontal-line> | <vertical-line> | <line-rectangle>
```

(a) Physical structure

```
<document info>  ::=  { <unit> }
<unit>           ::=  <title> | <graphical area> | <story> | <photoblock>
<photoblock>     ::=  [ <title> ] <photo> <caption>
<graphical area> ::=  <page banner> | <horizontal band> | <other graphics>
<story>          ::=  [ <sub-story> ] | <title> [ <sub-title> ]
                                    { <text-para> } [ <photoblock> ]
                                    [ [ <title> ] <chart> <caption> ]
                                    [ [ <title> ] <table> <caption> ]
<sub-story>      ::=  <story>
```

(b) Logical structure

Figure 2: Syntax of physical and logical structures of a typical newspaper.

The logical structure of a document reflects the hierarchy of logical units that comprise the document. Each logical unit is itself a composite of text or graphics elements. Logical structure is layout-independent; i.e., the contents of a newspaper story and of the various components in the story (e.g., text, photograph, caption, etc.), as well as the semantic relations between these components, are not affected by the manner in which the story is geometrically arranged on the newspaper page. The syntax of the logical structure of a typical newspaper page is shown in Figure 2 (b).

Layout rules may vary widely among different types of documents. Thus, spatial relationships between blocks in the title page of a journal article are likely to be different from those in a newspaper page, and even more different from a pre-printed form. Also, the identities of the blocks in these different types of documents are likely to be different. Thus, a knowledge base of layout rules for document logical structure derivation will contain some global rules that apply to a majority of documents and some domain-specific rules that apply only to the class of document being analyzed. In the case of newspaper images, for example, a knowledge base of layout rules will contain spatial rules that can be inferred from newspaper layouts. Examples are:

1. Captions are below photographs, unless two or more photographs have a common caption.
2. Thin vertical lines are column separators.

We have developed a computational model for the derivation of logical structure of a document. The model involves strategies for extracting the physical structure of a document (i.e., layout analysis), translating into the logical structure (i.e., logical structure derivation), and representing the logical structure in an appropriate symbolic form suitable for use by other processes that perform deeper levels of document understanding (e.g., text reading). The formalisms used in the design of this computational model are discussed in detail in Niyogi.[8] Figure 3 shows a schematic diagram of the computational model.



Figure 3: Computational model for logical structure derivation.

The computational model for deriving logical structure has the following components: a process for classifying all the distinct blocks in an image, a process for grouping these blocks into logical units, a process for determining the read-order of the text blocks within each logical unit, a control mechanism that monitors the above processes and creates the logical representation of the document, a knowledge base containing knowledge about document layout and structure, and a global data structure that maintains the domain and control data.

4. DELOS: A LOGICAL STRUCTURE DERIVATION SYSTEM

We have also developed and implemented a knowledge-based system for the derivation of document logical structure based on the computational model described in Section 3. This system, called DeLoS ("*De*rivation of *Lo*gical *S*tructure") takes as input the digitized image of a newspaper page and produces as output a symbolic description of the logical structure of the page. Data obtained by performing various image processing operations on the image is analyzed under the control of a rule-based system, which uses a global data structure to monitor the entire classification, grouping, and block-ordering process. The rule-based system is an enhancement of the one outlined in Niyogi,[10] and the computational model has been recently described in Niyogi.[9] Figure 4 shows the components of the DeLoS system.



Figure 4: The DeLoS logical structure derivation system.

The DeLoS system consists of a multi-level, rule-based reasoning system, an image processing sub-system, and a partitioned global data structure. The rule-based system utilizes a top-down, backward-chaining structure. An inference engine within the rule-based system makes deductions about the document using a hierarchical knowledge base that contains rules describing all the identifiable characteristics of document images. The global data structure facilitates the transfer of information from the image processing modules to the rule-based system. A common data area stores all intermediate computation results and other control information. The sub-processes that access and modify the data are sets of rules that are activated within the system's rule-invocation structure.

The image-processing modules directly access the document image to extract various kinds of information about the document. Intrinsic properties of the different printed blocks as well as the spatial relationships between the different blocks constitute the information that is passed back to the control structure through the global data structure.

The rule-based system consists of three levels of rules. (The three-level rule structure for this system was inspired by Nazif and Levine's work[7] on low-level image segmentation of natural scenes, which demonstrated that using a hierarchical structure of three progressively abstract levels of rules provided a large amount of flexibility in the inference mechanism, and allowed a modular formulation of the solution within the image analysis problem domain.) The three levels into which the rules in our system are classified are: Knowledge Rules (level 1), Control Rules (level 2), and Strategy Rules (level 3).

The *knowledge rules* comprise the knowledge base that contains all the domain knowledge for the system. These rules define the general characteristics expected of the usual components of a document image and the usual relationships between such components. Thus, all common characteristics of different types of document blocks (e.g., text blocks, photographs, etc.), as well as spatial constraints commonly followed in document layout (e.g., the positioning of captions relative to photographs, etc.), are encoded into the knowledge base. These knowledge rules can be used for block classification, block grouping, or text block ordering as and when required according to the control strategy.

The control structure for the rule-based system contains an inference engine which is also rule-based, and contains two levels of rules: *control rules* and *strategy rules*. These rules regulate the analysis of the document image, and decide when a consistent interpretation of the image has been obtained. The control structure determines the order in which these rules are executed in order to test various conditions effectively. Control rules regulate the invocation of the knowledge rules, based on appropriate data configurations or processing states.

Strategy rules guide the search in a more general way, i.e., they determine what control strategy is to be followed at any given time for analyzing the image. This means that the strategy rules regulate the invocation of, and determine the execution order of, the control rules. Strategy rules also decide on the stopping criteria for the system, i.e., whether a consistent interpretation and grouping of the blocks in the document image has been achieved (as determined by the absence of incomplete block or unit data in the global data structure, and by the completeness of the logical structure tree). Therefore, there is a set of strategy rules for block classification, another set for block grouping, and yet another for text block ordering.

The global data structure stores the physical structure and logical structure information for the document being processed. It also facilitates the transfer of information between the rule-based system and the image processing modules. A common data area stores all intermediate computation results and control information, and provides the framework for the construction of trees representing the document structures.

The input image data is initially represented as a list of blocks with their physical properties and their type. The physical structure tree is created from this list of blocks. Each block in the image data is represented by a frame. There are two kinds of frames: *block frames* represent physical characteristics of document blocks and are thus structural in nature; *unit frames* are more conceptual in nature, and represent the logical groupings of the different document blocks. Unit frames and block frames, when the slots are all filled in, make up a tree of frames, since each unit is a parent to several blocks or other sub-units. Thus, a tree structure is created, whose root node is the unit frame representing the entire document page, and all other nodes are either unit frames representing logical subdivisions of the page, or block frames representing physical blocks of printed matter in the page. The above representation therefore allows us to specify logical sub-units of a given unit. For example, a given story on a particular topic with one major headline may have sub-stories under separate minor headlines. The system, by allowing unit frames to be child nodes of other unit frames, allows us to efficiently represent such a hierarchy among the stories on a document page.

5. THE DELOS KNOWLEDGE BASE

The knowledge base in the DeLoS system contains rules that encapsulate the knowledge about document structure as well as block and unit properties for documents. The DeLoS system primarily concentrates on a specific class of documents, namely, newspapers, so as to achieve as high a degree of accuracy as possible. The reasoning behind this decision is that with a modular design for the system, an equivalent set of publication-specific rules for another document class can be substituted for the current set, and thus a comparably accurate system can be created that can process any document from that document class.

To ensure the above-mentioned modularity in the system, the knowledge base is conceptually divided into two parts: *Domain, or Publication-specific, Knowledge*, i.e., knowledge that applies to a specific class of documents, and *Document World Knowledge*, i.e., knowledge that applies to a wide variety of documents. As mentioned in Section 1, there are certain properties common to most classes of documents and some others that are specific only to a particular class of documents. Thus, the two conceptual parts of the knowledge base codify these different types of knowledge.

Domain knowledge is knowledge that describes specific characteristics of different classes of documents. Thus, different kinds of domain knowledge exists for newspapers, journals, magazines, forms, office documents, etc. The domain that the DeLoS system deals with is that of newspaper images. In the DeLoS system, publication-specific knowledge about *The Buffalo News* and *USA Today* has been encoded into knowledge rules in the knowledge base. Figure 5 shows rules in the DeLoS system that use domain knowledge about story bylines in newspaper articles. The first rule classifies a story byline by its position with respect to other adjacent blocks. The second rule groups the story byline with its appropriate adjacent blocks.

```
IF block B1 is a headline,
    AND IF block B2 is below B1,
    AND IF B2 is a text block,
    AND IF block B3 is below B2,
    AND IF B3 is a horizontal line,
    AND IF block B4 is below B3,
    AND IF B4 is a text block,
THEN block B2 is a story byline.
```

(i) Classification Rule

```
IF block B1 is a headline,
    AND IF block B2 is below B1,
    AND IF block B2 is a story byline,
    AND IF block B3 is below B2,
    AND IF block B3 is a horizontal line,
    AND IF block B4 is below B3,
    AND IF block B4 is a text block,
THEN blocks B1, B2, B3 and B4 belong to the same unit.
```

(ii) Grouping Rule

Figure 5: Rules that use domain knowledge.

Document world knowledge is knowledge that is required for the analysis of a document but which does not specifically describe a particular document being analyzed. This includes knowledge about general image characteristics common to all classes of documents, as well as information that is required for model-based analysis of any type of document image. In the DeLoS system, document world knowledge is encoded into knowledge rules in the knowledge base, as well as incorporated into the control structure in terms of control and strategy rules. This knowledge includes details of the general properties of documents, as well as strategies for traversal of blocks within a document. Figure 6 shows rules in the DeLoS system that use world knowledge about document structure. The first rule indicates that if a vertical line is present between two other blocks, one of which is a headline, then those two blocks belong to different units. The second one is the simplest read-ordering rule for text blocks (i.e., read-order is top-to-bottom for text blocks within the same column).

6. IMPLEMENTATION OF DELOS

The document logical structure derivation system (DeLoS) described here has been implemented on a Sun SPARC-2 workstation running the SunOS 4.1.3 operating system. Document images are scanned using a flatbed scanner at a resolution of 300 pixels per inch (ppi), and the resulting bitmap of the document in Sun raster format is converted into HIPS (a Unix-based image processing format) prior to any further processing.

```
IF block B1 is a headline,
    AND IF block B2 is right-of B1,
    AND IF B2 is a vertical line,
    AND IF block B3 is right-of B2,
THEN blocks B1 and B3 do not belong to the same unit.
```

(i) Grouping Rule

```
IF block B1 is a text block,
    AND IF block B2 is a text block,
    AND IF B2 is a neighbor of B1,
    AND IF B2 is below B1,
    AND IF B1 and B2 have equal width,
THEN B2 is next in read-order after B1.
```

(ii) Read-ordering Rule

Figure 6: Rules that use document world knowledge.

The rule-based control structure, being primarily a top-down backward-chaining system, is implemented in Prolog, and so is the knowledge base as well as the global data structure and the routines enabling its interaction with the rule-based system. The image processing routines are implemented in C. The interaction between these sub-systems is handled via system routines which perform tasks such as translation of formats, consolidation of image data, and document-structure reconstruction. Because of the modularity of the system design, this system interface is implemented in a fairly efficient manner in Prolog. Currently the DeLoS system's knowledge base contains 160 individual rule clauses describing the structure of newspapers and other documents. Of these, 114 are specific to newspapers, and the rest describe general characteristics of structured documents.

The basic image processing operations performed on the scanned gray-level document image include binarization, connected component analysis, image segmentation, and block categorization. The original, gray-level document image obtained by scanning the physical document is first converted from the original Sun raster format to the HIPS format. It is then binarized using an adaptive thresholding algorithm. Then, connected component analysis is performed on the binary image. Next, segmentation is performed on the image using the connected component data, by a method known as "docstrum" (originally proposed by O'Gorman[11]) which uses K-nearest-neighbor clustering of connected components.

The result of segmentation is that each of the printed blocks on the image is isolated and categorized as text or graphics. Further processing of the blocks information, using block size and connected component characteristics, results in the categorization of each block into a block *type*, i.e., "small-text", "medium-text", "large-text", "line-drawing", or "half-tone". The list of all the blocks in the image, giving the coordinates of their enclosing rectangle as well as the basic block type, is the input to the knowledge-based document logical structure derivation system.

The primary output from this knowledge-based system is a data representation of the logical structure of the document, i.e., a tree showing all the classified blocks in the document image, giving all the relevant extracted feature details for each block, and an indication of the logical unit to which the particular block belongs, as well as an ordered listing of all the text blocks in each unit. This data structure is output in the form of an editable text file that contains information about the identity, position, and other relevant properties of all the logical blocks in the image, as well as the logical groupings of these blocks into logical units. In addition to this, the output also contains pointers between blocks to represent the reading order of the text blocks within each unit.

7. EXPERIMENTAL RESULTS

The DeLoS system has been tested on a variety of pages from *The Buffalo News* and *USA Today.* A total of 44 binary images of newspaper pages (12 images of pages of *USA Today* and 32 images of pages of *The Buffalo News*) were analyzed through the system. Overall, the DeLoS system performed fairly well for images from *The Buffalo News* as well as *USA Today.* Table 1 shows the performance of the system for *The Buffalo News* newspaper pages, in terms of percentages of the original blocks correctly classified, grouped and read-ordered. Performance results for *USA Today* followed a similar pattern (and have been described in detail in Niyogi[8]).

Block segmentation and block type-categorization in the original images proved to be an important factor in the performance of the system. The "docstrum" program when run on the original binary images gave only the text blocks accurately, and categorized most of the headline blocks as graphics. The connected components comprising these blocks were then extracted and "docstrum" was re-run on these components, which then yielded a more accurate categorization of medium-sized text blocks (corresponding to minor headlines) and large-sized text blocks (corresponding to major headlines). Also, since graphical blocks often have similar geometrical extents as rectangular enclosing rectangles, the latter were categorized by computing the block's pixel density *pixden*, which is defined as the ratio of the number of pixels in the block to the area of the block. A very low value of *pixden* indicates an enclosing rectangle. In addition, horizontal and vertical lines were categorized by recognizing blocks which had a very small height or width respectively.

A few block segmentation errors remained even after further processing of the "docstrum" segmentation output as described above. In particular, touching blocks or text blocks in very close proximity (e.g., photo credits whose letters touched the photograph boundary, photo credits that were very close to the photo caption, etc.) were merged together by the segmentation process. Such errors influenced the accuracy of the DeLoS block classification process, and thus carried over into the block grouping and read-ordering processes as well. This can be remedied by re-segmenting the image using modified parameters based on feedback from the logical structure derivation process.

8. CONCLUSIONS

We have presented a computational model for the derivation of logical structure of a document using domain knowledge about document layout. In this model, domain and world knowledge about document structure is used to analyze the document. The rule-based structure is flexible enough to allow the addition of more knowledge rules to facilitate the analysis of additional document features, and the global data structure can allow the addition of more complex tree frames representing documents with varying levels of complexity or the results of more detailed document understanding methods. The multi-level rule structure also ensures efficiency in computation, since the computational time and effort required to fully analyze a document image is proportional to its quality and structural complexity.

As mentioned, the approach described here has been implemented in DeLoS, a system that can derive the logical structure of a document. We have shown through the development of the model and the results obtained from the implementation of the DeLoS system that:

- The geometric structure of a document can be translated into rules.
- The logical structure of different types of documents can similarly be encoded into rules.
- The logical structure of a document page can be derived from the physical structure by the application of these structural and semantic rules.

The most obvious use of the document logical structure derivation system is as a part of a comprehensive document understanding system that uses the logical structure information output by this system to read the

Document ID	Block Classif.	Block Grouping	Read-Ordering
BN-01	91.1 %	79.4 %	100 %
BN-02	96.9 %	93.9 %	100 %
BN-03	74.5 %	54.9 %	60 %
BN-04	89.1 %	83.7 %	100 %
BN-05	87.8 %	82.9 %	100 %
BN-06	91.4 %	85.7 %	90 %
BN-07	86.4 %	83.7 %	100 %
BN-08	88.5 %	82.8 %	87.5 %
BN-09	96.6 %	86.6 %	100 %
BN-10	90.9 %	81.8 %	90.9 %
BN-11	96.2 %	88.8 %	100 %
BN-12	96.8 %	87.5 %	83.3 %
BN-13	97.1 %	94.2 %	87.5 %
BN-14	86.2 %	86.2 %	100 %
BN-15	93.5 %	87 %	100 %
BN-16	86.6 %	80 %	100 %
BN-17	95 %	87.5 %	100 %
BN-18	97.5 %	90 %	75 %
BN-19	97.2 %	89.1 %	100 %
BN-20	90.9 %	79.5 %	100 %
BN-21	90.6 %	87.5 %	83.3 %
BN-22	95.6 %	91.3 %	75 %
BN-23	93.4 %	86.9 %	88.8 %
BN-24	96.7 %	90.3 %	71.4 %
BN-25	97.1 %	94.2 %	100 %
BN-26	97.2 %	91.8 %	88.8 %
BN-27	93 %	86 %	100 %
BN-28	88.2 %	82.3 %	87.5 %
BN-29	96.7 %	93.5 %	100 %
BN-30	91.4 %	85.1 %	100 %
BN-31	92.6 %	87.8 %	100 %
BN-32	96.9 %	90.9 %	85.7 %

```
BLOCK CLASSIF. = % of blocks correctly classified
BLOCK GROUPING = % of blocks correctly grouped
READ-ORDERING = % of text blocks correctly read-ordered
```

Table 1: Performance of DeLoS on pages of *The Buffalo News*.

information in the individual units in a document. Applications include document browsers and document library archival systems. In addition, the applications of document image understanding systems in creating intelligent digital libraries are manifold. Systems that can extract logically linked parts of a document and retrieve them on demand can significantly improve the usefulness and performance of document libraries. To this end, document logical structure derivation is an integral step towards the creation and organization of any intelligent digital document library.

Extensions to the document logical structure derivation system that are being pursued for future research work include multi-page logical grouping, linking non-adjacent blocks to logically grouped units, and semantic analysis for read-order determination.

9. REFERENCES

1. E.C. Arnold. *Modern Newspaper Design.* Harper and Row, New York, 1969.

2. A. Dengel and G. Barth. ANASTASIL: A hybrid knowledge-based system for document layout analysis. In *Proc. of 11th IJCAI*, volume 2, pages 1249–1254, Detroit, MI, Aug. 20–25, 1989.

3. J.L. Fisher, S.C. Hinds, and D.P. D'Amato. A rule-based system for document image segmentation. In *Proc. of 10th International Conference on Pattern Recognition*, volume 1, pages 567–572, Atlantic City, NJ, June 16–21, 1990.

4. K. Kubota, O. Iwaki, and H. Arakawa. Document understanding system. In *Proc. of 7th International Conference on Pattern Recognition*, pages 612–614, Montreal, Canada, July 30–Aug. 2, 1984.

5. Q. Luo, T. Watanabe, and N. Sugie. A structure recognition method for Japanese newspapers. In *Proc. of Symposium on Document Analysis and Information Retrieval*, pages 217–234, Las Vegas, NV, March 16–18, 1992.

6. G. Nagy. What does a machine need to know to read a document? In *Proc. of Symposium on Document Analysis and Information Retrieval*, pages 1–10, Las Vegas, NV, March 16–18, 1992.

7. A.M. Nazif and M.D. Levine. Low level image segmentation: An expert system. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, PAMI-6(5):555–577, September 1984.

8. D. Niyogi. *A Knowledge-Based Approach to Deriving Logical Structure from Document Images.* PhD thesis, State University of New York at Buffalo, 1994.

9. D. Niyogi and S.N. Srihari. Knowledge-based derivation of document logical structure. In *Fifth International Conference on Document Analysis and Recognition (ICDAR '95)*, pages 472–475, Montreal, Canada, August 14-16, 1995.

10. D. Niyogi and S.N. Srihari. A rule-based system for document understanding. In *Proceedings of AAAI-86*, volume 2, pages 789–793, Philadelphia, PA, August 15–22, 1986.

11. L. O'Gorman. The document spectrum for page layout analysis. In *IAPR International Workshop on Structural and Syntactic Pattern Recognition*, Bern, Switzerland, August 1992.

12. S.N. Srihari. Document image understanding. In *Proc. of ACM-IEEE Computer Society 1986 Fall Joint Computer Conference*, pages 87–96, Dallas, TX, November 2–6, 1986.

13. Y.Y. Tang, C.Y. Suen, C.D. Yan, and M. Cheriet. Document analysis and understanding: a brief survey. In *Proc. of ICDAR-91*, pages 17–31, Saint-Malo, France, Sept. 30–Oct. 2, 1991.

14. S.L. Taylor, M. Lipshutz, and C. Weir. Document structure interpretation by integrating multiple knowledge sources. In *Proc. of Symposium on Document Analysis and Information Retrieval*, pages 58–76, Las Vegas, NV, March 16–18, 1992.

15. S. Tsujimoto and H. Asada. Understanding multi-articled documents. In *Proc. of 10th International Conference on Pattern Recognition*, volume 1, pages 551–556, Atlantic City, NJ, June 16–21, 1990.

16. J.V. White. *Editing By Design.* R.R. Bowker Company, New York, 2nd edition, 1982.