

Algorithm-Independent Machine Learning

No Free Lunch Theorem

Ugly Duckling Theorem

Algorithm-Independent

- Mathematical Foundations that do not depend upon any particular classifier or learning algorithm used
- Techniques used in conjunction with different learning algorithms or provide guidelines in their use
 - E.g., cross-validation and resampling

No Free Lunch Theorem

- Lack of inherent superiority of any classifier
- If we make no prior assumption about the nature of the classification task, is any classification method superior overall?
- Is any algorithm overall superior to random guessing?
- Answer is No

No Free Lunch for Binary Data

	x	F	h1	h2
	000	1	1	1
<i>D</i>	001	-1	-1	-1
	010	1	1	1
	011	-1	1	-1
	100	1	1	-1
	101	-1	1	-1
	110	1	1	-1
	111	1	1	-1

h1: other than training data
always assigns to class1

h2: other than training
always assigns to class2

Off-training set errors:


$E1=0.4$, $E2=0.6$ or

h1 superior to **h2**

Averaged over all target
functions there is no
difference in off-training
set errors

No Free Lunch Theorem

Each square represents set of all classification problems



- + means higher than average generalization accuracy
- Means lower than average generalization accuracy
- 0 means average generalization accuracy

No Free Lunch Theorem




- Learning algorithm 1 is better than learning algorithm 2 are ultimately statements about the relevant target functions
- Experience with a broad range of techniques is the best insurance for solving arbitrary new classification problems

Ugly Duckling Theorem

- No-Free Lunch addresses learning or classification
- In the absence of assumptions there is no “best” feature representation

Patterns represented by Venn diagrams

Binary features f_i



f_1 represents **has_legs**

f_2 represents **has_right_arm**

f_3 represents **has_right_hand**


Pattern x_1 denotes person who has legs but no arm or hand

f_i represent eye colors
brown, green, blue

Venn diagrams represent biological constraints associated with real people

Most general Venn diagram with 2 features

For every configuration of f_1 and f_2 there is a pattern



Assuming each x_i is treated as binary-valued **Predicates:**

x_1 , $x_1 \text{ OR } x_2$, $x_1 \text{ OR } x_2 \text{ OR } x_4$

There are 2^{2^n} predicates of n binary features, or 16 above

Predicates of 2 binary features

4 Predicates of rank 1: x_1, x_2, x_3, x_4

f1	f2	$X_1=f_1 \text{ AND } \text{NOT} f_2$	$X_2=f_1 \text{ and } f_2$	$X_3=f_2 \text{ AND } \text{NOT } f_1$	$X_4=\text{NOT}(f_1 \text{ OR } f_2)$
0	0	0	0	0	1
0	1	0	0	1	0
1	0	1	0	0	0
1	1	0	1	0	0

Predicates of Rank 1 are the patterns themselves x_1, x_2, x_3, x_4

6 Predicates of rank 2:

$x_1 \text{ OR } x_2, x_1 \text{ OR } x_3, x_1 \text{ OR } x_4, x_2 \text{ OR } x_3, x_2 \text{ OR } x_4, x_3 \text{ OR } x_4$

4 Predicates of rank 3:

$x_1 \text{ OR } x_2 \text{ OR } x_3, x_1 \text{ OR } x_2 \text{ OR } x_4, x_1 \text{ OR } x_3 \text{ OR } x_4, x_2 \text{ OR } x_3 \text{ OR } x_4,$

Patterns sharing predicates

- Considering an arbitrary pair of patterns x_i and x_j
- There are no predicates of rank 1 shared by two patterns
- One predicate, x_i of rank 2: $x_i \text{OR} x_j$
- Two predicates of rank 3
- Total number of predicates shared by two patterns is 2^{d-2} where $d = 4$ in this example
- This is a constant

Ugly Duckling Theorem

- If we judge similarity based on the number of predicates the patterns share, then any two patterns are equally similar
- Even the simple notion of similarity is fundamentally based on the implicit assumptions of problem domain