

# Resampling for Estimation

Sargur Srihari

[srihari@cedar.buffalo.edu](mailto:srihari@cedar.buffalo.edu)

# Topics

- Training, Testing and Validation
- Small sample Size Issues
- Cross-Validation
- Jackknife Estimation
- Bootstrap Estimation
- References

# Training, Testing, Validation


- Predicting performance is the issue
- Partition data into 3 sets: Training Data, Validation Data, Test Data
- Training data is used for design
  - Determining parameters in Bayes
  - Samples used in Nearest-neighbor or SVM
  - Determining weights in a neural network using backprop
  - Determining coefficient vector in polynomial regression
- To avoid overfitting we use validation data
  - To determine no of iterations in neural network
- Final testing is done on Testing Set

# Small Sample Size Issues

- When supply of data for training and testing sets is limited
- Wish to use as much of data for training as possible
- If validation set is small will get noisy predictive performance (in regression)
- One solution to dilemma is to use cross validation

# S-fold Cross Validation

Held-out  
group



Run 1				
Run 2				
Run 3				
Run 4				

- Data ( $N$  samples) is partitioned into  $S$  groups (here  $S=4$ )
- $S-1$  groups are used to train a set of models that are evaluated on the remaining group
- Repeat for all  $S$  possible choices for the held-out group
- Performance for the  $S$  runs are averaged
- When data is scarce, with  $S=N$  we get the *Leave-one-out* method

# Disadvantages of Cross Validation

- Computationally Expensive
  - Number of training runs to be performed increases by a factor of  $S$
- Multiple complexity parameters for a single model
  - regularization parameters
- Need measure of performance which depends on training data and does not suffer from bias due to overfitting
  - Akaike Information Criterion  $\ln p(D/W_{ml}) - M$
  - Involves *best fit log-likelihood* and  $M$  is *no of free parameters*

# Jackknife Estimate of Parameters

- Not same as estimating classifier accuracy
- Resampling to yield more informative estimate of a general statistic
- Standard Estimate for Mean and Jackknife estimate are the same:

Sample mean

$$\hat{\mu} = \frac{1}{n} \sum_{i=1}^n x_i$$

Leave one out mean

$$\mu_{(i)} = \frac{1}{n-1} \sum_{j \neq i}^n x_j = \frac{n \hat{\mu} - x_i}{n-1}$$

$$\mu_{(\cdot)} = \frac{1}{n} \sum_{i=1}^n \mu_{(i)}$$

# Boot Strap Estimate of Parameters

- Bootstrap dataset is created by randomly selecting  $n$  points from the training set  $D$
- Because  $D$  itself contains  $n$  points there is nearly always duplication of individual points in a bootstrap set
- The process is repeated  $B$  times to yield  $B$  bootstrap datasets
- The mean of the  $B$  estimates is the estimate of the statistic



# References

- Bishop, 2006
- Duda, Hart and Stork 2001