Software Frameworks for Machine Learning

Sargur N. Srihari srihari@cedar.buffalo.edu

Topics

- Python
- Python versus C++
- ML Frameworks
- Tensorflow

Python

- Python
 - widely used high-level, general-purpose, *interpreted*, dynamic *programming* language.
 - Its design philosophy emphasizes code readability, and its syntax allows *programmers* to express concepts in fewer lines of code than would be possible in languages such as C++ or Java

Example of Python Code

• Problem: Count no of vowels in string

Assume s is a string of lower case characters.

Write a program that counts up the number of vowels contained in the string s.

Valid vowels are: 'a', 'e', 'i', 'o', and 'u'.

For example, if s = 'azcbobobegghakl', your program should print: *Number of vowels:* 5

- Code is given next
 - See

https://medium.com/cyberdoggo/mit-6-00-1x-problem-set-1-c5ba79ae2aad 4

Machine Learning

Python Code for vowel count

```
# variable s is predefined
```

define and set variable vowelCount to 0

```
vowelCount = 0
```

```
\ensuremath{\texttt{\#}} create a for loop to iterate through each character of s
```

for letter in s:

```
# if letter in s equal to each vowel, increment vowelCount by 1
if letter == "a":
    vowelCount += 1
elif letter == "e":
    vowelCount += 1
elif letter == "i":
    vowelCount += 1
elif letter == "o":
    vowelCount += 1
elif letter == "u":
    vowelCount += 1
```

```
# print the concatenated first string and vowelCount
print("Number of vowels: " + str(vowelCount))
```

Srihari

NumPy

- NumPy
 - an extension to the Python programming language
 - adds support for large, multi-dimensional arrays and matrices,
 - along with a large library of high-level mathematical functions to operate on these arrays.

Python vs C++

• FizzBuzz:

- Print i = 1 to 100, except:
 - if divisible by 3 print fizz,
 - if divisible by 5 print buzz,
 - if divisible by both 3 and 5 print fizzbuzz
- Code in C++ and Python:

```
1 #include <iostream>
    using namespace std;
 2
    int main()
 4 - {
 5 🔻
         for(int i=1;i<=100;i++){</pre>
 6
              if((i \otimes 3 == 0) \otimes (i \otimes 5 == 0))
 7
                   cout<<"FizzBuzz\n";</pre>
 8
              else if(i%3 == 0)
 9
                   cout<<"Fizz\n";</pre>
10
              else if(i%5 == 0)
11
                   cout<<"Buzz\n";
12
              else
13
                   cout<<i<"\n";</pre>
14
          }
15
         return 0;
16 }
```

```
# Enter your code here. Read input from STDIN. Print output to STDOUT
 2 for i in range(101):
        if i==0:
 3 🔻
 4
            continue
        elif i%15==0:
 5 🔻
 6
            print 'FizzBuzz'
        elif i%5==0:
 7 🔫
 8
            print 'Buzz'
 9 🚽
        elif i%3==0:
            print 'Fizz'
10
11 -
        else:
12
            print i
```

Python

Interpreted language, emphasizes code readability fewer lines of code than C++ or Java

NumPy

an extension to Python: library of functions to operate on arrays.

What are ML frameworks?

- Frameworks offer building blocks for designing, training and validating deep neural networks, through a high level programming interface
 - Optimized for performance
 - Provide parallelization for implementation on GPUs
 - Visualization of network modeling and interface

Srihari

Feedforward Networks

Discriminative Models



Generative Models



Generative Adversarial Network (GAN)













Probablistic Hidden Cell

Spiking Hidden Cell

Output Cell

Match Input Output Cell



Memory Cell

Different Memory Cell

Kernel





Srihari

Machine Learning Frameworks



Framework differences

- 1. Theano (terminated in 2018)
 - $-\operatorname{NumPy}{-}{\text{like numerical computation for CPU/GPUs}}$
- 2. Tensorflow (Google)
 - Large-scale deployment (cross-platform, embedded)
- 3. PyTorch (Facebook)
 - GPU enabled drop-in replacement for NumPy
 - For rapid prototyping
 - Dynamic computational graphs
- 4. Gluon (AWS, Microsoft)
 - Model and training algorithms brought closer,
 - High performance training

PyTorch

- PyTorch is essentially a GPU enabled drop-in replacement for NumPy
- Equipped with higher-level functionality for building and training deep neural networks.
 - This makes PyTorch especially easy to learn if you are familiar with NumPy, Python and the usual deep learning abstractions
 - (convolutional layers, recurrent layers, SGD, etc.).

PyTorch vs TensorFlow

- PyTorch is better for rapid prototyping in research, for hobbyists and for small scale projects.
- TensorFlow is better for large-scale deployments, especially when cross-platform and embedded deployment is a consideration
- See https://awni.github.io/pytorch-tensorflow/

Keras

- Keras is a higher-level API with a configurable back-end. IN 2018 TensorFlow, Theano and CNTK are supported not PyTorch.
- Keras is also distributed with TensorFlow as a part of tf.contrib.
- Keras API is especially easy to use. It's one of the fastest ways to get running with many of the more commonly used deep neural network architectures.
 - API is not as flexible as PyTorch or core TensorFlow.

Machine Learning

Tensorflow Fold

- DLwith dynamic computation graphs
 - <u>https://research.googleblog.com/2017/02/announcing-</u> tensorflow-fold-deep.html
- In much of machine learning, data used for training and inference undergoes a preprocessing step, where multiple inputs (such as images) are scaled to the same dimensions and stacked into batches. This lets high-performance deep learning libraries like <u>TensorFlow</u> run the same <u>computation graph</u> across all the inputs in the batch in parallel. Batching exploits the <u>SIMD</u> capabilities of modern GPUs and multi-core CPUs to speed up execution. However, there are many problem domains where the size and structure of the input data varies, such as parse trees in natural language understanding, abstract syntax trees in source code, DOM trees for web pages and more. In these cases, the different inputs have different computation graphs that don't naturally batch together, resulting in poor processor, memory, and cache utilization.
- TensorflowFold addresses these challenges

Natural Language Toolkit

- Import nltk
- Moby=nltk.text.Text(nltk.corpus.gutenberg. words('melville-moby_dick.txt'))
- print(moby.common_contexts("ahab")

Fizzbuzz using a simple MLP

– Given supervised output

1,2,Fizz,4,Buzz,7,8,Fizz,Buzz,11,Fizz,13,14,FizzBuzz,16,17,...

– As a simple MLP with one hidden layer



Input X: D=10 (i represented by 10 bits) No. of hidden units: M=1,000 Output Y: K=4 (One-hot vector with 4 values)

What is a tensor? What is flow?





Srihari

A linear classifier with bias eliminated $y = Wx^{T}$



Machine Learning

Computational Graph

- Network structure specified by computational graphs
- Makes it easy to visualize and debug







Fizzbuzz in Tensorflow

• Import numpy and Tensorflow libraries

import numpy as np

import tensorflow as tf

Input to Network

- Input i represented as a bit-vector
 - Distributed representation is key to deep learning
 - Turn each input into a vector of "activations"
 - Define a binary encoder for the input i

def binary_encode(i, num_digits): return np.array($[i >> d \& 1 \text{ for } d \text{ in } range(num_digits)]$)

- Python Syntax:
- $1. \quad i{>>}d \text{ returns } i \text{ shifted to right by } d \text{ places}$
- 2. &, e.g., a&b Bitwise logical AND operator

 $num_digits=D=$ no. of input bits



Output is a one-hot encoding of fizzbuzz representation of input, where the four positions indicate print as-is, fizz, buzz and fizzbuzz:

def fizz_buzz_encode(i): if i % 15 == 0: return np.array([0, 0, 0, 1]) elif i % 5 == 0: return np.array([0, 0, 1, 0]) elif i % 3 == 0: return np.array([0, 1, 0, 0]) else: return np.array([1, 0, 0, 0])

- Python Syntax:
- 1. % operator, e.g., b % a divide left operand by right operand and return remainder
- 2. == condition, e.g., a==bCondition becomes true if operands are equal



Generating Training Samples

- No cheating: can't use 1 to 100 in training data
 - We train on all remaining numbers up to 1024:
 - Define trX using binary_encode (101 to 1024)
 - Define trY using $fizz_buzz_encode$

$$num_digits = 10$$

Python Syntax: Range function, e.g., range(3) = [0,1,2]

No. of Hidden Units

- Could be 10
- Probably 100 is better

num_hidden= 100



2 Machine Learning 5

Input and Output Variables

- We'll need an input variable of width num_digits
- Output variable with width 4
 - X = tf.placeholder("float", [none, num_digits])

Y = tf.placeholder("float", [none, 4])

- A placeholder is a variable that we will assign data to at a later date. It allows us to create our operations and build our computation graph, without needing the data
- Computational graph
 - Operations and inputs are nodes
 - Values used in operations are directed edges



Randomly initialized weights

• One hidden layer and one output layer

def init_weights(shape):

return tf.Variable(tf.random_normal(shape, stddev=0.01))

w_h = init_weights([num_digits, num_hidden])
w_o = init_weights([num_hidden, 4])

Defining the model

 Define model using one hidden layer and ReLU activation

 $\frac{def \ model(X, w_h, w_o):}{h = tf.nn.relu(tf.matmul(X, w_h))}$

return tf.matmul(h, w_o)



- ReLu activation: $g(z) = \max\{0, z\}$
 - Easy to optimize due to similarity with linear units
 - Only difference is that they output 0 across half its domain
 - Derivative is 1 everywhere that the unit is active



Minimizing the Cost function

2 Machine Learning

8

• Softmax cross entropy (with *K* classes, *N* samples)



py_x = model(X, w_h, w_o) cost = tf.reduce_mean(tf.nn.softmax_cross_entropy_with_logits(py_x, Y)) train_op = tf.train.GradientDescentOptimizer(0.05).minimize(cost)

Prediction

Prediction will just be the largest output

 $predict_op = tf.argmax(py_x, 1)$

This will output a number from 0 to 3

 But we want a fizzbuzz output

def fizz_buzz(i, prediction):

return [str(i), "fizz", "buzz", "fizzbuzz"][prediction]

Training

- We are ready to train the model
 - grab a tensorflow session and initialize variables

with tf.Session() as sess:

tf.initialize all variables().run()

- Training epochs
 - -10,000 epochs of training
 - Shuffle them for each iteration

for epoch in range(10000):

p = np.random.permutation(range(len(trX))) trX, trY = trX[p], trY[p]

<u>– Each epoch trained in batches of 128</u> BATCH_SIZE=128

Each Training Pass

- Each epoch trained in batches of 128 BATCH_SIZE=128
- Each training pass looks like

for start in range(0, len(trX), BATCH_SIZE):
end = start + BATCH_SIZE
sess.run(train_op, feed_dict={X: trX[start:end], Y:
trY[start:end]})

Accuracy on the Training Data

It is helpful see how training accuracy evolves

print(epoch, np.mean(np.argmax(trY, axis=1) ==
 sess.run(predict_op, feed_dict={X: trX, Y:
 trY})))

Fizzbuzz Testing

- Once model is trained, it is Fizzbuzz time
- Input is binary encoding of numbers 1 to 100

numbers = np.arange(1, 101)

 $teX = np.transpose(binary_encode(numbers, num_digits))$

Output is fizzbuzz function applied to model output
 teY = sess.run(predict_op, feed_dict={X: teX})
 output = np.vectorize(fizz_buzz)(numbers, teY)
 print(output)

Performance on Test Set

- array(['1', '2', 'fizz', '4', 'buzz', 'fizz', '7', '8', 'fizz', 'buzz', '11', 'fizz', '13', '14', 'fizzbuzz', '16', '17', 'fizz', '19', 'buzz', '21', '22', '23', 'fizz', 'buzz', '26', 'fizz', '28', '29', 'fizzbuzz', '31', 'fizz', 'fizz', '34', 'buzz', 'fizz', '37', '38', 'fizz', 'buzz', '41', '42', '43', '44', 'fizzbuzz', '46', '47', 'fizz', '49', 'buzz', 'fizz', '52', 'fizz', 'fizz', 'buzz', '56', 'fizz', '58', '59', 'fizzbuzz', '61', '62', 'fizz', '64', 'buzz', 'fizz', '67', '68', '69', 'buzz', '71', 'fizz', '73', '74', 'fizzbuzz', '76', '77', 'fizz', '79', 'buzz', '81', '82', '83', '84', 'buzz', '86', '87', '88', '89', 'fizzbuzz', '91', '92', '93', '94', 'buzz', 'fizz', '97', '98', 'fizz', 'fizz', 'fizz']
- Running code on GitHub got some outputs wrong!
 - 0.90 fizz-accuracy, and 0.99 buzz-accuracy. So it's clearly harder to teach fizzing than buzzing.
- A deeper network may help

Performance of ML Fizzbuzz

- Running this code on GitHub got some of the outputs wrong!
 - -0.90 fizz-accuracy
 - -0.99 buzz-accuracy
- So it's harder to teach fizzing than buzzing
- A deeper network may help

Practical Methodology

- 1. Performance Metrics
- 2. Default Baseline Models
- 3. Determining whether to gather more data
- 4. Selecting hyperparameters
- 5. Debugging strategies

Performance Metrics

- 1. Metrics for Regression: squared error, RMS
- 2. Metric for Density Estimation: KL divergence
- 3. Metrics for Classification: Accuracy
- 4. Metrics for Unbalanced data:
 - Loss, Specificity/Sensitivity
- 5. Metrics for Retrieval: Precision and Recall
- 6. Combining Precision and Recall: F-Measure
- 7. Metrics for Image Segmentation: Dice Coefficient

Choice of Optimization Algorithm

- SGD with momentum with a decaying learning rate
 - Linear decay
 - Exponential decay
 - Decreasing learning rate by factor of 2-10 when validation error rate plateaus
- Adam batch normalization can have a dramatic effect on optimization performance
- Reasonable to omit batch normalization from very first baseline unless optimization is problematic

Regularization

- Unless training set includes tens of millions of examples, should include some form of regularization from start
- Early stopping should be used universally
- Dropout is easy to implement and compatible with many models/training

More data to improve performance

4 Machine Learning

- After end-to-end system established, it is time to measure performance and determine how to improve it
- Instead of other learning algorithms it is often better to get more data than improve learning algorithms

Determining whether more data needed

- Determine performance on training data
- If performance on training data is poor algorithm is not using training data already available, so more data is not needed
 - Instead try increasing model size

Machine Learning

- More layers, more hidden units within layers
- Try improving learning algorithm
 - E.g., tuning the learning rate hyperparameter
 - If performance unsatisfactory, quality if training data may be responsible; too noisy, not include right inputs
 - Suggesting starting over with new data

- Examples of hyperparameters:
 Learning rate ∈, regularizing coefficient λ
- Choosing them manually

4 Machine Learning

- Requires understanding of what they do
- Knowledge of how they achieve good generalization
- Choosing them automatically
 - Reduce the need to understand these ideas
 - But computationally expensive

Difficulty of Debugging

- When system performs poorly, difficult to tell:
 - poor performance is intrinsic to algorithm itself or
 - whether there is an implementation bug
- Cannot tell a priori the behavior of algorithm
- Entire point of ML:
 - it will discover useful behavior we were not able to specify ourselves
- If classification test error rate is 5%
 - we cannot tell whether this is expected behavior or suboptimal behavior

Multiple Adaptation Levels

- A difficulty is that ML models have multiple parts that are each adaptive
- If one part is broken, other parts can adapt and get acceptable performance

Debugging strategies

- Need to get around two difficulties:
 - 1. Whether performance is intrinsically poor or has a bug
 - 2. Whether parts are compensating for each other
- Design a test case that is so simple that the test behavior can be predicted, or
- Design a test that exercises one part of the neural net implementation in isolation

Important Debugging Tests

- 1. Visualize the model in action
- 2. Visualize the worst mistakes
- 3. Reasoning about software using train and test error
- 4. Fit a tiny dataset
- 5. Compare back-propagated derivatives to numerical derivatives
- 6. Monitor histograms of activations and gradient

What is a GPU?

- Main component in any computer is a CPU
 - CPU gets instructions and performs calculations
 - If a CPU can only process one set of instructions then it is single core processor
 - Process two sets of instructions: dual core processor
 - Four sets of instructions is a quad-core processor
- GPU
 - NVIDIA
 - 384 cores for mobile devices
 - Upto 2,560 cores



Installing Tensorflow

- TensorFlow with CPU support only
 - Typically easier to install (5 -10 mins)
- TensorFlow with GPU support
 - Significantly faster
 - Hardware: NVIDIA® GPU
 - Software: CUDA API & drivers

Companies using Tensorflow





3 x NVIDIA GTX 1080

