

Combining Models

Sargur Srihari

srihari@cedar.buffalo.edu

Methods of Combining Models

- Classification/regression performance can be improved by combining multiple models
 1. Committee: train L different models
 - Make predictions by average of the predictions
 2. Boosting: Variant of Committee
 - Train multiple models in sequence
 - Error function used to train a model depends on performance of previous models
 3. Decision Tree
 - Select one of L models to make the prediction
 - Choice of model is a function of input variables

Decision Tree


- Choice of model is function of input variables
 - Different models become responsible for making predictions in different regions of input space
 - A sequence of binary selections corresponding to traversal of a tree structure

Tree-based Models


- Partition the input space into cuboid regions
 - Edges aligned along the axes
 - Assign a simple model, e.g., a constant, to each region
- Can be viewed as a model combination method in which only one model is responsible for making predictions at any given point in space
- Process of selecting a model for input x corresponds to the traversal of a binary tree

Recursive Binary Tree Partitioning

2-D input space $\mathbf{x} = [x_1, x_2]$
 Partitioned into five regions
 using axis aligned boundaries



Binary Tree corresponding to
 Partitioning of input space




First step divides the whole of input space into two regions according to whether $x_1 \leq \theta_1$ or $x_1 > \theta_1$ where θ_1 is a parameter of the model. This creates two subregions, each of which can be subdivided independently e.g., region $x_1 \leq \theta_1$ is further subdivided according to whether $x_2 \leq \theta_2$ or $x_2 > \theta_2$ giving rise to the regions denoted A and B. For a new input \mathbf{x} we determine which region it falls into by starting at top of tree.

Use of Tree Models

- Can be used for both regression and classification
- So they are called Classification and Regression Trees (CART)
- Within each region there is a separate model to predict a target variable
 - In regression, we might simply predict a constant over each region
 - In classification, we might assign each region to a specific class
- **Key property: they are interpretable by humans**
 - To predict a disease, is temperature greater than a threshold?, is BP less than a threshold? Each leaf is a diagnosis

Regression Tree with 2 inputs

Two input attributes (x_1, x_2) , a real output



First node asks if $x_1 \leq t_1$

If yes, ask if $x_2 \leq t_2$

If yes, we are at quadrant R_1

Associate a value of y with each region


Result of axis-parallel splits:
2-d space partitioned into 5 regions

Each region is associated with a mean response

Result: piecewise constant function


Model can be written as:

$$f(\mathbf{x}) = E[y | \mathbf{x}] = \sum_{m=1}^M w_m I(\mathbf{x} \in R_m) = \sum_{m=1}^M w_m \phi(\mathbf{x}; \mathbf{v}_m)$$



Classification Tree (Binary Output)

PlayTennis has 4 input attributes



Day	Outlook	Temp	Humidity	Wind	PlayTennis
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rain	Mild	High	Weak	Yes
D5	Rain	Cool	Normal	Weak	Yes
D6	Rain	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rain	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rain	Mild	High	Strong	No

Learned function is a tree

