Causal Explanation

Sargur N. Srihari srihari@buffalo.edu

Topics in Causal Explanation

- Three waves of AI
- Explainable AI
- Probabilistic Graphical Models
- Causal Modeling
- Most Probable Explanation
- Explaning Forensic Evidence

Role of probability in explanation

SECOND WAVE

FIRST WAVE



Naturally suited for XAI

Most Probable Explanation

THIRD WAVE

Explainability of AI Models



Probabilistic Models in Explanation

- Generative models are useful for
 - Querying
 - BNs, MRFs
 - Sampling
 - VAEs, GANs
- Inference methods useful as explanation
 - Most Probable Explanation (MPE)
 - Causal Inference
 - Explaining Away

Probabilistic Graphical Models (PGMs)

Bayesian Networks



- CPDs: $p(x_i | pa(x_i))$
- Joint Distribution $\boldsymbol{x} = \{x_1, ..., x_n\}$

$$p(\boldsymbol{x}) = \prod_{i=1}^{N} p(x_i \mid pa(x_i))$$

$$\begin{split} P(D,I,G,S,L) = \\ P(D)P(I)P(G \mid D,I)P(S \mid I)P(L \mid G) \end{split}$$

Markov Networks



 $p(a,b,c,d,e,f) = \frac{1}{Z} \phi_{a,b}(a,b) \phi_{b,c}(b,c) \phi_{a,d}(a,d) \phi_{b,e}(b,e) \phi_{e,f}(e,f)$

Energy model E(a,b,c,d,e,f) = $E_{a,b}(a,b) + E_{b,c}(b,c) + E_{a,d}(a,d) + E_{b,e}(b,e) + E_{e,f}(e,f)$ $\phi_{a,b}(a,b) = \exp(-E(a,b))$

Restricted Boltzmann machine



XAI from Causal Model Induction

 Experiment with the learned model to learn an explainable, causal, probabilistic programming model



Causal Modeling

• For a G defining a causal directed PGM on variables $X=x_1,...,x_n$, the joint distribution is

$$P(x_1,...,x_n) = \prod_i P(x_i|pa_i)$$

- where pa_i are the parents of x_i
- An intervention on G by setting $x_i = x'_i$, denoted as $do(x'_i)$, induces a modified graph G' where the edges from pa_i to x_i are removed, resulting in post intervention distribution

$$P(x_1, ..., x_n | do(x'_i)) = \begin{cases} \prod_{j \neq i} P(x_j | pa_j) & \text{if } x_i = x'_i \\ 0 & \text{if } x_i \neq x'_i \end{cases}$$

 Semantics of causality are important for explaining DNNs, because explanations must be causal models

Explanation of DNN decision

- When one seeks an explanation of a network's decisions, one is equivalently asking "What changes can be made to the input for the output to change or stay the same?"
- Consider a causal model that defines the joint distribution P(O,P,X) over a set of DNN outputs O, inputs P, & intermediate variables X
- Explanation of an observed DNN output is formulated as intervention

Causal Representation in DNNs

- A user could ask counterfactual questions about the network, i.e. $P(\mathbb{O},\mathbb{P},\mathbb{X} | do(x'_i))$ for any input, output, or internal neuron in the network
- But it serves poorly as a model of explanation
 - due to the lack of human–level concepts that underlie any arbitrary neuron in the network:
 - saying neuron *i* caused the network to detect a pedestrian may be correct but does not satisfy human needing explanations
- Thus, a DNN causal model must be at a granularity meaningful to humans.

Mapping Neurons to Concepts

- A causal model for DNNs should be represented by joint distribution over O,P, and a set of concepts C
- The process for deriving \mathbb{C} is described by a function $f_{\mathbb{R}}$: $\mathbb{R} \to \mathbb{C}$ over a specific DNN that transforms the representation of neurons and their activations into a set of concept variables
- Ideally, $f_{\mathbb{R}}$ would have the following properties:

$$\int_{R} P(\mathbb{O}, \mathbb{P}, \mathbb{R}) = \int_{C} P(\mathbb{O}, \mathbb{P}, \mathbb{C})$$
$$P(\mathbb{O}, \mathbb{P} | R, do(p'_i)) = P(\mathbb{O}, \mathbb{P} | C, do(p'_i))$$

Concept Extraction

- One way to construct concepts that satisfy the semantics is to consider network activations
- But concepts needn't be restricted to those
 - 1. Concepts should be few to minimize amount of investigation a human would need to employ
 - 2. Concepts should be interpretable
 - in the case of images, we would like activations to be restricted to contiguous areas containing consistent, interpretable visual features
 - 3. Concepts should contain all relevent information needed for achieving network task

Auxiliary neural network

- Network constructs concept representations
 satisfying above properties
- Using an autoencoder with two loss functions
 - Shallow reconstruction loss: L_1 norm between input and output activations $\begin{bmatrix} L_{shallow}(\theta; a_i) = |d_{\theta}(c_{\theta}(a_i)) - a_i|_1 \\ L_{deep}(\theta; a_i) = KL(r(a_i)||r(d_{\theta}(c_{\theta}(a_i)))) \end{bmatrix}$
 - Deep reconstruction loss: reconstructed activations result in same classification output after being passed through the rest of network
 - Total autoencoder loss

$$\begin{split} L(\theta; x_i) = &\lambda_{shallow} L_{shallow}(\theta; x_i) + \\ &\lambda_{deep} L_{deep}(\theta; x_i) + \\ &\lambda_{interpretability} L_{interpretability}(\theta; x_i) \end{split}$$

Autoencoder for a single layer



14

Learned causal Bayes Net

For Inria pedestrian data set



Crossed boxes indicate that all nodes of a given level have edges incident on each of the nodes of the subsequent level.

Summary of Causal Learning XAI

- Approach to explain predictions to relate output prediction to concepts represented within
 - Series of autoencoders encouraging interpretable properties to construct concepts in activations throughout network
 - Pool features and intervene on autoencoded network to construct variables used to build a causal BN
 - Use network to identify features of causal relevance to individual classifications which are then visualized

Most Probable Explanation (MPE)

Observe evidence: student has received a job offer $J=j^{1}$. We want an explanation for each of the following two queries

- 1. Most probable (MAP) setting for all variables *I*,*D*,*G*,*S*,*L*,*A*
- 2. Most probable setting for a particular variable *I*



P(I,D,G,S,L,A,J) = P(I)P(D)P(G|I,D)P(S|I)P(L|G)P(A)P(J|A,S,L)

Query 1: Inferring all variables

Conditioning with *Job* with $J=j^{1}$

Conditional Probability:

$$P(I, D, G, S, L, A | J = j^{1}) = \frac{P(I, D, G, S, L, A, J = j^{1})}{P(J = j^{1})}$$

Numerator:

 $P(I, D, G, S, L, A, J = j^{1}) = P(I)P(D)P(G|D, I)P(L|G)P(S|I)P(A)P(J = j^{1}|A, S, L)$

Denominator requires Marginal Inference

$$P(J = j^{1}) = \sum_{I} \sum_{D} \sum_{G} \sum_{S} \sum_{L} \sum_{A} P(I, D, G, S, L, A, J = j^{1}) = 0.3679$$

MPE for all variables

$$P(I, D, G, S, L, A | J = j^{1}) = \frac{P(I, D, G, S, L, A, J = j^{1})}{P(J = j^{1})}$$

Exhaustive listing of 96 Combinations of numerator with probabilities

Sr. No. 🔻	Difficult 🔻	Intelliger 🔻	Grade 🔻	Letter 🔻	SAT 🔻	- vlqqA	T- dol	Joint Probabil 🔻
3	0	1	0	1	1	1	1	0.0629856
5	0	0	0	1	0	1	1	0.0387828
10	0	0	1	1	0	1	1	0.0344736
13	1	1	0	1	1	1	1	0.023328
16	1	0	2	0	0	0	1	0.01474704
18	1	0	1	1	0	1	1	0.014364
21	1	0	2	0	0	1	1	0.01106028
22	0	1	0	1	0	1	1	0.0104976
23	1	1	2	0	1	1	1	0.01026432
25	0	0	2	0	0	0	1	0.00948024
27	0	1	0	1	1	0	1	0.0093312
28	1	1	1	1	1	1	1	0.0093312
29	0	0	0	1	0	0	1	0.0086184
31	0	0	1	1	0	0	1	0.0076608
32	0	0	2	0	0	1	1	0.00711018
33	0	1	0	0	1	1	1	0.0069984
37	1	1	1	0	1	1	1	0.0062208

Max of numerator (a joint probability):

 $P(I,D,G,S,L,A, J=j^{1}) = 0.9 * 0.6 * 0.8 * 0.9 * 0.9 * 0.3 * 0.6 = 0.0629856$

Max Conditional Probability (MAP):

P(I, D, G, S, L, A|J = 1) = 0.0629856/0.3679 = 0.1712

MPE is:

- $I = i^{1}$: Is Intelligent
- $D = d^{0}$: course is *Difficult*
- $G = g^{0}$: Grade is A
- $S = s^{1}$: high SAT
- $L = l^1$: strong Letter
- $A = a^{1}$: Apply for Job

Query 2: Marginal for I given $J = j^{1}$

The most probable explanation of Intelligence given $Job: J=j^1$ Answer: $I = i^1$: Is Intelligent

Formula:

P(I|J = 1) = P(I,J)/P(J = 1)P(I,J) = P(I)P(J|A,S,L)P(A)P(S|I)P(L|G)P(G|D,I)P(D)

P(I = 0, J = 1) = 0.9 * 0.6 * 0.8 * 0.9 * 0.9 * 0.3 * 0.6 = 0.0629P(I = 1, J = 1) = 0.6 * 0.7 * 0.3 * 0.9 * 0.95 * 0.6 * 0.6 = 0.0387

$$\begin{split} P(I=0|J=1) &= 0.0387/(0.0629 + 0.0387) = 0.381 \\ P(I=1|J=1) &= 0.0629/(0.0629 + 0.0387) = 0.619 \end{split}$$

MAP of Student Intelligence

++.	+
intel 0	0.381
+	
тт.	
intel_1	0.619
++	+

Compare to Prior of Student Intelligence



MPE is NP-Hard

- BN is an MRF whose factors are conditional probabilities and Z=1
- MAP inference is simpler than Marginal Inference since we can ignore Z

Marginal
$$p(y=1) = \sum_{x_1} \sum_{x_2} \cdots \sum_{x_n} p(y=1,x_1,x_2,\ldots,x_n)$$
Needs
Partition functionMAP $\max_{x_1,\ldots,x_n} p(y=1,x_1,\ldots,x_n)$ Can ignore
Partition function

However MAP inference is still not easy
 Both Marginal and MAP inference are NP-hard

Sampling from Student BN

		apply	ply intel	sat	diff	grade	letter	job	
	0	1	1	1	1	0	1	1	
d Sampling in a Bayesian network	1	0	0	0	0	0	1	0	
ard-Sample (2	1	1	1	1	1	1	1	
\mathcal{B} // Bayesian network over \mathcal{X}		1	0	0	1	2	0	0	
$\dots X_n$ be a topological ordering of \mathcal{X}	4	1	1	1	0	2	0	1	
\dots, n	5	0	0	0	1	2	0	1	
$oldsymbol{u}_i \leftarrow oldsymbol{x} \langle \mathrm{Pa}_{X_i} angle ~//$ Assignment to Pa_{X_i} in x_1, \ldots, x_{i-1}		1	0	0	0	0	1	0	
$x_i \text{ from } P(X_i \mid u_i)$ (x_1, \dots, x_n)	7	1	0	1	0	1	1	1	
, , , , , , , , , , , , , , , , , , ,		1	0	0	0	1	1	1	
	9	1	0	0	1	1	0	0	
		•							
	993	0	0	1	1	1	1	0	
Y:	994	1	1	1	0	0	1	1	
ing import BayesianModelSampling	995	1	0	0	0	2	0	0	
<pre>= BayesianModelSampling(student) rd_sampler.forward_sample(size=1000)</pre>	996	0	0	0	0	0	1	0	
,	997	1	0	0	1	2	0	0	
	998	0	0	0	0	0	0	1	

PGM classification over 1000 samples

from pgmpy.models import BayesianModel
from pgmpy.factors.discrete import TabularCPD
from pgmpy.inference import VariableElimination

student.fit(train)

Accuracy is: 88.125

Results:

- Training Accuracy: 92%
- Testing Accuracy: 88%





Logistic Regression for Intelligence

Training Hyperparameters:

- Number of Epochs: 100
- Batch Size: 100
- Number of samples: 1000
- Number of Training samples: 800
- Number of Validation samples: 200

Results:

- Training Accuracy: 94.62%
- Training Loss: 0.1580
- **Testing Accuracy: 96%**
- Testing Loss: 0.1534

Logistic Regression output:

	Intelligence = 0	Intelligence = 1
Job = 1	0.038	0.962

Explanation:

MPE

evidence: student gets job explanation: 96% probability that student is intelligent;

Formula: P(I = 0|J = 1) = 0.498P(I = 1|J = 1) = 0.502



Explainability vs Performance



Figure 5.3 The Student example augmented with a Job variable



Explainable System Results:

- Training Accuracy: 92%
- Testing Accuracy: 88%



High Performance System Results:

- Training Accuracy: 95%
- Testing Accuracy: 96%

Forensic Comparison

- Impression Evidence: materials with characteristics of impressed objects
 - Footwear impressions



latent fingerprints





- Handwriting samples

2 6

Expert Features



Image 1: Human observed features mapped to image

Feature Vector

Handwriting comparison-expert features



PGM for human observed 'and' dataset



PGM for Writer Verification



Finding LLR

$$LLR = \ln \left(\frac{P(k, q \mid h = 0)}{P(k, q \mid h = 1)} \right)$$

Approach 1

[•] A simple **Distance based LLR** approach defines scalar distance between known and questioned samples defining loglikelihood ratio as follows:

$$LLR_D = \ln\left(\frac{P(d(k,q) \mid h=0)}{P(d(k,q) \mid h=1)}\right)$$

Disadvantage: Distribution of N variables is mapped into a scalar thereby incurring severe loss of information (many pairs of k and q can have the same distance).

Approach 2

Rarity with Distance based
 LLR approach uses strength of
 the features between the known
 and the questioned samples
 defining loglikelihood ratio as

follows:

$$LLR_{RD} = \ln \left(\frac{\frac{1}{\sqrt{2\sigma}} e^{-\frac{(k-q)^2}{4\sigma^2}}}{\frac{1}{\tau} e^{-\frac{(m-\mu)^2}{4\tau^2}}} \right)$$
Distance
Rarity

Disadvantage: Not always computationally tractable

Feature extraction architecture/performance



Feature Name	Val		
	acc		
pen_pressure	98%		
letter_spacing	78%		
size	92%		
dimension	89%		
is_lowercase	99%		
is_continuous	94%		
slantness	72%		
tilt	98%		
entry_stroke_a	97%		
staff_of_a	84%		
formation_n	95%		
staff_of_d	86%		
exit_stroke_d	66%		
word_formation	89%		
constancy	84%		

Code: https://github.com/mshaikh2/HDL Forensics

Comparison performance

Performance based on Overall Similarity

Metric	Seen	Unseen	Shuffled
Intra Writer Accuracy	88%	71%	81%
Inter Writer Accuracy	96%	93%	95%
Average Accuracy	96%	94%	95%

Explainability:

 Compare corresponding 'SoftMax_x' (x : {1 to 15}) of two images using cosine similarity to obtain feature wise explanation

Explanation of Comparison



Image 6: Graph of Similarity Score of Left & Right Image Features **Different Writer Samples**

Image 7: Graph of Similarity Score of Left & Right Image Features Same Writer Samples

Medium Yes

Table 5: Predicted Classes

Report Card of Comparing two Samples

Future of XAI



Source: https://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=8466590

Summary and Conclusion

- Deep Learning models are often blackboxes
- Ante-hoc XAI models are new learning models with an explanatory interface
- Post-hoc models retain high performance
- Several new ideas developing: Bayesian Teaching, Causal learning of deep neural nets
- Probabilistic AI is useful for deep learning
- XAI may be an inflection point in AI