

# Two frameworks for analyzing learning algorithms

## 1. *Probably Approximately Correct (PAC)* framework

- Identify classes of hypotheses that can/cannot be learned from a polynomial number of training samples
  - Finite hypothesis space
  - Infinite hypotheses (*VC dimension*)
- Define natural measure of complexity for hypothesis spaces (*VC dimension*) that allows bounding the number of training examples required for inductive learning



## 2. *Mistake bound (MB)* framework

- Number of training errors made by a learner before it determines correct hypothesis

# Different learning settings considered in COLT

1. How **training samples** are generated?
  - Passive observation of random examples
  - Active querying by the learner
2. **Noise** in the data
  - Noisy
  - Error Free
3. Definition of **success**
  - Target concept must be learned exactly
  - Only probably and approximately
4. **Assumptions** made by the learner
  - For distribution of instances
  - Whether  $C \leq H$
5. **Measure** according to which learner is evaluated
  - No training examples, no of mistakes, total time

## Mistake Bound (MB) Model Of Learning

- Problem setting:
  - Learner receives a sequence of training examples
  - Upon receiving each sample  $x$ , learner must predict target value  $c(x)$  before it is shown correct target value by trainer
- How many mistakes will learner make in its predictions before it learns the target concept?

---

## In the MB model, learning is in stages

In each stage:

1. Learner gets unlabeled example
2. Learner predicts classification
3. Learner is told correct label

**Goal:** Bound the total number of mistakes

## Practical use of MB learning model

- Significant in practical settings where learning must be done while the system is in actual use, rather than in an off-line training stage
- *Example:* system to learn to approve credit card purchases based on data collected during use
  - How many mistakes in approving credit card purchases before system learns?
  - Total number of mistakes is more important than number of training examples

## Study of MB Model: Problem Setting

- Number of mistakes made before learning the target concept exactly (rather than *PAC*)
- *DEFINITION:*  
Algorithm  $A$  has mistake-bound  $M$  for learning class  $C$  if  $A$  makes at most  $M$  mistakes on any sequence that is consistent with a function in  $C$

## Mistake Bound for *Find-S* algorithm

- *Find-S*
- Initialize  $h$  to the most specific hypothesis

$$\mathbf{l}_1 \wedge \neg \mathbf{l}_1 \wedge \mathbf{l}_2 \wedge \neg \mathbf{l}_2 \cdots \wedge \mathbf{l}_n \wedge \neg \mathbf{l}_n$$

- For each positive training instance  $x$ 
  - Remove from  $h$  any literal that is not satisfied by  $x$
- Output hypothesis  $h$
- Total no. of mistakes can be at most  $n+1$

## Mistake Bound for *HALVING* Algorithm

- *HALVING ALGORITHM:*
  - predict using majority vote over all concepts in  $C$  consistent with past data
- *Candidate Elimination and List-then-eliminate are halving algorithms*
- *Candidate Elimination*
  - maintains a description of the version space, incrementally refining the version space as each new sample is encountered
  - Assume majority vote is used among all hypotheses in the current version space



---

## Mistake Bound for HALVING Algorithm

- Total no. of mistakes can be at most  $\log_2 |H|$

## Optimal Mistake Bound

- For any target concept  $c$ , let  $M_A(c)$  denote the maximum number of mistakes, over all possible sequences, made by learning algorithm  $A$  to exactly learn  $c$
- *Definition:* The optimal *mistake bound* for  $C$ , denoted  $Opt(C)$  is the minimum over all possible learning algorithms  $A$  of  $M_A(C)$
- Then  $VC(C) \leq Opt(C) \leq \log_2(|C|)$

## Weighted Majority Algorithm

- A classifier combination method
- Takes a weighted vote among a pool of prediction algorithms, e.g., alternative hypotheses in  $H$ , or alternative learning algorithms
- It begins by weighting each algorithm by 1
- Whenever an algorithm misclassifies its weight is decreased by  $\beta$ , where  $0 \leq \beta \leq 1$

## Weighted Majority Algorithm

- If  $A$  is any set of  $n$  prediction algorithms
- If  $k$  is the minimum number of mistakes made by any algorithm in  $A$
- The number of mistakes made over any training sequence is at most

$$\frac{k \log_2 \frac{1}{\beta} + \log_2 n}{\log_2 \frac{2}{1 + \beta}}$$