

# Multiclass SVMs

[srihari@buffalo.edu](mailto:srihari@buffalo.edu)



# SVM Discussion Overview

1. Importance of SVMs
2. Overview of Mathematical Techniques Employed
3. Margin Geometry
4. SVM Training Methodology
5. Overlapping Distributions
6. Dealing with Multiple Classes
7. SVM and Computational Learning Theory
8. Relevance Vector Machines

# SVM Classifier

- SVM is a 2-class, maximum margin classifier


Data Space  $x$       Feature Space  $\phi(x)$       Gaussian Kernel:



$$k(x_i, x_j) = \phi(x_i)^T \cdot \phi(x_j)$$

$$k(x_i, x_j) = \exp\left\{-\beta \|x_i - x_j\|^2\right\}$$

$$\phi(x) = e^{-x^2/2\sigma^2} \left[ 1, \sqrt{\frac{1}{1!\sigma^2}}x, \sqrt{\frac{1}{2!\sigma^4}}x^2, \sqrt{\frac{1}{3!\sigma^6}}x^3, \dots \right]^T$$



- $\phi(x)$  maps  $x$  to an infinite space
- Achieves perfect separation


For sufficiently small kernel bandwidth, decision boundary will look like you just drew little circles around the points whenever they are needed to separate positive and negative examples.

# Multiclass SVM

- SVM is fundamentally a two-class classifier
- In practice we have to tackle problems involving  $K > 2$  classes
- Various methods have been suggested for combining multiple two-class SVMs to build a multiclass classifier

# Multiclass SVM: One-versus-All (OVA)

- Commonly used: *one-versus-rest* approach
- Construct  $K$  separate SVMs
  - $k^{\text{th}}$  model  $y_k(\mathbf{x})$  is trained
    - Using data from class  $C_k$  as positive examples and data from remaining  $k-1$  classes as negative examples



# Dealing with multiple class assignments

- Decisions of individual classifiers can lead to multiple classes simultaneously
  - Sometimes addressed by making predictions for new inputs  $\mathbf{x}$  using

$$y(\mathbf{x}) = \max_k y_k(\mathbf{x})$$


- It suffers from fact that different classifiers are trained on different tasks
    - No guarantee  $y_k(\mathbf{x})$  of  $K$  classifiers have same scale
- Defining a single objective for training  $K$  SVMs simultaneously is much slower:  
 $O(K^2 N^2)$

# Imbalance problem of One-vs-Rest

- Training sets are imbalanced
  - With a 10-class problem, 90% are one class and 10% are another
  - Symmetry of original problem is lost

## Multiclass SVMs: All-versus-All (AVA)

- Train  $K(K-1)/2$  different 2-class SVMs on all possible pairs of classes
  - Classify test points according to which class has highest number of votes
  - Again leads to ambiguities in classification







## Computation difficulty of All-versus-All

- For large  $K$  requires significantly more training time than one-versus rest
  - Also more computation time for evaluation
- Can be alleviated by organizing into a directed acyclic graph (DAGSVM)
  - DAGSVM has  $K(K-1)/2$  classifiers
  - To classify a new test point only  $K-1$  pairwise classifiers are used
    - Depending on which path through graph is traversed

# AVA vs OVA



$M=3$  classes,  $N=\text{no of classifiers}$

$$\text{All vs All (AVA): } R = \begin{pmatrix} 1 & 1 & 0 \\ -1 & 0 & 1 \\ 0 & -1 & -1 \end{pmatrix} \quad N = \begin{pmatrix} M \\ 2 \end{pmatrix}$$

$$\text{One vs All (OVA): } R = \begin{pmatrix} 1 & -1 & -1 \\ -1 & 1 & -1 \\ -1 & -1 & 1 \end{pmatrix} \quad N = M$$

Output code matrix  $R$  of size  $M \times N$  and  $R_{ij} \in \{1, 0, -1\}$