

# Graph Cut Algorithm

Sargur Srihari

[srihari@cedar.buffalo.edu](mailto:srihari@cedar.buffalo.edu)

# Topics

- Overview of MAP as a graph cut problem
- Graphcuts
- Min-cut problem
- Reducing MAP to min-cut problem
- A simple example

# Overview of Graph Cuts

- Graph Cut algorithm provides a MAP solution for metric and semi-metric MRFs
  - It is important in computer vision applications
  - Close to optimal for densely connected networks
- Graph Cuts is an efficient exact MAP inference algorithm for certain Potts models
  - Over binary-valued variables  $X_i \in \{0,1\}$
  - The algorithm is tractable even when the model has large tree-width

# Graph Cut

- We first define the min-cut problem for a graph and show how the MAP problem can be reduced to it
- The min-cut problem is defined by a set of vertices  $Z$  plus two distinguished nodes generally known as  $s$  and  $t$ 
  - We have a set of directed edges  $\varepsilon$  over  $Z \cup \{s, t\}$
  - Where each edge  $(z_1, z_2) \in \varepsilon$  is associated with a non-negative cost  $\text{cost}(z_1, z_2)$
- A graph cut is a disjoint partition of  $Z$  into  $Z_s \cup Z_t$  such that  $s \in Z_s$  and  $t \in Z_t$

# Cost of a Graph Cut

- A *graph cut* of an undirected graph  $G=(V, \varepsilon)$  is a partition of  $V$  into 2 disjoint sets  $V_s \cup V_t$
- When each edge  $(v_1, v_2) \in \varepsilon$  is associated with a nonnegative cost  $\text{cost}(v_1, v_2)$ 
  - the cost of a graph cut is the sum of the costs of the edges that cross between the two partitions:

$$\text{cost}(V_s, V_t) = \sum_{v_1 \in V_s, v_2 \in V_t} \text{cost}(v_1, v_2)$$

# Min Cut Problem

- The *min-cut* problem is to find the partition  $V_s, V_t$  that minimizes the cost of the graph cut

# Reducing MAP to Computing Cuts

- We need to design our graph so that a cut corresponds to an assignment to  $\chi$  and its cost to the value of the assignment
- The construction follows from this intuition
  - Vertices, other than  $s$  and  $t$  represent variables in our MRF
  - We use  $s$  to represent the label 0 and  $t$  to represent the label 1
  - Thus we map a cut  $C=(Z_s, Z_t)$  to the following assignment  $\xi^C$ :
    - $x_i^C=0$  iff  $z_i \in Z_s$

# Construction for Ising model

- Generalized Ising model has the form

$$\epsilon_{ij} = \begin{cases} 0 & x_i = x_j \\ \lambda_{ij} & x_i \neq x_j \end{cases}$$

• for  $\lambda_{ij} \geq 0$

- For every node  $i$  either  $\epsilon_i(1)=0$  or  $\epsilon_i(0)=0$
- We now construct the graph as follows:
  - If  $\epsilon_i(1)=0$  we introduce an edge  $z_i \rightarrow t$  with cost  $\epsilon_i(0)$
  - If  $\epsilon_i(0)=0$  we introduce an edge  $s \rightarrow z_i$  with cost  $\epsilon_i(1)$
  - For each pair of variables  $X_i, X_j$  that are connected by an edge in the MRF we introduce both an edge  $(z_i, z_j)$  and an edge  $(z_j, z_i)$ , both with cost  $\lambda_{i,j}=0$



# Cost of Cut

- Consider the cost of a cut  $(Z_s, Z_t)$ 
  - If  $z_i \in Z_s$ , then  $X_i$  is assigned a value of 0
    - Here  $z_i$  and  $t$  are on opposite sides of the cut and so we will get a contribution of  $\varepsilon_i(0)$  to the cost of the cut
    - This is precisely the  $X_i$  node energy of the assignment  $X_{i=0}$  as we would want
  - Similar argument applies when  $z_i \in Z_t$ 
    - We now consider the edge potential
- Cost of cut is precisely the same as the energy of the corresponding assignment
  - Thus min-cut algorithm is guaranteed to find assignment to  $X$  that minimizes energy, i.e.,  $\xi^{MAP}$

# A simple example


- We have an undirected graph of four variables  $X_1, X_2, X_3, X_4$ 
  - Connected in a loop with edges

$$X_1-X_2, X_2-X_3, X_3-X_4, X_1-X_4$$


- Assume the following energies

$$\varepsilon_1(0)=7, \varepsilon_2(0)=2, \varepsilon_3(0)=1, \varepsilon_4(0)=6$$

$$\lambda_{1,2}=6, \lambda_{2,3}=6, \lambda_{3,4}=2, \lambda_{1,4}=1$$



# Example of a minimum cut



Numbers on the edges represent their weight  $\lambda_{i,j}$

The cut is represented by the set of nodes in  $Z_t$

Dashed edges are ones that participate in the cut

In the MAP assignment  $X_1, X_2$ , and  $X_3$  are assigned label 1  
 $X_4$  is assigned label 0