Knowledge Graphs

Sargur N. Srihari srihari@buffalo.edu

Topics

- Knowledge Graphs (KGs)
- Statistical Relation Learning (SRL) for KGs
- Latent Feature Models
 - RESCAL, ER-MLP, Latent distance
 - Training SRL
- Markov Random Fields from KGs
- References

Google Knowledge Panel


Knowledge panels are information boxes that appear on Google when you search for entities (people, places, organizations, things) that are in the Knowledge Graph.

They are meant to help you get a quick snapshot of information on a topic based on Google's understanding of available content on the web.

en.wikipedia.org > wiki > Leonard_Nimoy 🔻

Leonard Nimoy - Wikipedia

Jump to **Star Trek** - The first six **Star Trek** movies feature the original **Star Trek** cast including **Nimoy**, who also directed two of the films. He played the elder Spock in the 2009 **Star Trek** movie and reprised the role in a brief appearance in the 2013 sequel, **Star Trek** Into Darkness, both directed by J. J. Abrams.



Knowledge Graph

• Fact: Leonard Nimoy was an actor who played the character Spock in the science-fiction movie Star Trek



Subject	Predicate	Object
(LeonardNimoy,	profession,	Actor)
(LeonardNimoy,	starredIn,	StarTrek)
(LeonardNimoy,	played,	Spock)
(Spock,	characterIn	, StarTrek)
(StarTrek,	genre,	ScienceFiction)

Subject and Object are *entities* and Predicate is the relation between them

[RDF standard: represent facts in the form of binary relationships]

Combine SPO triples to form a multi-graph:


Nodes represent entities

(all subjects and objects)


Directed edges represent relationships.

Edge direction indicates whether entities occur as subjects or objects, (edge points from subject to object)

Different relations are represented via different types of edges (also called edge labels)



Expanded Knowledge Graph



Nodes represent entities

Edge labels represent types of relations

Edges represent existing relationships


In addition to being a collection of facts, knowledge graphs provide type hierarchies (Leonard Nimoy is an actor, which is a person, which is a living thing)

and type constraints (e.g., a person can only marry another person, not a thing)

Open vs Closed-world assumption

- In closed world assumption (CWA)
 - a non-existing triple is a false relationship
 - No starredIn edge from Leonard Nimoy to Star Wars means

that Nimoy did not star in this movie



- In open world assumption (OWA)
 - a non-existing triple is interpreted as unknown
 - Corresponding relationship is either true or false
 - Missing edge does not mean that Nimoy did not star in Star Wars
- RDF and the Semantic Web make the OWA
- LWA often used for training relational models

Knowledge-Base Construction

- Curated approaches:
 - Triples created manually by closed group of experts
- Collaborative approaches:
 - Triples created manually by volunteers
- Automated semi-structured approaches:
 - Triples extracted automatically from semi-structured text (e.g.,infoboxes in Wikipedia)
 - via rules (hand-crafted or learned), or regular expressions
- Automated unstructured approaches
 - Triples extracted automatically from unstructured text via ML, NLP

KB Projects and Size

Method	Schema	Examples
Curated	Yes	Cyc/OpenCyc [23], WordNet [24], UMLS [25]
Collaborative	Yes	Wikidata [26], Freebase [7]
Auto. Semi-Structured	Yes	YAGO [4] [27], DBPedia [5], Freebase [7]
Auto. Unstructured	Yes	Knowledge Vault [28], NELL [6], PATTY [29], PROSPERA [30], DeepDive/Elementary [31]
Auto. Unstructured	No	ReVerb [32], OLLIE [33], PRISMATIC [34]

In schema-based approaches, entities and relations are represented via globally unique identifiers and all possible relations are predefined in a fixed vocabulary.


Knowledge Graph	Number of			
	Entities	Relation Types	Facts	
Freebase ³	40 M	35,000	637 M	
Wikidata <mark>**</mark>	18 M	1,632	66 M	
DBpedia (en) ⁵ YAGO2 ⁶	4.6 M	1,367	538 M	
YAGO2 6	9.8 M	114	447 M	
Google Knowledge Graph ⁷	570 M	35,000	18,000 M	


Uses of Knowledge Graphs

- KGs provide semantically structured information that is interpretable by computers
 - a property that is regarded as an important ingredient to build more intelligent machines
- Google's KG, stores 18 billion facts about 570 million entities, into the results of Google's search engine

Bing Satori Knowledge Graph

Richer Data for Entity Pane, Carousel, and Facts Across Segments







Semantic Knowledge Graph

en.wikipedia.org > wiki > Roberto_Benigni > Roberto Benigni - Wikipedia

YouTube - Oct 27, 2010

www.imdb.com⇒name ▼ Roberto Benigni - IMDb

People also ask

Roberto Remigio Benigni Cavallere di Gran Croce OMRI is an Italian actor, comedian screenwriter and director. Benigni made his acting debut in 1977's ...

Roberto Benigni was born on October 27, 1952 in Manciano La Misericordia, Castiglior Fiorentino, Tuscany, Italy as Roberto Remigio Benigni. He is an actor ...

YouTube - Jan 15, 201

Roberto Benigni


Italian actor, comedian, screenwriter and director, Benjani made his

acting debut in 1977's Berlinguer ti voglio bene, which he also wrote, and was directed by Giuseppe Berlolucci. Wikipedia Born: 27 October 1952 (age 67 years), Manciano, Italy

Awards: Academy Award for Best Actor, MORE

TV shows: La niù bella del mondo. I Dieci Com

Part of a semantic KG representing relationships, described as RDF triples, between the entities Roberto Benigni (e_1) and the film Life is Beautiful (e_2)



Tasks in KG construction/curation

Typical Knowledge Graph Tasks are:

1.Link Prediction

Predicting the existence of an edge

2. Entity Resolution

Is A. Guiness the same as Alec Guiness?

3.Link-based Clustering


 Extend feature-based clustering to relation based on similarity of entities and relations

Link Prediction

- Predicting the existence (or probability of correctness) of (typed) edges in the graph (i.e.,triples)
 - Existing KGs are often missing many facts, and some edges are incorrect

Entity Resolution

 Problem of identifying which objects in relational data refer to the same underlying entities



Nodes 1 and 3 refer to the identical entity, the actor Alec Guinness.

Node 2 on the other hand refers to Arthur Guinness, the founder of the Guinness brewery.

The surface name of node 2 ("A. Guinness") alone would not be sufficient to perform a correct matching as it could refer to both Alec Guinness and Arthur Guinness.

However, since links in the graph reveal the occupations of the persons, a relational approach can perform the correct matching

Link-based Clustering

- Extends feature-based clustering to a relational learning setting and groups entities in relational databases based on their similarity
- However, in link-based clustering, entities are not only grouped by the similarity of their features but also by the similarity of their links
- In social network analysis, link-basedclustering is also known as community detection