

Depth of a Model

Sargur N. Srihari

srihari@cedar.buffalo.edu


This is part of lecture slides on [Deep Learning](http://www.cedar.buffalo.edu/~srihari/CSE676):
<http://www.cedar.buffalo.edu/~srihari/CSE676>

Perspectives on Deep Learning

- Perspective 1
 - Learning the right representation
- Perspective 2
 - Depth allows computer to learn a multi-step computer program
 - Each layer is state of computer memory after executing another layer of instructions
 - More depth means more instructions in sequence
 - Sequential instructions offer greater power since later instructions can refer back to results of earlier ones



Measuring Depth of a Model

- View 1 (Computational Graph View)
 - No. of instructions to be executed
 - Longest path through the flowchart
 - Two equivalent computer programs will have different lengths depending on programming language




Different Depths in Computation

- Each node represents a computation
- Depth is length of longest path from input to output
- Graphs compute logistic regression $\sigma(w^T x)$
- Different programming languages provide different depth



Measuring Depth of a Model

- View 2 (Deep Probabilistic Model View)
 - Depth of graph describing how concepts are related to each other
 - Each concept may have a more complex underlying graph
 - Simpler concepts may be refined based on more complex concepts
 - Eye is more complex than face (which consists of two eyes)



Which depth is correct?

- No single correct value for depth of architecture just as no single correct length of a program
- Deep learning differs from traditional ML in that models involve
 - (a) composition of learned functions
 - (b) learned concepts