

Directed Generative Nets

Sargur N. Srihari

srihari@cedar.buffalo.edu

Topics in Deep Generative Models

- Boltzmann Machines
- Restricted Boltzmann Machines
- Deep Belief Networks
- Deep Boltzmann Machines
- Boltzmann Machines for Real-Valued Data
- Convolutional Boltzmann Machines
- Boltzmann Machines for Structured Sequential Objects
- Other Boltzmann Machines
- Back-Propagation through Random Operations
- **Directed Generative Nets**
- Drawing Samples from Autoencoders
- Generative Stochastic Networks
- Other Generation Schemes
- Evaluating Generative Models

Topics in Directed Generative Nets

- What are deep, fully directed models
 1. Sigmoid belief nets
 2. Differentiable generator nets
 3. Variational autoencoders (VAE)
 4. Generative adversarial networks (GAN)
 5. Generative moment matching networks
 6. Convolutional generative networks
 7. Autoregressive networks
 8. Linear autoregressive networks
 9. Neural autoregressive networks
 10. Neural Autoregressive density estimators (NADE)



Deep Generative Nets

- Directed models are prominent among PGMs
 - But in Deep Learning community they have been overshadowed by undirected models such as RBM
 - Note that DBNs are partially directed
 - Sparse coding models are shallow directed models
 - Used primarily for feature learners
 - Perform poorly in sample generation and density estimation
- Here we describe a variety of deep fully directed models

Sigmoid Belief Nets

- They are a simple form of directed PGMs with a specific kind of CPD
- It has a vector of binary states \mathbf{s} , with each element influenced by its ancestors:

$$p(s_i) = \sigma \left(\sum_{j < i} W_{j,i} s_j + b_i \right)$$



Structure of Sigmoid Belief Nets

- Most common structure is one that is divided into many layers
- Ancestral sampling proceeds through many hidden layers, finally generating the visible layer
 - Structure is very similar to a DBN
 - except that the units at the beginning of the sampling process are independent of each other rather than sampled from an RBM

—

Why study Sigmoidal Belief Nets?

- Such a structure is interesting for several reasons:
- One is that it is a universal approximator of probability distributions over the visible units
 - It can approximate any probability distribution over binary variables arbitrarily well, given enough depth, even if the width of individual layers is restricted to the dimensionality of the visible layer

Operation efficiency

- While generating a sample of the visible units is very efficient in a sigmoid belief network, most other operations are not
- Inference over the hidden units is intractable
- Mean field inference is also intractable
 - Because the lower variational bound involves taking expectations of cliques that encompass entire layers

Approaches to Performing Inference

1. Construct a different lower bound that is specialized for sigmoidal belief networks
 - This approach is applied to only very small networks
2. Use a learned inference mechanism
 - The Helmholtz machine is a sigmoid belief network combined with an inference network that predicts the parameters of the mean field distribution over the hidden units