

# GAN Variants

Sargur N. Srihari

[srihari@cedar.buffalo.edu](mailto:srihari@cedar.buffalo.edu)

# Topics in GANs

1. [GAN Motivation](#)
2. [GAN Theory](#),
3. [Mode Collapse](#)
4. [Wasserstein GAN](#)

## 5. GAN Variants


0. Increasing popularity of GANs
1. DCGAN
2. Conditional GAN
3.  $f$ -GAN
4. Laplacian Pyramid GAN
5. Other GAN Variants

Discussed here

# Why GANs are popular

- GANs can learn high-dimensional, complex real data distributions
  - Without relying on any assumptions
  - Can simply generate realistic samples from latent space
- This has lead to various applications
  - image synthesis, image attribute editing, image translation, domain adaptation and other academic fields

# Growth of GAN papers




[https://deephunt.in/  
the-gan-  
zoo-79597dc8c347](https://deephunt.in/the-gan-zoo-79597dc8c347)



# Deep Convolutional GAN

- DCGAN used for LSUN scene modeling
  - 100-d uniform distribution  $Z$  is projected to a small spatial extent convolutional representation with many feature maps
  - A series of four fractionally-strided convolutions convert this high level representation into a  $64 \times 64$  pixel image



# Deep Convolutional GAN (DCGAN)

- GAN architecture performs well when model architecture and hyperparameters are carefully selected
- A crafted DCGAN performs very well for image synthesis tasks
  - Latent representation space captures important factors of variation

# Images generated by DCGAN



Images trained on the LSUN data set

Images of bedrooms generated by DCGAN

# Conditional GAN

- GAN learning problem can be simplified by breaking the generation process into many levels of detail
- Can train conditional GANs that learn to sample from a distribution  $p(\mathbf{x}|y)$  rather than simply sampling from the marginal distribution  $p(\mathbf{x})$

# Extension to Conditional Model


- GANs can be extended to a conditional model if both  $G$  and  $D$  are conditioned on some extra information  $y$
- $y$  could be any kind of auxiliary information,
  - such as class labels or data from other modalities
- We can perform the conditioning by feeding  $y$  into both  $D$  and  $G$  as additional input layer

# Conditional GAN Objective Function

- In the generator the prior input noise  $p_z(z)$ , and  $y$  are combined in joint hidden representation, and the adversarial training framework allows for considerable flexibility in how this hidden representation is composed.
- In the discriminator  $x$  and  $y$  are presented as inputs and to a discriminative function (embodied again by a MLP in this case)
- Objective function two-player minimax game is


$$\min_G \max_D V(D, G) = E_{x \sim p_{\text{data}}(x)} [\log D(x|y)] \\ + E_{z \sim p(z)} [\log(1 - D(G(z|y)))]$$

# CGAN Architecture



# MNIST Results with CGAN

Generated MNIST digits, each row conditioned on one label





# $f$ -GAN

- GAN is a special case of a more general variational divergence estimation approach
- Any  $f$ -divergence can be used for training generative neural samplers
- Choices of divergence functions affect training complexity and quality of obtained generative models

# $f$ -Divergence Family

- Given two distributions  $P$  and  $Q$  that possess, respectively, an absolutely continuous density function  $p$  and  $q$  with respect to a base measure  $dx$  defined on the domain  $X$ , we define the  $f$ -divergence,

$$D_f(P \parallel Q) = \int_X q(x) f(p(x)/q(x)) dx$$

- where the generator function  $f: R^+ \rightarrow R$  is a convex, lower-semicontinuous function satisfying  $f(1) = 0$

# List of $f$ -Divergences

Name	$D_f(P  Q)$	Generator $f(u)$	$T^*(x)$
Kullback-Leibler	$\int p(x) \log \frac{p(x)}{q(x)} dx$	$u \log u$	$1 + \log \frac{p(x)}{q(x)}$
Reverse KL	$\int q(x) \log \frac{q(x)}{p(x)} dx$	$-\log u$	$-\frac{q(x)}{p(x)}$
Pearson $\chi^2$	$\int \frac{(q(x)-p(x))^2}{p(x)} dx$	$(u-1)^2$	$2\left(\frac{p(x)}{q(x)} - 1\right)$
Squared Hellinger	$\int \left(\sqrt{p(x)} - \sqrt{q(x)}\right)^2 dx$	$(\sqrt{u}-1)^2$	$\left(\sqrt{\frac{p(x)}{q(x)}} - 1\right) \cdot \sqrt{\frac{q(x)}{p(x)}}$
Jensen-Shannon	$\frac{1}{2} \int p(x) \log \frac{2p(x)}{p(x)+q(x)} + q(x) \log \frac{2q(x)}{p(x)+q(x)} dx$	$-(u+1) \log \frac{1+u}{2} + u \log u$	$\log \frac{2p(x)}{p(x)+q(x)}$
GAN	$\int p(x) \log \frac{2p(x)}{p(x)+q(x)} + q(x) \log \frac{2q(x)}{p(x)+q(x)} dx - \log(4)$	$u \log u - (u+1) \log(u+1)$	$\log \frac{p(x)}{p(x)+q(x)}$

# Variational estimation of $f$ -Divergence

- A lower bound on  $f$ -Divergence

$$\begin{aligned} D_f(P\|Q) &= \int_{\mathcal{X}} q(x) \sup_{t \in \text{dom}_{f^*}} \left\{ t \frac{p(x)}{q(x)} - f^*(t) \right\} dx \\ &\geq \sup_{T \in \mathcal{T}} \left( \int_{\mathcal{X}} p(x) T(x) dx - \int_{\mathcal{X}} q(x) f^*(T(x)) dx \right) \\ &= \sup_{T \in \mathcal{T}} (\mathbb{E}_{x \sim P} [T(x)] - \mathbb{E}_{x \sim Q} [f^*(T(x))]), \end{aligned}$$

– Where  $\mathcal{T}$  is an arbitrary class of functions  $T: X \rightarrow R$

This yields a lower bound for two reasons:

- Because of Jensen's inequality when swapping the integration and supremum operations.
- The class of functions  $\mathcal{T}$  may contain only a subset of all possible functions.

# Variational Divergence Minimization

- We use the variational lower bound on the  $f$ -divergence  $D_f(P||Q)$  in order to estimate a generative model  $Q$  given a true distribution  $P$
- We use two neural networks,  $Q$  and  $T$ 
  - $Q$  is our generative model, taking as input a random vector and outputting a sample of interest.
    - We parametrize  $Q$  through a vector  $\theta$  and write  $Q_\theta$
  - $T$  is our variational function, taking as input a sample and returning a scalar.
    - We parametrize  $T$  using a vector  $\omega$  and write  $T_\omega$

# Learning the Generative Model

- We can learn a generative model  $Q_\theta$  by finding a saddle-point of the following  $f$ -GAN objective function, where we minimize with respect to  $\theta$  and maximize with respect to  $\omega$ ,

$$F(\theta, \omega) = E_{x \sim P}[T_\omega(x)] - E_{x \sim Q_\theta}[f^*(T_\omega(x))]$$

# Algorithm for Variational Divergence Minimization

---

**Algorithm 1** Single-Step Gradient Method

---

- 1: **function** SINGLESTEPGRADIENTITERATION( $P, \theta^t, \omega^t, B, \eta$ )
  - 2:     Sample  $X_P = \{x_1, \dots, x_B\}$  and  $X_Q = \{x'_1, \dots, x'_B\}$ , from  $P$  and  $Q_{\theta^t}$ , respectively.
  - 3:     Update:  $\omega^{t+1} = \omega^t + \eta \nabla_{\omega} F(\theta^t, \omega^t)$ .
  - 4:     Update:  $\theta^{t+1} = \theta^t - \eta \nabla_{\theta} F(\theta^t, \omega^t)$ .
  - 5: **end function**
-

# The LAPGAN Model

- A series of conditional GANs can be trained to first generate a very low resolution version of an image
- Then incrementally add details to the image
- Called LAPGAN due to the use of a Laplacian pyramid to generate varying levels of detail



# Images generated by LAPGAN



Images of churches generated by LAPGAN model

# GAN framework

- Framework corresponds to a minimax two-player game
  - For arbitrary  $G$  and  $D$ , a unique solution exists
  - If  $G$  and  $D$  are MLPs can be trained using backprop
- In the space of arbitrary functions  $G$  and  $D$ , a unique solution exists, with  $G$  recovering the training data distribution and  $D$  equals to  $\frac{1}{2}$  everywhere
- There are hundreds of types of GANs

# Other GAN Variants

<b>GAN Type</b>	<b>Description</b>
GAN	The original (JSD Divergence)
WGAN	EMD Objective
Improved WGAN	No weight clipping WGAN
LS GAN	L2 Loss Objective
RWGAN	Relaxed WGAN Framework
McGAN	Mean/Covariance minimization objective
GMMN	Maximum mean discrepancy objective
MMDGAN	Adversarial kernel to GMMN
Cramer GAN	Cramer distance
Fisher GAN	Chi-square objective
EBGAN	Autoencoder instead of Discriminator
BEGAN	WGAN and BEGAN merger
MAGAN	Dynamic margin on hinge loss from EBGAN

# Converting zebras to horses



# References

- <https://towardsdatascience.com/gan-objective-functions-gans-and-their-variations-ad77340bce3c>
- <https://arxiv.org/pdf/1411.1784.pdf>
- <https://arxiv.org/pdf/1606.00709.pdf>