

# Numerical Computation

Sargur N. Srihari

srihari@cedar.buffalo.edu

This is part of lecture slides on [Deep Learning](http://www.cedar.buffalo.edu/~srihari/CSE676):  
<http://www.cedar.buffalo.edu/~srihari/CSE676>

# Topics

- Numerical Computation
  - Overflow and Underflow
  - Poor Conditioning
- Gradient-based Optimization

# Overview

- ML algorithms usually require a high amount of numerical computation
  - To update estimate of solutions iteratively
    - not analytically derive formula providing expression
- Common operations:
  - Optimization
    - Determine maximum or minimum of a function
  - Solving system of linear equations
- Just evaluating a mathematical function of real numbers with finite memory can be difficult

# Overflow and Underflow

- Problem caused by representing real numbers with finite bit patterns
  - For almost all real numbers we encounter approximations
- Although a rounding error it compounds across many operations and algorithm will fail
  - Numerical errors
    - Underflow: when nos close to zero are rounded to zero
      - $\log 0$  is  $-\infty$  (which becomes not-number for further operations)
    - Overflow: when nos with large magnitude are approximated as  $-\infty$  or  $+\infty$  (Again become not-no.)

# Function needing stabilization for Over/Underflow

- Softmax probabilities in multinoulli

$$\text{softmax}(\mathbf{x})_i = \frac{\exp(x_i)}{\sum_{j=1}^n \exp(x_j)}$$

- Consider when all  $x_i$  are equal to some  $c$ . Then all probabilities must equal  $1/n$ . This may not happen
  - When  $c$  is a large negative; denominator = 0, result undefined underflow
  - When  $c$  is large positive,  $\exp(c)$  will overflow
- Circumvented using  $\text{softmax}(\mathbf{z})$  where  $\mathbf{z} = \mathbf{x} - \max_i x_i$
- Another problem: underflow in numerator can cause  $\log \text{softmax}(\mathbf{x})$  to be  $-\infty$ 
  - Same trick can be used as for softmax

# Dealing with numerical considerations

- Developers of low-level libraries should take this into consideration
- ML libraries should be able to provide such stabilization
  - Theano for Deep Learning detects and provides this

# Poor Conditioning

- Conditioning refers to how rapidly a function changes with a small change in input
- Rounding errors can rapidly change the output
- Consider  $f(\mathbf{x}) = A^{-1}\mathbf{x}$ 
  - $A \in \mathbb{R}^{n \times n}$  has a eigendecomposition
    - Its condition no. is  $\max_{i,j} \left| \frac{\lambda_i}{\lambda_j} \right|$ , i.e. ratio of largest to smallest eigenvalue
    - When this large, the output is very sensitive to input error
    - Poorly conditioned matrices amplify pre-existing errors when we multiply by its inverse