

# Regularization and Underconstrained Problems

Sargur N. Srihari  
[srihari@cedar.buffalo.edu](mailto:srihari@cedar.buffalo.edu)

# Regularization Strategies

1. Parameter Norm Penalties
2. Norm Penalties as Constrained Optimization
3. Regularization and Under-constrained Problems
4. Data Set Augmentation
5. Noise Robustness
6. Semi-supervised learning
7. Multi-task learning
8. Early Stopping
6. Parameter tying and parameter sharing
7. Sparse representations
8. Bagging and other ensemble methods
9. Dropout
10. Adversarial training
11. Tangent methods

# Topics in Underconstrained Problems

1. Need for proper definition of ML problems
  1. Underconstrained closed-form solution
  2. Underconstrained iterative solution
2. Regularization for Logistic Regression with linearly separable classes
3. Moore Penrose inverse

# Underconstrained closed-form linear regression

- Regularization is often necessary for a machine learning problem to be properly defined
- Many linear models including PCA and linear regression depend on inverting the  $\Phi^T\Phi$  matrix

$$y(\mathbf{x}, \mathbf{w}) = \sum_{j=0}^{M-1} w_j \phi_j(\mathbf{x}) = \mathbf{w}^T \boldsymbol{\phi}(\mathbf{x})$$

$$\Phi = \begin{pmatrix} \phi_0(\mathbf{x}_1) & \phi_1(\mathbf{x}_1) & \dots & \phi_{M-1}(\mathbf{x}_1) \\ \phi_0(\mathbf{x}_2) & & & \\ & & & \\ \phi_0(\mathbf{x}_N) & & & \phi_{M-1}(\mathbf{x}_N) \end{pmatrix}$$

Samples X Dimensions

$$\mathbf{w}_{ML} = \Phi^+ \mathbf{t}$$

$$\Phi^+ = (\Phi^T \Phi)^{-1} \Phi^T$$

- This is not possible when  $\Phi^T\Phi$  is singular
  - This happens with fewer samples than dimensions

# Underconstrained logistic regression

- Logistic regression with linearly separable classes

- Task is under-determined

$$\boxed{\mathbf{w}^{\tau+1} = \mathbf{w}^{\tau} - \eta \nabla E_n} \quad \boxed{\nabla E_n = (y_n - t_n) \phi_n} \quad \text{where } y_n = \sigma(\mathbf{w}^T \phi_n)$$

- If  $\mathbf{w}$  separates perfectly, so will  $2\mathbf{w}$  and with higher likelihood

- SGD will continually increase  $\mathbf{w}$  and will never halt

- Solution left to the overflow handler

# Solution for Underconstrained Iterative

- Logistic regression with linearly separable classes is under-determined

$$\boxed{\mathbf{w}^{\tau+1} = \mathbf{w}^{\tau} - \eta \nabla E_n} \quad \boxed{\nabla E_n = (y_n - t_n) \phi_n} \quad \text{where } y_n = \sigma(\mathbf{w}^T \phi_n)$$

- Solution: Most forms of regularization guarantee convergence of iterative methods
  - e.g., weight decay

$$\boxed{\nabla E_n = -\sum_{n=1}^N \{ t_n - \mathbf{w}^T \phi(x_n) \} \phi(x_n)^T} \quad \text{without regularization}$$

$$\boxed{\nabla E_n = \left[ -\sum_{n=1}^N \{ t_n - \mathbf{w}^T \phi(x_n) \} \phi(x_n)^T \right] + \lambda \mathbf{w}} \quad \text{with regularization}$$

- Stops when slope of likelihood equals weight decay coefficient

# Regularization in linear algebra problems

- Several basic linear algebra problems use regularization
- We can solve underdetermined linear equations using Moore Penrose inverse

$$X^+ = \lim_{\alpha \rightarrow 0} (X^T X + \alpha I)^{-1} X^T$$

- Recall closed-form solution to linear regression with design matrix  $\Phi$

$$\Phi^+ = (\Phi^T \Phi)^{-1} \Phi^T$$