

Generative Models for Fingerprint Individuality using Ridge Types

Gang Fang, Sargur N. Srihari and Harish Srinivasan
Center of Excellence for Document Analysis and Recognition (CEDAR)
University at Buffalo, State University of New York
Amherst, New York 14228, U.S.A
{gfang2,srihari,hs32,vk33}@cedar.buffalo.edu

Abstract

Generative models of pattern individuality attempt to represent the distribution of observed quantitative features, e.g., by learning parameters from a database, and then use such distributions to determine the probability of two random patterns being the same. Considering fingerprint patterns, Gaussian distributions have been previously used for minutiae location and von-Mises distributions for minutiae orientation so as to determine the probability of random correspondence (PRC) between two fingerprints. Motivated by the fact that ridges have not been modeled in generative models, and using representative ridge points in fingerprint matching, ridge information is incorporated into the generative model by using a third distribution for ridge types. The joint probability of minutiae location, minutiae orientation and ridge type is modeled as a mixture distribution. The proposed model offers a more accurate fingerprint representation from which more reliable PRCs can be computed. Based on parameters estimated from fingerprint databases, PRCs using ridge types are seen to be much smaller than PRCs computed with only minutiae.

1 Introduction

Fingerprints have been used for identification from the early 1900s. Their use for uniquely identifying a person has been based on two premises: (i) they do not change with time and (ii) they are unique for each individual. Until recently, fingerprints had been accepted by courts as a legitimate proof of identification. But, after the 1999 case *US vs Byron Mitchell*, fingerprint identification has been challenged under the basis that the above premises have not been objectively tested and error rates have not been scientifically established. Though the first premise has been accepted, the second on individuality is the widely challenged.

Studies on the individuality of fingerprints date back to the late 1800s. More than twenty models have been pro-

posed to establish the improbability of two random people having the same fingerprint. All models try to quantify the uniqueness property to be able to defend fingerprint identification as a legitimate proof of identification in the courts. Each of these models tries to find out the probability of false correspondence, i.e. probability that a wrong person is identified given a latent fingerprint collected from a crime scene from a set of previously recorded whole fingerprints, i.e., the probability that the features of two fingerprints match though they are taken from different individuals. A match here does not necessarily mean an exact match but a match within given tolerance levels.

In a recent comprehensive survey paper [7], all previous models are classified into five different categories, namely, grid-based models, ridge-based models, fixed probability models, relative measurement models and generative models. Grid-based models include Galton [5] and Osterburgh [9] which were proposed in the late 80s and the early 90s respectively. One instance of ridge-based models is introduced by Roxburgh [11]. Fixed probability models contain the class of Henry-Balthazard models [6]. Relative measurement models include the Champod model [1] and the Trauring model [12]. The latest class of models, namely, the generative models aim at being flexible to represent observed distributions through different fingerprint databases and then ascertained uncertainties from models. Based on the the assumed non-independence of minutia locations and orientations, various mixture models could be used [10, 3].

In existing generative models only minutiae have been modeled without considering ridge features. These generative models are sufficient to model biometric algorithms based purely on minutiae. However they are insufficient to model forensic scenarios where latent prints are used. Due to the poor quality of latent prints ridge information is important in discrimination. With this motivation, we further embed ridge information into existing generative models by using a third distribution for ridge types. The proposed model offers more reasonable and accurate fingerprint representation and therefore a more reliable probability of ran-

dom correspondence (*PRC*).

Details of previous grid-based models, ridge-based models, fixed probability models and relative measurement models have been covered in the survey [7]. This paper only focuses on generative models. Section 2 reviews two existing generative models for minutiae location and orientation [10] and [3]. Section 3 introduces two new approaches to model ridges into different ridge types and the corresponding generative models for both minutiae and ridges. Experimental results are given in Section 4. The paper concludes with a summary in Section 5.

2 Generative Models for Minutiae

Two representative generative models are described respectively by Pankanti, et. al. [10] and Dass et. al. [3], both of which model the location and orientation of minutiae using a mixture model. The models are reviewed in details below. We will then introduce the improved models for both minutiae and ridges.

2.1 Mixture model using Hyper geometric and Binomial Distributions

In the fingerprint individuality model of [10], the following assumptions are made: (i) only ridge ending and ridge bifurcation are used without distinction, (ii) minutia orientation is independent of minutia position, (iii) minutiae are uniformly distributed with the restriction that they are not very close to each other, (iv) correspondences between minutiae in template and input are independent and have an equal weight, (v) fingerprint quality is not considered, (vi) positive matches are considered, negative ones are ignored, (vii) ridge widths are assumed to be the same, and (viii) only one true alignment exists between fingerprints.

Based on these assumptions, hyper geometric and binomial distributions are used to build a generative model on minutiae. Uniform distribution is assumed on minutiae location and direction, but eventually, a "correction" is introduced to account for this non-uniformity. [10] underestimates the probability of obtaining exactly k feature matches when compared to what is empirically observed from actual fingerprint databases. Another important observation is that the location and direction of minutiae points are not independent of one another; minutiae points in different regions of the fingerprint domain are observed to be associated with different region-specific minutiae directions. Moreover, minutiae points that are spatially close tend to have similar directions with each other.

The improved generative model in [3] addresses the deficiencies in [10]. In this paper ridge information is embedded into the model in [3] so as to further improve it.




Figure 1. Von-Mises distribution PDF

2.2 Mixture Model using Gaussian and Von-Mises Distributions for minutiae

In [3], a minutia is denoted by (X, D) where X denotes the location of a minutia and D denotes the orientation. A joint distribution of (X, D) , assuming that minutiae location and orientation are independent, can be represented by the mixture density function as in equation 1

$$f(s, \theta | \Theta_G) = \sum_{g=1}^G \tau_g f_g^X(s | \mu_g, \Sigma_g) \cdot f_g^D(\theta | \nu_g, \kappa_g, \rho_g) \quad (1)$$

where G is the number of mixture models, τ_g is the non-negative weight for that model. $f_g^X(s | \mu_g, \Sigma_g)$ is the probability density function of a bivariate Gaussian distribution over the position of minutiae. $f_g^D(\theta | \nu_g, \kappa_g, \rho_g)$ is the probability density function over the orientations, given by

$$\rho_g v(\theta) \cdot I\{0 \leq \theta < \pi\} + (1 - \rho_g) v(\theta - \pi) \cdot I\{\pi \leq \theta < 2\pi\} \quad (2)$$

where $v(\theta)$ is the von-mises distribution modeling the angular random variables in $[0, \pi)$ with ν_g and κ_g are the von-mises parameters. Figure 2.2 shows the nature of Von-Mises distribution.

Each model in the mixture model represents a cluster of minutiae. The minutiae location corresponding to the g^{th} cluster also has its orientation corresponding to the same cluster therefore establishing the interdependence between the two. Minutiae arising from the g^{th} component have directions that are either θ or $\theta + \pi$ and the probabilities associated with these two occurrences is ρ_g and $1 - \rho_g$ respectively. The model allows the ridge orientations to be different at different regions (different regions can be denoted by different models) while it makes sure that nearby minutiae have similar orientations (as nearby minutiae will belong to the same model).

Given a template T with n minutiae and an input/query Q with m minutiae and w out of them match, the probability

of Random Correspondence is given by

$$PRC_0 = p^*(w; Q, T) = \binom{n}{w} \cdot (p_m(Q, T))^w (1 - p_m(Q, T))^{n-w} \quad (3)$$

The probability is a binomial probability whose parameters are n and $p_m(Q, T)$. The latter is the probability that a random minutia from Q will match a minutia from T . Since most of the matchers try to maximize the number of matchings (i.e. they would find a matching even in a fingerprint that are totally different, we calculate the conditional expectation, conditioned on that fact that the number of matches is always greater than zero and equating this to the number of minutia matches between Q and T , the estimation is then

$$\frac{n \cdot p_m(Q, T)}{(1 - (1 - p_m(Q, T))^n)} = w_0 \quad (4)$$

w_0 is found out by the proposed models fit into Q and T and determining the number of matches by $k - pleat$ [2] matching algorithm. Value of $p_m(Q, T)$ can be found from Equ. 4. In a database contains N different fingers with L impressions of the same finger, $(Q, T)_{impostor}$ is used to denote all the $N(N - 1)L^2/2$ impostor pairs.

$$\overline{PRC} = \frac{1}{N(N - 1)L^2/2} \sum_{(Q, T)_{impostor}} p^*(w; Q, T) \quad (5)$$

3 Generative model for minutiae and ridges

Until now, only minutiae were used in the framework of generative models for fingerprints. Ridge details in fingerprints provide vital information about fingerprints and it is intuitive to see that any generative model that can utilize ridge detail as well into its framework can only be a better representation of the generative model for fingerprints. In [4], we proposed an algorithm to utilizes ridge information more effectively– by choosing representative points along the ridges. In specific, the chosen ridge points are used, together with minutiae, in existing minutiae matching algorithms with modification to benefit from their well-developed tolerance to non-linear deformation. Our extensive experimental results on both full-size fingerprint matching and partial fingerprint matching demonstrate that fingerprint verification using minutiae together with general ridge information is more accurate than using minutiae only. These observations, in the meanwhile, implicates that, the fingerprint individuality would be more accurately studied if we could consider general ridges together with minutiae when designing a generative model. Motivated by this work, we formulate below two possible ways to introduce ridge information to the existing generative model




Figure 2. Three types of ridge: left turn, right turn and unknown

for minutiae discussed in section 2.2. A fourth parameter ridge type \mathcal{T} is appended to the three existing parameters of x, y, θ of the minutiae and a generative model is built for these four parameters. The ridge type \mathcal{T} is discussed under two different ridge models. Both of these two models could be essentially summarized as: Two minutiae matching with each other on location and orientation may actually have two very different ridge shapes Thus, to make more reliable decision on whether on earth two minutiae match with each other or not, we use ridge shape information as well as minutiae location and orientation information.

3.1 Simple Ridge Model with three types

The aim of this simple ridge model is add ridge information to the generative model and at the same time ensure as little change as possible to the learning of the parameters of the generative model for minutiae discussed in section 2.2. Three types of ridges are defined as (i) left turn, (ii) right turn and (iii) unknown (Fig. 2). The shape of the ridge (one of three types) is inferred by considering the ridge as a set of ridge points sampled at equal interval of inter ridge width. A ridge point is considered as a left or a right according to the angle between (a) orientation of connection from minutia to ridge point, and (b) minutiae orientation. When k continuous lefts (rights) are observed on a ridge, this ridge is defined to be a left (right) turn ridge. If a ridge is neither a left turn nor a right turn, it is unknown type.

These three possible ridge types can be associated with any minutiae. Without loss of generality we can assume, that there exist only three possibly ridge shapes corresponding to a minutiae. For the generative model, the ridge type \mathcal{T} is modeled as a uniform distribution between the three types and the equation of the generative model is modified from Equ. 1 to include the uniform distribution and it is given in Equ. 6.




Figure 3. Ridge point categorized as “forward” or “backward” depending upon its orientation with the minutiae.

Table 1. Ridge Type IDs (RTID) Derived from RRP Types

RTID	T_i^6	T_i^{12}	RTID	T_i^6	T_i^{12}
1	1	1	2	1	2
3	1	3	4	1	4
5	2	1	6	2	2
7	2	3	8	2	4
9	3	1	10	3	2
11	3	3	12	3	4
13	4	1	14	4	2
15	4	3	16	4	4




Figure 4. Complex ridge model - 16 types. Circles (minutiae), squares near minutiae (6th RRP) and squares far from minutiae (12th RRP).

$$f(s, \theta, T | \Theta_G) = \sum_{g=1}^G \tau_g f_g^X(s | \mu_g, \Sigma_g) \cdot f_g^D(\theta | \nu_g, \kappa_g, \rho_g) \cdot f_g^T(T | a, b) \quad (6)$$

where $f_g^T(T | a, b)$ is a uniform distribution in the interval $[a, b]$ for the parameter ridge type. Ridge type frequencies in FVC2002 DB1 are used as the parameters in f_g^T . The three frequencies are found to be all around $\frac{1}{3}$. With the matching constraint that two ridges could match with each other if either (a) they have the same ridge type or (b) one of the ridge type is unknown, the probability that two random ridges could match with each other is $\frac{7}{9}$, which is fairly high and implicate that this simple ridge model may not introduce sufficient discriminative power into previous generative models. In experiments, we found that, the *PRC* values remain exactly the same as previous results as shown in Tab. 2. So, a more sophisticated model is designed next.

3.2 Sophisticated Ridge Model

The naive formulation of ridge types in section 3.1 enabled the experiments with individuality to be performed with very little change to the learning method discussed in 2.2. However, for better representation of fingerprints, a more accurate model is called for. The need for this is evident from the experiments and results (discussed next)




Figure 5. Corresponding drawn complex 16 ridges.




Figure 6. Ridge types labeled on real fingerprint ridges.

which do not show significant difference in the PRC values between the Generative models with and without ridge information. A more complex ridge model that includes more number of ridge types is described here. As mentioned before and in [4], a ridge is represented as ridge points, and the 6^{th} and 12^{th} ridge points are picked as two anchors. The reason for choosing these two numbers is described in [4]. By measuring the orientation θ of the connection from minutiae to these two ridge points, they are categorized as “forward” and “backward” types. Figure 3 depicts this idea.

We use T_i^6 and T_i^{12} to denote the RRP type of 6^{th} and 12^{th} ridge points on ridge R_i . T_i^6 and T_i^{12} could equals to 1, 2, 3, and 4 respectively decoded as left-backward, left-forward, right-forward and ridge-backward – the four possible RRP types, 16 different types can be derived for a ridge according to the mapping in Tab. 3.2. Fig. 4 shows all these 16 different types. Two ridges R_i and R_j could match with each other if and only if $|T_i^6 - T_j^6| \leq 1$ and $|T_i^{12} - T_j^{12}| \leq 1$, because mostly non-linear deformation could only change an RRP type to as far as its neighbor type. We also constrain that minutiae generated by the same gaussian model have the same ridge type. A generative model can be built with a similar equation as Equ. 6 except that uniform distribution is replaced by an empirical distribution. In specific, the frequencies of ridge types (Fig. 4), which will be used as the to replace f_g^T .

4 Experiments and Results

Generative models without ridge information and with the sophisticated ridge type model introduced in 3.2 have




Figure 7. Ridge type frequencies on FVC2002 Database 1.

been implemented and experiments have been conducted on FVC2002 DB1 [8]. The number of components G for the mixture model was found after validation using k -means clustering. The database has 100 different fingerprints with 8 impressions of the same finger. Thus, there are a total of 800 fingerprints using which the model has been developed.

We compare the results to that of [3]. We fit the mixture model on the database and then generate random fingerprints from the model. Values of PRC_0 and \overline{PRC} are calculated using the formulae introduced in Section 3. The results are presented in Table 2 and 3. The PRCs are calculated through varying number of minutiae in template (m), Input (n) and the number of minutiae matched (w). Table 2 shows that more the number of minutiae in the template and the input, the higher the PRC. In experiments conducted on the FVC2002 DB1, there are some differences between the results obtained here and the results in Jain et al. [3]. This may result from use of different matching algorithms, which w_0 depends on. Our highlight is that the PRC values embedded with ridge types model are never greater than PRC values without ridge information. Table 3 shows the PRC values corresponding to use of the sophisticated ridge type model in the generative model and these probabilities are lesser when compared to those in Table 2 indicating that ridge information strengthens individuality of fingerprints.

Because the ridge type models are independent on generative models, other recently proposed generative models such as [13] could also be embedded with ridge information in similar manner and are also expected to offer more reliable PRC values.

5 Conclusions

Generative models of individuality attempt to model the distribution of features and then use the models to determine the probability of random correspondence. While models have been proposed for minutiae information, ridge infor-

Table 2. PRC for different fingerprint matches with varying m (number of minutiae in template),n (number of minutiae in input) and w (number of matched minutiae) - Without ridge information. PRC_0 is PRC for the general population and \overline{PRC} is for PRC for FVC2002-DB1.

m	n	w	PRC_0	\overline{PRC}
26	26	12	6.0×10^{-6}	7.5×10^{-5}
		16	7.8×10^{-10}	1.3×10^{-6}
		26	1.2×10^{-25}	2.8×10^{-18}
36	36	12	1.1×10^{-5}	6.0×10^{-6}
		16	3.4×10^{-9}	3.0×10^{-8}
		36	2.4×10^{-40}	9.1×10^{-24}
46	46	12	2.9×10^{-4}	1.1×10^{-5}
		16	5.7×10^{-7}	7.6×10^{-8}
		46	8.3×10^{-50}	1.7×10^{-32}

mation has not been included in previous generative models. The paper has proposed two models for ridge types, a simple illustrative ridge type model with three ridge types and a more sophisticated model with 16 ridge types. We then modified the previous generative model with an empirical distribution to model ridge types. The new generative models are then compared by implementation and experiments with the previous generative model without ridge information on the FVC2002 DB1. The PRC obtained for a fingerprint template and input with 36 minutiae each with 12 matching minutiae is 3.1×10^{-8} (or three in a 100 million, or equivalently, 1 in 33 million). This is a much stronger result than without using ridge information which is 1 in 100,000 as reported in [3]. With 16 matching minutiae this probability is one in a trillion, as opposed to the earlier result of 1 in 100 million in [3]. The proposed ridge type model offers a more reasonable and more accurate fingerprint representation. PRC values with ridge types are much smaller than PRC values without ridge information. The results provide a much stronger argument for the individuality of fingerprints in forensics than previous generative models.

Acknowledgement This work was supported by a grant from the Department of Justice, Office of Justice Programs Grant NIJ 2005-DD-BX-K012. The opinions expressed are those of the authors and not of the DOJ.

References

[1] C. Champod and P. Margot. Computer assisted analysis of minutiae occurrences on fingerprints. *Proc. International Symposium on Fingerprint Detection and Identification*, J. Almog and E. Spinger, editors, Israel National Police, Jerusalem, page 305, 1996.

Table 3. PRC for different fingerprint matches with varying m (number of minutiae in template),n (number of minutiae in input) and w (number of matched minutiae) - With ridge information. PRC_0 is PRC for the general population and \overline{PRC} is for PRC for FVC2002-DB1.

m	n	w	PRC_0	\overline{PRC}
26	26	12	6.0×10^{-6}	7.5×10^{-5}
		16	7.8×10^{-10}	1.3×10^{-6}
		26	1.2×10^{-25}	2.8×10^{-18}
36	36	12	3.1×10^{-8}	3.6×10^{-8}
		16	9.1×10^{-13}	2.1×10^{-11}
		36	4.2×10^{-49}	9.5×10^{-32}
46	46	12	4.3×10^{-8}	2.9×10^{-9}
		16	2.0×10^{-12}	6.6×10^{-13}
		46	1.6×10^{-67}	3.1×10^{-49}

[2] S. Chikkerur, A. N. Cartwright, and V. Govindaraju. K-plet and cbfs: A graph based fingerprint representation and matching algorithm. *International Conference on Biometrics*, 2006.

[3] S. Dass, Y. Zhu, and A. K. Jain. Statistical models for assessing the individuality of fingerprints. *Fourth IEEE Workshop on Automatic Identification Advanced Technologies, 2005*, pages 3–9, 2005.

[4] G. Fang, S. N. Srihari, H. Srinivasan, and P. Phatak. Use of ridge points in partial fingerprint matching. *Proc. of the SPIE Biometric Technology for Human Identification IV conference*, 2007.

[5] F. Galton. *FingerPrints*. McMillan, London, 1892.

[6] E. Henry. *Classification and Uses of FingerPrints*. Routledge & Sons London, 1900.

[7] V. Krishnaswamy, S. N. Srihari, H. Srinivasan, and G. Fang. Individuality of finger prints: An assessment of models. *Submitted to Journal of Forensics Science*, 2007.

[8] D. Maio, D. Maltoni, and R. Cappelli. Fingerprint verification competition. <http://bias.csr.unibo.it/fvc2002/>, 2002.

[9] J. Osterburg. Development of a mathematical formula for the calculation of fingerprint probabilities based on individual characteristics. *Journal of American Statistical Association*, 772:72, 1997.

[10] S. Pankanti, S. Prabhakar, and A. K. Jain. On the individuality of fingerprints. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 24(8), 2002.

[11] T. Roxburgh. Galton’s work on the evidential value of fingerprints. *Indian Journal of Statistics*, 1:62, 1933.

[12] M. Trauring. Automatic comparison of finger-ridge patterns. *Nature*, page 197, 1963.

[13] Y. Zhu, S. Dass, and A. Jain. Compound stochastic models for fingerprint individuality. *Proc. of International Conference on Pattern Recognition*, 3:532–535, 2006.