

# Comparison of Classification Methods for Fingerprint Verification with Variable Numbers of Minutiae

Harish Srinivasan, Sargur N. Srihari and Matthew J. Beal

{hs32@cedar, mbeal@cse, srihari@cedar}.buffalo.edu

Department of Computer Science and Engineering,  
University at Buffalo, The State University of New York, Buffalo NY, USA

## 1. EXTENDED ABSTRACT

The fingerprint verification task answers the question of whether or not two fingerprints belongs to the same finger. The paper focuses on the classification aspect of fingerprint verification. Classification is the third and final step after the two earlier steps of feature extraction, where a known set of features (minutiae points) have been extracted from each fingerprint, and scoring, where a matcher has determined a degree of match between the two sets of features. Since this is a binary classification problem involving a single variable, the commonly used threshold method is related to the so-called receiver operating characteristics (ROC). In the ROC approach the optimal threshold on the score is determined so as to determine match or non-match. Such a method works well when there is a well-registered fingerprint image. On the other hand more sophisticated methods are needed when there exists a partial imprint of a finger- as in the case of latent prints in forensics or due to limitations of the biometric device. In such situations it is useful to consider classification methods based on computing the likelihood ratio of match/non-match. Such methods are commonly used in some biometric and forensic domains such as speaker verification where there is a much higher degree of uncertainty. This paper compares the two approaches empirically for the fingerprint classification task when the number of available minutiae are varied.

In both ROC-based and likelihood ratio methods, learning is from a general population of ensemble of pairs, each of which is labelled as being from the same finger or from different fingers. In the ROC-based method the best operating point is derived from the ROC curve. In the likelihood method the distributions of same finger and different finger scores are modeled using Gaussian and Gamma distributions. The performance of the two methods are compared for varying numbers of minutiae points available. Results show that the likelihood method performs better than the ROC-based method when fewer minutiae points are available. Both methods converge to the same accuracy as more minutiae points are available.

### 1.1. Scoring

We briefly review the method of matching two sets of minutiae obtained by a feature extractor. In order to compare two samples and to quantify their similarity, a similarity measure or a distance measure is used to compute a score that signifies the strength of match between the features of the two samples. The similarity measure converts the data from feature space to *distance* space. Features for fingerprints are characterized by minutiae. Data in distance space for fingerprints results out of comparing two sets of minutiae points. Each minutia is characterized by a triplet  $\{x, y, \theta\}$ , corresponding to the  $(x, y)$  coordinates of the minutia and its angular direction  $\theta$ . The following procedure can be used to compute a distance measure between two fingerprint imprints. Let  $T$  be a template image with  $M$  minutiae and  $I$  be the input image with  $N$  minutiae:

$$T = \{m_1, m_2, \dots, m_M\} \quad \text{where} \quad m_i = \{x_i, y_i, \theta_i\}. \quad i = 1..M. \quad (1)$$

$$I = \{m_1', m_2', \dots, m_M'\} \quad \text{where} \quad m_i' = \{x_j', y_j', \theta_j'\}. \quad j = 1..N. \quad (2)$$

The distance between a minutia  $m_j'$  in  $I$  and a minutia  $m_i$  in  $T$  can be calculated using *spatial distance* (sd) and *direction difference* (dd)

$$sd(m_j', m_i) = \sqrt{(x_j' - x_i)^2 + (y_j' - y_i)^2} \quad (3)$$

$$dd(m_j', m_i) = \min(|\theta_j' - \theta_i|, 360^\circ - |\theta_j' - \theta_i|) \quad (4)$$

In this paper we use a standard available *Bozorth matcher* to match two sets of minutiae points. In this way one can arrive at a distance space representation of the data that characterizes the strength of match between two samples.

## 1.2. Classification

The classification tasks answers the question whether or not a given pair of fingerprints came from the same finger or different finger. In forensic classification one sample in the pair can be referred to as is the *known* sample and the other considered to be the *questioned* sample. This task is called 1:1 verification.

### 1.2.1. The ROC approach

The ROC-based method classifies a pair of fingerprints as belonging to the same finger or different, by learning from a large general population of ensemble of pairs. The pairs of sample either belong to the same finger or different finger. Features are extracted for each sample, and feature vectors between the two samples in a pair are compared using the bozorth matcher. The result of such a matching is vector of distances, one distance value corresponding to every pair matched. The absolute value of these distances help classify whether the two samples in a pair belonged to the same finger or not. The ROC based method aims at deciding on a particular threshold in distance that separates the pairs that belonged to different to those that belonged to the same finger. The score obtained from the Bozorth matcher are such that, generally when the samples from a pair truly came from the same finger, the score is higher than if they come from different finger. The threshold to decide for classification is obtained by moving the threshold from left to right; and at every point the number of pairs that were classified incorrectly is calculated. An incorrect classification can be of two types.

- (i) Pairs truly belonged to the different finger but classified as same(False Positive).
- (ii) Pairs truly belonged to the same finger but classified as different(False Negative).

In a similar way a correct classification can be of two types.

- (i) Pairs truly belonged to the same finger and classified same(True Positive).
- (ii) Pairs truly belonged to different finger and classified different(True Negative).

As the threshold is moved from left to right on the distance scale, one can measure the four different variables mentioned above. A plot of True Positive against False Positive is the ROC. The best threshold, or the operating point is decided by choosing the threshold that gives the least average error. The average error is defined to be the average between False Negative and False positive. This definition of the average error gives equal importance to False Negative and False Positive.

Once the optimum threshold has been obtained by analyzing the ROC the classification task is easy. For a new pair of finger print samples, features are extracted and a similarity score is obtained using the Bozorth matcher. If this score is greater than the threshold, the the pair is classified as belonging to the same finger or else to different different fingers.

### 1.2.2. Likelihood Ratio Approach

As with the ROC method an ensemble of pairs of fingerprint samples are takenas the training set. The set is divided into two categories. Set *one* consists of pairs of finger print samples where each pair truly belongs the same finger. Set *two* consists of a pairs of finger print samples where each pair truly belongs to different persons. Features are extracted for these samples and the bozorth matcher computes a similarity score between the samples of each pair. Let  $\vec{D}_S$  denote the vector of distances between all pairs in set *one*, which represents the distribution of distances when samples truly came from the same finger. Similarly let  $\vec{D}_D$  denote the vector of distances between all pairs in set *two*, which represents the distribution of distances when samples truly came from different finger.

The two distributions can be modeled using parametric distributions such as Gaussian or Gamma whose probability density functions (pdfs) are as follows:

Gaussian:

Gamma:

The gamma distribution was chosen since the matcher always returns a positive score. On the other hand a Gaussian pdf assigns non-zero probabilities to negative scores. Also, since the gamma distribution can model the Gaussian it is potentially the better model.

The parameters that need to be learnt for such a model are typically derived from the sufficient statistics of the distribution, and are namely  $\mu$  (mean) and  $\sigma$  (variance) for a Gaussian, or  $\alpha$  (shape) and  $\beta$  (width) for a Gamma. These distributions are the same- and different-finger distributions.

The process of such 1:1 verification starts with minutiae extraction and then computing the score  $d$  between the features using the bozorth matcher. The likelihood ratio defined as  $\frac{P(D_S|d)}{P(D_D|d)}$  can be calculated, where  $P(D_S|d)$  is the probability density function value under the  $D_S$  distribution at the distance  $d$  and  $P(D_D|d)$  is the probability density function value under the  $D_D$  distribution at the distance  $d$ . If the likelihood ratio is greater than 1, then the classification answer is that the two samples do belong the same person and if the ratio is less than 1, they belong to different persons. If there are a total of  $N$  known samples from a person, then for one questioned sample  $N$ , 1:1 verifications can be performed and the likelihood ratios multiplied. In these circumstances it is convenient to deal with log likelihood-ratios rather than with just likelihood ratios. The log likelihood-ratio (LLR) is given by  $\log P(D_S|d) - \log P(D_D|d)$ . The decision of same-person is favored if  $\log P(D_S|d) - \log P(D_D|d) > 0$ , and the decision of different-person chosen if  $\log P(D_S|d) - \log P(D_D|d) < 0$ . When  $N$  of these 1:1 verifications are performed these LLR's are summed and then the decision is taken.

### 1.3. Experiments and Results

A database of fingerprint images from the FVC2002 data set was used. The FVC2002 data set contains four different databases. In each database a total of 10 fingers, each providing 8 samples contributing a total of 80 samples was taken as the data set. For the task of verification, a number of pairs of fingers can be considered. For a given finger that has 8 samples, there are  $\binom{8}{2} = 28$  same finger pairs. Hence for all the 10 fingers together there are  $28 \times 10 = 280$  same finger pairs. Similarly there are 2880 pairs of different finger samples. For the purpose of learning, half of the set was used as the training set and the remaining for testing. i.e., 140 samples from same finger pairs and 1440 pairs from different fingers were used for the purpose of training. Both ROC and likelihood methods were trained and tested using the same corresponding data sets. The first set of experiments were based on using all the minutiae points available for each sample and the second set of experiments were based on fingerprint verification with reduced number of minutiae points in each sample.

#### 1.3.1. All Minutiae Preserved

For each of the 4 databases, the training set consisted of 140 pairs of same fingers and 1440 pairs of different fingers. Each of these pairs resulted in a similarity score as a result of matching the samples in the pair using the Bozorth matcher. The reamaining pairs were used for testing the accuracy of the model. The average error rate defined as average of False positives and False negatives is used a measure of the error rate for the model. After deciding on the operating point, the thresholds were used to classify the test data set. Similarly the log-likelihood ratio is used to determine the classification. The classification decision boundary is given by the sign of the log likelihood-ratio, LLR,  $\log P(D_S|d) - \log P(D_D|d)$ .

The error rates on the four different datasets for both the ROC based method and the likelihood method using Gaussian and Gamma distributions were as follows: *Database 1*: ROC: 4.16, Gaussian: 3.93, Gamma: 3.93. *Database 2*: ROC: 6.45, Gaussian: 2.57, Gamma: 3.65. *Database 3*: ROC: 14.43, Gaussian: 13.96, Gamma: 13.96. *Database 4*: ROC: 6.14, Gaussian: 6.14, Gamma: 7.24.

The overall performance over all four databases was: ROC: , Gaussian: , Gamma: Thus showing that the likelihood methods, Gaussian and Gamma, did better than the ROC method.

#### 1.3.2. Reduced Minutiae Set

The 80 samples of fingerprints in each of the four databases were modified by reducing the numbers of minutiae points in each gradually. When the number of minutiae points are reduced in the sample, the minutiae matches between a pair reduces significantly. As a result, there is more uncertainty in the classification. The differences between the methods when the number of minutiae were reduced by \*\*\*x\*\*\* was \*\*\*y\*\*\*.

As the number of minutiae points were reduced, the same experiments were carried out and the average error rate of the two methods were compared with the average number of minutiae points per sample. Five different experimental setups were created, each of which had on an average 5 minutiae points less than the previous setup. The process of selecting the minutiae points to be removed from the sample was done at random. Since the process of removing the points were at random, the experiments discussed in this section were averaged over 5 different iterations. Also the number of minutiae points removed from each sample was proportional to the total amount of minutiae points present in the sample. The size of the training and test set was fixed to be the same as discussed in the previous section. The likelihood methods perform better when there are fewer number of minutiae points available on certain databases. As more minutiae points are available, the error rates converge. Also to note that modelling the distribution statistically was never worse than the ROC-based method. Thus the likelihood models perform better than the ROC-based method.

#### 1.4. Discussion

Motivated by the issue of quality and quantity in fingerprint data an empirical comparison of two different classification methods has been performed. Both methods involve mapping from feature space to distance space and the focus is on the methods of classification after certain desired number of features(minutiae points) have been extracted. As the number of minutiae points in the samples were reduced, the error rates increase with the statistical methods doing better than the ROC-based methods. The superior performance of the likelihood methods can be explained by the fact that they model the score distributions better and are not overly influenced by outliers in the data.