

Bayesian Network Structure Learning and Inference Methods for Handwriting

Mukta Puri, Sargur N. Srihari and Yi Tang

CEDAR, University at Buffalo, The State University of New York, Buffalo, New York, USA

mpuri2@buffalo.edu, srihari@cedar.buffalo.edu, yitang@buffalo.edu

Abstract—Forensic analysis of handwriting can benefit from constructing probabilistic models of characteristics specified by Questioned Document (QD) examiners. The task considered is as follows. We are given samples of the word *and*, together with a set of discrete characteristics. The characteristics are different for cursive writing and for hand-printing. The goal is to construct a model of the probability distribution and to make useful inferences using the model. Since the number of parameters needed for the complete joint distribution is over a million, a Bayesian network (BN) approach is proposed. The goal is to learn the structure of the BN and perform useful inferences. Since the structure learning problem is NP-hard, an approximate method that uses chi-squared tests between pairs of variables is used. Directed edges are included one at a time to minimize log-loss. The learned structure was used to obtain samples using Gibbs sampling and their rarity determined by inferring several probabilities: the joint probability of the formation, the probability of random correspondence (PRC) as a measure of the discriminatory power of the characteristics, conditional PRC associated with a given sample and the probability of finding a similar one within tolerance in a database of given size.

Keywords-Bayesian networks; structure learning; forensics

I. INTRODUCTION

Forensic handwriting examination, also known as questioned document (QD) examination, is based on the fact that no two persons write the same way while considering the fact that the writing of each person has its own individual characteristics [1], [2]. Based on years of training, QD examiners specify the individualizing characteristics in a given handwritten item. Our goal here is to construct a probabilistic model so that it may be used to quantify the degree of individualization provided by the characteristics.

II. CHARACTERISTICS AND PROBLEM COMPLEXITY

Consider the common English word *and*. Characteristics for this word given by QD examiners is in Table I for both cursive writing and for hand-printing. The handwritten *and* has nine characteristics $X = X_1, X_2, \dots, X_9$ where X_i takes up to 5 values for the cursive dataset and 6 values for the handprint dataset. Each sample with a set of characteristics can represent several instances of *and*. For instance, the three samples of cursive and in the first row in Table II(a) all contain the following feature values: $X_1 = 0$ $X_2 = 1$ $X_3 = 1$ $X_4 = 1$ $X_5 = 0$ $X_6 = 2$ $X_7 = 0$ $X_8 = 2$ $X_9 = 2$. The three samples of handprint and in the first row in Table II(d)

all contain the following feature values: $X_1 = 0$ $X_2 = 0$ $X_3 = 0$ $X_4 = 0$ $X_5 = 1$ $X_6 = 0$ $X_7 = 0$ $X_8 = 1$ $X_9 = 2$.

In the probabilistic formulation each feature is considered to be a random variable. The 9 features each have multinomial distributions with 4, 5, 3, 5, 4, 4, 4, 5 and 3 possible values for cursive data and 5, 6, 5, 5, 3, 5, 6, 4, and 3 possible values for handprint data. If we assume that all variables are dependent on every other variable, the number of parameters needed for cursive data is $4 \times 5 \times 3 \times 5 \times 4 \times 4 \times 4 \times 5 \times 3 - 1 = 287,999$ and for handprint data is $5 \times 6 \times 5 \times 5 \times 3 \times 5 \times 6 \times 4 \times 3 - 1 = 809,999$.

III. BAYESIAN NETWORKS

The computational complexity and the need for samples can be minimized by exploiting statistical independencies that exist between variables using Probabilistic graphical models [3], [4]. Bayesian Networks (BN) are directed graphical models, where the nodes correspond to variables and edges their dependencies. Lack of edges indicate independencies. BNs are more straight-forward to construct than undirected models known as Markov networks, principally because the latter involve a global partition function while BNs can be factored into local dependencies.

A. Bayesian Network Structure Learning (BNSL)

BN structure is learned using Algorithm BNSL which is a variant of one described in [5]. Its performance is compared to the case where all variables are assumed to be independent. The pairwise chi-squared (χ^2) test, which yields a measure of independence between two variables, is used to obtain values between all possible pairs of nodes (features) is first calculated using Equation 1 and stored in a set E_p in non-increasing order of χ^2 statistics.

$$\chi^2(\mathcal{D}) = \sum_{i,j} \frac{(O[x_i,y_j] - E[x_i,y_j])^2}{E[x_i,y_j]} \quad (1)$$

Starting from a model without any edges but containing all the vertices, G , the first pair in E_p , (v_i, v_j) was removed from the set and a new edge $(v_i \rightarrow v_j)$ or $(v_j \rightarrow v_i)$ was added to G based on which edge increased the log-likelihood value of the model more while creating a directed acyclic graph (DAG). The isDAG function was used to verify that the newly created graph would not be a DAG. The score for the BN is given by the negative log-likelihood, or the *log-loss*:

Table I
CHARACTERISTICS OF HANDWRITTEN *and* AS SPECIFIED BY QD EXAMINERS.

(a) Cursive

Initial stroke of formation of 'a' (X_1)	Formation of staff of 'a' (X_2)	Number of arches of 'n' (X_3)	Shape of arches of 'n' (X_4)	Location of midpoint of 'n' (X_5)	Formation of staff of 'd' (X_6)	Formation of initial stroke of 'd' (X_7)	Formation of terminal stroke of 'd' (X_8)	Symbol in place of the word 'and' (X_9)
Right of staff (0)	Tented (0)	One (0)	Pointed (0)	Above baseline (0)	Tented (0)	Overhand (0)	Curved up (0)	Formation (0)
Left of staff (1)	Retraced (1)	Two (1)	Rounded (1)	Below baseline (1)	Retraced (1)	Underhand (1)	Straight across (1)	Symbol (1)
Center of staff (2)	Looped (2)	No fixed pattern (2)	Retraced (2)	At baseline (2)	Looped (2)	Straight across (2)	Curved down (2)	None (2)
No fixed pattern (3)	No staff (3)		Combination (3)	No fixed pattern (3)	No fixed pattern (3)	No fixed pattern (3)	No obvious ending stroke (3)	
	No fixed pattern (4)		No fixed pattern (4)				No fixed pattern (4)	

(b) Hand-print

Number of strokes of formation of 'a' (X_1)	Formation of staff of 'a' (X_2)	Number of strokes of formation of 'n' (X_3)	Formation of staff of 'n' (X_4)	Shape of arch of 'n' (X_5)	Number of strokes of formation of 'd' (X_6)	Formation of staff of 'd' (X_7)	Initial stroke of 'd' (X_8)	Unusual formation (X_9)
One continuous (0)	Tented (0)	One continuous (0)	Tented (0)	Pointed (0)	One continuous (0)	Tented (0)	Top of staff (0)	Formation (0)
Two strokes (1)	Retraced (1)	Two strokes (1)	Retraced (1)	Rounded (1)	Two strokes (1)	Retraced (1)	Bulb (1)	Symbol (1)
Three strokes (2)	Looped (2)	Three strokes (2)	Looped (2)	No fixed pattern (2)	Three strokes (2)	Looped (2)	No fixed pattern (2)	None (2)
Upper case (3)	No staff (3)	Upper case (3)	No staff (3)		Upper Case (3)	Single down (3)	Undetermined (3)	
No fixed pattern (4)	Single line down (4)	No fixed pattern (4)	No fixed pattern (4)		No fixed pattern (4)	Single up (4)		
	No fixed pattern (5)					No fixed pattern (5)		

Table II

EXAMPLES OF SAMPLES WITH HIGHEST AND LOWEST JOINT PROBABILITIES: (A) CURSIVE- HIGHEST (B) CURSIVE- LOWEST (C) HANDPRINT- HIGHEST (D) HANDPRINT- LOWEST. THE SAMPLES WERE OBTAINED BY GIBBS SAMPLING OF BNs.

(a) Cursive-Common

Samples with Characteristics	Probability
and and [111022022]	5.47×10^{-3}
and and [211022022]	5.10×10^{-3}
and and and [111322022]	4.41×10^{-3}
and [111022012]	4.32×10^{-3}
and and [111022122]	4.21×10^{-3}

(b) Cursive-Rare

Samples with Characteristics	Probability
and and and [002432212]	2.50×10^{-9}
and and [342433102]	1.24×10^{-9}
and and [342431242]	3.2×10^{-10}
and and [242433342]	1.63×10^{-10}
and and [222433342]	1.61×10^{-10}

(c) Handprint-Common

Samples with Characteristics	Probability
and and [010110112]	1.67×10^{-2}
and [010110302]	1.64×10^{-2}
and and [000110112]	1.29×10^{-2}
and and [000110302]	1.27×10^{-2}
and and [010110212]	8.43×10^{-3}

(d) Handprint-Rare

Samples with Characteristics	Probability
and and [313323122]	1.31×10^{-9}
and [353423532]	8.38×10^{-10}
and and [333323332]	6.69×10^{-10}
and and [453124532]	4.39×10^{-10}
and and [353423522]	2.85×10^{-10}




Figure 1. Heuristics of determining Structure in Algorithm BNSL

$$s(\mathcal{D}|G) = - \sum_{i=1}^N \sum_{j=1}^n \log P(x_{ij}|\text{pa}_{ij}), \quad (2)$$

If either edges do not increase the log-likelihood of the model or do not create a DAG, no edge was added to G . This process is repeated until the set E_p became empty.

Algorithm 1 BNSL

Input: set $S = \{v_1, \dots, v_n\}$ of n random variables, training data \mathcal{D}_r and validation data \mathcal{D}_v


Output: Graph $G^* = \{V, E^*\}$

1. Compute pairwise χ^2 statistics, $\chi^2_{(v_i, v_j)}$
 2. Construct ordered set $E_p = \{(v_i, v_j) | i \neq j\}$ in descending order of χ^2
 3. Set $G^* = \{V, E^*\}$, where $V = S$, $E^* = \emptyset$
 4. Set $k = 1$
 5. **Repeat**
 6. Pick the first pair (v_i, v_j) from E_p
 7. Create $G_{c_1} = (V, E_{c_1}), E_{c_1} = E^* + \{v_i \rightarrow v_j\}$
 8. Create $G_{c_2} = (V, E_{c_2}), E_{c_2} = E^* + \{v_j \rightarrow v_i\}$
 9. Compute s_{k-1}, s_{c_1} for G^* and G_{c_1} from \mathcal{D}_r
 10. **If** $(s_{c_1} > s_{k-1})$ & (isDAG(G_{c_1}))
 11. **Then** $G^* = G_{c_1}$
 12. Compute s_{k-1}, s_{c_2} for G^* and G_{c_2} from \mathcal{D}_r
 13. **If** $(s_{c_2} > s_{k-1})$ & (isDAG(G_{c_2}))
 14. **Then** $G^* = G_{c_2}$
 15. Increment k by 1
 16. $E_p = E_p - \{(v_i, v_j)\}$
 17. **Until** $E_p = \emptyset$
 18. **return** G^*
-


Since determining the log-likelihood to determine the addition of each edge takes exponential-time, while constructing the models, only up to two parents per node was considered. As shown in Figure 1(a) and 1(b), if the new node 'b' to be added will become the parent of node 'a', the edge is added to our structure as long as 'a' has no parent or 'a' has only a single parent. As shown in Figure 1(c), if 'a' already has 2 parents 'c' and 'd', the new edge is not added to the graph whether or not it decreases the log loss.

B. Parameter Estimation

Based on the learnt BN structures the component conditional probability distributions (CPDs) are shown in Figure



(a) Cursive: $P(X) = P(X_2)P(X_9)P(X_4/X_2) \cdot P(X_6/X_2)P(X_7/X_4)P(X_3/X_4)P(X_8/X_6)P(X_1/X_7)P(X_5/X_3)$



(b) Hand-print: $P(X) = P(X_2)P(X_3) \cdot P(X_6)P(X_7)P(X_9)P(X_1/X_6)P(X_8/X_6)P(X_5/X_1)P(X_4/X_5)$

Figure 2. BN models determined using Algorithm BNSL

2. If we assume all variables are independent, the joint probability is a product of the marginals: $P(X) = \prod_{i=1}^9 X_i$.

The parameters of the models were determined by evaluating the Conditional Probability Tables (CPTs) for only the factors in the joint probability. The CPTs were calculated using maximum likelihood estimates. In order to avoid zero probabilities, or to avoid cases of being divided by zero, additive smoothing was used.

The values of marginal densities calculated are shown in Table III whereas the values of conditional densities calculated are shown in Tables IV and IV.

$$\theta_i = P(X_i) = (n_i(X_i) + \alpha) / (N + \alpha d), \quad (3)$$

where, $\alpha = 1$ for add-one smoothing, and The number of independent parameters needed the BNs are as follows: *Cursive*: $2 + 4 + 12 + 15 + 20 + 15 + 10 + 12 + 9 = 99$.

Table IV
CONDITIONAL PROBABILITY TABLES OF CHARACTERISTICS
FOR CURSIVE WRITING:

(a) $X_4|X_2$

X_4/X_2	0	1	2	3	4
0	3.83e-1	3.79e-1	4.50e-1	1.54e-1	3.08e-1
1	3.03e-1	2.21e-1	1.56e-1	3.85e-1	1.88e-1
2	3.31e-2	9.52e-2	7.41e-2	3.85e-2	4.96e-2
3	2.39e-1	2.95e-1	3.10e-1	3.85e-1	4.18e-1
4	4.26e-2	9.52e-3	1.06e-2	3.85e-2	3.66e-2

(b) $X_6|X_2$

X_6/X_4	0	1	2	3	4
0	4.50e-2	1.32e-2	1.33e-2	4.e-2	1.57e-2
1	2.58e-1	2.64e-1	1.11e-1	1.20e-1	1.26e-1
2	5.55e-1	6.23e-1	7.80e-1	6.40e-1	6.65e-1
3	1.42e-1	1.e-1	9.55e-2	2.e-1	1.94e-1

(c) $X_7|X_4$

X_7/X_4	0	1	2	3	4
0	4.26e-1	5.28e-1	3.86e-1	4.95e-1	3.52e-1
1	3.98e-1	2.87e-1	4.94e-1	3.27e-1	2.96e-1
2	1.18e-1	1.36e-1	8.30e-2	1.10e-1	1.48e-1
3	5.81e-2	4.96e-2	3.73e-2	6.78e-2	2.04e-1

(d) $X_3|X_4$

X_3/X_4	0	1	2	3	4
0	4.70e-2	1.55e-1	4.46e-1	2.65e-2	2.08e-1
1	9.44e-1	8.23e-1	5.46e-1	9.54e-1	2.26e-1
2	9.41e-3	2.19e-2	8.33e-3	1.91e-2	5.66e-1

(e) $X_8|X_6$

X_8/X_6	0	1	2	3
0	7.14e-2	2.14e-1	1.98e-1	1.68e-1
1	1.61e-1	2.90e-1	2.79e-1	1.21e-1
2	5.e-1	3.34e-1	3.39e-1	2.47e-1
3	2.14e-1	1.14e-1	1.01e-1	3.13e-1
4	5.36e-2	4.85e-2	8.26e-2	1.51e-1

(f) $X_1|X_7$

X_1/X_7	0	1	2	3
0	9.67e-2	1.74e-1	1.96e-1	7.57e-2
1	3.22e-1	3.96e-1	3.90e-1	3.41e-1
2	3.96e-1	2.64e-1	3.15e-1	2.92e-1
3	1.85e-1	1.66e-1	9.94e-2	2.92e-1

(g) $X_5|X_3$

X_5/X_3	0	1	2
0	5.21e-1	1.60e-1	3.07e-1
1	3.30e-3	2.51e-2	1.33e-2
2	4.59e-1	8.02e-1	4.53e-1
3	1.65e-2	1.33e-2	2.27e-1

Handprint: $5 + 4 + 5 + 2 + 4 + 15 + 20 + 10 + 12 = 77$. Also, as calculated in Section II, the number of parameters needed for cursive and handprint *and* assuming all features are dependent to each other is 287,999 and 809,999 respectively. The number of parameters required for the BNs is far fewer than the number of parameters required when assuming all dependencies.

C. Evaluation of Model Complexity and Accuracy

The previous BNSL [5] model had a few drawbacks. The direction of the edge added to the first pair of nodes was not checked. Hence, it only supplied a sub-optimal

Table V
CONDITIONAL PROBABILITY TABLES OF CHARACTERISTICS
FOR HANDPRINT WRITING:

(a) $X_1|X_6$

X_1/X_6	0	1	2	3	4
0	9.56e-1	8.15e-1	2.e-1	2.13e-2	3.45e-2
1	1.32e-2	1.07e-1	2.e-1	1.06e-1	3.45e-2
2	1.10e-3	5.95e-3	2.e-1	2.13e-2	3.45e-2
3	2.31e-2	4.17e-2	2.e-1	8.09e-1	3.45e-2
4	1.10e-3	5.95e-3	2.e-1	2.13e-2	3.45e-2

(b) $X_8|X_6$

X_8/X_6	0	1	2	3	4
0	3.45e-1	3.77e-1	2.50e-1	4.78e-1	3.57e-2
1	6.38e-1	4.97e-1	2.50e-1	2.17e-2	3.57e-2
2	6.59e-3	1.20e-2	2.50e-1	1.74e-1	3.57e-2
3	9.89e-3	1.14e-1	2.50e-1	3.26e-1	3.57e-2

(c) $X_5|X_1$

X_5/X_1	0	1	2	3	4
0	1.35e-1	5.41e-2	3.33e-1	3.79e-1	7.14e-2
1	7.97e-1	7.57e-1	3.33e-1	2.12e-1	7.14e-2
2	6.80e-2	1.89e-1	3.33e-1	4.09e-1	7.14e-2

(d) $X_4|X_5$

X_4/X_5	0	1	2
0	4.76e-1	2.31e-1	2.45e-1
1	2.98e-1	6.09e-1	3.73e-1
2	2.38e-2	9.17e-3	9.09e-3
3	1.07e-1	4.93e-2	1.36e-1
4	9.52e-2	1.02e-1	2.36e-1

Table VI
EVALUATION OF MODELS (LOG LOSS).

	Bayesian Network	Independent Variables
Cursive	25329	25994
Handprint	7898	8059

solution to structure learning. Also, as the possibility of each node having any number of parents was considered, the complexity of calculating the log-loss while determining the addition of each edge could turn out to be exponential. Also, the log loss of the previous model when compared to that of the independent case was not very low. The new BNSL algorithm that we constructed in this paper tries to overcome these drawbacks.

1) *Evaluation of Model Accuracy:* The models were evaluated by calculating the log-loss of each model. The log-loss is given by negating the log-likelihood given in Equation 2.

The log-loss values were calculated for both the BN model and the model that assumes all variables are independent as shown in Table VI. For both cases the log loss is higher when all variables are assumed independent indicating that the BN structure is the better model.

2) *Evaluation of Model Complexity:* In this algorithm, exponential search for each edge is reduced to polynomial-time by exploiting dependency constraints, the chi-squared values, between variables. Also, the exponential complex-

Table III
MARGINAL PROBABILITIES OF CHARACTERISTICS:

(a) Cursive									
	X_1	X_2	X_3	X_4	X_5	X_6	X_7	X_8	X_9
0	1.34e-1	1.36e-1	9.75e-2	3.79e-1	1.99e-1	1.69e-2	4.66e-1	1.96e-1	3.25e-4
1	3.58e-1	6.12e-1	8.79e-1	2.22e-1	2.21e-2	2.26e-1	3.58e-1	2.61e-1	3.25e-4
2	3.34e-1	1.21e-1	2.34e-2	7.73e-2	7.61e-1	6.40e-1	1.17e-1	3.31e-1	9.99e-1
3	1.74e-1	7.14e-3		3.06e-1	1.82e-2	1.17e-1	5.91e-2	1.31e-1	
4		1.23e-1		1.66e-2				8.18e-2	

(b) Handprint									
	X_1	X_2	X_3	X_4	X_5	X_6	X_7	X_8	X_9
0	9.02e-1	3.16e-1	9.25e-1	2.68e-1	1.44e-1	7.96e-1	2.89e-2	3.51e-1	4.04e-2
1	3.07e-2	4.09e-1	6.14e-3	5.44e-1	7.63e-1	1.44e-1	2.62e-1	5.90e-1	8.79e-4
2	8.77e-4	5.70e-2	8.77e-4	9.65e-3	9.31e-2	8.77e-4	1.32e-1	1.49e-2	9.59e-1
3	5.61e-2	4.29e-2	6.67e-2	6.49e-2		3.77e-2	4.34e-1	4.39e-2	
4	1.05e-2	2.89e-2	1.75e-3	1.13e-1		2.19e-2	5.08e-2		
5		1.45e-1					9.20e-2		

ity of determining log-loss was reduced by considering a maximum of only two parents per node.

IV. INFERRING RARITY OF SAMPLES FROM MODEL

A number of inference tasks can be done in order to determine the rarity of a given handwriting sample such as the calculation of: joint probability of the sample, PRC or the Probability of Random Correspondence, n PRC, and conditional n PRC [7].

A. Joint Probability

A higher joint probability of a sample signifies that the sample is more common whereas a lower joint probability signifies that the sample is rare. Hence, the calculation of the joint probability gives a direct relation to the rarity of a sample, or its degree of individualization. The joint probability is estimated using the factorizations in Figure 2.

Values of the joint probabilities for several Gibbs samples are in Table II, where samples with the highest and lowest joint probabilities are shown. The rare samples are that have individualizing characteristics.

B. PRC

PRC is the probability that two independent, identically distributed samples x and y have the same characteristics within a specified tolerance, ϵ . It is given by:

$$\rho = P(z = 1) = \sum_X \sum_Y P(z = 1|X, Y)P(X)P(Y) \quad (4)$$

Where $P(X) = P(Y)$ is the joint probability of X . z is an indicator variable such that $P(z = 1|X, Y) = 1$ if $X = Y \pm \epsilon$ and 0 otherwise. Here, we assume $\epsilon = 0$ and evaluate PRC for $X = Y$. However, it is not compulsory for ϵ to be 0; for any value of $\epsilon \neq 0$, the complexity of calculating the PRC becomes exponential and is hence such a case is not considered.




Figure 3. n PRC vs n for cursive and handprint datasets. Cursive dataset is more individualistic

Using Equation 4 on the BN model constructed in Section III-A and parameters learned as described in Section III-B, the PRC was evaluated as: (1) *Cursive PRC* = 7.90×10^{-4} (2) *Handprint PRC* = 6.85×10^{-3}

This value of PRC can be used to compare the discriminative power of *and* to those of other letters and combinations.

C. n PRC

n PRC is the probability that among a set of n samples y_1, y_2, \dots, y_n some pair have the same characteristics within a specific tolerance (ϵ), where $n \geq 2$. The n PRC can be written as:

$$\rho[n] = 1 - (1 - \rho)^{\frac{n(n-1)}{2}}. \quad (5)$$

The different values of n PRC obtained for different values of n were plotted as shown in Figure 3.

It is observed that the n PRC for both cursive and handprint gradually increases until it reaches 1. However, the

n PRC for the hand-print data seems to increase faster and reach 1 faster than the n PRC for the cursive dataset.

D. Conditional n PRC

The conditional n PRC finds the probability that in a set of n samples, one sample with a specific value coincides, within tolerance, with another sample. It finds the probability of finding a match in the database. In the case of identical match the conditional n PRC can be shown to be equivalent to the following equation.

$$1 - (1 - P(X_s))^n \quad (6)$$

V. SUMMARY AND DISCUSSION

Individualizing characteristics are central to writer identification. We have proposed a method for modeling the probability distribution of a given set of characteristics, so that a small probability of evidence (or high rarity) can be considered as a measure of individualization. It is based on directed graphical models known as Bayesian networks (BNs)— which do not suffer from the severe computational complexity of full joint distributions but work better than the extreme assumption of independent variables. Since BN construction is NP-hard, an approximate algorithm has been proposed and demonstrated with samples of handwritten *and*.

Samples obtained from the BNs using Gibbs sampling were used to demonstrate several inferences: determining joint probability, PRC, n PRC, and conditional n PRC of the samples. The joint probability gave a direct measure of the rarity; the PRC helped to compare the discriminative power of the given letter combination to those of other letters and combinations; the n PRC gave the probability of finding a pair with the same features in a group of samples; and the conditional n PRC gave the probability of finding a similar sample within tolerance in a database of given size.

REFERENCES

- [1] A. S. Osborn, *Questioned Documents*, Nelson Hall Pub, 1929.
- [2] R. A. Huber and A. M. Headrick, *Handwriting Identification: Facts and Fundamentals*, CRC Press, 1999.
- [3] C. M. Bishop, *Pattern Recognition and Machine Learning*, Springer, 2006.
- [4] D. Koller, *Probabilistic Graphical Models*, MIT Press, 2009.
- [5] Y. Tang, S. N. Srihari, Efficient and Accurate Learning of Bayesian Networks using Chi-Squared Independence Tests, *Proc. Intl. Conf. Pattern Recognition*, 2012.
- [6] J. Peters, D. Janzing and B. Scholkopf, Causal Inference on Discrete Data Using Additive Noise Models, *IEEE TPAMI*, 33(12):2436 -2450, Dec 2011.
- [7] C. Su and S. N. Srihari, Probability of Random Correspondence of Fingerprints, *Proc. International Workshop on Computational Forensics*, Springer, 2009, pp. 55-66.
- [8] S. N. Srihari, Evaluating the Rarity of Handwriting Formations, *Proc. Int. Conf. Document Analysis and Recognition*, 2011, 618-622.
- [9] S. N. Srihari, S. Cha, H. Arora and S Lee, Individuality of Handwriting, *Journal of Forensic Sciences*, 2002, 47(4): 856-872.