Individuality of Fingerprints

Sargur N. Srihari

Department of Computer Science and Engineering University at Buffalo, State University of New York srihari@cedar.buffalo.edu

IAI Conference, San Diego, CA July 25, 2007



- 1. Motivation
- 2. Previous Individuality Models
- 3. New Models and Studies
 - 1. Generative Models
 - 2. Cohort Studies: Twins
- 4. Conclusions

1. Motivation

- Foundation of fingerprint identification has two premises:
 - 1. Fingerprints never change
 - 2. No two fingerprints (from different fingers) are alike
- Scientific basis for establishing positive identification
 - Daubert v Merrell Dow (1993)
 - Second premise challenged in USA v Mitchell (1999)
- Leads to statistical basis for fingerprint identification

Probability of Random Correspondence



- What is the probability that the observed fingerprint matches with a template fingerprint purely due to chance?
 - This probability can be assessed by estimating the variability inherent in fingerprint ridge patterns

2. Previous Individuality Models

- Soon after value of fingerprints for personal identification became known
 - Degree of individuality present in a fingerprint became of interest
- Twenty approaches
 - Galton (1892), Henry-Balthazard(1900-1943)
 - Roxburgh (1933), Amy
 - Trauring (1963), Kingston (1964)
 - Osterburgh (1977-1980)
 - Stony and Thornton (1985-1989), Champod (1995)
 - Meagher, Budowle and Zelsig (1999)
 - Jain, et.al. (2001-2005)

Grid Model (Galton)

- Find square where ridge detail is predicted with probability ¹/₂ given surrounding ridges
- Size estimated as 5 ridges
- 24 squares cover fingerprint
- Probability of specific fingerprint configuration given surrounding ridges P(C/R)=(1/2)²⁴
- Two factors: fingerprint pattern type = (1/16)
- Correct numbers of ridges entering/exiting = (1/256)
- Probability of a fingerprint P(FP) =(1/16)(1/256)(1/2)²⁴ = 1.45 x 10⁻¹¹
- Assume world population of 16 billion fingers
- Odds of finding another finger with same ridge detail is 1.45 x 10⁻¹¹ x 16 x 10⁹ = (1/4)



Grouping of individuality models

- 1. Models dividing Fingerprint into Grids Galton, Osterburgh
- 2. Fixed Probability Models

Henry, Balthazard, Bose, Wentworth & Wilder, Cummins & Midlo, Gupta

- 3. Models using Polar coordinate system Roxburgh
- 4. Models using Relative Distances between Minutiae

Trauring, Champod

- 5. Generative Models
 - Jain et al, Srihari et al

Taxonomy of Individuality Models



Computational Approaches

- Availability of
 - AFIS algorithms
 - Fingerprint databases
 - NIST FVC
 - IAI Twins
- Individuality model to relate to algorithms

 Generative Models (with NIST FVC)
 - Cohort Studies (with IAI database)

3. Generative Model

- Compute probability of Random correspondence (PRC)
- Model the distribution of fingerprint features as a probability distribution
 - Since distribution can be used to generate fingerprints it is generative
 - Use distribution to estimate PRC

Generative Model of Height Individuality

- Probabilistic model whose parameters are estimated
- Probability of two individuals having same height within a tolerance
 - Using N(μ , σ^2) feet , probability for tolerance ε is $\int_{-\infty}^{\infty} \left(\int_{a-\epsilon}^{a+\epsilon} P(h|\mu,\sigma)dh \right)^2 da$



Prob for ε = 0.1 is 0.0094

Generative Model with Minutiae



 Minutiae represented as (x,y,θ)

Generative Model with Minutiae







Generative model based on Minutiae



Generative Model with Ridge types

- More than minutiae are used in fingerprint matching
- Ridge information is important in latent print and partial print matching
- Sixteen ridge types can be defined



Minutiae and 6th and 12th Ridge Points





RRP Types and Ridge Types



All 16 ridge types & matching rules

,□	∠ d > (2)	d ↓ (3) ₫	(4)
∠ k (5)	Ъ (6)	(7)	(8)
ي ک (9)	`⊾ ☑´ ₫(10)	₫ (11)	₫ <mark>\</mark> (12)
(13)	■ È (14)		ر (16)

 T_i^6 and T_i^{12} to denote the RRP type of the 6^{th} and 12^{th} ridge points on ridge R_i

Two ridges R_i and R_j could match with each other if and only if $|T_i^6 - T_j^6| \le 1$ and $|T_i^{12} - T_j^{12}| \le 1$

Ridge types in a fingerprint



Two Generative Models

Generative model for minutiae only

 $- f(s,\theta|\Theta_G) = \sum_{g=1}^{G} \tau_g f_g^X(s|\mu_g, \Sigma_g) \cdot f_g^D(\theta|\nu_g, \kappa_g, \rho_g)$

Gaussian Mixture Models for (x,y) minutiae location

Von-mises for (**Θ**) minutiae orientation

- Generative model for minutiae and ridges
 - **IS** $f(s, \theta, \mathcal{T}|\Theta_G) = \sum_{g=1}^G \tau_g f_g^X(s|\mu_g, \Sigma_g) \cdot f_g^D(\theta|\nu_g, \kappa_g, \rho_g)$

Uniform distribution for (t) Ridge type, (x,y,⊖,t)

Generative model with minutiae and ridge type



Better representation More reliable PRC values

Table 1. PRC for different fingerprint matches with varying m (number of minutiae in template),n (number of minutiae in input) and w (number of matched minutiae) - Without ridge information.

m	n	w	PRC ₀	PRC
26	26	12	6.0×10^{-6}	$7.5 imes 10^{-5}$
		16	7.8×10^{-10}	$1.3 imes 10^{-6}$
		26	1.2×10^{-25}	2.8×10^{-18}
36	36	12	1.1×10^{-5}	6.0×10^{-6}
		16	3.4×10^{-9}	3.0×10^{-8}
		36	2.4×10^{-40}	9.1×10^{-24}
46	46	12	$2.9 imes 10^{-4}$	$1.1 imes 10^{-5}$
		16	5.7×10^{-7}	7.6×10^{-8}
		46	8.3×10^{-50}	1.7×10^{-32}

Table 2. PRC for different fingerprint matches with varying m (number of minutiae in template),n (number of minutiae in input) and w (number of matched minutiae) - With ridge information.

m	n	w	PRC ₀	PRC
26	26	12	6.0×10^{-6}	7.5×10^{-5}
		16	7.8×10^{-10}	$1.3 imes 10^{-6}$
		26	1.2×10^{-25}	2.8×10^{-12}
36	36	12	3.1×10^{-8}	3.6×10^{-8}
		16	9.1×10^{-13}	2.1×10^{-11}
		36	4.2×10^{-49}	9.5×10^{-32}
46	46	12	$4.3 imes 10^{-8}$	2.9×10^{-9}
		16	2.0×10^{-12}	6.6×10^{-13}
		46	$1.6 imes 10^{-67}$	3.1×10^{-49}

PRC values modeling ridge types are (never higher in all cases) significantly lowered from previous values without ridge information.

Conclusion of Individuality using Generative models

- Previous Result
 - Probability of Random Correspondence (PRC) using minutiae alone is 1 in 100,000 when 12 or more points match with 36 minutiae available in input and template prints
 - PRC using minutiae alone is 1 in a billion when 16 or more points match with 36 minutiae available in input and template prints
- New Result
 - With RRP these numbers are 1 in 100 million and 1 in a trillion

Comparison of 14 Individuality Models Madal

Author

lviouer	Author	rear	Size	of False Corre- spondence (N=12)	model	Windolae Types
Grid	Galton	1892	75	1.45×10^{-11}	${}^{1/16}_{(1/2)^{24}} \times {}^{1/256}_{} \times {}^{}_{}$	Ending Ridge, Fork
	Osterburgh	1977	39	10 ⁻²⁰	$P = p_0^{k_0} p_1^{k_1} \dots p_{12}^{k_{12}}$	Bridge, Dot, Ending Ridge, Fork, Island, Lake, Delta, Spur, Tri- furcation and Double Bifurcation
Fixed Prob- ability	Henry	1900		5.9×10^{-8}	0.25 ^N	Ending Ridge, Fork
	Balthazard	1911		5.9×10^{-8}	0.25 ^N	Ending Ridge, Fork
	Bose	1933		5.9×10^{-8}	0.25 ^N	Ending Ridge, Fork, dot, continuous ridge
	Wentworth and Wilder	1918		4.1×10^{-21}	0.02^{N}	Ending Ridge, Fork, Is- land, Break
	Cummins and Midlo	1943		1.3×10^{-22}	$0.032 imes 0.02^N$	
	Gupta	1968				Ending Ridge, Fork, Compound Minutiae
Ridge Based	Roxburgh	1933	80	3×10^{-16}	$(P/C)(RT/Q)^N$	Ending Ridge, Fork
Relative Measure- ment	Trauring	1963		4×10^{-18}	$10r(9\pi s/16)^{N}$	Ending Ridge, Fork
	Champod	1995	1000			Ending Ridge, Fork, Is- land, Lake, opposed bi- furcations, Bridge, Dou- ble bifurcation, Hook, bi- furcation opposed with ending
Generative	Pankanti, Prabhakar and Jain (minutiae only)	2001	2672	1.22×10^{-20}	Mixture model us- ing Hyper geomet- ric and Binomial distributions	Ending Ridge, Fork
	Dass, Zhu and Jain (minutiae only)	2005	2560	1.1×10^{-5}	Mixture model us- ing Gaussian and Von-Mises distrib- utions	Ending Ridge, Fork
	Fang, Sri- hari and Srinivasan (minutiae and ridges)	2006	800	3.1×10^{-8}	Mixture model using Gaussian, Von-Mises dis- tributions and Empirical distri- bution for ridge type	Ending Ridge, Fork, Ridge Points

Von Sample Probability Probabilistic

Minutine Types

Ridge Features in AFIS

Published in

- Proc. Biometric Technology for Human Identification IV, SPIE, April 2007
- Being revised for Journal Publication

Symbol Definitions



d : sample rate: average inter-ridge distance(11 pixels in FV2002)

- Measured in pixels
- Depend on image resolution
- Li: number of ridge points sampled on a ridge Ri
 - Depend on ridge length and "d".
- L: Average number of ridge points sampled on the longest ridge in each fingerprint in a database. (18 in FVC2002)
 - Depend on how much region of a finger is captured in an image
- Ridge point index : starts from minutia and increases [1,18]

Representation of Fingerprint



- Minutiae $(x^{M}, y^{M}, \theta^{M})$
 - $-x^{M}$, y^{M} : x, y coordinates of minutiae
 - θ^{M} : orientation of minutiae
- Ridge Points (x^{R} , y^{R} , θ^{R})
 - $-x^{R}$, y^{R} : x, y coordinates of RRP
 - θ^{R} : orientation of RRP
 - Ridge flow orientation where RRP is located (towards minutiae)

Fingerprint Matcher Inputs : Minutiae + RRPs

Benefit from existing minutiae-based matching algorithms that could tolerate non-linear deformation very well, with **Modification**: Minutia only with Minutia, RRP only with RRP

RRP selection scheme

- How many RRPs should be selected?
 Answer: Only one per ridge
- Which RRPs should be selected?
 Answer: all the ridge points with index

 $k = \left[\frac{2}{3}L\right]$

L : Average number of ridge points sampled on the longest ridge in each fingerprint in a database. (18 in FVC2002)

– Reasons are as following pages

Why?

Minutiae & RRP → Ridge Shape



A real ridge *Ri*



Q: If we only know the minutia and only one RRP, do these two offer sufficient info. to infer the shape of the ridge?

A: Yes,approximately!

Fingerprint : Smoothly Flowing

- "A fingerprint: a smoothly flowing pattern"
 - "fingerprint reconstruction from minutiae" [Ross et al. SPIE'05]
- Similar to using French Curves (but with constraint)



One RRP per ridge is sufficient

- "A fingerprint: a smoothly flowing pattern"
 - "fingerprint reconstruction from minutiae" [Ross et al. SPIE'05]
- Why is *B* the only possible ridge segment?
 1.(x^M,y^M)(x^R,y^R) → locate *beginning* & *end point* 2.Index of the ridge point → length of segment



ding directions

- 1 and 2 filter all the others but A,
 B, C and D. (approximately)
- "approximately" is enough. Recall "non-linear deformation"

3 implicates that only B is true!

Which index k to select?

Ridge R_i

Should be far from minutia



- Correlation with minutiae de minutiae.
 - Minutiae M_i
- To infer as many other ridge points between the minutiae & the RRP
- Should be not be too large
 - Few ridges are long enough to have too large index RRP (less) info.)
 - Poorer image quality in periphery of fingerprint images than inner



L: Average number of ridge points sampled on the longest ridge in each fingerprint in a database. (18 in FVC2002)

In FVC 2002, $L = 18 \rightarrow k = 12$.

Summary of RRP Selection and Minutiae Matcher Modification

- RRP selection
 - On each ridge, only one RRP with $inc^k = [\frac{2}{3}L]$ is selected
- Minutiae matcher modification
 - A minutia is only allowed to match with another minutiae (but not any RRP)
 - An RRP is only allowed to match with another RRP with the same ridge point index

Generating partial prints



Experiments on Partial Fingerprint Matching

FVC 2002 DB3



Experiments on Partial Fingerprint Matching



Conclusion of Use of Ridge Features in AFIS

- Performance of existing minutiae-based matchers could be improved by representative ridge points especially for partial fingerprint matching
- Simple modification of minutiae based matching algorithm

4. Discriminability of Twins

• To appear in

Journal of Forensic Identification, November 2007

Twins Data Distribution

- Friction Ridge Images of 610 individuals
 - 291 sets of twins
 - 5 pairs of twins along with their families
 - 5 sets of twins with inconclusive or no DNA analysis results
 - 3 Sets of triplets
- MetaData Table
 - Gives the code for an individual along with his/her twin
 - Gives other information
 - whether the twins are identical or fraternal,
 - demographics,
 - characteristics etc

Livescan Images

610 folders with 18 images each:

- 10 rolled fingerprint images
- 2 flat impressions of thumbs
- 2 flat impressions of other 4 fingers
- 2 palm prints
- 2 writer palms, Writer Palm

Palm Print





Rolled fingerprints



Flat scan of other 4 fingers



Separated images from 4-scan



Fingerprints of Twins: Questions addressed

- 1. How often the prints of the same finger in a pair of twins *are similar* ?
 - 1. Level 1
 - 2. Level 2
- 2. How does this compare to those of nontwins?
- 3. Do prints of identical twins differ from those of fraternal twins?

Distribution of Meta Data





Manual interface for classification



- Two individuals performed the classification.
- On images with conflicting labels, a third individual did an arbitration
 - Classification results are authenticated by a professional.

Level 1 Distribution



Level 1: Examples of same/different



Fraternal twins Right Loop Right Loop

Fraternal twins Whorl Right Loop

Level 1 Conclusion

54.68 % of twins have same level 1*

 Identical-twins: 56.92 % similarity
 Fraternal-twins: 39.44 %

31.76 % of non-twins have same level 1

*with 6 possible level 1 types

Level 2 Study - Minutiae

- Primarily Ridge Endings and Bifurcations
- How often are twin prints similar (same finger)?
 - Use a Standard AFIS type matcher Bozorth: to give a similarity score

Level 2 – AFIS Error rate with Hard Threshold

	FP Error Rate	EER Threshold
		(Bozorth Score)
Twins	6.17 %	26
(same finger)		
Non-Twins	2.91 %	18

Conclusion: Using AFIS decision, a pair of twins prints are more likely to be classified as Genuine prints.

Level 2: Motivation for statistical tests

 How to arrive at a conclusion without having to use a threshold?



Level 2: Score distributions



Level 2 Study – Statistical comparisons

- Compare two distributions
- Disprove null hypothesis
 - two distributions are drawn from same population
 - with required level of significance
- Tests available
 - Chi Square
 - Kolmogorov Smirnov
 - Students T test
 - ANOVA(Analysis Of VAriance)

Level 2 Statistical comparisons

Test	Twins vs Non- Twin	Identical vs Fraternal	Genuine vs Twin	Genuine vs Non-Twin
Chi-Square	1403.03	34.06	2703.00	2737.00
Kolmogorov- Smirnov	0.1174	0.9999	0.0010	0.0004
Students-T	6.50	0.1481	85.05	89.13
ANOVA	81.02	0.024	2618.34	18790.62

All tests numbers are 100 % statistically significant

Summary

- 1. Identical vs Fraternal have significantly small values indicating high similarity.
- 2. Genuine vs Twin have significantly large values indicating Twins can be discriminated
- 3. Genuine vs Non-Twin have the highest values indicating Twins are harder to discriminate than Non-Twins (when comparing with column 3).
- 4. Twins are different from Non-Twins (column 1)

Twins Study Conclusions

- Level 1 Twins are more likely than nontwins to have same type (55% and 32%).
- Level 2
 - Twins have higher False Positive Error Rate than non-twins in automatic verification (6% and 3%).
 - Statistical Tests Twins are discriminable but less so than non-twins.
 - Identical and Fraternal twins are not different

5. Future Work

- 1. Twins Data Set 2 Study
- 2. Palmprint Study

Future Work

- 1. Twins Data Set 2 Study
 - Data to be collected by IAI in August 2007.
 - Multiple samples for each finger to be collected.
 - Use new twins data to analyze Genuine pair distribution.
 - Study the change in fingerprints over time.
 - Compare Twins Data sets 1 and 2.

Future Work

Palm print Analysis

• Classification of area – Interdigital area, Cat scratch, long and short ridges etc.



Latent print orientation

Publications (2005-2007)

- 1. Discriminability of Fingerprints of Twins Journal of Forensic Identification, November 2007
- 2. Generative models for fingerprint individuality using Ridge Points

International Workshop on Computational Forensics. August 2007, IEEE PAMI submitted.

3. Comparison of ROC and likelihood methods in fingerprint matching

SPIE Homeland Security April 2006

Int. J. PR and AI, Special Issue on Biometrics, Accepted

- 4. Survey of Individuality models for fingerprints Forensic Science International Journal, submitted.
- 5. Use of ridge points in fingerprint matching SPIE Homeland Security April 2007 Journal version in preparation
- 6. Use of Writer Palm for Identification Under preparation

Summary

- New databases allow more
 comprehensive studies of individuality
- Individuality models relate to AFIS algorithms
- Generative methods and Twins studies presented

Further Information

• Contact

srihari@buffalo.edu