Research on Friction Ridge Pattern Analysis

Sargur N. Srihari

Department of Computer Science and Engineering University at Buffalo, State University of New York

Research Supported by National Institute of Justice Grant NIJ 2005-DD-BX-K012

National Conference on Science, Technology and Law St. Petersburg, Florida, November 4, 2006

Why Research in Friction Ridge Analysis?

- Pattern recognition is an actively researched scientific area
 - All science progresses with research
 - New methods developed
- Ironically Daubert inadvertently caused some delay in funding for research
 - Since critics claimed that fingerprint research was funded by NIJ because it does not have a scientific basis

What Research is Needed?

- Biometric Community (machine identification)
 - Need for faster algorithms
 - Need for more accurate algorithms
 - Reduce scan area of fingerprint
- Forensic Community (interactive manmachine identification)
 - Latent Print matching Computational tools
 - Quantity versus quality
 - Studies of individuality (theoretical limits)

Latent Prints can be of poor quality



Interactive Tools for Latent Print Enhancement

Sharpen \rightarrow HighPassFilter \rightarrow Change input levels \rightarrow Blur \rightarrow Brightness and Contrast adjustment



Research Methods

Computational methods make many new studies possible

- 1. Efficient AFIS to separate "wheat" from "chaff"
- 2. New tools for the latent print examiner: Methods to simulate latent print examiner's approaches
- 3. Quantity-quality studies Full/partial prints
- 4. Individuality models from large scale analysis Analysis of twins' patterns Generative models
- 5. Palm prints

Minutiae based methods and use of ridge information

minutiae, (x, y, θ) , where θ is the orientation of ridge towards minutiae





Ridge points included

Partial fingerprint images



Partial Fingerprint Error Rates

Fror rates for NIST DB-3

(Poor quality images)

Frror rates for NIST-DB1 (Good Quality images)

EERs vs Number of Available Minutiae in Partial Fingerprints(DB1)



- 30 partial print databases (5 levels with increasing number of available minutiae)
- In each partial print database
 - Total images = 800 (100 different fingers, 8 impressions each)
 - Number of same finger pairs : 5600
 - Number of different finger pairs per noise level : 9900

Fingerprint Individuality Models

- Fixed Probability Models
 - Starting with Henry, Balthazard
- Models using Polar coordinate system
 - Roxburgh
- Models using Relative Distances between Minutiae
 - Trauring, Champod
- Models dividing Fingerprint into Grids
 - Galton, Osterburgh
- Generative Models
 - Probability of Random Correspondence (PRC) is calculated for N matching minutiae

Comparison of Individuality Models

Models	Ву	Sample Size	PRC (N=12)	Minutiae considered	
Grid Models	Galton	75	1.45*10 ⁻¹¹	None	
	Osterburgh	39	10 ⁻²⁰	Bridge, Dot, Ridge Ending, Fork, Island, Lake, Delta, Spur, Double and Triple Bifurcation	
Polar System Models	Roxburgh	80	5.98*10 ⁻⁴⁶	Ridge Endings and Ridge Bifurcations	
Relative Measurement Models	Champod	1000		Ridge Endings, Bifurcations, Island, Lake, Opposed Bifurcations, Bridge, Hook	
	Trauring		4*10 ⁻¹⁸	Ridge Endings and Ridge Bifurcations	
Generative Models	Pankanti	2672	1.22*10 ⁻²⁰	Ridge Endings and Ridge Bifurcations	
	Jain	2560	1.8*10 ⁻⁸	Ridge Endings and Ridge Bifurcations	
Fixed Probability Models (P ^N)	Henry		1/4 ¹²	None	
	Balthazard		1/4 ¹²	Ridge Endings and Ridge Bifurcations	
	Bose		1/4 ¹²	Dot, Fork, Ending ridge and Continuous Ridge	
	Wentworth and Wilder		1/50 ¹²	None	
	Cummins and Midlo		1/31 * 1/50 ¹²	None	
	Gupta	1000		Forks, Ridge Endings	

Generative Model of Individuality (Height)

Generative Model for Individuality of Height

- A probabilistic generative model whose parameters are estimated (Eg: gaussian)
- Evaluate probability of two individuals having same height within a tolerance

Using a Gaussian with mean μ and variance σ feet , this probability for tolerance ϵ can be calculated using $\int_{0}^{\infty} \left(\int_{0}^{a+\epsilon} \right)^{2}$



٠







Prob for $\varepsilon = 0.1$ is 0.0094

Generative Model for Minutiae

Minutiae Location (Gaussian)





Generative model for minutiae is calculated as

$$f(s,\theta|\Theta_G) = \sum_{g=1}^G \tau_g f_g^X(s|\mu_g, \Sigma_g) . f_g^D(\theta|\nu_g, \kappa_g, \rho_g)$$

where $f_g^X(s|\mu_g, \Sigma_g)$ is the Gaussian model for location

$$\begin{split} f_g^D(\theta|\nu_g,\kappa_g,\rho_g) &= \rho_g \upsilon(\theta).I\{0 \leq \theta < \pi\} + (1-\rho_g)\upsilon(\theta-\pi).I\{\pi \leq \theta < 2\pi\}\\ \upsilon(\theta) \text{ is the von-mises distribution for orientation} \end{split}$$

100 minutiae clustered using EM. Optimum number of clusters is 2

Minutiae Orientation (von Mises)





The PRC for 12 minutiae matches with 36 minutiae in both the input and the template is **7.1** * **10^-5**

Twins' Livescan Images (IAI)

610 persons with18 images each:

- 10 rolled fingerprint images
- 2 flat impressions of thumbs
- 2 flat impressions of other 4 fingers
- 2 palm prints
- 2 writer palms, Writer Palm

Palm Print





Rolled fingerprints



Flat scan of other 4 fingers



Separated images from 4-scan



Statistical study of twins



Results of Twins' Study

Test	Twins vs Non-Twin	Identical vs Fraternal	Genuine vs Twin	Genuine vs Non- Twin
Chi-Square	780	34	2250	2737

- 1. Identical vs Fraternal have significantly small values indicating high similarity.
- 2. Genuine vs Twin have significantly large values indicating Twins can be discriminated
- 3. Genuine vs Non-Twin have the highest values indicating Twins are harder to discriminate than Non-Twins (when comparing with column 3).
- 4. Twins are different from Non-Twins (column 1)

Ongoing Work

- Level 3 Features
 - Pores
 - Ridge Contours
 - Score fusion with
- Palm prints
 - Matching
 - Writer palms



Summary of Ongoing Research

- Performance of AFIS can be improved by using ridge information and likelihood functions
- Performance of AFIS can be related to quantity of minutiae and image quality
- Individuality models have been compared and a generative models of individuality has been evaluated
- Twins data has been analyzed
- Level 3 feature in fingerprints and palm prints will be studied

Publications

- "Comparison of ROC-based and likelihood methods for fingerprint verification", *Proc. of SPIE: Biometric Technology for Human Identification,* April 17-18, 2006, Kissimmee, Florida, pp. 620209-1to 12.
- 2. "Use of Ridge Points in Partial Fingerprint Matching", Submitted to SPIE: Biometric Technology for Human Identification, 2007. IEEE Transcations on Pattern Analysis and Machine Intelligence
- 3. "Assessment of Individuality Models for Fingerprint Verification", To be submitted.
- 4. "Twins Study", Journal of Identification

Conclusion

- When there is good data reliable identification can be made
 Algorithms have 1% error rate
- Research ongoing is on further decreasing error rate and dealing with poor quality data
- Research initially hindered by Daubert is now on right course