Use of Ridge Points in Partial Fingerprint Matching

Sargur N. Srihari with G. Fang, H. Srinivasan and P. Phatak

CEDAR

Department of Computer Science and Engineering University at Buffalo, State University of New York

Outline

- 1. Loss of discriminative power with partial fingerprints
- 2. Previous Use of Ridge Information
- 3. Representative Ridge Points
- 4. Experimental Results
- 5. Conclusion and Future work

1. Loss of Discriminative Power with Partial Fingerprints

- Smaller
 fingerprint
 segment
 - fewer minutiae
 - higher EER

DB1 & DB3 Average Number of Matching Minutae in Genuine Pairs 30 20 10 Π Ο 10 EER (%) DB1(Matching) DB3(Matching) 20 DB1(EER) DB3(EER) 30 25 15 20 30 35 full Number of Available Minutae

With good image quality

Features other than minutiae

- Singular points (e.g. core/delta)
 - Not guaranteed to exist





Missing core

Missing delta

- General ridges
 - Agrees with human examiners' method for fingerprint verification

[D.A. Ashbaugh 1999]

2. Use of Ridge Information (Prior Work)

For alignment

- Ridge pair shape similarity for alignment [Jain et al. PAMI '97] [Luo et al. ICPR '00] [Cheng et al. ICBA '04]
 - Pro: Efficient for on-line usages
 - Con: Sensitive to non-linear deformation
- Ridge with Hough Transform for alignment [Marana and Jain SIBGRAPI '05]
 - Pro: More reliable alignment (hough & try all pairs)
 - Con: Time consuming (8 sec per match [no CPU info found])

Singular points (core and delta) may help alignment, but in partial fingerprint matching, core and delta are not always available.



Ridge vs. Other local models

- Non-linear deformation
 - The essential difficulty of fingerprint matching
- Local minutia relationships
 - Minutia pairs [Bozorth, '99, NIST]
 - Minutia triples [Jea PR'05]
 - Minutia n-tuples [Chikkerur ICB'06]
- Ridge vs. other local models
 - Ridge covers a larger region than other local models
 - Larger region means more variation of non-linear deformation

		100 100 100	- XII
			5) 1 8 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -
:			•

Previous Use of Ridge Information

- For both alignment and matching
 - Minutiae and all ridge points are used for both alignment and matching [Feng et al. PR '06]
 - Pro: Higher accuracy than using minutiae only
 - Con: Alignment requires <u>high minutiae number</u> (not scalable for partial print) & <u>low non-linear deformation</u>
 - Con: Matching with all ridge points → low efficiency
- For fingerprint warping
 - Deformation model based on ridge curve correspondence [Ross et al. PAMI '06]
 - Pro: Better than using minutiae correspondence only
 - Con: Depend on minutiae based matching.

Summary of Previous Use of Ridge Information

Pros

 Ridge features offers better accuracy than using minutiae only

- Cons
 - Sensitive to non-linear deformation
 - Computational complexity



Outline

- 1. Loss of discriminative power with partial fingerprints
- 2. Previous Use of Ridge Information
- 3. Representative Ridge Points
- 4. Experimental results
- 5. Conclusion and Future work

Representative Ridge Points (RRPs) to Improve Minutiae based Matching

(Sparsely select one/two ridge points on each ridges. Same representation as minutiae, (x, y, θ) , where θ is the orientation of ridge towards minutiae)



1) Genuine pair: Minutiae Matched, as well as ridges.

2) No minutiae in the regions within the five blue rectangles

Motivation: Both minutiae and discrete ridge points are used to increase contrast between Genuine and Impostor.

Ridge Shape Inferred From Minutiae & Ridge Points



Proposed Fingerprint Representation

- Minutiae $(x^{M}, y^{M}, \theta^{M})$
 - x^{M} , y^{M} : x, y coordinates of minutiae
 - θ^{M} : orientation of minutiae
- Ridge Points (x^{R} , y^{R} , θ^{R})
 - x^{R} , y^{R} : x, y coordinates of RRP
 - θ^{R} : orientation of RRP
 - Orientation of ridge flow where RRP is located
 - Towards minutiae
- Matcher Inputs
 - Minutiae + Ridge Points
 - Use existing minutiae-based matching algorithms
 - to tolerate nonlinear deformations,
 - with Modification:
 - matching Minutiae only with Minutia,
 - RRP only with RRP

Computational Complexity

- Theoretically
 - Higher accuracy with more RRPs
- Run-time concern

No. of RRPs selected per Ridge (r)	0	1	2	3	4	5	6
No. of Minutiae (n) and RRPs $(n(1 + r))$	n	2n	3n	4n	5n	6n	7n
Theoretical Ratio(RRP+Min:Min) ($(1 + r)^3$)	1	8	27	64	125	216	343

(Actual run-time is given in experiments section)

- Goal 1: Use as few RRPs as possible
- Goal 2: Significant accuracy improvement

Before we start, some symbol definitions

Symbol Definitions



- d: sampling rate: average inter-ridge distance
 - Measured in pixels (11 in FVC2002)
 - Depend on image resolution
- Li: number of ridge points sampled on a ridge Ri
 - Depend on ridge length and "d".
- L: Average number of ridge points sampled on longest ridges in each fingerprint in a database (18 in FVC2002)
 - Depend on how much region of a finger is captured in an image.
- Ridge point index : starts from minutia and increases [1,18]

Ridge Point Selection Scheme

- Q1: How many ridge points to use?
 Answer: Only one per ridge
- Q2: Which ridge points to use? – Answer: all the ridge points with index $k = \frac{2}{3}L$
- Why?

- Reasons are as following pages

Inverse Inference: Minutiae & RRP → Ridge Shape

1 minutia + 1 ridge point → ridge shape



A real ridge Ri

Q: If we only know the minutia and only one RRP, do these two offer sufficient info. to infer the shape of the ridge?

A: Yes, approximately!

Fingerprint : Smoothly Flowing

- Fingerprint: "a smoothly flowing pattern"
 - "fingerprint reconstruction from minutiae" [Ross et al. SPIE'05]
- Similar to using French Curves (but with constraint)



Single Ridge Point Suffices

- 1. $(x^{M}, y^{M})(x^{R}, y^{R}) \rightarrow \text{locate beginning \& end point}$
- 2. Index of the ridge point \rightarrow length of segment
- 3. θ^{M} , θ^{R} > Beginning & ending directions



• 1 and 2 filter all the others but A, B, C and D. (approximately)

- "approximately" is enough. Recall "non-linear deformation"
- 3 implicates that only B is true

B is only possible ridge segment

Which Ridge Point to Select

- "Only and All" Ridge Points with a predefined index. E.g. {9th}
 - To guarantee that genuine fingerprints have genuine RRPs



Selection of index k

Ridge R_i



Minutiae M_i

- Should be far from minutia
 - Correlation with minutiae decreases when further from minutiae.
 - To infer as many other ridge points between the minutiae & the RRP
- Should be not be too large
 - Few ridges are long enough to have too large index RRP (less info.)
 - Poorer image quality in periphery of fingerprint images than inner

$$k = \left[\frac{2}{3}L\right]$$

In FVC 2002,
$$L = 18 \implies k = 12$$
.

Process to Extract Representative Ridge Points (RRPs)



Summary of RRP Selection and Minutiae Matcher Modification

- RRP selection
 - On each ridge, only one RRP with index $k = [\frac{2}{3}L]$ is selected
- Minutiae matcher modification
 - A minutia is only allowed to match with another minutiae (but not any RRP)
 - An RRP is only allowed to match with another RRP with the same ridge point index

Outline

- 1. Loss of discriminative power with partial fingerprints
- 2. Previous Use of Ridge Information
- 3. Representative Ridge Points
- 4. Experimental results
- 5. Conclusion and Future work

Full print matching on FVC2002

		EER on FVC2002 Database						
		DB1	DB2	DB3	DB4			
Bozorth	Minutiae	3.5 %	3.0 %	8.1 %	3.9 %			
	Minutiae + RRPs	↓ 2.2 %	↓ 2.2 %	↓ 6.1 %	↓ 3.2 %			
Minutiae n- tuple	Minutiae	1.0 %	1.2 %	8.5 % 企	3.7 %			
	Minutiae + RRPs	0.7 %	1.0 %	↓ 7.8 %	3.4 %			

Bozorth [Bozorth, '99, NIST]

1) **Red bold** indicates best accuracy in each database. 2) $\hat{\parallel}$

indicates significant improvement with 95% confidence interval.

Full prints matching on FVC2002 (cont.)



Generating partial fingerprint images



All Partial print matching EERs decrease with RRP



Practical Factors of Actual Run-time

- Experiments show that only half ridges have $\left[\frac{2}{3}L\right]$ RRP, the input will be $n + \frac{n}{2} = \left(\frac{3}{2}\right)n$, and time ratio decreases $to\left(\frac{3}{2}\right)^3 \approx 3.3$
- When number of RRPs per ridge r > 1, we do not input RRPs together but in r rounds. In each round we input minutiae and RRPs with a single index. Time ratio decreases to $k(1+1)^3 = 8k$
- Modified matcher will reject two potential pair as soon as the pair is found to be a minutiae and an RRP, which means the coefficient before $O(n^3)$ will be smaller in practice.
- Only double original time using 1 RRP per ridge (entries is with K-Plet)

No. of RRPs selected per Ridge (\mathcal{F})	0	1	2	3	4	5	6
No. of Minutiae (n) and RRPs $(n(1+r))$	n	2n	3n	4n	5n	бn	7n
Theoretical Ratio(RRP+Min:Min) $((1 + r)^3)$	1	8	27	64	125	216	343
Estimated Ratio(RRP+Min:Min)	1	2	8	12	16	20	24
Actual Run-Time on Intel ^R Xeon [™] 2.8GHz	0.20	0.38	1.52	2.4	3.2	4.0	4.8
four processors (secs/match)							

In forensics where candidates are not too many, long run-time is acceptable for better accuracy.

Outline

- 1. Loss of discriminative power with partial fingerprints
- 2. Previous Use of Ridge Information
- 3. Representative Ridge Points
- 4. Experimental results
- 5. Conclusion and Future work

5. Conclusion and Future Work

- Proposed a method to utilize ridge information in fingerprint matching:
 - 1) Ridge point selection scheme
 - 2) Minutiae matcher modification guideline
- Highlights of algorithm
 - very effective and fairly efficient
 - performance of most existing minutiae-based matchers could be improved especially for partial fingerprint matching
- Future work
 - designing better fingerprint individuality models by embedding ridge information into generative models

Thank you

Further information: srihari@cedar.buffalo.edu