

Mapping Transcripts to Handwritten Text

Sargur Srihari, Chen Huang


CEDAR, Department of Computer Science and Engineering
University at Buffalo, State University of New York, USA

Outline


1. Problem Definition
2. Motivation
3. Pre-processing
4. Word String Alignment
5. Post-processing
6. Experimental Results
7. Comparison with Previous Methods
8. Conclusions and Future Work

Transcript mapping


Handwritten
Document



Transcript-mapped document



Transcript
Text File




Transcript is of entire page
No line information in transcript

Motivation: Uses of transcript mapping

- Recognition
 - Creating set of labeled handwritten word images
 - for adapting to a particular writer
 - for creating a corpus for training/testing of algorithms
- Writer Recognition
 - Automatic extraction of words and characters for analysis
- Document Retrieval
 - Enables word level indexing of handwritten document images for document retrieval

Proposed algorithm



Pre-processing

- Automatic line segmentation
 - Statistical approach (to appear in DRR 2007)
- Automatic word segmentation
 - 11 features extracted
 - 5 global features (line-based)
 - 6 local features (connected components-based)
 - Classifier is a neural network

However, the extra hours affected her health; halfway through the show she passed out. We rushed her to the hospital, and several questions, xrays and blood tests later, we were told it was just exhaustion.

Kate has been in very bad health since. Could you kindly take a look at the results and give us your opinion?

Thank you!

However, the extra hours affected her health; halfway through the show she passed out. We rushed her to the hospital, and several questions, xrays and blood tests later, we were told it was just exhaustion.

Kate has been in very bad health since. Could you kindly take a look at the results and give us your opinion?

Thank you!

Word recognition

- Lexicon-based
 - Word image is segmented into “segments”
 - 74 (2 global and 72 local) features are extracted from all possible combinations of 1-4 consecutive segments
 - Matching using character-level dynamic programming
- Lexicon
 - Size
 - Coarse word recognition: 20 or less
 - Fine word recognition: 10 or less
 - Obtained from relevant portion of transcript

Alignment of Transcript and Recognition Result

- Align words such that longest common subsequence is found
- Given:
 - “However the extra hours affected her health”
 - “Hours her the extra hours affected health”
- Solution:
 - the extra hours affected health
- Global Anchor (high confidence word):
 - affected

Word string alignment

Dynamic programming to maximize score

- For two word sequences, $\langle p_1, \dots, p_i \rangle$ and $\langle q_1, \dots, q_j \rangle$, the alignment score $V(i, j)$, is solved by the recurrence formula:

$$V(i, j) = \max \left\{ \begin{array}{l} V(i-1, j-1) + \sigma(p_i, q_j), \\ V(i-1, j) + \sigma(p_i, -), \\ V(i, j-1) + \sigma(-, q_j) \end{array} \right\}$$

where $\sigma(p_i, q_j)$ is the score of aligning p_i with q_j , defined as

$$\sigma(p_i, q_j) = \begin{cases} 1 + c_j & \text{if } p_i = q_j \\ -1 & \text{otherwise} \end{cases}$$

and c_j is the confidence value returned from the word recognizer.

Recognized results (conf.)


However the extra hours affected her health

	hours	her	the(0.7)	extra(0.7)	hours(0.7)	affected(0.8)	health(0.3)
However	-1	-1	-1				
the	-1	-2	0.7				
extra				2.4			
hours					4.1		
affected						5.9	4.9
her						4.9	4.9
health						3.9	6.2

Truth

However
the
extra
hours
affected
her
health


Post Processing to Improve Segmentation

- Transcript
 - “However the extra hours affected her health”
- Recognition result
 - “Hours her the extra hours affected health”


Post-processing

- Under-segment


- Combined text is put into word lexicon
- Perform word recognition again using new lexicon



“herjob” and “joband” are put into lexicon
(distance between 2nd word image and “herjob” is 6.80)

- Over-segment

- Images will be grouped to become one word image
- Perform word recognition again with new word image



last two bounding boxes are grouped together
(distance between the grouped word image and “required” is 8.15)

Experimental results

- Data set
 - 20 full page images of “CEDAR letter”
 - Each contains 156 words including all the characters
 - Vocabulary size is 124
- Alignment accuracy
 - 78.3%, without post processing
 - 84.7%, with post processing

Comparison with Previous Algorithms

- Improved from Zhang and Tomai's algorithm
 - Usage of global anchors
 - No multiple segment hypotheses, thus more efficient and more robust
 - Better performance
- Difference from Kornfield and Rothfeder's algorithm
 - Usage of word recognizer
 - Results of automatic word segmentation is also improved
 - No (or less) training needed for different types of datasets

Conclusion

- Proposed a recognition-based alignment algorithm for transcript mapping
- Word recognition done using a dynamically created lexicon
 - size of lexicon reduced as much as possible to get a higher recognition accuracy
- Global anchors were detected and used to reduce lexicon size
- Word segmentation improved during post-processing

Future Work

- A better automatic word segmentation algorithm with punctuation detection
- Post processing can be more intelligent and more effective
- More extensive experiments on a larger dataset and also on different types of collections (such as historical manuscript)